

STANDARD BAR SPLICER ASSEMBLY

Minimum Lap Lengths						
Bar size to be spliced	Table 1	Table 2	Table 3	Table 4	Table 5	
3, 4	1'-5''	1'-11''	2'-1''	2'-4''	2'-3''	
5	1'-9''	2'-5''	2'-7''	2'-11''	2'-10''	
6	2'-1''	2'-11''	3'-1''	3'-6''	3'-4''	
7	2'-9''	3′-10′′	4'-2''	4'-8''	4'-6''	
8	3'-8''	5′-1′′	5′-5′′	6'-2''	5′-10′′	
9	4'-7''	6′-5″	6′-10′′	7'-9''	7'-5''	

Table 1: Black bar, 0.8 Class C

Table 2:Black bar, Top bar lap, 0.8 Class CTable 3:Epoxy bar, 0.8 Class CTable 4:Epoxy bar, Top bar lap, 0.8 Class C

Table 5: Epoxy bar, Top bar lap, Class B

Threaded splicer bar length = min. lap length + l_2'' + thread length

* Epoxy not required on Bar Splicer Assembly components used in conjunction with black bars.

Location	Bar size	No. assemblies required	Table for minimum lap length		



INSTALLATION AND SETTING METHODS

"A" : Set bar splicer assembly by means of a template bolt.
"B" : Set bar splicer assembly by nailing to wood forms or cementing to steel forms.
(E) : Indicates epoxy coating.





BSD-1

7-1-10

	USER NAME =	DESIGNED - ESH REVISED -		BAR SPLICER ASSEMBLY AND MECHANICAL SPLICER DETAILS		SECTION	COUNTY	TOTAL SHEET SHEETS NO.	
LIN ENGINEERING, LTD.	FILE NAME =	CHECKED - MTH	REVISED -	STATE OF ILLINOIS	STRUCTURE NOS. 084–0152 & 084–0153	72	(84-10-1)BDR	SANGAMON	35 32
Consulting Engineers Springfield, Illinois	PLOT SCALE =	DRAWN - ESH CHECKED - MTH	REVISED -	DEPARTMENT OF TRANSPORTATION	SHEET NO. 18 OF 20 SHEETS			CONTRACT	T NO. 72F01
	FLUI DHIE -	CHECKED - MTH	REVISED -		SHEET NO. 18 OF 20 SHEETS		ILLINOIS FED. A	AID PROJECT	



STANDARD MECHANICAL SPLICER

Location	Bar size	No. assemblies required

NOTES

Splicer bars shall be deformed with threaded ends and have a minimum 60 ksi yield strength.

All reinforcement shall be lapped and tied to the splicer bars. Bar splicer assemblies shall be epoxy coated according to the requirements for reinforcement bars. See Section 508 of the Standard Specifications. See special provision for Mechanical Splicers. See approved list of bar splicer assemblies and mechanical splicers for alternatives.