


PIPE SIZE	FLAT BAR SIZE	I.D. OF STRAP	C © BOLT TO © PIPE	D HEIGHT OF STRAP	E © OF BOLT TO END OF STRAP	F CLEARANCE AT BOLTS	G BOLT DIAMETER MIN	H FLAT BAR SIZE MIN	WELD SIZE
1/4"	1/8"×3/4"	13/16"	15/16"	13/64"	5/16"	1∕8"	1/4"	3/16"×3/4"	⅓"
1/2"	1/8"×3/4"	11/8"	11/8"	23/64"	5/16"	1/8"	14"	3/16"×3/4"	1⁄8"
3/4"	⅓"×1"	15/16"	11/4"	15/32"	3/8"	1∕8"	5/16"	1/4"x1"	1⁄8"
11/2"	⅓"×1"	25/16"	111/16"	57/ ₆₄ "	3/8"	1⁄8"	5/16"	1/4"×1"	1/8"
2"	⅓"×1"	25/8"	2"	11/8"	3/8"	⅓"	5/16"	1/4"×1"	1/8"

TYPICAL PIPE HANGER DETAIL SCALE: NONE




PIPE SIZE	A PIPE O.D.	8 I.D. *	C 0.D. *	CUTOUT DIA	E WELD SIZE	l Sleeve Length	THICKNESS
3/4"	1.050"	1.075"	1.387"	1.5"	5/32"	4"	0.156"
1½"	1.90"	1.930"	2.242"	2.375"	5/32"	4"	0.156"
2"	2.375"	2.420"	2.870"	3"	³∕16"	4"	0.225"

* NOTE:

SLEEVE MATERIAL SHALL BE ASTM A 106, GRADE B AND SHALL BE ORDERED FROM THIS STANDARD DRAWING BY SPECIFYING I.D. SIZE (COL"B"), O.D. SIZE (COL "C"), AND THICKNESS (COL "T"). INSIDE DIAMETER ACCURACY SHALL HAVE PRECEDENCE OVER O.D. AND THICKNESS DIMENSIONS.

3 TYPICAL CONTINUOUS PIPING RUN PENETRATION DETAIL 5 SCALE: NONE



PIPE SIZE	A ROD DIA MIN	B INSIDE RADIUS OF U-BOLT MIN	C APPROXIMATE LENGTH	D THREAD LENGTH MIN
<i>Y</i> ₄ "	<i>Y</i> 4"	19/64"	1 ¹³ /16"	1 ¹³ / ₁₆ "
1/2"	<i>Y</i> 4"	7/6"	1 ¹⁵ /16"	1 13/16"

TYPICAL PIPE RAMP HANGER DETAIL SCALE: NONE


GENERAL NOTES

- 1. RULES AND REGULATIONS: ALL WORK AND MATERIALS SHALL BE IN FULL ACCORDANCE WITH FEDERAL, STATE AND LOCAL RULES AND REGULATIONS, FIRE MARSHAL REGULATIONS, CODE OF FEDERAL REGULATIONS ITILE 46 SHIPPING, STANDARDS OF THE NATIONAL FIRE PROTECTION ASSOCIATIONS, AND ALL OTHER APPLICABLE LAWS, CODES OR REGULATIONS. NOTHING IN THE DRAWINGS OR SPECIFICATIONS SHALL BE CONSTRUED TO PERMIT WORK NOT CONFORMING TO THESE CODES.
- MISCELLANEOUS MATERIALS AND HARDWARE SUCH AS NUTS, BOLTS, SCREWS, PLASTIC SEALANT, AND OTHER SUCH ANCILLARY ITEMS MAY NOT BE INCLUDED IN THE BILL OF MATERIALS'. HOWEVER, ALL ITEMS NECESSARY TO COMPRISE A COMPLETE, FINISHED AND OPERATIONAL INSTALLATION CONFORMING TO USCG REQUIREMENTS AND GOOD SHIPBUILDING PRACTICE SHALL BE PROVIDED BY THE INSTALLER.
- 3. STEEL PIPE SIZES SHOWN ON THE DRAWING ARE NPS.
- 4. PIPING SHALL BE ADEQUATELY SUPPORTED TO CARRY WEIGHT, INCLUDING DYNAMIC LOADING AND TO PREVENT DAMAGE FROM VIBRATION AND IMPACT. PIPING SHALL BE SUPPORTED BY HANGERS WITH RESILIENT LINERS FABRICATED AND INSTALLED IN ACCORDANCE WITH ASTM F708 AND THIS DRAWING.
- 5. ALL WELDS SHALL BE NEATLY FINISHED WITH ALL SLAG AND SPLATTER REMOVED.
- 6. WELDED PIPING JOINTS SHALL BE IN ACCORDANCE WITH ASTM F-722.
- 7. WATERTIGHT INTEGRITY SHALL BE MAINTAINED. ALL PIPING PENETRATING WATERTIGHT BULKHEADS AND DECKS SHALL BE INSTALLED WITH USCG APPROVED PIPE SLEEVES OR AS SHOWN ON THIS DRAWING.
- 8. INSPECTION: DO NOT ALLOW ANY WORK TO BE COVERED UP OR ENCLOSED UNTIL INSPECTED, TESTED AND APPROVED BY THE ENGINEER, OWNER'S REPRESENTATIVE OR OTHER AUTHORITIES HAVING JURISDICTION OVER THE WORK.
- 9. SHOULD ANY WORK BE ENCLOSED OR COVERED UP BEFORE SUCH INSPECTION AND TEST, CONTRACTOR SHALL, AT HIS OWN EXPENSE, UNCOVER WORK AND, AFTER IT HAS BEEN INSPECTED, TESTED AND APPROVED, MAKE ALL REPAIRS AS NECESSARY TO RESTORE ALL DISTURBED WORK TO ITS ORIGINAL CONDITION.

MECH	ANICAL SYMBOLS LIST
SYMBOL	DESCRIPTION
<u> </u>	CHECK VALVE
*	ANGLE GLOBE VALVE W/ REMOTE OPERATOR
─ ₩─	GLOBE VALVE
	BALL VALVE
, <u> </u>	PUMP
0	SUCTION
N	REDUCER
	FLEXIBLE HOSE
Ø [₽]	DIFFERENTIAL PRESSURE GAGE







ART ANDERSON
202 PACIFIC AVE. BREMERTON, WA 98337 (360) 479-5800

LE NAME =	USER NAME =	DESIGNED		M. McKAY	REVISED	 REV A	07/21/2011	
		DRAWN	_	C. FAWVER	REVISED			
	PLOT SCALE =	CHECKED	_	P. MARTIN	REVISED	 		
	PLOT DATE =	DATE		10/04/2010	REVISED	 		

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

	MECH			BRUSSELS UTFIT GEN		Y NOTES - BARGE
SCALE:	AS SHOWN	SHEET NO.	OF	SHEETS	STA.	TO STA.

-0"	DRAWING NO	o. CEIDTOO	001BA-500-201			
.a.p. Rte.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.		
304	213	JERSEY	26	12		
		CONTRACT N	0. 76	D29		
FED. RO	DAD DIST NO. HUNOIS FED A	ID PROJECT				