

1) STAGE 1 WILL BE CONSTRUCTED AT THE UPSTREAM END OF EACH CULVERT LOCATION


2) STANDARD 701326 SHALL BE UTILIZED TO CONSTRUCT BITUMINOUS 6HOULDER FOR TEMPORARY WIDENING


3) STANDARD 701201 SHALL BE USED FOR CULVERT REMOVAL AND REPLACEMENT

4) ADDITIONAL QUANTITY OF 122 C.Y. OF AGGREGATE SURFACE COURSE, TYPE B HAVE BEEN ADDED TO THE CONTRACT TO PROVIDE FOR TEMPORARY ROADWAY ACCESS

5) NO OVERNIGHT LANE CLOSURES WILL BE ALLOWED ON THIS PROJECT. THE CONTRACTOR WILL FILL ANY OPEN TRENCH WITH AGGREGATE CAPPED WITH 3" OF BITUMINOUS COLD MIX AT THE END OF THE WORK DAY TO THE SATISFACTION OF THE ENGINEER. COST SHALL BE INCLUDED IN THE COST OF THE TRAFFIC CONTROL.

6) "LOOSE GRAVEL" SIGNS SHALL BE PLACED IN ADVANCE
OF EACH END OF STAGING WORK FOR ANY TRAVEL ON
AGGREGATE AS A SURFACE MATERIAL. AGGREGATE SURFACE
WILL NOT BE PERMITTED OVERNIGHT OR DURING ANY
NON-FLAGGER CONTROLLED HOURS. COSTS OF SIGNS WILL
BE INCLUDED IN THE TRAFFIC CONTROL ITEMS SHOWN IN
THE PLANS.








DETAIL FOR DOUBLE OUTLET TYPE 1 FOR TYPE A GUTTER

SEE STANDARD 606106 FOR REMAINING DIMENSIONS AND DETAILS

F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
586	60R-2, 37R-1	MADISON	502	246
CONTI	RACT NO.: 76301			







PIPE CULVE	ERTS "CL EMPORAF		TYPE 1"	
HEADWALL LOCATIONS		CULVERT LENGTHS		
STA.	LOC.	24"	30"	
65Ø+91.55	RT.	5′		
663+07.76	LT.		6′	
674+69.09	LT.	8′		
686+17.53	LT.	3′		
696+Ø5.68	LT.	5′		
TOTALS		21′	67	

STAGE CONSTRUCTION CULVERT REPLACEMENT TRAFFIC CONTROL

NAME	DATE	TELEVISION DELIVERY OF THE OWNER OF	.,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
		MISCELLANEOUS DETAILS	
		FAP 586 SECTION 60R-2, 37R-1 MADISON COUNTY	
		SCALE: HORIZ. DRAWN E	3Y
		DATE CHECKED	BY

ILLINOIS DEPARTMENT OF TRANSPORTATION