

10/29

Ë DA

F.A.U. RTE,	SECTION	COUNTY		TOTAL	SHEET NO.	
3732	00-00125-00-BR		C	DOK	58	30
STA. 102+57.23 TO STA. 103+82.77						
FED, RO	AD DIST. NO.	IS PR	OJECT	BHM-700	3(802)	
h C 17 - C 00				CONT	RACT 839	584

Sheef S-13 of S-28 CONTRACT 83584

GENERAL NOTES

The strip seal shall be made continuous and shall have a minimum thickness of ${}^{l}_{4}$ ". The configuration of the strip seal shall match the configuration of the Locking

Edge Rails. The height and thickness of the Locking Edge Rails shown are minimum dimensions. The actual configuration of the Locking Edge Rails and matching strip seal may vary from manufacturer to manufacturer. Flanged edge rails will not be allowed.

Locking Edge Rails may be spliced at slope discontinuities and stage construction joints.

The manufacturer's recommended installation methods shall be followed.

The joint opening and deck dimensions detailed on the superstructure are based on a preformed joint seal. If the contractor elects to use the alternate strip seal joint, the opening and deck dimensions shall be modified according to the dimensions detailed on this sheet, Required modifications shall be made at no additional cost to the State.



	CHOTIDE GTOUP, Inc. CONSULTINE ENGINEERS SIGN NORTH COMERCIANA DEVINCE :: CEICAGO, ILLINOIS 8066 :: (775) 775-4976				
REVISIONS	CITY OF EVANSTON, ILLINOIS				
NAME DATE					
	BRIDGE JOINT SYSTEM-EXPANSION (ALTERNATE)				
	ASBURY AVENUE OVER CTA YELLOW LINE				
	SECTION 00-00215-00-BR				
	COOK COUNTY				
	STA. 103+20.00				
	STRUCTURE NO. 016-6959				
	SCALE: NONE				
	DATE: OCTOBER 2004 DRAWN BY: IMG				
	FILE: 3212 CHECKED BY: SCD				