

PROPOSED

EXISTING ROAD SURFACE

BUTT JOINT DETAIL

GRINDING OF BITUMINOUS PAVEMENT

VARIES - SEE PLAN

PRIVATE ENTRANCE DETAIL

P.E.R. STA. 10+10 AND P.E.R. STA. 11+50

4:1_


FOR BUTT JOINT.


2' FARTH SHOULDER

4:1

10'


EXISTING BITUMINOUS PAVEMENT.





PROPOSED TYPICAL SECTION (STA. 3+80 TO STA. 8+40)


SEC COUNTY 26 4 ILLINOIS PROJECT BHOS-037(39) * 99-00103-01-BR



EXISTING TYPICAL SECTION (STA. 8+40 TO STA. 24+00)

100'-0" R.O.W. North of Bridge 50'-0" North of Bridge 50'-0" North of Bridge 6'-0" 11'-0" 11'-0" 6'~0" ← E OF ROADWAY 1' SLOPE 3/16/FT. SLOPE 1/2"/FT. - BITUMINOUS CONCRETE SURFACE COURSE, SUPERPAVE, IL—9:5L LOW ESAL (1 1/2" COMPACTED THICKNESS) - BITUMINOUS CONCRETE BINDER COURSE, SUPERPAVE, IL-19.0L LOW ESAL (3" COMPACTED THICKNESS) PAVEMENT REMOVAL (SURFACE COURSE) - AGGREGATE BASE COURSE, TYPE B (THICKNESS VARIES) -AGGREGATE SHOULDERS, TYPE B (4" COMPACTED THICKNESS)

> PROPOSED TYPICAL SECTION (STA. 13+00 TO STA. 24+00)



PROPOSED TYPICAL SECTION (STA. 8+40 TO STA. 13+00)

TYPICAL SECTIONS & DETAILS SECTION 99-00103-01-BR KIRKLAND RD. (CO. HIGHWAY 29) DEKALB COUNTY