TRAFFIC SIGNAL LEGEND

i e e e e e e e e e e e e e e e e e e e											
<u>ITEM</u>	REMOVAL	EXISTING	PROPOSED	ITEM	REMOVAL	EXISTING	PROPOSED	ITEM	REMOVAL	EXISTING	PROPOSED
CONTROLLER CABINET	\bowtie ^R			EMERGENCY VEHICLE LIGHT DETECTOR	· • ·	\bowtie	•	ELECTRIC CABLE IN CONDUIT, TRACER, NO. 14 1/C, UNLESS NOTED OTHERWISE			
RAILROAD CONTROL CABINET	a	R R		CONFIRMATION BEACON	R _{o-} g	○ —(]	 €	COAXIAL CABLE		_6_	— <u>c</u> —
COMMUNICATIONS CABINET	CC	ECC	CC	HANDHOLE	R □			oomana onde			
MASTER CONTROLLER		EMC	MC	HEAVY DUTY HANDHOLE	R	H	B	VENDOR CABLE FOR CAMERA			(v)
MASTER MASTER CONTROLLER UNINTERRUPTIBLE POWER SUPPLY	R [UPS]	EMMC EUPS	MMC UPS	DOUBLE HANDHOLE	R			COPPER INTERCONNECT CABLE,		-/	
SERVICE INSTALLATION,		D	P	JUNCTION BOX	R	O	0	NO. 18 3 PAIR TWISTED, SHIELDED		(6)	-6-
(P) POLE OR (G) GROUND MOUNT	-□ ⁻ R	-D ^r	- 	GALVANIZED STEEL CONDUIT				FIBER OPTIC CABLE NO. 62.5/125, MM12F		—(12F)—	
TELEPHONE CONNECTION (P) POLE OR (G) GROUND MOUNT	R	P	P	IN TRENCH (T) OR PUSHED (P) TEMPORARY SPAN WIRE, TETHER WIRE,	R			FIBER OPTIC CABLE NO. 62.5/125, MM12F SM12F		<u> </u>	—(24F)—
STEEL MAST ARM ASSEMBLY AND POLE	R	0	•	AND CABLE			<u> </u>			,	
ALUMINUM MAST ARM ASSEMBLY AND POLE	R			COMMON TRENCH			СТ	FIBER OPTIC CABLE NO. 62.5/125, (NUMBER OF FIBERS & TYPE TO BE		_	
STEEL COMBINATION MAST ARM ASSEMBLY AND POLE WITH LUMINAIRE	^R O-⊐	0->≭	•	COILABLE NONMETALLIC CONDUIT (EMPTY) SYSTEM ITEM		S	CNC S	OROUND ROD AT (C) CONTROLLER,		Car	C
STEEL COMBINATION MAST ARM ASSEMBLY AND POLE WITH PTZ CAMERA	PTZ]	Q	PIZ	INTERSECTION ITEM		I	IP	(H) HANDHOLE, (P) POST, (M) MAST ARM, OR (S) SERVICE		C 11	c¶ ⊢•
SIGNAL POST	RO	0	•	REMOVE ITEM	R			CONTROLLER CABINET AND FOUNDATION TO BE REMOVED	RCF		
TEMPORARY WOOD POLE (CLASS 5 OR BETTER) 45 FOOT (13.7m) MINIMUM	R⊗	\otimes	•	RELOCATE ITEM ABANDON ITEM	RL A			STEEL MAST ARM POLE AND	RMF		
GUY WIRE	>R	>	>_	12" (300mm) TRAFFIC SIGNAL SECTION		(R)	R	FOUNDATION TO BE REMOVED	Ü		
SIGNAL HEAD	R -	>	▶	12" (300mm) RED WITH 8" (200mm)		R	- Landerson d	ALUMINUM MAST ARM POLE AND FOUNDATION TO BE REMOVED	RMF		
SIGNAL HEAD CONSTRUCTION STAGES (NUMBERS INDICATE THE CONSTRUCTION STAGE)			2	YELLOW AND GREEN TRAFFIC SIGNAL FACE				STEEL COMBINATION MAST ARM ASSEMBLY AND POLE WITH LUMINAIRE AND	RMF		
SIGNAL HEAD WITH BACKPLATE	+C> R	+>>	+			R	R	FOUNDATION TO BE REMOVED			
SIGNAL HEAD OPTICALLY PROGRAMMED	R -□>''P''	>′′Þ′′		SIGNAL FACE		©	G ← Y	SIGNAL POST AND FOUNDATION TO BE REMOVED	RMF		
FLASHER INSTALLATION (S DENOTES SOLAR POWER)	R O-⊠"F"	O-D ^{"F"}	→ "F"			€6	4 G	INTERSECTION & SAMPLING (SYSTEM) DETECTOR		IS	IS
PEDESTRIAN SIGNAL HEAD	<u>-</u> 0	-0	-			R	R	SAMPLING (SYSTEM) DETECTOR		S S	S
PEDESTRIAN PUSHBUTTON DETECTOR	R ©	6	©	SIGNAL FACE WITH BACKPLATE. "P" INDICATES PROGRAMMED HEAD			G	EXISTING INTERSECTION LOOP DETECTOR PROPOSED INTERSECTION AND SAMPLING (SYSTEM) DETECT	OB	P	-
ACCESSIBLE PEDESTRIAN PUSHBUTTON DETECTOR	R	@APS	APS			★ 6	4 Y 4 G	EXISTING PREFORMED INTERSECTION LOOP DETECTOR	OK .	ę —	
ILLUMINATED SIGN "NO LEFT TURN"	R		9				"P"	PROPOSED INTERSECTION AND SAMPLING (SYSTEM) DETECT	OR	1 <u>PP</u>	
ILLUMINATED SIGN	R			12" (300mm) PEDESTRIAN SIGNAL HEAD WALK/DON'T WALK SYMBOL		OW W		PREFORMED INTERSECTION AND SAMPLING (SYSTEM) DETECTOR		PIS	PIS
"NO RIGHT TURN"		8	®	12" (300mm) PEDESTRIAN SIGNAL HEAD INTERNATIONAL SYMBOL, OUTLINED				PREFORMED SAMPLING (SYSTEM) DETECTOR		[PS]	PS
DETECTOR LOOP, TYPE I				12" (300mm) PEDESTRIAN SIGNAL HEAD							
PREFORMED DETECTOR LOOP		}	Р	INTERNATIONAL SYMBOL, SOLID		©	*	RAILROAD SYMBOLS			
MICROWAVE VEHICLE SENSOR	R MJ	MH	(M)	PEDESTRIAN SIGNAL HEAD, INTERNATIONAL SYMBOL, WITH COUNTDOWN TIMER		C C C D	₽ C ↑ D			EXISTING	PROPOSED
VIDEO DETECTION CAMERA	R Vþ	(V)	∑ •	RADIO INTERCONNECT	##*O	##+0		RAILROAD CONTROL CABINET		R ≪R	B. E
VIDEO DETECTION ZONE				RADIO REPEATER	RERR	ERR	RR	RAILROAD CANTILEVER MAST ARM	×	COX X X	X OX X X
PAN, TILT, ZOOM CAMERA	R PTZ]]	PT	PTZ	DENOTES NUMBER OF CONDUCTORS, ELECTRIC	haranna manana d		America Anna Constructed	FLASHING SIGNAL		$\boxtimes \ominus \boxtimes$	X⊖X
WIRELESS DETECTOR SENSOR	RW	W	W	CABLE NO. 14, UNLESS NOTED OTHERWISE, ALL DETECTOR LOOP CABLE TO BE SHIELDED				CROSSING GATE		X0X>	XOX
WIRÈLESS ACCESS POINT	R			GROUND CABLE IN CONDUIT NO. 6 SOLID COPPER (GREEN)		(1)	1	CROSSBUCK		}	*
FILE NAME = USER NAME = konthaphixagb ct\pw_work\PWIDOT\KANTHAPHIXAYBC\d01126 4\traffic.legend_v7.dgn PLDT SCALE = 20.0000 / / IN	DRA	AWN - BCK CKED - DAD	REVISED - REVISED - REVISED -	STATE DEPARTMENT	OF ILLINOIS OF TRANSPO			DISTRICT 1 STANDARD TRAFFIC SIGNAL DESIGN DETAIL	F.A. RTÉ.	SECTION 98-B	COUNTY TOTAL SHEETS NO. COOK 65 49 CONTRACT NO. 60H20