## INDEX OF SHEETS

## SHEET NO. NO. DESCRIPTION 1 COVER SHEET 2 INDEX, GENERAL NOTES AND HIGHWAY STANDARDS 3 SUMMARY OF QUANTITIES 4 SCHEDULE OF QUANTITIES 5 TYPICAL SECTIONS 6-23 ROADWAY AND PAVEMENT MARKING PLANS 24 DETAILS FOR DEPRESSED CURB AND GUTTER AND SHOULDER TREATMENT AT TBT TY 1 SPL (BD34) 25 TRAFFIC CONTROL AND PROTECTION FOR SIDEROADS, INTERSECTIONS AND DRIVEWAYS (TC10)

26 TEMPORARY INFORMATION SIGNING (TC22)

## HIGHWAY STANDARDS

482001 -0 <b>2</b>	HMA SHOULDER ADJACENT TO FLEXIBLE PAVEMENT
630001-09	STEEL PLATE BEAM GUARDRAIL
630301-05	SHOULDER WIDENING FOR TYPE 1 (SPECIAL) GUARDRAIL TERMINALS
635006 <b>- 03</b>	REFLECTOR AND TERMINAL MARKER PLACEMENT
635011-02	REFLECTOR MARKER AND MOUNTING DETAILS
642001 - 0/	SHOULDER RUMBLE STRIPS
701006 <i>-03</i>	OFF-ROAD OPERATIONS, 2L, 2W, 15' (4.5 m) TO 24" (600 mm) FROM PAVEMENT EDGE
701011-02	OFF-ROAD MOVING OPERATIONS, 2L, 2W, DAY ONLY
701301 <i>-04</i>	LANE CLOSURE, 2L, 2W, SHORT TIME OPERATIONS
701326 <b>- 04</b>	LANE CLOSURE, 2L, 2W, PAVEMENT WIDENING, FOR SPEEDS $\geq$ 45 MPH
701901 <i>-01</i>	TRAFFIC CONTROL DEVICES
720001-01	SIGN PANEL MOUNTING DETAILS
720006 - <i>O</i> Z	SIGN PANEL ERECTION DETAILS
728001-01	TELESCOPING STEEL SIGN SUPPORT

STD. NO. TITLE

## GENERAL NOTES

- BEFORE STARTING ANY EXCAVATION, THE CONTRACTOR SHALL CALL "J.U.L.I.E."
  AT 800-892-0123 OR "CUAN" (CHICAGO UTILITY ALERT NETWORK), 312-744-7000
  FOR FIELD LOCATIONS OF BURIED ELECTRIC, TELEPHONE AND GAS FACILITIES
  (48 HOUR NOTIFICATION IS REQUIRED).
- 2. THE CONTRACTOR SHALL COORDINATE CONSTRUCTION ACTIVITIES WITH UTILITY COMPANIES AND LOCAL AGENCIES.
- 3. THE CONTRACTOR WILL NOT BE ALLOWED TO SET UP A YARD OR FIELD OFFICE ON STATE PROPERTY WITHOUT WRITTEN PERMISSION FROM THE DEPARTMENT.
- 4. THE RESIDENT ENGINEER SHALL CONTACT THE TRAFFIC CONTROL SUPERVISOR AT (847) 705-4470 A MINIMUM 72 HOURS PRIOR TO THE PLACEMENT OF ANY TEMPORARY TRAFFIC CONTROL DEVICES.
- 5. WHEN GUARDRAIL POSTS ARE PLACED BEHIND CONCRETE HEADWALLS, THE POSTS SHALL NOT BE PLACED TO BLOCK THE DRAINAGE OPENING.
- 6. WHEN MILLED PAVEMENT IS OPEN TO TRAFFIC THE MAXIMUM GRADE DIFFERENTIAL BETWEEN PASSES OF THE MILLING MACHINE SHALL NOT EXCEED 1 1/2 INCHES (40 MM) WHERE THE SPEED LIMIT IS 45 MPH (80 KM/H) OR LESS AND 1 INCH (25 MM) WHERE THE SPEED LIMIT IS GREATER THAN 45 MPH (80 KM/H). WITH WRITTEN APPROVAL FROM THE ENGINEER, A MAXIMUM GRADE DIFFERENTIAL OF 3 INCHES (75 MM) MAY BE ALLOWED IF THE EDGE OF THE MILLING IS SLOPED A MINIMUM 1:3 (V:H).
- FOR PAVEMENT MARKING, REFER TO DISTRICT ONE TYPICAL MARKINGS FOR DETAILS NOT SHOWN.
- 8. THE RESIDENT ENGINEER SHALL CONTACT DEBBIE HANLON, AREA TRAFFIC FIELD ENGINEER, AT 847-438-2300 AT LEAST (2) WEEKS PRIOR TO PLACING PERMANENT PAVEMENT MARKINGS.

FILE NAME =	USER NAME = _USER_	DESIGNED -		EF	REVISED -
sFiLELs	The second secon	DRAWN		EF	REVISED -
	PLOT SCALE = 50.0000 '/ IN.	CHECKED -	-	RS	REVISED -
	PLOT DATE = 8/9/2010	DATE		08-10-2010	REVISED -
Large contract to the second s			-		

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

IL 173 – HARVARD HILLS ROAD TO PRICE ROAD	F.A.P. RTE.	SECTION	COUNTY	TOTAL
INDEX OF SHEETS, HIGHWAY STANDARDS, AND GENERAL NOTES	303	132-1	MCHENRY CONTRACT	26
SCALE: 50 SHEET NO. 1 OF 1 SHEETS STA. TO STA.		ILLINGIS FED. AI		NO.