


# PART OF SECTION 24, T35N, R12E, OF THE 3RD PM, WILL COUNTY, ILLINOIS

## LEGEND



- EXISTING CENTERLINE
- EXISTING RIGHT OF WAY LINE
- PROPOSED CENTERLINE
- PROPOSED RIGHT OF WAY LINE
- PROPOSED TEMPORARY EASEMENT LINE
- PROPOSED PERMANENT EASEMENT LINE
- SECTION LINE
- QUARTER SECTION LINE
- QUARTER QUARTER SECTION LINE
- PLATTED LOT LINE
- PROPERTY (DEED) LINE
- APPARENT PROPERTY LINE
- ACCESS CONTROL LINE
- MEASURED OR COMPUTED DIMENSION RECORD DATA
- FOUND IRON PIPE OR IRON ROD
- SET 5/8 INCH IRON ROD
- PERMANENT SURVEY MONUMENT, I.D.O.T. STD. 2135 (TO BE SET BY OTHERS)
- CUT CROSS FOUND OR SET
- FOUND CONCRETE RIGHT-OF-WAY MARKER
- SAME OWNERSHIP
- FENCE LINE
- SIGN



BEARINGS SHOWN HEREON REFERENCE THE ILLINOIS STATE PLANE COORDINATE SYSTEM, EAST ZONE, NORTH AMERICAN DATUM OF 1983 (1997 ADJUSTMENT). ALL MEASURED AND CALCULATED VALUES ARE "GROUND."

COMBINED SCALE FACTOR:  
(GROUND TO GRID) = 0.999964  
(GRID TO GROUND) = 1.000036

- T1 THESE STAKES REFERENCE FOUND OR SET MONUMENTATION. SET 3/8 INCH IRON ROD FLUSH WITH GROUND. IDENTIFIED BY COLORED PLASTIC CAP BEARING SURVEYORS REGISTRATION NUMBER.
- BT1 THESE STAKES, IN CULTIVATED AREAS, REFERENCE FOUND OR SET MONUMENTATION. BURIED 3/8 INCH IRON ROD 20 INCHES BELOW GROUND SURFACE. IDENTIFIED BY COLORED PLASTIC CAP BEARING SURVEYORS REGISTRATION NUMBER.
- STAKING OF PROPOSED RIGHT OF WAY. SET DIVISION OF HIGHWAYS SURVEY MARKER TO MONUMENT THE POSITION SHOWN. IDENTIFIED BY INSCRIPTION DATA AND SURVEYORS REGISTRATION NUMBER.
- M STAKING OF PROPOSED RIGHT OF WAY IN CULTIVATED AREAS. BURIED 3/8 INCH IRON ROD 20 INCHES BELOW GROUND SURFACE TO MARK FUTURE SURVEY MARKER POSITION. IDENTIFIED BY COLORED PLASTIC CAP AND SURVEYORS REGISTRATION NUMBER.
- U STAKING OF PROPOSED RIGHT OF WAY IN CLOSE PROXIMITY TO UNDERGROUND UTILITIES. SET DIVISION OF HIGHWAYS SURVEY MARKER ON 3/8 INCH IRON ROD (BETWEEN 6 INCHES AND 12 INCHES IN LENGTH) TO MONUMENT THE POSITION SHOWN. IDENTIFIED BY INSCRIPTION DATA AND SURVEYORS REGISTRATION NUMBER.

STATE OF ILLINOIS )  
                                  ) S.S.  
COUNTY OF COOK    )

THIS IS TO CERTIFY THAT I, COVENTINE FIDIS, AN ILLINOIS PROFESSIONAL LAND SURVEYOR, HAVE SURVEYED THE PLAT OF HIGHWAYS SHOWN HEREON IN SECTION 24, TOWNSHIP 35 NORTH, RANGE 12 EAST OF THE THIRD PRINCIPAL MERIDIAN, IN WILL COUNTY, THAT THE PLAT CORRECTLY REPRESENTS SAID SURVEY, THAT ALL MONUMENTS FOUND AND ESTABLISHED ARE OF PERMANENT QUALITY AND OCCUPY THE POSITIONS SHOWN THEREON AND THAT THE MONUMENTS ARE SUFFICIENT TO ENABLE THE SURVEY TO BE RETRACED. MADE FOR THE DEPARTMENT OF TRANSPORTATION, STATE OF ILLINOIS.

DATED AT CHICAGO, ILLINOIS THIS 16TH DAY OF JANUARY, 2009.

COVENTINE FIDIS  
ILLINOIS PROFESSIONAL LAND SURVEYOR NO. 2159  
LICENSE EXPIRATION DATE 11/30/2010

THIS PROFESSIONAL SERVICE CONFORMS TO THE CURRENT ILLINOIS MINIMUM SURVEY STANDARDS.



RECEIVED  
JAN 28 2009  
PLATS & LEGALS

**PLAT OF HIGHWAYS**  
STATE OF ILLINOIS  
DEPARTMENT OF TRANSPORTATION  
F.A.P. 353  
LINCOLN HIGHWAY (U.S. ROUTE 30)

SECTION: WILL COUNTY  
PROJECT: JOB NO. R-91-016-01  
STATION: 539+73 TO STATION: 589+50  
SCALE: NONE SHEET E15

**BUREAU OF LAND ACQUISITION**  
201 WEST CENTER COURT  
SCHAUMBURG, ILLINOIS 60196

539+73.00 / 62.00' LT. 20012 	539+86.73 / 77.00' LT. 20013 	539+88.00 / 58.00' RT. 20036 	540+02.15 / 70.00' RT. 20035 	540+53.13 / 76.64' LT. 21660 	540+68.62 / 71.00' RT. 20034 
TIE DISTANCE DESCRIPTION	TIE DISTANCE DESCRIPTION	TIE DISTANCE DESCRIPTION	TIE DISTANCE DESCRIPTION	TIE DISTANCE DESCRIPTION	TIE DISTANCE DESCRIPTION
T1 X X	T1 X X	T1 X X	T1 X X	T1 X X	T1 X X
T2 X X	T2 X X	T2 X X	T2 X X	T2 X X	T2 X X
T3 X X	T3 X X	T3 X X	T3 X X	T3 X X	T3 X X
540+82.00 / 56.00' RT. 20033 	543+54.42 / 77.22' LT. 21658 	544+36.19 / 75.17' LT. 21659 	544+63.51 / 89.56' LT. 21656 	544+66.00 / 56.00' RT. 20032 	544+82.21 / 72.00' RT. 20031 
TIE DISTANCE DESCRIPTION	TIE DISTANCE DESCRIPTION	TIE DISTANCE DESCRIPTION	TIE DISTANCE DESCRIPTION	TIE DISTANCE DESCRIPTION	TIE DISTANCE DESCRIPTION
T1 X X	T1 X X	T1 X X	T1 X X	T1 X X	T1 X X
T2 X X	T2 X X	T2 X X	T2 X X	T2 X X	T2 X X
T3 X X	T3 X X	T3 X X	T3 X X	T3 X X	T3 X X
545+46.30 / 85.00' LT. 20017 	545+47.15 / 81.00' RT. 20030 	545+50.00 / 73.00' LT. 20018 	545+62.00 / 66.00' RT. 20029 	546+90.61 / 66.00' RT. 20028 	555+19.72 / 75.00' LT. 20020 
TIE DISTANCE DESCRIPTION	TIE DISTANCE DESCRIPTION	TIE DISTANCE DESCRIPTION	TIE DISTANCE DESCRIPTION	TIE DISTANCE DESCRIPTION	TIE DISTANCE DESCRIPTION
T1 X X	T1 X X	T1 X X	T1 X X	T1 X X	T1 X X
T2 X X	T2 X X	T2 X X	T2 X X	T2 X X	T2 X X
T3 X X	T3 X X	T3 X X	T3 X X	T3 X X	T3 X X
555+19.75 / 64.00' LT. 20021 	558+47.96 / 75.00' LT. 20023 	558+47.99 / 65.00' LT. 20022 	566+74.23 / 78.37' LT. 21603 	575+98.00 / 103.00' LT. 20025 	575+98.00 / 83.00' LT. 20024 
TIE DISTANCE DESCRIPTION	TIE DISTANCE DESCRIPTION	TIE DISTANCE DESCRIPTION	TIE DISTANCE DESCRIPTION	TIE DISTANCE DESCRIPTION	TIE DISTANCE DESCRIPTION
T1 X X	T1 X X	T1 X X	T1 X X	T1 X X	T1 X X
T2 X X	T2 X X	T2 X X	T2 X X	T2 X X	T2 X X
T3 X X	T3 X X	T3 X X	T3 X X	T3 X X	T3 X X
576+73.66 / 103.00' LT. 20026 	576+73.88 / 68.76' LT. 21599 	580+80.18 / 90.00' LT. 20097 	584+65.00 / 69.22' LT. 20099 	584+65.00 / 90.00' LT. 20098 	589+50.00 / 80.00' LT. 20101 
TIE DISTANCE DESCRIPTION	TIE DISTANCE DESCRIPTION	TIE DISTANCE DESCRIPTION	TIE DISTANCE DESCRIPTION	TIE DISTANCE DESCRIPTION	TIE DISTANCE DESCRIPTION
T1 X X	T1 X X	T1 X X	T1 X X	T1 X X	T1 X X
T2 X X	T2 X X	T2 X X	T2 X X	T2 X X	T2 X X
T3 X X	T3 X X	T3 X X	T3 X X	T3 X X	T3 X X

### DESCRIPTION LEGEND

- |   |   |   |
|---|---|---|
| 950 - MAG NAIL IN UTILITY POLE                | 957 - NE CORNER OF BUILDING                     | 965 - "4" ON CONCRETE RETAINING WALL            |
| 951 - MAG NAIL IN TREE                        | 958 - SE CORNER OF BUILDING                     | 966 - "4" ON CONCRETE HEADWALL                  |
| 952 - "4" IN POLE FOUNDATION, BASE, OR BOLT   | 959 - SW CORNER OF BUILDING                     | 967 - MAG NAIL IN LIGHT POLE                    |
| 953 - CENTER TOP SPINDLE BOLT OF FIRE HYDRANT | 960 - IRON ROD WITH YELLOW PLASTIC CAP          | 968 - MAG NAIL IN WOOD SIGN POST                |
| 954 - "4" ON CURB                             | 961 - "4" ON METAL FENCE POST                   | 969 - MAG NAIL IN RAILROAD TIE                  |
| 955 - "4" ON WALK / CONCRETE PAD              | 962 - MAG NAIL IN FENCE POST                    | 970 - "4" ON LEG OF ELECTRIC TRANSMISSION TOWER |
| 956 - NW CORNER OF BUILDING                   | 963 - "4" ON MANHOLE, CATCH BASIN, OR VAULT RIM | 971 - CORNER OF LARGE SIGN                      |
|   | 964 - MAG NAIL IN PAVEMENT                      | 972 - FENCE CORNER                              |
|   |   | 973 - MAG NAIL ON WOOD GUARDRAIL POST           |
|   |   | 974 - "4" ON CONC. SIGN FOUNDATION              |
|   |   | 975 - MAG NAIL ON STUMP                         |
|   |   | 976 - "4" ON BUILDING FACE                      |
|   |   | 977 - "4" ON RAILROAD SPIKE                     |
|   |   | 978 - CORNER OF PLANTER                         |
|   |   | 979 - CORNER OF COLUMN                          |

**AMERICAN SURVEYING & ENGINEERING, P.C.**  
841 N. Galena Avenue / Dixon, IL 61021 / 815-288-6231  
8604 W. Catapa Avenue / Chicago, IL 60656 / 773-444-0800  
888 S. Edgelawn Drive / Aurora, IL 60506 / 630-897-4105  
Illinois Professional Design Firm No. 184-003192