				TRAFFIC								
<u>ITEM</u>	REMOVAL	EXISTING	PROPOSED	<u>ITEM</u>	REMOVAL	EXISTING	PROPOSED	ITEM		REMOVAL	EXISTING	PROPOSED
CONTROLLER CABINET	R R R R R R R R R R R R R R R R R R R	\bowtie		EMERGENCY VEHICLE LIGHT DETECTOR	R≪✓	—————————————————————————————————————	•	ELECTRIC CABLE IN CONDUIT, TRACE	R ,			
RAILROAD CONTROL CABINET		M		CONFIRMATION BEACON	R _{o-} d	-7 -	•4	NO. 14 1/C, UNLESS NOTED OTHERWIS	SE TO THE SECOND SE			—1)—
COMMUNICATIONS CABINET	C C R	ECC	CC					COAXIAL CABLE			<u>—©</u>	—(c)—
ASTER CONTROLLER		EMC	MC	HANDHOLE	R □							
MASTER MASTER CONTROLLER		EMMC	MMC	HEAVY DUTY HANDHOLE	ÎH .	H	•	VENDOR CABLE FOR CAMERA			<u> </u>	_(V)_
NINTERRUPTIBLE POWER SUPPLY	UPS R	EUPS	<u>UPS</u>	DOUBLE HANDHOLE	R _{□□□}			COPPER INTERCONNECT CABLE,			α	, i
ERVICE INSTALLATION, P) POLE OR (G) GROUND MOUNT	-□ <u>R</u>	- _ _		JUNCTION BOX	R O	0	0	NO. 18 3 PAIR TWISTED, SHIELDED			<u> </u>	<u> </u>
ELEPHONE CONNECTION				GALVANIZED STEEL CONDUIT				FIBER OPTIC CABLE NO. 62.5/125, MM12F			—12 F	
POLE OR (G) GROUND MOUNT	R	ľo	P ∏	IN TRENCH (T) OR PUSHED (P)				FIBER OPTIC CABLE			64	6
TEEL MAST ARM ASSEMBLY AND POLE	R _O	0	•	TEMPORARY SPAN WIRE, TETHER WIRE, AND CABLE	<u>R</u>			NO. 62.5/125, MM12F SM12F			<u>—</u> @45—	—24F—
LUMINUM MAST ARM ASSEMBLY AND POLE	R	O	•==	COMMON TRENCH			ст	FIBER OPTIC CABLE NO. 62.5/125, (NUMBER OF FIBERS & TYPE TO BE			\prec	
TEEL COMBINATION MAST ARM SSEMBLY AND POLE WITH LUMINAIRE	^R O-≭	0-¥	• *	COILABLE NONMETALLIC CONDUIT (EMPTY)			CNC	NOTED ON PLANS)				
이번째 열리가 그 나는데 다시의 경기가 있다.				SYSTEM ITEM		S	S	GROUND ROD AT (C) CONTROLLER,			¢⊩	°∥⊸
TEEL COMBINATION MAST ARM SSEMBLY AND POLE WITH PTZ CAMERA	`Q——— PRZ\$I		€ FîZ¶	INTERSECTION ITEM		I	ΙP	(H) HANDHOLE, (P) POST, (M) MAST AF OR (S) SERVICE	₹М,			₩•
GNAL POST	P _O	0		REMOVE ITEM	R			CONTROLLER CABINET AND		RCF		
EMPORARY WOOD POLE (CLASS 5 OR	R⊗	⊗		RELOCATE ITEM	RL			FOUNDATION TO BE REMOVED				
ETTER) 45 FOOT (13.7m) MINIMUM				ABANDON ITEM	Å			STEEL MAST ARM POLE AND		ORMF		
JY WIRE	> <u>R</u>		\rightarrow	12" (300mm) TRAFFIC SIGNAL SECTION		R	R	FOUNDATION TO BE REMOVED				
GNAL HEAD	R A	. →		12" (700mm) PED WITH 0" (000mm)				ALUMINUM MAST ARM POLE AND FOUNDATION TO BE REMOVED		RMF		
GNAL HEAD CONSTRUCTION STAGES JMBERS INDICATE THE CONSTRUCTION STAGE)			2	12" (300mm) RED WITH 8" (200mm) YELLOW AND GREEN TRAFFIC SIGNAL FACE		(C) (S)		STEEL COMBINATION MAST ARM ASSE AND POLE WITH LUMINAIRE AND	MBLY	RMF		
GNAL HEAD WITH BACKPLATE	+D ^R	+⊳	+-			R	R	FOUNDATION TO BE REMOVED		<u>0-≭</u>		
GNAL HEAD OPTICALLY PROGRAMMED	_R >"P"	- ⊳ ″p″	- ▶ "P"	SIGNAL FACE) E	Y	SIGNAL POST AND FOUNDATION		RMF		
ASHER INSTALLATION	R O-D>''F''	O- ⊳ ″F″	●→ "F"				₹Y	TO BE REMOVED				
DENOTES SOLAR POWER)	04>1			[일] 보호이 모든 이름으움이 만중다.		€ •0	 4G	INTERSECTION & SAMPLING (SYSTEM) DETECTOR			IS	IS
DESTRIAN SIGNAL HEAD	R -□	-0				a	R	영화에 보다면 얼마를 되었다고 하다.				
DESTRIAN PUSHBUTTON DETECTOR	R	©	•	SIGNAL FACE WITH BACKPLATE. "P" INDICATES PROGRAMMED HEAD		X	Y	SAMPLING (SYSTEM) DETECTOR EXISTING INTERSECTION LOOP DETECTOR	TOR		[s] [a]	S
CESSIBLE PEDESTRIAN PUSHBUTTON DETECTOR	R APS	@APS	(a) APS			€ C	4 Y 4 C	PROPOSED INTERSECTION AND SAMPLI		OR	ĽĽ	
LUMINATED SIGN O LEFT TURN''	R R	<u>-</u>	©			₩₩₩₩₩₩₩₩₩₩₩₩₩₩₩₩₩₩₩₩₩₩₩₩₩₩₩₩₩₩₩₩₩₩₩₩₩	[4G] "P"	EXISTING PREFORMED INTERSECTION ! PROPOSED INTERSECTION AND SAMPLI		OR	[PP]	
LUMINATED SIGN				12" (300mm) PEDESTRIAN SIGNAL HEAD WALK/DON'T WALK SYMBOL		(W)		PREFORMED INTERSECTION AND SAMPL	ING		PIS	PIS
O RIGHT TURN"	R	®	®	12" (300mm) PEDESTRIAN SIGNAL HEAD		<u>w</u>		(SYSTEM) DETECTOR				
TECTOR LOOP, TYPE I				INTERNATIONAL SYMBOL, OUTLINED				PREFORMED SAMPLING (SYSTEM) DETE	CTOR		[PS]	PS
EFORMED DETECTOR LOOP			P	12" (300mm) PEDESTRIAN SIGNAL HEAD INTERNATIONAL SYMBOL, SOLID			₽ X	R4	AILROAD	SYMBO	210	
CROWAVE VEHICLE SENSOR	R ∭∏	(M)	∭ ¶	PEDESTRIAN SIGNAL HEAD, INTERNATIONAL SYMBOL, WITH COUNTDOWN TIMER		C C C C C C C C C C C C C C C C C C C	₽C X D				<u>EXISTING</u>	DDODOS
DEO DETECTION CAMERA	R [√]1	[Ŷ]	D									<u>PROPOS</u>
DEO DETECTION ZONE				RADIO INTERCONNECT	##•0	##+0		RAILROAD CONTROL CABINET				
		=		RADIO REPEATER	R ERR	ERR	RR	RAILROAD CANTILEVER MAST ARM		X	XOX X	Xex
N, TILT, ZOOM CAMERA	R ₽□ZJI	e z)	₽	DENOTES NUMBER OF CONDUCTORS, ELECTRIC				FLASHING SIGNAL			Zo Z	XOX
RELESS DETECTOR SENSOR	RW		w)	CABLE NO. 14, UNLESS NOTED OTHERWISE, ALL DETECTOR LOOP CABLE TO BE SHIELDED		_ 5	-5-	CROSSING GATE			⊠ >	X 0 X =
RELESS ACCESS POINT	R			GROUND CABLE IN CONDUIT NO. 6 SOLID COPPER (GREEN)		0		CROSSBUCK			 ₩	`*
E = 06508-SGNL-DTLS-01 - P06		IGNED — DAG/BCK	REVISED -				<u> </u>					
PLOT SCALE = 50.0000 '/	CHE	CKED — BCK	REVISED	STATE	STATE OF ILLINOIS			DISTRICT ONE		F.A.P. RTE. 348	SECTION 06-00104-00-CH	COUNTY
PLOT SCALE = 50.0000 // PLOT DATE = 11/4/2009		WN — DAD CKED — 10-28-09	REVISED -	DEPARTMENT OF TRANSPORTATION				STANDARD TRAFFIC SIGNAL DESIGN DETAILS SCALE: NONE SHEET NO. 33 OF 60 SHEETS STA. TO STA.			06-00104-00-CH	COOK CONTRACT N