


TYPICAL PAVEMENT MARKINGS


ARROW LAYOUT



- ONE-WAY AMBER MARKER
- ONE-WAY CRYSTAL MARKER
- TWO-WAY AMBER MARKER

ALL DIMENSIONS ARE IN MILLIMETERS (INCHES) UNLESS OTHERWISE NOTED.


TYPICAL PAVEMENT MARKING FOR FLUSH MEDIAN



RECOMMENDED SPACING BETWEEN DIAGONALS (IN FEET)

Speed Limit Range	Continuous Median Area	Intersection Channelization	Objects (Islands)
less than 50Km/H (30MPH)	15.3m (50')	4.53m (15')	3.05m (10')
50-60Km/H (30-40MPH)	22.9m (75')	6.1m (20')	4.53m (15')
70Km/H (45MPH) & over	22.9m (75')	9.05m (30')	6.1m (20')

NOTE: If the spacing recommended in the Table does not permit at least five diagonal lines in the area being marked, the spacing from the next lowest speed range should be used. The recommended spacing is measured parallel to the pavement center line.



TYPICAL PAVEMENT MARKINGS SHEET 2 OF 3 41.1

FILE NAME =	USER NAME = mado-02377	DESIGNED -	REVISED - 10-21-08	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	REGION 2 /DISTRICT 2 STANDARD	SCALE: SHEET NO. OF SHEETS STA. TO STA.	F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
		DRAWN -	REVISED -				280	81-11B-1,11B-1B-2,11B-2,11B-3,11B-4	ROCK ISLAND	503	460
MODEL NAME =	PLAT SCALE = 50.0000 1/4" = 1'	CHECKED -	REVISED -				CONTRACT NO. 64815				
D2 Detail 24	PLAT DATE = 07/23/10	DATE - 07/23/10	REVISED -				FED. ROAD DIST. NO. 7 ILLINOIS FED. AID PROJECT 7				