### GENERAL NOTES

THIS SECTION SHALL BE CONSTRUCTED IN ACCORDANCE WITH THE PLANS, THE "STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION", ADOPTED JANUARY 1, 2007; THE "SUPPLEMENTAL SPECIFICATIONS AND RECURRING SPECIAL PROVISIONS" INDICATED ON THE CHECK SHEET, AND "THE SPECIAL PROVISIONS" INCLUDED IN THE PROPOSAL.

THE WORK INCLUDED IN SECTION (13-1)R &(25-6-1)R CONSISTS OF HMA SURFACE REMOVAL, PCC PAVEMENT RUBBLIZATION, PAVEMENT PATCHING, RESURFACING WITH HMA, REPAIRS ON TWO BRIDGE STRUCTURES AND OTHER WORK NECESSARY TO COMPLETE THE SECTION.

PLAN DIMENSIONS AND DETAILS RELATIVE TO THE EXISTING STRUCTURES HAVE BEEN TAKEN FROM EXISTING PLANS AND ARE SUBJECT TO NOMINAL CONSTRUCTION VARIATIONS. IT SHALL BE THE CONTRACTOR RESPONSIBILITY TO VERIFY SUCH DIMENSIONS AND DETAILS IN THE FIELD AND MAKE NECESSARY APPROVED ADJUSTMENTS PRIOR TO THE CONSTRUCTION OR ORDERING OF MATERIAL. SUCH VARIATIONS SHALL NOT BE CAUSE FOR ADDITIONAL COMPENSATION OR A CHANGE IN THE SCOPE OF THE WORK. THE CONTRACTOR WILL BE PAID FOR THE OUANTITY ACTUALLY FURNISHED AT THE UNIT PRICE BID FOR THE WORK.

SHORT TERM PAVEMENT MARKING ON THE MILLED SURFACE SHALL BE PAINT. ALL OTHER SHORT TERM PAVEMENT MARKINGS SHALL BE TAPE.

THE ACTUAL LOCATIONS OF PAVEMENT PATCHING SHALL BE DETERMINED BY THE ENGINEER IN THE FIELD.

ALL DISTURBED AREAS WITHIN THE CONSTRUCTION LIMITS SHALL BE SEEDED AND MULCHED. SEEDING SHALL BE CLASS 2 IN ACCORDANCE WITH THE APPLICABLE ARTICLES OF SECTION 250 OF THE STANDARD SPECIFICATIONS. COST SHALL BE INCLUDED IN THE BID PRICE FOR THE ITEMS CAUSING THE DISTURBANCE.

TREES SHALL BE PRESERVED THROUGHOUT THIS SECTION AS DIRECTED BY THE ENGINEER. THE INFIELDS OF THE EDGEWOOD INTERCHANGE AND THE MEDIAN BETWEEN STATIONS 4455+00 AND 4495+00 ARE PLANTED IN PRAIRIE GRASS AND ARE OFF-LIMITS FOR PARKING AND STORAGE OF MATERIALS AND MACHINERY.

THE LOCATIONS AND/OR DEPTHS OF UNDERGROUND UTILITIES SHOWN HAVE BEEN TAKEN FROM INFORMATION FURNISHED BY THE UTILITY OWNERS AND MUST BE CONSIDERED APPROXIMATE. FIELD MARKINGS OF ACILITIES IN CRITICAL AREAS MAY BE OBTAINED BY PROVIDING A MINIMUM OF 96 HOURS ADVANCE NOTICE THROUGH THE J.U.L.I.E. SYSTEM BY CALLING 800-892-0123.

THE CONTRACTOR SHALL PROVIDE INTERNET ACCESS TO THE BITUMINOUS PLANT QUALITY CONTROL LAB SO THAT BITUMINOUS PLANT REPORTS CAN BE E-MAILED TO THE DISTRICT HEADQUARTERS. THIS WORK WILL NOT BE PAID FOR SEPARATELY BUT SHALL BE INCLUDED IN THE UNIT PRICES FOR OTHER ITEMS IN THE CONTRACT.

THE RESIDENT ENGINEER SHALL BE THE SOLE JUDGE CONCERNING THE CURING TIME FOR THE BITUMINOUS SURFACE COURSE.

THE MATERIAL USED FOR BITUMINOUS MATERIALS (PRIME COAT) SHALL BE RC-70, SS-1H, OR SS-1HP APPLIED AT THE RATE DIRECTED BY THE ENGINEER. THE CONTRACTOR WILL BE REQUIRED TO FOG COAT ALL BINDER LIFTS WITH SS-1HP. THE TOP OF THE RUBBLIZED PAVEMENT WILL NOT BE PRIMED.

A MATERIAL TRANSFER DEVICE SHALL BE USED ON THE FINAL LIFT OF BINDER (2.25") AND ON THE SMA SURFACE LIFT (2") THROUGHOUT THE MAINLINE INTERSTATE PORTION OF THE PROJECT. USE OF A MATERIAL TRANSFER DEVICE ON THE RUBBLIZED PCC WILL BE PROHIBITED. A LOADED MATERIAL TRANSFER DEVICE MAY CROSS STRUCTURES 025-0067 AND 025-0069.

THE FACTOR USED TO COMPUTE THE QUANTITY OF THE STONE MATRIX ASPHALT SURFACE COURSE IS 130 POUNDS PER SQUARE YARD PER INCH AND 112 POUNDS PER SQUARE YARD PER INCH FOR ALL OTHER MIXES.

TOP LIFT OF HMA PAVEMENT (FULL-DEPTH) SHALL BE CONSTRUCTED USING POLYMERIZED HMA SURFACE COURSE, SMA. COST SHALL BE INCLUDED IN THE BID PRICE FOR HMA PAVEMENT (FULL-DEPTH).

AGGREGATE FOR AGGREGATE SHOULDERS SHALL BE CRUSHED STONE OR CRUSHED CONCRETE.

COST OF REMOVAL OF EXISTING GUARD POSTS SHALL BE INCLUDED IN THE UNIT PRICE FOR GUARD POST.

COST OF REMOVAL OF TEMPORARY RAMP SHALL BE INCLUDED IN THE UNIT PRICE FOR TEMPORARY RAMP.

THE FOLLOWING MIXTURE REQUIREMENTS ARE APPLICABLE TO THIS PROJECT:

APPLICATION	AC/PG	DESIGN AIR VOIDS	MIXTURE COMPOSITION	FRICTION AGGREGATE
POLYMERIZED HMA SURFACE COURSE, SMA, N8O	SBS PG 76-22	4.0% @ N=80	IL - 12.5	N/ A
POLYMERIZED HMA SURFACE COURSE, MIX "D", N105	SBS PG 70-22	4.0% @ N=105	IL - 9.5	MIX D
HMA SURFACE COURSE, MIX "C", N70	PG 64-22	4.0% @ N=70	IL - 9.5	MIX C
POLYMERIZED HMA BINDER COURSE, IL-19.0, N105	SBS PG 70-22	4.0% @ N=105	IL - 19.0	N/ A
HMA BINDER COURSE, IL-19.0, N90	PG 64-22	4.0% @ N=90	IL - 19.0	N/ A
HMA BINDER COURSE IL-19.OL, N3O	PG 64-22	4.0% @ N=30	IL - 19.0L	N/ A
HMA SHOULDERS	PG 64-22	4.0% @ N=30	IL - 9.5L	N/A
HMA LEVELING BINDER	PG 64-22	4.0% @ N=70	IL - 9.5	N/A
HMA SHOULDERS, 13"	PG 64-22	4.0% @ N=70	IL - 19.0	N/ A
CLASS D PATCHING	PG 64-22	4.0% @ N=90	IL - 19.0	N/A

#### 

# STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION

# GENERAL NOTES & F.A.I. RTE. INDEX OF SHEETS SHEET NO. OF SHEETS STA. TO STA.

### 

## INDEX OF SHEETS

44

SHEET NO TITLE COVER SHEET GENERAL NOTES. INDEX OF SHEETS SUMMARY OF QUANTITIES EXISTING TYPICAL SECTIONS PROPOSED TYPICAL SECTIONS - MAINLINE PROPOSED TYPICAL SECTIONS - RAMPS & CH 29 STAGE CONSTRUCION DETAILS BUTT JOINT & TRANSITION DETAILS 1.0 MISCELLANEOUS DETAILS RESURFACING SCHEDULE PAVEMENT MARKING SCHEDULE MISCELLANEOUS QUANTITY SCHEDULES 13 PLAN SHEETS - MAINLINE 14-19 PLAN SHEET - CH 29 21 PLAN SHEET - RAMPS 22 DETOUR SIGNING SN 025-0067 BRIDGE REHABILITATION 23-32 33-42 SN 025-0069 BRIDGE REHABILITATION OUTLET PROTECTOR DETAILS 43

TYPICAL PAVEMENT MARKING DETAILS

THE FOLLOWING STANDARDS ARE A PART OF THESE PLANS AND ARE INCLUDED FOLLOWING THE LAST NUMBERED SHEET OF THE PLANS.

000001-06 STANDARD SYMBOLS, ABBREVIATIONS, AND PATTERNS 001001-02 AREAS OF REINFORCEMENT BARS 001006 DECIMAL OF AN INCH AND OF A FOOT 442201-03 CLASS C AND D PATCHES 515001-03 NAME PLATE FOR BRIDGES 542301-03 PRECAST REINFORCED CONCRETE FLARED END SECTION 601001-04 SUB-SURFACE DRAINS 601101-01 CONCRETE HEADWALL FOR PIPE DRAIN 602301-03 INLET, TYPE A 604066-02 FRAME AND LID, TYPE 15 606001-04 CONCRETE CURB TYPE B AND COMBINATION CONCRETE CURB AND GUTTER 630001-09 STEEL PLATE BEAM GUARDRAIL 631011-07 TRAFFIC BARRIER TERMINAL, TYPE 2 631031-09 TRAFFIC BARRIER TERMINAL, TYPE 6 631033-04 TRAFFIC BARRIER TERMINAL, TYPE 6B 635001-01 DELINEATORS 635006-03 REFLECTOR AND TERMINAL MARKER PLACEMENT 635011-02 REFLECTOR MARKER AND MOUNTING DETAILS 642001-01 SHOULDER RUMBLE STRIPS 701011-02 OFF-ROAD MOVING OPERATIONS, 2L, 2W, DAY ONLY 701101-02 OFF-ROAD OPERATIONS, MULTILANE, 15' TO 24" FROM PAVEMENT EDGE 701201-04 LANE CLOSURE, 2L, 2W, DAY ONLY, FOR SPEEDS >= 45 MPH 701301-04 LANE CLOSURE, 2L, 2W, SHORT TIME OPERATIONS 701306-03 LANE CLOSURE, 2L, 2W, SLOW MOVING OPERATIONS DAY ONLY, FOR SPEEDS >= 45 MPH 701311-03 LANE CLOSURE, 2L, 2W, MOVING OPERATIONS - DAY ONLY 701336-06. LANE CLOSURE, 2L, 2W, WORK AREAS IN SERIES, FOR SPEEDS >= 45 MPH 701400-05 APPROACH TO LANE CLOSURE, FREEWAY/EXPRESSWAY 701401-06 LANE CLOSURE, FREEWAY/EXPRESSWAY 701402-08 LANE CLOSURE, FREEWAY/EXPRESSWAY, WITH BARRIER 701406-06 LANE CLOSURE, FREEWAY/EXPRESSWAY, DAY OPERATIONS ONLY 701411-07 LANE CLOSURE, MULTILANE, AT ENTRANCE OR EXIT RAMP, FOR SPEEDS >= 45 MPH 701451-01 RAMP CLOSURE, FREEWAY/EXPRESSWAY 701456-01 PARTIAL EXIT RAMP CLOSURE, FREEWAY/EXPRESSWAY 701901-01 TRAFFIC CONTROL DEVICES 704001-06 TEMPORARY CONCRETE BARRIER 720011-01 METAL POSTS FOR SIGNS, MARKERS AND DELINEATORS 780001-02 TYPICAL PAVEMENT MARKINGS 781001-03 TYPICAL APPLICATIONS RAISED REFLECTIVE PAVEMENT MARKERS 701426-04