# INDEX OF SHEETS

## SHEET

### DESCRIPTION

- 1 COVER SHEET
- 2 INDEX, GENERAL NOTES AND HIGHWAY STANDARDS
- 3 SUMMARY OF QUANTITIES
- 4 TYPICAL SECTIONS
- 5-7 ROADWAY AND PAVEMENT MARKING PLANS
- 8 PAVEMENT PATCHING FOR HMA SURFACED PAVEMENT (BD22)
- 9 BUTT JOINTS AND BITUMINOUS TAPER (BD32)
- 10 TRAFFIC CONTROL AND PROTECTION FOR SIDEROADS, INTERSECTIONS AND DRIVEWAYS (TC10)
- 11 RAISED REFLECTIVE PAVEMENT MARKERS (SNOW PLOW RESISTANT) (TC11)
- 12 DISTRICT ONE TYPICAL PAVEMENT MARKINGS (TC13)
- 13 ARTERIAL ROAD INFORMATION (TC22)

# HIGHWAY STANDARDS

STD. NO. TITLE

442201-03 CLASS C AND D PATCHES

606001-04 CONCRETE CURB TYPE B AND COMBINATION CONCRETE CURB AND GUTTER

630001-09 STEEL PLATE BEAM GUARDRAIL

635006-03 REFLECTOR AND TERMINAL MARKER PLACEMENT

701006-03 OFF-ROAD OPERATIONS, 2L, 2W, 4.5 m (16') TO 600 mm (24") FROM PAVEMENT EDGE

701301-04 LANE CLOSURE, 2L, 2W, SHORT TIME OPERATIONS

701326-04 LANE CLOSURE, 2L, 2W, PAVEMENT WIDENING, FOR SPEEDS ≥ 45 MPH

701501-06 URBAN LANE CLOSURE, 2L, 2W, UNDIVIDED

780001-02 TYPICAL PAVEMENT MARKINGS
 781001-03 TYPICAL APPLICATIONS RAISED REFLECTIVE PAVEMENT MARKERS

701901~0/ TRAFFIC CONTROL DEVICES

### GENERAL NOTES

- BEFORE STARTING ANY EXCAVATION, THE CONTRACTOR SHALL CALL "J.U.L.I.E."
   AT 800-892-0123 FOR FIELD LOCATIONS OF BURIED ELECTRIC, TELEPHONE AND GAS FACILITIES. (48 HOUR NOTIFICATION IS REQUIRED).
- 2. THE CONTRACTOR SHALL COORDINATE CONSTRUCTION ACTIVITIES WITH UTILITY COMPANIES.
- 3. THE CONTRACTOR WILL NOT BE ALLOWED TO SET UP A YARD OR FIELD OFFICE ON STATE PROPERTY WITHOUT WRITTEN PERMISSION FROM THE DEPARTMENT.
- 4. WHEN ARTIFICIAL LIGHTING IS USED IN NIGHT OPERATIONS THE CONTRACTOR SHALL EXERCISE THE UTMOST PRECAUTIONS IN PREVENTING ADVERSE VISIBILTY TO THE MOTORING PUBLIC AND ADJOINING RESIDENTIAL AREAS.
- 1. WHEN MILLED PAVEMENT IS OPEN TO TRAFFIC THE MAXIMUM GRADE DIFFERENTIAL BETWEEN PASSES OF THE MILLING MACHINE SHALL NOT EXCEED 1 1/2 INCHES (40 MM) WHERE THE SPEED LIMIT IS 45 MPH (80 KM/H) OR LESS AND 1 INCH (25 MM) WHERE THE SPEED LIMIT IS GREATER THAN 45 MPH (80 KM/H). WITH WRITTEN APPROVAL FROM THE ENGINEER, A MAXIMUM GRADE DIFFERENTIAL OF 3 INCHES (75 MM) MAY BE ALLOWED IF THE EDGE OF THE MILLING IS SLOPED A MINIMUM 1:3 (V:H).
- 6. BUTT JOINTS WILL BE INSTALLED AT THE ENDS OF ALL RESURFACING (WHERE RESURFACING MEETS EXISTING PAVEMENT), IN ACCORDANCE WITH THE "BUTT JOINT AND HMA TAPER DETAILS" SHEET INCLUDED IN THE PLANS, UNLESS OTHERWISE SPECIFIED.
- 7. FOR PAVEMENT MARKING AND RAISED REFLECTIVE PAVEMENT MARKERS, REFER TO DISTRICT ONE TYPICAL MARKINGS FOR DETAILS NOT SHOWN.
- 8. THE RESIDENT ENGINEER SHALL CONTACT THE TRAFFIC CONTROL SUPERVISOR AT (847) 705-4470 A MINIMUM 72 HOURS PRIOR TO THE PLACEMENT OF ANY TEMPORARY TRAFFIC CONTROL DEVICES.
- 9. MATCH EXISTING PAVEMENT MARKINGS AT PROJECT LIMITS.
- 10. THE RESIDENT ENGINEER SHALL CONTACT LAWRENCE HILL, AREA TRAFFIC FIELD ENGINEER, AT (815) 485-6475 AT LEAST (2) WEEKS PRIOR TO PLACING PERMANENT PAVEMENT MARKINGS.
- 11. BEFORE BEGINNING ANY WORK, THE CONTRACTOR SHALL RETAIN AND RECORD FOR FUTURE REFERENCE, ALL EXISTING PAVEMENT MARKING LINES (AND RAISED REFLECTIVE PAVEMENT MARKERS) IN ORDER THAT THESE LOCATIONS CAN BE REESTABLISHED FOR STRIPING, EXACT LOCATIONS OF ALL PAVEMENT MARKINGS SHALL BE AS DIRECTED BY THE ENGINEER.

CONTRACT NO. 60L59

FILE NAME =	USER NAME = _USER_	DEŚIGNED -	AR/EF	REVISED -
\$FILEL\$	And the second s	DRAWN -	AR/EF	REVISED -
	PLOT SCALE = 50.0000 '/ IN.	CHECKED -	- RS	REVISED -
	PLOT DATE = 9/7/2010	DATE -	10-16-2010	REVISED -

STATE	OF	ILLINOIS
DEPARTMENT	OF .	TRANSPORTATION

SCALE:

IL 113 - COAL CITY RD TO MAIN ST.	F.A.S. RTE.	SECTION
IDEX OF SHEETS, HIGHWAY STANDARDS AND GENERAL NOTES	2320	113X-RS-4
SHEET NO. 1 OF 1 SHEETS STA. TO STA.	and all the same of the same o	ILLINOI: