

NOTES

Detail I - With Bar Splicer or Couplers: Connect one (1) 1" x 7" 'x "W" steel 12 to the top layer of couplers with $2^{-5}8'' \phi$ bolts screwed to coupler at approximate Q of each barrier panel.

Detail II - With Extended Reinforcement Bars:


Connect one (l) 1" x 7" x "W" steel \mathbb{P} to the concrete


slab or concrete wearing surface with 2-5g" \phi Expansion Anchors or cast in place inserts spaced between the top layer of reinforcement at approximate Q of each barrier panel.

Cost of anchorage is included with Temporary Concrete Barrier. The 1" x 7" x "W" plate shall not be removed until stage II construction forms and all reinforcement bars are in place and the concrete is ready to be placed.

SECTIONS THRU SLAB OR DECK BEAM

- *** Dimension shown is minimum required embedment into concrete. If hot-mix asphalt wearing surface is present, minimum embedment shall be in addition to wearing surface depth.
- **** If existing deck beam is to remain in place after stage construction, embedment shall only be into wearing surface and not into existing deck beam concrete.





EXISTING DECK BEAM

"W" Top bars – Detail I spacing – Detail II -@ ⁷8'' ¢ Holes *@ 1" x 12" Notch

STEEL RETAINER P 1" x 7" x "W"

* Required only with Detail II

** Wood blocks may be omitted when required to provide minimum stage traffic lane width. When the wood blocks are omitted, the concrete barrier shall be in direct contact with the steel retainer plate.

"W" = Top bars spacing + 4"

R-27

7-1-10

	Bollinger, Lach & Associates, Inc.	U
l D		
	itasca. Illinois	Ρ
	HASCA, ILLINOIS	Р

	USER NAME =	DESIGNED -	REVISED
		CHECKED -	REVISED
•	PLOT SCALE =	DRAWN - GM	REVISED
	PLOT DATE = 8/15/2013	CHECKED - JJI	REVISED

STATE	OF ILLINOIS
DEPARTMENT O	F TRANSPORTATION

TEMPORARY BARRIER DETAILS STRUCTURE NO. 016-3035						
SHEET NO. 8 OF 62 SHEETS						

A.P. TE.	SECTION		COUNTY	TOTAL SHEETS	SHEET NO.			
307	7 541Y-3-B		COOK	143	69			
CONTRACT NO. 60J1								
ILLINOIS FED. AID PROJECT								