



# Illinois Department of Transportation

2300 South Dirksen Parkway / Springfield, Illinois / 62764

February 21, 2014

SUBJECT: FAP 347 (Roosevelt Road)  
Section 12-00079-00-SW (Broadview)  
Cook County  
Contract No. 63768  
Item 061  
February 28, 2014 Letting  
Addendum (A)

## NOTICE TO PROSPECTIVE BIDDERS:

Due to clarify information necessary to revise the following:

### **1. Revised page 6 of the Special Provisions.**

Prime contractors must utilize the enclosed material when preparing their bid and must include any Schedule of Prices changes in their bidding proposal.

Bidders using computer-generated bids are cautioned to reflect any and all Schedule of Prices changes, if involved, into their computer programs.

Very truly yours,

John Baranzelli, P.E.  
Acting Engineer of Design and Environment

A handwritten signature in black ink, reading "Ted B. Walschleger P.E." with a stylized flourish at the end.

By: Ted B. Walschleger, P.E.  
Engineer of Project Management

Basis of Payment: This item shall be paid for at the Contract Unit Price per Square Yard for PORTLAND CEMENT CONCRETE BASE COURSE 8”.

### **INCIDENTAL HOT-MIX ASPHALT SURFACING**

This item includes the installation of hot-mix asphalt surface course in areas adjacent to the proposed concrete sidewalk and driveway pavement improvements. It shall typically be used to restore small sections of asphalt areas that are disturbed by the construction of the proposed improvements. It shall not include the asphalt placed within the street pavement. **PLEASE NOTE THE QUANTITY LISTED IN THE SCHEDULE OF PRICES IS INCORRECT AND THE ANTICIPATED IN PLACE QUANTITY FOR THIS ITEM IS 60 TONS.**

The asphalt thickness shall typically be 3”. The asphalt shall be installed in accordance with Section 406 of the Standard Specifications.

Basis of Payment: This item shall be paid for at the Contract Unit Price per Ton for INCIDENTAL HOT MIX ASPHALT SURFACING.

### **PROTECTIVE COAT**

This item includes the placement of protective coat on all exposed concrete surfaces at locations shown on the plans or as directed by the Engineer. Regardless of when the concrete is poured, a protective coat shall be applied to all concrete curb and gutter, driveways, concrete pavement, and sidewalks in accordance with the requirements of Section 421 of the Standard Specifications.

Two successful applications will need to be made prior to payment being made. The contractor will be responsible for staging the application of the protective coat so as not to have it tracked into businesses.

Basis of Payment: This item shall be paid for at the Contract unit price per Square Yard of PROTECTIVE COAT.

### **PORTLAND CEMENT CONCRETE DRIVEWAY PAVEMENT, 8 INCH**

This item shall consist of the placement of eight-inch (8”) concrete driveway pavement at locations shown on the plans and as directed by the Engineer. The work shall be performed in accordance with Section 423 of the “Standard Specifications for Road and Bridge Construction”.

The driveway shall be placed upon compacted crushed stone bedding, Gradation CA-6, having a minimum thickness of two inches (2”). The cost for the 2” stone cushion shall be included in this item.

Full depth expansion joints shall be placed between the driveway pavement and the back of any adjacent curb, sidewalk, or buildings, and as directed by the Engineer.