

= PARTIAL DEPTH REMOVAL

AIR EQUIPMENT OR MECHANICAL SWEEPER REMOVAL OF LOOSE AND/OR UNSOUND CONCRETE

GENERAL NOTES

ALL VOLUME OF PARTIAL DEPTH REMOVAL SHALL BE REPLACED WITH HOT-MIX ASPHALT (HMA) AND PAID FOR AT THE CONTRACT UNIT PRICE PER TON FOR PARTIAL DEPTH PATCHING.

(of the thickness specified)

T = THICKNESS OF HMA OVERLAY(S). SEE EXISTING TYPICAL

GENERAL NOTE 406H SHALL INCLUDE MIXTURE REQUIREMENTS

HMA REPLACEMENT IN RESURFACED PCC PAVEMENT LOCATIONS SHALL BE ACCORDING TO SECTION 406 OF THE STANDARD

DEPTH OF PARTIAL DEPTH REMOVAL DOES NOT EXTEND INTO EXISTING PCC PAVEMENT. WHERE PCC PAVEMENT IS ENCOUNTERED BETWEEN MIN. AND MAX. DEPTHS, THE MILL WILL BE HELD TO A DEPTH WHICH JUST ROUGHENS THE SURFACE OF THE EXISTING PCC.

WHERE REINFORCING STEEL IS ACCIDENTALLY EXPOSED, IT SHALL BE REMOVED IN ACCORDANCE WITH CHECKSHEET #15

TRANSVERSE CONTRACTION JOINT SHOWN - OTHER LOCATIONS

Note: All dimensions are in INCHES (millimeters) unless otherwise shown.

PHALI PAICHING 29 29 . TO STA. FED. ROAD DIST. NO. ILLINOIS/FED. AID PROJECT		F.A. RTE.	SECTION			COUNTY	TOTAL SHEETS	SHEET NO.	
	PHALT PATCHING							29	29
TO STA. FED BOAD DIST NO TILINOIS FED AD PROJECT						CONTRACT NO. 70A38			
	. TO STA.	FED. RO	AD DIST.	NO.	ILLINOIS	FED. A	ID PROJECT		