INDEX OF SHEETS

36

37

STATE STANDARDS

	SHEET NO.	DESCRIPTION	<u>s1</u>	TANDARD NO. DESCRIPTION
	1	TITLE SHEET		000001-05 TYPICAL SYMBOLS, ABBREVIATIONS AND PATTERNS
	2	INDEX OF SHEETS, STATE STANDARDS & GENERAL NOTES		420001-07 PAVEMENT JOINTS
	3-4	SUMMARY OF QUANTITIES		420701-02 PAVEMENT FABRIC
	5-7	EXISTING AND PROPOSED TYPICAL SECTIONS		442101-07 CLASS B PATCHES
	8-16	ROADWAY AND PAVEMENT MARKING PLANS		442201-03 CLASS C AND D PATCHES
	17-23	DETECTOR LOOP REPLACEMENT PLANS		604001-03 FRAME AND LIDS, TYPE 1
	24	DRIVEWAY DETAILS DISTANCE BETWEEN ROW AND FACE OF CURB < 15	5'	604086-02 FRAME AND GRATE, TYPE 23
	25	DETAILS FOR FRAME AND LIDS ADJUSTMENT WITH MILLING		604091-02 FRAME AND GRATE, TYPE 24
	26	PAVEMENT PATCHING FOR HMA SURFACED PAVEMENT		606001-04 CONCRETE CURB AND COMBINATION CONCRETE CURB AND GUTTER
	27	CURB OR CURB AND GUTTER REMOVAL AND REPLACEMENT		606306-03 CORRUGATED PC CONCRETE MEDIANS
	28	BUTT JOINT AND HMA TAPER		630301-05 SHOULDER WIDENING FOR TYPE 1 (SPECIAL) GUARDRAIL TERMINALS
	29	HMA TAPER AT EDGE OF P.C.C. PAVEMENT		635006-03 REFLECTOR AND TERMINAL MARKER PLACEMENT
	70	TRAFFIC CONTROL AND PROTECTION FOR SIDE ROADS,		701426-03 LANE CLOSURE, MULTILANE, INTERMITTENT OR MOVING OPERATIONS
	30	INTERSECTIONS AND DRIVEWAYS		701606-00 URBAN LÂNE CLOSURE, MULTILANE 2W WITH MOUNTABLE MEDIAN
	31	TYPICAL APPLICATIONS: RAISED REFLECTIVE PAVEMENT MARKERS (SNOW-PLOW RESISTANT)		701701-00 URBAN LANE CLOSURE, MULTILANE INTERSECTION
	32	DISTRICT ONE TYPICAL PAVEMENT MARKINGS		701901-01 TRAFFIC CONTROL DEVICES
	33	TRAFFIC CONTROL AND PROTECTION OF TURN BAYS		886001-0/ DETECTOR LOOP INSTALLATION
	33	(TO REMAIN OPEN TO TRAFFIC)		886006-01 TYPICAL LAYOUT FOR DETECTION LOOPS
	34	PAVEMENT MARKING LETTERS AND SYMBOLS FOR TRAFFIC STAGING		
	35	ARTERIAL INFORMATION SIGNING		

GENERAL NOTES

BEFORE STARTING ANY EXCAVATION, THE CONTRACTOR SHALL CALL "JULIE" AT (800) 892-0123 OR 811 FOR FIELD LOCATIONS OF BURIED ELECTRIC, TELEPHONE, AND GAS FACILITIES. (48 HOUR NOTIFICATION REQUIRED)

THE CONTRACTOR WILL NOT BE ABLE TO SET UP A YARD OR FIELD OFFICE ON STATE PROPERTY WITHOUT THE WRITTEN PERMISSION OF THE DEPARTMENT.

BUTT JOINTS WILL BE INSTALLED AT THE ENDS OF RESURFACING (WHERE RESURFACING MEETS EXISTING PAVEMENT) IN ACCORDANCE WITH THE "BUTT JOINT AND HMA TAPER DETAILS" SHEET INCLUDED IN THE PLANS UNLESS OTHERWISE SPECIFIED.

WHEN MILLED PAVEMENT IS OPEN TO TRAFFIC, THE MAXIMUM GRADE DIFFERENTIAL BETWEEN PASSES OF THE MILLING MACHINE SHALL NOT EXCEED 1½ INCHES WHERE THE SPEED LIMIT IS 45 MPH OR LESS, AND 1 INCH WHERE THE SPEED LIMIT IS OVER 45 MPH. WITH WRITTEN APPROVAL FROM THE RESIDENT ENGINEER, A MAXIMUM GRADE DIFFERENTIAL OF 3 INCHES MAY BE ALLOWED IF THE EDGE OF THE MILLING IS SLOPED A MINIMUM OF 1:3 (V:H).

WHEN ARTIFICIAL LIGHTING IS UTILIZED IN NIGHT OPERATIONS, THE CONTRACTOR SHALL EXERCISE THE UTMOST PRECAUTIONS IN PREVENTING ADVERSE VISABILITY TO THE MOTORING PUBLIC AND ADJOINING RESIDENTIAL AREAS.

ALL PAVEMENT PATCHING AND CURB AND GUTTER REMOVAL AND REPLACEMENT LOCATIONS WILL BE DETERMINED IN THE FIELD BY THE ENGINEER.

BEFORE BEGINNING ANY WORK, THE CONTRACTOR SHALL RETAIN AND RECORD FOR FUTURE REFERENCE, ALL EXISTING PAVEMENT MARKING LINES (AND RAISED REFLECTIVE PAVEMENT MARKERS) IN ORDER THAT THESE LOCATIONS CAN BE RE-ESTABLISHED FOR STRIPING. EXACT LOCATIONS OF ALL PAVEMENT MARKINGS SHALL BE AS DIRECTED BY THE ENGINEER.

DOUBLE LANE MARKERS ARE TO BE USED AS SHOWN ON THE DISTRICT ONE DETAIL "TYPICAL APPLICATIONS - RAISED REFLECTIVE PAVEMENT MARKERS (SNOW-PLOW RESISTANT)" SNOWN IN THE PLANS.

THE RESIDENT ENGINEER SHALL CONTACT MS. CORA MATHIS, AREA TRAFFIC FIELD ENGINEER, AT (815) 485-6475 A MINIMUM OF 2 WEEKS PRIOR TO PLACEMENT OF FINAL PAVEMENT MARKINGS.

THE RESIDENT ENGINEER SHALL CONTACT THE TRAFFIC CONTROL SUPERVISOR AT (847) 705-4470 A MINIMUM OF 72 HOURS PRIOR TO THE INSTALLATION OF ANY TEMPORARY TRAFFIC CONTROL DEVICES.

THE CONTRACTOR SHALL COORDINATE CONSTRUCTION ACTIVITIES WITH UTILITY COMPANIES AND THE VILLAGES OF UNIVERSITY PARK, RICHTON PARK AND MATTESON.

FILE NAME =	USER NAME = smithkl	DESIGNED -	REVISED -			
c:\pw_work\PWIDOT\SMITHKL\d0146173\D183309-sht-plan.dgn		DRAWN -	REVISED -			
	PLOT SCALE = 50.0000 '/ IN.	CHECKED -	REVISED -			
	PLOT DATE = 12/5/2009	DATE -	REVISED -			

DISTRICT ONE STANDARD TRAFFIC SIGNAL DESIGN

ROADWAY RESURFACING

DISTRICT 1 DETECTOR LOOP INSTALLATION DETAILS FOR

	STATE	OF	ILLINOIS
DEPART	MENT	OF '	TRANSPORTATION

SCALE:

GOVERNORS HWY (IL 50 TO US 30)	F.A.U. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
INDEX OF SHEETS, STATE STANDARDS AND GENERAL NOTES	3778	144 RS-5	WII . & COOK	37	2
MULA OF SHELIS, STATE STANDARDS AND GENERAL NOTES			CONTRACT	NO. 6	50H93
SHEET NO. OF SHEETS STA. TO STA.		ILLINOIS FED. AI	D PROJECT		