


**INDEX OF SHEETS**

- 1. COVER SHEET
- 2. GENERAL NOTES
- 3 - 5. SUMMARY OF QUANTITIES
- 6. TYPICAL SECTIONS
- 7. SCHEDULES
- 8. TRAFFIC CONTROL AND PROTECTION, STANDARD 701400
- 9 - 10. TRAFFIC CONTROL AND PROTECTION, STANDARD 701402
- 11 - 18. STRUCTURE PLANS FOR STRUCTURE NO. 050-0210 (SB) AND STRUCTURE NO. 050-0211 (NB)
- 19 - 29. STRUCTURE PLANS FOR STRUCTURE NO. 050-0212 (SB) AND STRUCTURE NO. 050-0213 (NB)
- 30. MICELLANEOUS DETAILS

**STANDARDS**

- 000001-08 STANDARD SYMBOLS, ABBREVIATIONS AND PATTERNS
- 001001-02 AREAS OF REINFORCEMENT BARS
- 001006 DECIMAL OF AN INCH AND OF A FOOT
- 420001-09 PAVEMENT JOINTS
- 420701-03 PAVEMENT WELDED WIRE REINFORCEMENT
- 421001-03 BAR REINFORCEMENT FOR CRC PAVEMENT
- 483001-05 PCC SHOULDER
- 630001-12 STEEL PLATE BEAM GUARDRAIL
- 631026-06 TRAFFIC BARRIER TERMINAL, TYPE 5
- 631031-17 TRAFFIC BARRIER TERMINAL, TYPE 6
- 701101-05 OFF-ROAD OPERATIONS, MULTILANE, 15' (4.5 m) TO 24" (600 mm) FROM PAVEMENT EDGE
- 701106-02 OFF-ROAD OPERATIONS, MULTILANE, MORE THAN 15' (4.5 m) AWAY
- 701426-09 LANE CLOSURE, MULTILANE INTERMITTENT OR MOVING OPERATION, FOR SPEEDS ≥ 45 MPH
- 701428-01 TRAFFIC CONTROL, SETUP AND REMOVAL, FREEWAY/EXPRESSWAY
- 701901-08 TRAFFIC CONTROL DEVICES
- 704001-08 TEMPORARY CONCRETE BARRIER
- 782001-01 PRISMATIC CURB REFLECTORS
- 782006-01 GUARDRAIL AND BARRIER WALL REFLECTOR MOUNTING DETAILS
- 610001-09 SHOULDER INLET WITH CURB



FULL SIZE PLANS HAVE BEEN PREPARED USING STANDARD ENGINEERING SCALES. REDUCED SIZED PLANS WILL NOT CONFORM TO STANDARD SCALES. IN MAKING MEASUREMENTS ON REDUCED PLANS, THE ABOVE SCALES MAY BE USED.

J.U.L.I.E.  
JOINT UTILITY LOCATION INFORMATION FOR EXCAVATION  
1-800-892-0123  
OR 811

**PROJECT ENGINEER JOE KANNEL P.E.**  
**UNIT CHIEF RON WOODSHANK**  
DISTRICT 3 NO. (815) 434-6131  
CONTRACT NO. 66L17

STATE OF ILLINOIS  
DEPARTMENT OF TRANSPORTATION


**PROPOSED  
HIGHWAY PLANS**

F.A.I. ROUTE 39 (I-39)  
SECTION (50-1VB & 50-1B)BRR  
BRIDGE EXPANSION JOINT &  
APPROACH SLAB REPLACEMENT  
LASALLE COUNTY

C-93-103-20

**PROJECT LOCATION #1**  
STRUCTURE NO. 050-0210 (SB) &  
STRUCTURE NO. 050-0211 (NB)  
CARRYING F.A.I. ROUTE 39 (I-39)  
OVER THE NOR-FOLK SOUTHERN RAILWAY  
1.48 MILES NORTH OF IL ROUTE 18


**PROJECT LOCATION #2**  
STRUCTURE NO. 050-0212 (SB) &  
STRUCTURE NO. 050-0213 (NB)  
CARRYING F.A.I. ROUTE 39 (I-39)  
OVER SANDY CREEK  
1.23 MILES NORTH OF IL ROUTE 18



POINT LOCATION

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
39	(50-1VB & 50-1B)BRR	LASALLE	1	30
		ILLINOIS	CONTRACT NO. 66L17	

D-93-069-20



LOCATION OF SECTION INDICATED THUS: - [black rectangle] -

**FUNCTIONAL CLASSIFICATION**

RURAL - INTERSTATE  
F.A.I. ROUTE 39 (I-39)  
2019 ADT = 18400  
P.V. 87.0% S.U. 5.0% M.U. 8.0%

STATE OF ILLINOIS  
DEPARTMENT OF TRANSPORTATION

SUBMITTED December 17, 2020  
*[Signature]*  
REGIONAL ENGINEER  
January 29, 2021  
*[Signature]*  
ENGINEER OF DESIGN AND ENVIRONMENT  
January 29, 2021  
*[Signature]*  
DIRECTOR OF HIGHWAYS PROJECT IMPLEMENTATION

PRINTED BY THE AUTHORITY  
OF THE STATE OF ILLINOIS

**GENERAL NOTES**

SHORT TERM PAVEMENT MARKING SHALL BE USED TO OUTLINE THE CENTERLINE AND SHOULDER DIAGONALS PRIOR TO PLACEMENT OF PERMANENT PAVEMENT MARKINGS.

THE FOLLOWING RATES OF APPLICATION HAVE BEEN USED IN CALCULATING PLAN QUANTITIES:

SHORT TERM PAVEMENT MARKING	10	FT /100 FT OF APPLICATION
-----------------------------	----	---------------------------

**COMMITMENTS**

STATE OF ILLINOIS  
DEPARTMENT OF TRANSPORTATION  
DISTRICT THREE  
AS BUILT INFORMATION

\_\_\_\_\_  
SUPERVISING CONSTRUCTION FIELD ENGINEER

\_\_\_\_\_  
RESIDENT ENGINEER / TECHNICIAN

START & END DATES  
OF CONSTRUCTION:

INSPECTORS:

\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

STATE OF ILLINOIS  
DEPARTMENT OF TRANSPORTATION  
DISTRICT THREE

PREPARED BY: \_\_\_\_\_  
DISTRICT STUDIES & PLANS ENGINEER

DATE: \_\_\_\_\_

EXAMINED BY: \_\_\_\_\_  
DISTRICT CONSTRUCTION ENGINEER

\_\_\_\_\_  
DISTRICT MATERIALS ENGINEER

\_\_\_\_\_  
DISTRICT OPERATIONS ENGINEER

MODEL: Default  
FILE: \\nas101.cpe.ppublanroom.dta.illinois.gov\PI\DOT\Documents\DOT\_Offices\District 3\Projects\0366L17\Cadd\0366L17-cover.dgn

USER NAME = woodshankr1	DESIGNED - RW	REVISED -
	DRAWN - RW	REVISED -
PLOT SCALE = 100.0000 ' / in.	CHECKED - EM	REVISED -
PLOT DATE = 12/17/2020	DATE - 8/5/2020	REVISED -

**STATE OF ILLINOIS  
DEPARTMENT OF TRANSPORTATION**

**GENERAL NOTES**

SCALE: SHEET 1 OF 1 SHEETS STA. TO STA.

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
39	(50-1VB & 50-1B)BRR	LASALLE	30	2
CONTRACT NO. 66L17				
		ILLINOIS	FED. AID PROJECT	

CODE NO.	ITEM	UNIT	TOTAL QUANTITY	CONSTRUCTION CODE	
				07E0	07A0
				100% STATE BRIDGE	100% STATE BRIDGE
				0047	0047
		S.N. 050-0210/0211	S.N. 050-0212/0213		
4200060	WELDED WIRE REINFORCEMENT	SQ YD	472	98	374
4200080	PAVEMENT CONNECTOR (PCC) FOR BRIDGE APPROACH SLAB	SQ YD	1980	684	1296
44004250	PAVED SHOULDER REMOVAL	SQ YD	816	272	544
44213208	TIE BARS 1 1/4"	EACH	234	78	156
50102400	CONCRETE REMOVAL	CU YD	65.6	42	23.6
50300225	CONCRETE STRUCTURES	CU YD	78.6	26.6	52
50300255	CONCRETE SUPERSTRUCTURE	CU YD	65	42	23
50300260	BRIDGE DECK GROOVING	SQ YD	2832	944	1888
50300300	PROTECTIVE COAT	SQ YD	2880	984	1896
50301350	CONCRETE SUPERSTRUCTURE (APPROACH SLAB)	CU YD	280.8	115.6	165.2
50800205	REINFORCEMENT BARS, EPOXY COATED	POUND	181,840	61,840	120000
50800515	BAR SPLICERS	EACH	1310	510	800
52000110	PREFORMED JOINT STRIP SEAL	FOOT	336	168	168
63300575	REMOVE AND REERECT RAIL ELEMENT OF EXISTING GUARDRAIL	FOOT	30		30

MODEL: Default  
 FILE: M:\GIS\Projects\GIS\Projects\DOT - Office\District 3\Project\03366L17\CD\03366L17-cover.dwg

USER NAME = woodshankr	DESIGNED - RW	REVISED -
PLOT SCALE = 100.0000' / in.	DRAWN - RW	REVISED -
PLOT DATE = 12/17/2020	CHECKED - EM	REVISED -
	DATE - 8/5/2020	REVISED -

**STATE OF ILLINOIS  
DEPARTMENT OF TRANSPORTATION**

**SUMMARY OF QUANTITIES**

SCALE: SHEET 1 OF 3 SHEETS STA. TO STA.

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
39	(50-1VB & 50-1B)BRR	LASALLE	30	3
CONTRACT NO. 66L17				
ILLINOIS FED. AID PROJECT				

MODEL: Default  
 FILE: M:\GIS\Projects\GIS\Projects\DOT\Office\District 3\Project\03366L17\03366L17-cover.dwg

CODE NO.	ITEM	UNIT	TOTAL QUANTITY	CONSTRUCTION CODE	
				07E0 100% STATE	07A0 100% STATE
				BRIDGE	BRIDGE
				0047	0047
		S.N. 050-0210/0211	S.N. 050-0212/0213		
63301210	REMOVE AND REERECT STEEL PLATE BEAM GUARDRAIL, TYPE A	FOOT	700		700
63302400	REMOVE AND REERECT TRAFFIC BARRIER TERMINALS, TYPE 5	EACH	1		1
63302700	REMOVE AND REERECT TRAFFIC BARRIER TERMINALS, TYPE 6	EACH	6		6
67000400	ENGINEER'S FIELD OFFICE, TYPE A	CAL MO	6		6
67100100	MOBILIZATION	L SUM	1	0.25	0.75
70100207	TRAFFIC CONTROL AND PROTECTION, STANDARD 701402	EACH	2		2
70107025	CHANGEABLE MESSAGE SIGN	CAL DA	28		28
70300100	SHORT TERM PAVEMENT MARKING	FOOT	800		800
70300150	SHORT TERM PAVEMENT MARKING REMOVAL	SQ FT	264		264
70400100	TEMPORARY CONCRETE BARRIER	FOOT	1600		1600
70400200	RELOCATE TEMPORARY CONCRETE BARRIER	FOOT	1600		1600
70600250	IMPACT ATTENUATORS, TEMPORARY (NON- REDIRECTIVE), TEST LEVEL 3	EACH	4		4
70600350	IMPACT ATTENUATORS, RELOCATE (NON- REDIRECTIVE), TEST LEVEL 3	EACH	4		4
* 78008210	POLYUREA PAVEMENT MARKING TYPE I - LINE 4"	FOOT	6748		6748

\*= SPECIALTY ITEM

USER NAME = woodshankr	DESIGNED - RW	REVISED -
PLOT SCALE = 100.0000' / in.	DRAWN - RW	REVISED -
PLOT DATE = 12/17/2020	CHECKED - EM	REVISED -
	DATE - 8/5/2020	REVISED -

**STATE OF ILLINOIS**  
**DEPARTMENT OF TRANSPORTATION**

SUMMARY OF QUANTITIES			
SCALE:	SHEET	OF	SHEETS
	2	3	
	STA.		TO STA.

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
39	(50-1VB & 50-1B)BRR	LASALLE	30	4
CONTRACT NO. 66L17				
ILLINOIS FED. AID PROJECT				

CODE NO.	ITEM	UNIT	TOTAL QUANTITY	CONSTRUCTION CODE	
				07E0	07A0
				100% STATE BRIDGE	100% STATE BRIDGE
				0047	0047
		S.N. 050-0210/0211	S.N. 050-0212/0213		
* 78008230	POLYUREA PAVEMENT MARKING TYPE I - LINE 6"	FOOT	1520		1520
* 78200005	GUARDRAIL REFLECTORS, TYPE A	EACH	67		67
X0327809	LINEAR DELINEATOR PANELS, 4 INCH	EACH	67		67
78300202	PAVEMENT MARKING REMOVAL - WATER BLASTING	SQ FT	2856		2856
X1200234	SHOULDER INLET WITH CURB	EACH	4		4
X2700001	TEMPORARY RUMBLE STRIPS (SPECIAL)	EACH	8		8
Z0001495	BRIDGE APPROACH SHOULDER REMOVAL	SQ YD	138	44	94
Z0004552	APPROACH SLAB REMOVAL	SQ YD	1602	534	1068
Z0048665	RAILROAD PROTECTIVE LIABILITY INSURANCE	L SUM	1	1	

\*= SPECIALTY ITEM

MODEL: Default  
FILE NAME: P:\p1212020\DOT\Illinois\gov-PWD\DOT\Documents\DOT\_Offices\District 3\Project\03366L17\CD\0000\03366L17-cover.dwg


USER NAME = woodshankr	DESIGNED - RW	REVISED -
	DRAWN - RW	REVISED -
PLOT SCALE = 100.0000' / in.	CHECKED - EM	REVISED -
PLOT DATE = 12/17/2020	DATE - 8/5/2020	REVISED -

**STATE OF ILLINOIS  
DEPARTMENT OF TRANSPORTATION**

**SUMMARY OF QUANTITIES**

SCALE: SHEET 3 OF 3 SHEETS STA. TO STA.

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
39	(50-1VB & 50-1B)BRR	LASALLE	30	5
CONTRACT NO. 66L17				
ILLINOIS FED. AID PROJECT				



## TYPICAL SECTIONS

MODEL: Default  
 FILE: Model: P:\pub\baronm.dwg  
 PROJECT: I:\projects\366L17\CADD\366L17-cover.dwg

USER NAME = woodshankr	DESIGNED - RW	REVISED -
	DRAWN - RW	REVISED -
PLOT SCALE = 100.0000' / in.	CHECKED - EM	REVISED -
PLOT DATE = 12/17/2020	DATE - 8/5/2020	REVISED -

**STATE OF ILLINOIS  
DEPARTMENT OF TRANSPORTATION**

<b>TYPICAL SECTIONS</b>	
SCALE:	SHEET 1 OF 1 SHEETS STA. TO STA.

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
39	(50-1VB & 50-1B)BRR	LASALLE	30	6
CONTRACT NO. 66L17				
ILLINOIS FED. AID PROJECT				

**SCHEDULE  
TRAFFIC CONTROL**

LOCATION	TRAFFIC CONTROL AND PROTECTION STANDARD 701402	TEMPORARY RUMBLE STRIPS (SPECIAL)	CHANGEABLE MESSAGE SIGN
	EACH	EACH	CAL DAY
NORTHBOUND LANES	1	4	14
SOUTHBOUND LANES	1	4	14
<b>TOTAL</b>	<b>2</b>	<b>8</b>	<b>28</b>

**SCHEDULE - TEMPORARY CONCRETE BARRIER**

LOCATION	TEMPORARY CONCRETE BARRIER	RELOCATE TEMPORARY CONCRETE BARRIER	IMPACT ATTENUATORS, TEMPORARY (NON-REDIRECTIVE), TEST LEVEL 3	IMPACT ATTENUATORS, RELOCATE (NON-REDIRECTIVE), TEST LEVEL 3
	FOOT	FOOT	FOOT	FOOT
<b>STRUCTURE NO. 050-0210 (SB)</b>				
STAGE I	400		1	
STAGE II		400		1
<b>STRUCTURE NO. 050-0211 (NB)</b>				
STAGE I	400		1	
STAGE II		400		1
<b>STRUCTURE NO. 050-0212 (SB)</b>				
STAGE I	400		1	
STAGE II		400		1
<b>STRUCTURE NO. 050-0213 (NB)</b>				
STAGE I	400		1	
STAGE II		400		1
<b>TOTAL</b>	<b>1600</b>	<b>1600</b>	<b>4</b>	<b>4</b>

**SCHEDULE - GUARDRAIL**

LOCATION	REMOVE AND REERECT RAIL ELEMENT OF EXISTING GUARDRAIL	REMOVE AND REERECT STEEL PLATE BEAM GUARDRAIL TYPE A	REMOVE AND REERECT TRAFFIC BARRIER TERMINALS TYPE 6	REMOVE AND REERECT TRAFFIC BARRIER TERMINALS TYPE 5	GUARDRAIL MARKERS TYPE A	LINEAR DELINEATOR PANELS 4 INCH
	FOOT	FOOT	EACH	EACH	EACH	EACH
<b>STRUCTURE NO. 050-0210 (SB)</b>						
APPROACH		200	2		16	16
DEPARTURE						
<b>STRUCTURE NO. 050-0211 (NB)</b>						
APPROACH	30				4	4
DEPARTURE					8	8
<b>STRUCTURE NO. 050-0212 (SB)</b>						
APPROACH		200	2		17	17
DEPARTURE						
<b>STRUCTURE NO. 050-0213 (NB)</b>						
APPROACH		200	2		9	9
DEPARTURE		100		1	13	13
<b>TOTAL</b>	<b>30</b>	<b>700</b>	<b>6</b>	<b>1</b>	<b>67</b>	<b>67</b>

**SCHEDULE - PAVEMENT MARKING**

LOCATION	PAVEMENT MARKING REMOVAL WATER BLASTING	SHORT-TERM PAVEMENT MARKING	SHORT-TERM PAVEMENT MARKING REMOVAL	POLYUREA PAVEMENT MARKING LINE 4"	POLYUREA PAVEMENT MARKING LINE 6"
	SQ FT	FOOT	SQ FT	FOOT	FOOT
NORTHBOUND LANES	1428	400	132	3374	760
SOUTHBOUND LANES	1428	400	132	3374	760
<b>TOTAL</b>	<b>2856</b>	<b>800</b>	<b>264</b>	<b>6748</b>	<b>1520</b>



MODEL: Default  
FILE: M:\GIS\_Plan\planroom.dwg  
PROJECT: I:\Projects\0366L17\CADD\0366L17-cover.dwg

USER NAME = woodshankr	DESIGNED - RW	REVISED -
PLOT SCALE = 100.0000' / in.	DRAWN - RW	REVISED -
PLOT DATE = 12/17/2020	CHECKED - EM	REVISED -
	DATE - 8/5/2020	REVISED -

**STATE OF ILLINOIS  
DEPARTMENT OF TRANSPORTATION**

<b>SCHEDULES</b>			
SCALE:	SHEET 1 OF 1 SHEETS	STA.	TO STA.


F.A.I. RTE. 39	SECTION (50-1VB & 50-1B)BRR	COUNTY LASALLE	TOTAL SHEETS 30	SHEET NO. 7
CONTRACT NO. 66L17				
ILLINOIS FED. AID PROJECT				



**TEMPORARY RUMBLE STRIP**  
 FOR QUANTITY PURPOSES, "EACH" LANE OF TRAFFIC SHALL BE CONSIDERED "ONE EACH"

- ① THE ROAD CONSTRUCTION AHEAD SIGN SHALL BE LOCATED 3 MILES IN ADVANCE OF THE PROJECT LIMITS.
- ② THE MESSAGE AND SIZE OF THE WORK ZONE PUBLIC INFORMATION SIGN SHALL BE AS SPECIFIED BY THE DEPARTMENT.
- ③ TO BE PLACED IN THE MEDIAN WHEN FEASIBLE. THE MESSAGE BOARD SHALL BE USED TO DISPLAY STATUS OF LANES WITHIN THE PROJECT. THE PRIMARY MESSAGES SHALL BE:  
 "RIGHT LANE CLOSED" / " x MILES AHEAD"  
 "LEFT LANE CLOSED" / " x MILES AHEAD"  
 "ALL LANES OPEN"
- ④ THREE, TYPE II BARRICADES, DRUMS, OR VERTICAL BARRICADES AT 25' CENTERS.
- ⑤ THIS SIGN SHALL BE USED WHEN 2 LANES ARE CLOSED.
- ⑥ WHEN THE LEFT LANE IS CLOSED, SWITCH THESE TWO SIGNS AND THE DIRECTION OF THE MERGE ARROW.
- ⑦ THIS SIGN SHALL ONLY BE USED IF THE EXISTING SPEED LIMIT IS GREATER THAN 65 MPH.

- ⑧ 48"x36" FLUORESCENT ORANGE SIGN WITH BLACK LETTERS.



- ↑ ARROW BOARD
- ☐ PORTABLE CHANGEABLE MESSAGE SIGN
- ⊥ SIGN
- TRAFFIC CONTROL DRUM WITH MONODIRECTIONAL FLASHING LIGHT
- ≡ TEMPORARY RUMBLE STRIPS (SEE SPECIAL PROVISION)

**GENERAL NOTE:**  
 THIS STANDARD IS USED WHERE AT ANY TIME A LANE IS CLOSED ON A FREEWAY/EXPRESSWAY.  
 WHEN THE LEFT LANE IS CLOSED, LEFT LANE CLOSED SIGNS SHALL BE SUBSTITUTED FOR THE RIGHT LANE CLOSED SIGNS.  
 THE FIRST THREE SIGNS, RUMBLE STRIPS AND THE MESSAGE BOARD ARE STATIONARY. THE OTHER SIGNS AND ARROWBOARDS SHALL BE MOVED AS NECESSARY TO MAINTAIN THE REQUIRED DISTANCE FROM THE START OF THE LANE CLOSURE TAPER(S).  
 SEE SPECIAL PROVISIONS.

ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SHOWN.

MODEL: Default  
 FILE: \\nas101\pub\baronm.dwg  
 PROJECT: \\nas101\pub\baronm.dwg  
 OFFICE: \\nas101\pub\baronm.dwg  
 DATE: 12/17/2020

USER NAME = woodshankr	DESIGNED - RW	REVISED -
	DRAWN - RW	REVISED -
PLOT SCALE = 100.0000' / in.	CHECKED - EM	REVISED -
PLOT DATE = 12/17/2020	DATE - 8/5/2020	REVISED -

**STATE OF ILLINOIS  
 DEPARTMENT OF TRANSPORTATION**


**TRAFFIC CONTROL AND PROTECTION  
 STANDARD 701400**

SCALE: SHEET 1 OF 1 SHEETS STA. TO STA.

F.A.I. RTE. 39	SECTION (50-1VB & 50-1B)BRR	COUNTY LASALLE	TOTAL SHEETS 30	SHEET NO. 8
CONTRACT NO. 66L17				
ILLINOIS FED. AID PROJECT				







**GENERAL NOTES**

PLAN DIMENSIONS AND DETAILS RELATIVE TO EXISTING PLANS ARE SUBJECT TO NOMINAL CONSTRUCTION VARIATIONS. THE CONTRACTOR SHALL FIELD VERIFY EXISTING DIMENSIONS AND DETAILS AFFECTING NEW CONSTRUCTION AND MAKE NECESSARY APPROVED ADJUSTMENTS PRIOR TO CONSTRUCTION OR ORDERING OF MATERIALS. SUCH VARIATIONS SHALL NOT BE CAUSE FOR ADDITIONAL COMPENSATION FOR A CHANGE IN SCOPE OF WORK; HOWEVER, THE CONTRACTOR WILL BE PAID FOR THE QUANTITY ACTUALLY FURNISHED AT THE UNIT PRICE BID FOR THE WORK.

REINFORCEMENT BARS DESIGNATED (E) SHALL BE EPOXY COATED.

PRIOR TO POURING THE NEW CONCRETE DECK, ALL HEAVY OR LOOSE RUST, LOOSE MILL SCALE, AND OTHER LOOSE OR POTENTIALLY DETRIMENTAL FOREIGN MATERIAL SHALL BE REMOVED FROM THE SURFACES IN CONTACT WITH CONCRETE. TIGHTLY ADHERED PAINT MAY REMAIN UNLESS OTHERWISE NOTED. REMOVAL SHALL BE ACCOMPLISHED BY METHODS THAT WILL NOT DAMAGE THE STEEL AND THE COST WILL BE INCLUDED IN THE PAY ITEM COVERING REMOVAL OF THE EXISTING CONCRETE.

THE NEW DECK AT THE SOUTH ABUTMENT SHALL HAVE IT'S FINAL FINISH TINED ACCORDING TO ARTICLE 420.09(e)(1) OF THE STANDARD SPECIFICATIONS. COST INCLUDED WITH CONCRETE SUPERSTRUCTURES.

AS DIRECTED BY THE ENGINEER, EXISTING CONSTRUCTION ACCESSORIES WELDED TO THE TOP FLANGE OF BEAMS AND GIRDERS SHALL BE REMOVED. THE WELD AREAS SHALL BE GROUND FLUSH AND INSPECTED FOR CRACKS USING MAGNETIC PARTICLE TESTING (MT) OR DYE PENETRANT TESTING (PT) BY QUALIFIED PERSONNEL APPROVED BY THE ENGINEER.

PROTECTIVE COAT SHALL BE APPLIED TO THE DESIGNATED SURFACE AREAS OF "ALL" NEW CONCRETE AND PARAPETS (TOP AND INSIDE FACES.)


JOINT PLATES AND ATTACHED BARS SHALL BE SHOP PAINTED WITH THE INORGANIC ZINC RICH PRIMER. NO FIELD PAINT REQUIRED.

EXISTING REINFORCEMENT BARS EXTENDING INTO THE REMOVAL AREA SHALL BE CLEANED, STRAIGHTENED AND INCORPORATED INTO THE NEW CONSTRUCTION. ANY REINFORCEMENT BARS THAT ARE DAMAGED DURING CONCRETE REMOVAL SHALL BE REPLACED WITH AN APPROVED BAR SPLICER OR ANCHORAGE SYSTEM. COST INCLUDED WITH CONCRETE REMOVAL.

JOINT OPENING SHALL BE ADJUSTED ACCORDING TO ARTICLE 520.04 OF THE STANDARD SPECIFICATIONS WHEN THE DECK IS POURED AT AN AMBIENT TEMPERATURE OTHER THAN 50 DEGREES F.

**TOTAL BILL OF MATERIALS FOR TWO STRUCTURES**

ITEM	UNIT	SUPER	SUB	TOTAL
CONCRETE REMOVAL	CU. YD.	42		42
APPROACH SLAB REMOVAL	SQ. YD.	534		534
BRIDGE APPROACH SHOULDER REMOVAL	SQ. YD.	44		44
PAVED SHOULDER REMOVAL	SQ. YD.	272		272
CONCRETE SUPERSTRUCTURE	CU. YD.	28.8		28.8
CONCRETE SUPERSTRUCTURE (APPROACH SLAB)	CU. YD.	115.6		115.6
CONCRETE STRUCTURES	CU. YD.		26.6	26.6
REINFORCEMENT BARS, EPOXY COATED	POUND	57840	4000	61840
BAR SPLICERS	EACH	430	80	510
PREFORMED JOINT STRIP SEAL	FOOT	168		168
WELDED WIRE REINFORCEMENT	SQ. YD.	98		98
PAVEMENT CONNECTOR (PCC) FOR BRIDGE APPROACH SLAB	SQ. YD.	648		648
BRIDGE DECK GROOVING	SQ. YD.	944		944
TIE BARS 1 1/4"	EACH	78		78
PROTECTIVE COAT	SQ. YD.	984		984



**PLAN**  
**STRUCTURE NO. 050-0210 (SB)**  
**STRUCTURE NO. 050-0211 (NB)**



Expires 11-30-2022

*David Carl Puze*

01/28/2021

**STATE OF ILLINOIS**  
**DEPARTMENT OF TRANSPORTATION**


**GENERAL PLAN AND ELEVATION**  
**STRUCTURE NO. 050-0210 (SB) & STRUCTURE NO. 050-0211 (NB)**

SCALE: SHEET 1 OF 8 SHEETS STA. TO STA.

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
39	(50-1VB & 50-1B)BRR	LASALLE	30	11
CONTRACT NO. 66L17				
ILLINOIS FED. AID PROJECT				


USER NAME = woodshankr	DESIGNED - RW	REVISED -
	DRAWN - RW	REVISED -
PLOT SCALE = 100.0000' / in.	CHECKED - EM	REVISED -
PLOT DATE = 1/27/2021	DATE - 8/5/2020	REVISED -

MODEL: Default  
 FILE: \\nas0101\pub\baroncom.dta\illinois\pwr\DOT\Documents\DOT - Offices\Dist\ct\_3\Projects\0366L17\CADD\0366L17-cover.dgn




**PLAN @ NORTH ABUTMENT - NORTHBOUND**  
 NORTH ABUTMENT - SOUTHBOUND SIMILAR  
 SOUTH ABUTMENT DETAILS SHALL BE SIMILAR THRU 180° ROTATION. (EXCEPT AS NOTED)


**LEGEND**  
 CONCRETE REMOVAL



**SECTION D-D**



**CROSS SECTION THRU PARAPET**



**CROSS SECTION THRU WING WALL**

MODEL: Default  
 FILE: Abutment\_ExpansionJointRemovalDetails.dwg  
 PROJECT: 0366L17-CADD  
 DATE: 1/27/2021



USER NAME = woodshankr	DESIGNED - RW	REVISED -
PLOT SCALE = 100.0000' / in.	DRAWN - RW	REVISED -
PLOT DATE = 1/27/2021	CHECKED - EM	REVISED -
	DATE - 8/5/2020	REVISED -

**STATE OF ILLINOIS  
 DEPARTMENT OF TRANSPORTATION**

**EXPANSION JOINT REMOVAL DETAILS  
 STRUCTURE NO. 050-0210 (SB) & STRUCTURE NO. 050-0211 (NB)**

SCALE: SHEET 2 OF 8 SHEETS STA. TO STA.



F.A.I. RTE. 39	SECTION (50-1VB & 50-1B)BRR	COUNTY LASALLE	TOTAL SHEETS 30	SHEET NO. 12
			CONTRACT NO. 66L17	
ILLINOIS FED. AID PROJECT				




**PLAN DETAIL**  
 STRUCTURE NO. 050-0210 (SB)  
 STRUCTURE NO. 050-0211 (NB)

- NOTES:**
1. DETAILS SHOWN ARE FOR THE NORTH ABUTMENT, NORTHBOUND STRUCTURE. NORTH ABUTMENT, SOUTHBOUND STRUCTURE DETAILS SHALL BE SIMILAR FROM WHAT IS SHOWN.
  2. EXCAVATION REQUIRED FOR THE CONSTRUCTION OF THE NEW APPROACH SLAB SHALL NOT BE PAID FOR SEPARATELY BUT SHALL BE INCLUDED IN THE COST OF THE "CONCRETE SUPERSTRUCTURE (APPROACH SLAB)".


**LEGEND**



**SECTION A-A**



**SECTION B-B**



**SECTION C-C**

MODEL: Default  
 FILE: \\nas01\pub\baroncom.dad\illinois\p050-0210\Documents\DOT Office\Drawings\3\Project\050-0210\0366L17-cover.dgn

USER NAME = woodshankr	DESIGNED - RW	REVISED -
PLOT SCALE = 100.0000' / in.	DRAWN - RW	REVISED -
PLOT DATE = 12/17/2020	CHECKED - EM	REVISED -
	DATE - 8/5/2020	REVISED -





**STATE OF ILLINOIS  
 DEPARTMENT OF TRANSPORTATION**

**APPROACH SLAB REMOVAL DETAILS**  
**STRUCTURE NO. 050-0210 (SB) & STRUCTURE NO. 050-0211 (NB)**

F.A.I. RTE. 39	SECTION (50-1VB & 50-1B)BRR	COUNTY LASALLE	TOTAL SHEETS 30	SHEET NO. 13
CONTRACT NO. 66L17				
ILLINOIS FED. AID PROJECT				

SCALE: SHEET 3 OF 8 SHEETS STA. TO STA.





**GENERAL NOTES:**  
 THE JOINT OPENING SHALL BE ADJUSTED FOR TEMPERATURE PER ARTICLE 520.04 OF THE STANDARD SPECIFICATIONS. HOWEVER, SINCE THIS DETAIL IS FOR JOINTLESS STRUCTURES, THE LENGTH OF BRIDGE USED TO CALCULATE THE ADJUSTMENT SHALL BE EQUAL TO HALF THE TOTAL BRIDGE LENGTH PLUS THE LENGTH OF THE BRIDGE APPROACH SLAB.  
 APPROACH SLAB SHALL BE PAID FOR AS CONCRETE SUPERSTRUCTURE (APPROACH SLAB).  
 APPROACH FOOTING CONCRETE SHALL BE PAID FOR AS CONCRETE STRUCTURES.  
 THE APPROACH FOOTING MAXIMUM APPLIED SERVICE BEARING PRESSURE (QMAX) = 2.0 KSF.  
 COST OF EXCAVATION FOR APPROACH SLAB/FOOTING SHALL BE INCLUDED WITH CONCRETE SUPERSTRUCTURE/STRUCTURES.

MODEL: Default  
 FILE: Model - P:\pub\baron\050-0210-0211\DOT\Documents\IBOT - Office\IBOT\050-0210-0211\050-0210-0211\17-cover.dgn


USER NAME = woodshankr	DESIGNED - RW	REVISED -
	DRAWN - RW	REVISED -
PLOT SCALE = 100.0000' / in.	CHECKED - EM	REVISED -
PLOT DATE = 12/17/2020	DATE - 8/5/2020	REVISED -

**STATE OF ILLINOIS  
 DEPARTMENT OF TRANSPORTATION**


<b>APPROACH SLAB CONSTRUCTION DETAILS</b>	
<b>STRUCTURE NO. 050-0210 (SB) &amp; STRUCTURE NO. 050-0211 (NB)</b>	
SCALE:	SHEET 5 OF 8 SHEETS STA. TO STA.

F.A.I. RTE. 39	SECTION (50-1VB & 50-1B)BRR	COUNTY LASALLE	TOTAL SHEETS 30	SHEET NO. 15
CONTRACT NO. 66L17				
ILLINOIS		FED. AID PROJECT		







**PLAN AT PARAPET**



**DETAIL A**



**SHOWING ROLLED RAIL JOINT**




**SHOWING WELDED RAIL JOINT**

\* 5/8" Ø X 6" STUDS @ 6" CTS. (ALTERNATE ANGLED/BENT STUDS WITH HORIZONTAL STUDS)

3/8" Ø THREADED RODS IN 7/16" Ø HOLES AT ±4'-0" CTS. FOR HOLDING THE PROPER JOINT OPENING BASED ON THE TEMPERATURE DURING THE DECK POUR. PLACE TO MISS STUDS. ALL RODS SHALL BE BURNED, OR SAWED OFF FLUSH WITH THE PLATES AFTER CONCRETE IS SET.

**SECTION A-A**

\* GRANULAR OR SOLID FLUX FILLED HEADED STUDS CONFORMING TO ARTICLE 1006.32 OF THE STD. SPECS., AUTOMATICALLY END WELDED.



**LOCKING EDGE RAILS**

\*\* BACK GOUGE NOT REQUIRED IF COMPLETE JOINT PENETRATION IS VERIFIED BY MOCK-UP.

**LOCKING EDGE RAIL SPLICE**

THE INSIDE OF THE LOCKING EDGE RAIL GROOVE SHALL BE FREE OF WELD RESIDUE. ROLLED RAIL SHOWN, WELDED RAIL SIMILAR.

**NOTES:**

THE STRIP SEAL SHALL BE MADE CONTINUOUS AND SHALL HAVE A MINIMUM THICKNESS OF 1/4". THE CONFIGURATION OF THE STRIP SEAL SHALL MATCH THE CONFIGURATION OF THE LOCKING EDGE RAILS. OPEN OR "WEBBED" STRIP SEAL GLAND CONFIGURATIONS ARE NOT PERMITTED. THE GLAND SHALL BE SIZED FOR A MAXIMUM RATED MOVEMENT OF 4 INCHES.

THE LOCKING EDGE RAILS DEPICTED ARE CONFIGURED FOR TYPICAL APPLICATIONS AND ARE CONCEPTUAL ONLY. THE ACTUAL CONFIGURATION OF THE LOCKING EDGE RAILS AND MATCHING STRIP SEAL MAY VARY FROM MANUFACTURER TO MANUFACTURER PROVIDED THEY FIT THE APPLICATION AND MEET THE MINIMUM ANCHORAGE SHOWN. FLANGED EDGE RAILS, HOWEVER, WILL NOT BE ALLOWED. LOCKING EDGE RAILS MAY EXCEED THE 4 1/2" MAXIMUM DEPTH PROVIDED THE ANCHORAGE SYSTEM IS REVISED ACCORDING TO THE MANUFACTURER'S RECOMMENDATION.

THE MANUFACTURER'S RECOMMENDED INSTALLATION METHODS SHALL BE FOLLOWED.

ALL STEEL COMPONENTS SHALL BE GALVANIZED AFTER FABRICATION ACCORDING TO ARTICLE 520.03 OF THE STANDARD SPECIFICATIONS.

THE MAXIMUM SPACE BETWEEN LOCKING EDGE RAIL SEGMENTS SHALL BE 3/16" AND SEALED WITH A SUITABLE SEALANT; HOWEVER, ANY RAIL JOINT WITHIN 10' MEASURED PERPENDICULAR TO THE FACE OF THE CURB OR PARAPET SHALL BE WELDED AS SHOWN IN THE LOCKING EDGE RAIL SPLICE DETAIL.

COST OF PARAPET SLIDING PLATES, EMBEDDED PLATES, AND ANCHORAGE STUDS INCLUDED WITH PREFORMED JOINT STRIP SEAL.

39" CONSTANT SLOPE BARRIER SHOWN, 44" CONSTANT SLOPE BARRIER SIMILAR AS NOTED.

THE CONCRETE OPENING BELOW THE STRIP SEAL WILL VARY BASED ON THE LOCKING EDGE RAIL CHOSEN BY THE CONTRACTOR. DECK AND PARAPET LENGTHS SHOWN ELSEWHERE IN THE PLANS ARE DIMENSIONED TO THE CONCRETE OPENING, NOT THE JOINT OPENING, AND ARE BASED ON THE ROLLED LOCKING EDGE RAIL. IF THE CONTRACTOR ELECTS TO USE A DIFFERENT LOCKING EDGE RAIL, DIMENSIONAL ADJUSTMENTS MAY BE REQUIRED. ONE EXCEPTION TO THIS WOULD BE THE STRIP SEAL JOINT AT THE END OF THE PRECAST BRIDGE APPROACH SLAB. FOR THESE CASES THE PAVEMENT CONNECTOR LENGTH SHALL BE ADJUSTED, NOT THE LENGTH OF THE BRIDGE APPROACH SLAB.

**BILL OF MATERIAL FOR STRUCTURE NO. 050-0210 (SB)**

LOCATION	ITEM	UNIT	TOTAL
NORTH ABUTMENT	PREFORMED JOINT STRIP SEAL	FOOT	42
SOUTH ABUTMENT			42

**BILL OF MATERIAL FOR STRUCTURE NO. 050-0211 (NB)**

LOCATION	ITEM	UNIT	TOTAL
NORTH ABUTMENT	PREFORMED JOINT STRIP SEAL	FOOT	42
SOUTH ABUTMENT			42

MODEL: Default  
FILE: \\nas01c:\pub\baronm.d\at\links\poc\PROJECTS\DOT\Documents\DOT\Office\Drawings\Projects\050-0210\050-0210-17-cover.dgn


USER NAME = woodshankr	DESIGNED - RW	REVISED -
	DRAWN - RW	REVISED -
PLOT SCALE = 100.0000' / in.	CHECKED - EM	REVISED -
PLOT DATE = 1/25/2021	DATE - 8/5/2020	REVISED -

**STATE OF ILLINOIS  
DEPARTMENT OF TRANSPORTATION**

**PREFORMED JOINT STRIP SEAL FOR  
STRUCTURE NO. 050-0210 (SB) & STRUCTURE NO. 050-0211 (NB),**

SCALE: SHEET 7 OF 8 SHEETS STA. TO STA.

F.A.I. RTE. 39	SECTION (50-1VB & 50-1B)BRR	COUNTY LASALLE	TOTAL SHEETS 30	SHEET NO. 17
CONTRACT NO. 66L17				
ILLINOIS FED. AID PROJECT				



**STANDARD BAR SPLICER ASSEMBLY PLAN**  
(ALL COMPONENTS SHALL BE PROVIDED FROM ONE SUPPLIER)


THREADED SPLICER BAR LENGTH = MIN. LAP LENGTH + 1 1/2" + THREAD LENGTH  
 \* EPOXY NOT REQUIRED ON BAR SPLICER ASSEMBLY COMPONENTS USED IN CONJUNCTION WITH BLACK BARS.

**STRUCTURE NO. 050-0210 (SB)**

LOCATION	BAR SIZE	NO. ASSEMBLIES REQUIRED	MINIMUM LAP LENGTH
N. ABUT. DECK	#5	9	3'-6"
N. ABUT END DAM	#6	4	4'-0"
N. APPROACH SLAB	#5	45	3'-6"
	#8	60	4'-9"
N APPROACH SLEEPER SLAB	#5	40	3'-0"
N APPROACH PAVEMENT CONNECTOR	#4	18	2'-5"
S. ABUT. DECK	#5	9	3'-6"
S. ABUT END DAM	#6	4	4'-0"
<b>TOTAL</b>		<b>193</b>	


**STRUCTURE NO. 050-0211 (NB)**

LOCATION	BAR SIZE	NO. ASSEMBLIES REQUIRED	MINIMUM LAP LENGTH
N. ABUT. DECK	#5	9	3'-6"
N. ABUT END DAM	#6	4	4'-0"
N. APPROACH SLAB	#5	45	3'-6"
	#8	60	4'-9"
N APPROACH SLEEPER SLAB	#5	40	3'-0"
N APPROACH PAVEMENT CONNECTOR	#4	18	2'-5"
S. ABUT. DECK	#5	9	3'-6"
S. ABUT END DAM	#6	4	4'-0"
<b>TOTAL</b>		<b>193</b>	



**INSTALLATION AND SETTING METHODS**

"A" : SET BAR SPLICER ASSEMBLY BY MEANS OF A TEMPLATE BOLT.  
 "B" : SET BAR SPLICER ASSEMBLY BY NAILING TO WOOD FORMS OR CEMENTING TO STEEL FORMS.  
 (E) : INDICATES EPOXY COATING.



**STRUCTURE NO. 050-0210 (SB)**

LOCATION	BAR SIZE	NO. ASSEMBLIES REQUIRED
N. ABUT END DAM	#5	62

**STRUCTURE NO. 050-0211 (NB)**

LOCATION	BAR SIZE	NO. ASSEMBLIES REQUIRED
N. ABUT END DAM	#5	62

NOTES:  
 SPLICER BARS SHALL BE DEFORMED WITH THREADED ENDS AND HAVE A MINIMUM 60 KSI YIELD STRENGTH.  
 ALL REINFORCEMENT SHALL BE LAPPED AND TIED TO THE SPLICER BARS.  
 BAR SPLICER ASSEMBLIES SHALL BE EPOXY COATED ACCORDING TO THE REQUIREMENTS FOR REINFORCEMENT BARS. SEE SECTION 508 OF THE STANDARD SPECIFICATIONS.  
 SEE APPROVED LIST OF BAR SPLICER ASSEMBLIES AND MECHANICAL SPLICERS FOR ALTERNATIVES.

MODEL: Default  
FILE NAME: \\paulhanrahan.com\dca\illinois\dot\Documents\DOT\_Office\Drawings\3\Projects\0366\17\CADD\0366\17-cover.dgn


USER NAME = woodshank1	DESIGNED - RW	REVISED -
	DRAWN - RW	REVISED -
PLOT SCALE = 100,0000' / in.	CHECKED - EM	REVISED -
PLOT DATE = 1/27/2021	DATE - 8/5/2020	REVISED -

**STATE OF ILLINOIS  
DEPARTMENT OF TRANSPORTATION**

**BAR SPLICER ASSEMBLY AND MECHANICAL SPLICER DETAILS FOR  
STRUCTURE NO. 050-0210 (SB) & STRUCTURE NO. 050-0211 (NB)**

SCALE: SHEET 8 OF 8 SHEETS STA. TO STA.

F.A.I. RTE. 39	SECTION (50-1VB & 50-1B)BRR	COUNTY LASALLE	TOTAL SHEETS 30	SHEET NO. 18
			CONTRACT NO. 66L17	
			ILLINOIS FED. AID PROJECT	



**ELEVATION**

**GENERAL NOTES**

PLAN DIMENSIONS AND DETAILS RELATIVE TO EXISTING PLANS ARE SUBJECT TO NOMINAL CONSTRUCTION VARIATIONS. THE CONTRACTOR SHALL FIELD VERIFY EXISTING DIMENSIONS AND DETAILS AFFECTING NEW CONSTRUCTION AND MAKE NECESSARY APPROVED ADJUSTMENTS PRIOR TO CONSTRUCTION OR ORDERING OF MATERIALS. SUCH VARIATIONS SHALL NOT BE CAUSE FOR ADDITIONAL COMPENSATION FOR A CHANGE IN SCOPE OF WORK; HOWEVER, THE CONTRACTOR WILL BE PAID FOR THE QUANTITY ACTUALLY FURNISHED AT THE UNIT PRICE BID FOR THE WORK.

REINFORCEMENT BARS DESIGNATED (E) SHALL BE EPOXY COATED.

PRIOR TO POURING THE NEW CONCRETE DECK, ALL HEAVY OR LOOSE RUST, LOOSE MILL SCALE, AND OTHER LOOSE OR POTENTIALLY DETRIMENTAL FOREIGN MATERIAL SHALL BE REMOVED FROM THE SURFACES IN CONTACT WITH CONCRETE. TIGHTLY ADHERED PAINT MAY REMAIN UNLESS OTHERWISE NOTED. REMOVAL SHALL BE ACCOMPLISHED BY METHODS THAT WILL NOT DAMAGE THE STEEL AND THE COST WILL BE INCLUDED IN THE PAY ITEM COVERING REMOVAL OF THE EXISTING CONCRETE.

AS DIRECTED BY THE ENGINEER, EXISTING CONSTRUCTION ACCESSORIES WELDED TO THE TOP FLANGE OF BEAMS AND GIRDERS SHALL BE REMOVED. THE WELD AREAS SHALL BE GROUND FLUSH AND INSPECTED FOR CRACKS USING MAGNETIC PARTICLE TESTING (MT) OR DYE PENETRANT TESTING (PT) BY QUALIFIED PERSONNEL APPROVED BY THE ENGINEER.

PROTECTIVE COAT SHALL BE APPLIED TO THE DESIGNATED SURFACE AREAS OF "ALL" NEW CONCRETE AND PARAPETS (TOP AND INSIDE FACES.)

JOINT PLATES AND ATTACHED BARS SHALL BE SHOP PAINTED WITH THE INORGANIC ZINC RICH PRIMER. NO FIELD PAINT REQUIRED.


EXISTING REINFORCEMENT BARS EXTENDING INTO THE REMOVAL AREA SHALL BE CLEANED, STRAIGHTENED AND INCORPORATED INTO THE NEW CONSTRUCTION. ANY REINFORCEMENT BARS THAT ARE DAMAGED DURING CONCRETE REMOVAL SHALL BE REPLACED WITH AN APPROVED BAR SPLICER OR ANCHORAGE SYSTEM. COST INCLUDED WITH CONCRETE REMOVAL.

JOINT OPENING SHALL BE ADJUSTED ACCORDING TO ARTICLE 520.04 OF THE STANDARD SPECIFICATIONS WHEN THE DECK IS POURED AT AN AMBIENT TEMPERATURE OTHER THAN 50 DEGREES F.

**TOTAL BILL OF MATERIALS FOR TWO STRUCTURES**

ITEM	UNIT	SUPER	SUB	TOTAL
CONCRETE REMOVAL	CU. YD.	23.6		23.6
APPROACH SLAB REMOVAL	SQ. YD.	1068		1068
BRIDGE APPROACH SHOULDER REMOVAL	SQ. YD.	94		94
PAVED SHOULDER REMOVAL	SQ. YD.	544		544
CONCRETE SUPERSTRUCTURE	CU. YD.	23		23
CONCRETE SUPERSTRUCTURE (APPROACH SLAB)	CU. YD.	165.2		165.2
CONCRETE STRUCTURES	CU. YD.	52		52
REINFORCEMENT BARS, EPOXY COATED	POUND	110964	9036	120000
BAR SPLICERS	EACH	720	80	800
PREFORMED JOINT STRIP SEAL	FOOT	168		168
WELDED WIRE REINFORCEMENT	SQ. YD.	374		374
PAVEMENT CONNECTOR (PCC) FOR BRIDGE APPROACH SLAB	SQ. YD.	1296		1296
BRIDGE DECK GROOVING	SQ. YD.	1830		1830
SHOULDER INLET WITH CURB	EACH	4		4
TIE BARS 1 1/4"	EACH	156		156
PROTECTIVE COAT	SQ. YD.	780		780

\* REMOVAL OF EXISTING FRAME AND GRATES, FURNISHING AND INSTALLING NEW FRAME AND GRATES SHALL BE PAID FOR AS "SHOULDER INLET WITH CURB".



**PLAN**

**STRUCTURE NO. 050-0212 (SB)**  
**STRUCTURE NO. 050-0213 (NB)**



Expires 11-30-2022

*David Carl Puzey*

01/28/2021

**STATE OF ILLINOIS**  
**DEPARTMENT OF TRANSPORTATION**


**GENERAL PLAN AND ELEVATION**  
**STRUCTURE NO. 050-0212 (SB) & STRUCTURE NO. 050-0213 (NB)**

SCALE: SHEET 1 OF 11 SHEETS STA. TO STA.

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
39	(50-1VB & 50-1B)BRR	LASALLE	30	19
CONTRACT NO. 66L17				
ILLINOIS FED. AID PROJECT				

USER NAME = woodshankr	DESIGNED - RW	REVISED -
	DRAWN - RW	REVISED -
PLOT SCALE = 100.0000' / in.	CHECKED - EM	REVISED -
PLOT DATE = 1/25/2021	DATE - 8/5/2020	REVISED -





**PLAN @ SOUTH ABUTMENT**

STRUCTURE NO. 050-0212 (SB)  
STRUCTURE NO. 050-0213 (NB)


**NOTES:**

1. DETAILS SHOWN ARE FOR THE SOUTH ABUTMENT, NORTHBOUND STRUCTURE.
2. SOUTH ABUTMENT, SOUTHBOUND STRUCTURE, DETAILS SHALL BE SIMILAR TO WHAT IS SHOWN.
3. EXISTING SHOULDER INLET BOXES AND GRATES (WHEN PRESENT) SHALL REMAIN IN PLACE AND BE INCORPORATED INTO THE NEW CONSTRUCTION.


**LEGEND**




EXISTING REINFORCEMENT BAR SHALL BE CUT OFF FLUSH WITH BACKWALL SEAT.



**SECTION N-N  
SOUTH ABUTMENT**



**CROSS SECTION THRU PARAPET**



**CROSS SECTION THRU WING WALL**

**STATE OF ILLINOIS  
DEPARTMENT OF TRANSPORTATION**

**EXPANSION JOINT REMOVAL DETAILS  
STRUCTURE NO. 050-0212 (SB) & STRUCTURE NO. 050-0213 (NB)**


F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
39	(50-1VB & 50-1B)BRR	LASALLE	30	21
CONTRACT NO. 66L17				

SCALE: SHEET 3 OF 11 SHEETS STA. TO STA.

ILLINOIS FED. AID PROJECT

MODEL: Default  
 FILE: \\nas0101\pub\baroncom.dwg  
 PROJECT: \\nas0101\pub\baroncom.dwg  
 OFFICE: \\nas0101\pub\baroncom.dwg  
 DATE: 12/17/2020






**PLAN DETAIL**  
 STRUCTURE NO. 050-0212 (SB)  
 STRUCTURE NO. 050-0213 (NB)


**LEGEND**

- APPROACH SLAB REMOVAL**
- BRIDGE APPROACH SHOULDER REMOVAL**
- PCC SHOULDER REMOVAL**


- NOTES:**
1. DETAILS SHOWN ARE FOR THE SOUTH ABUTMENT, NORTHBOUND STRUCTURE.
  2. SOUTHBOUND STRUCTURE, DETAILS SHALL BE SIMILAR FROM WHAT IS SHOW.
  3. EXISTING SHOULDER INLET BOXES AND GRATES (WHEN PRESENT) SHALL REMAIN IN PLACE AND BE INCORPORATED INTO THE NEW CONSTRUCTION.



**SECTION 0-0**



**SECTION P-P**



**SECTION Q-Q**

MODEL: Default  
 FILE: \\nas0101\pub\baronon.dwg  
 PROJECT: \\nas0101\pub\baronon.dwg  
 PLOT DATE: 12/17/2020


USER NAME = woodshankr	DESIGNED - RW	REVISED -
DRAWN - RW	REVISIONS -	
PLOT SCALE = 100.0000' / in.	CHECKED - EM	REVISIONS -
PLOT DATE = 12/17/2020	DATE - 8/5/2020	REVISIONS -

**STATE OF ILLINOIS  
 DEPARTMENT OF TRANSPORTATION**

**APPROACH SLAB REMOVAL DETAILS - SOUTH APPROACH**  
**STRUCTURE NO. 050-0212 (SB) & STRUCTURE NO. 050-0213 (NB)**

F.A.I. RTE. 39	SECTION (50-1VB & 50-1B)BRR	COUNTY LASALLE	TOTAL SHEETS 30	SHEET NO. 23
CONTRACT NO. 66L17				
ILLINOIS FED. AID PROJECT				

SCALE: SHEET 5 OF 11 SHEETS STA. TO STA.




**PLAN @ NORTH ABUTMENT**  
 STRUCTURE NO. 050-0212 (SB)  
 STRUCTURE NO. 050-0213 (NB)


**NOTE: DETAILS SHOWN ARE FOR THE NORTHBOUND STRUCTURE  
 SOUTHBOUND STRUCTURE SHALL BE A MIRROR IMAGE FROM WHAT IS SHOWN**

**NOTES:**

1. DETAILS SHOWN ARE FOR THE NORTH ABUTMENT, NORTHBOUND STRUCTURE. DETAILS FOR THE SOUTH ABUTMENT SHALL BE A MIRROR IMAGE.
2. SOUTHBOUND STRUCTURE, DETAILS SHALL BE SIMILAR FROM WHAT IS SHOWN.
3. EXISTING SHOULDER INLET BOXES AND GRATES (WHEN PRESENT) SHALL REMAIN IN PLACE AND BE INCORPORATED INTO THE NEW CONSTRUCTION.



**SECTION R-R  
 NORTH ABUTMENT**




**SECTION S-S  
 SOUTH ABUTMENT**


\*SEE SHEET 28 OF 30 FOR EXPANSION JOINT DETAILS

\*\*v<sub>1</sub>(E), v<sub>2</sub>(E) AND BAR SPLICER, SHALL BE DRILLED AND GROUTED INTO EXISTING CONCRETE ACCORDING TO SECTION 584 OF THE STANDARD SPECIFICATIONS.

v<sub>1</sub>(E) BARS, WHEN DRILLED SHALL BE SPACED A MIN. OF 1 1/2" FROM BAR SPLICERS



**CROSS SECTION THRU PARAPET**



**CROSS SECTION THRU WING WALL**

MODEL: Default  
 FILE: Abutment\_ExpansionJointDetails.dwg  
 PROJECT: I:\Projects\050-0212\050-0212.dwg  
 PLOT DATE: 12/17/2020

USER NAME = woodshankr	DESIGNED - RW	REVISED -
	DRAWN - RW	REVISED -
PLOT SCALE = 100,0000' / in.	CHECKED - EM	REVISED -
PLOT DATE = 12/17/2020	DATE - 8/5/2020	REVISED -


**STATE OF ILLINOIS  
 DEPARTMENT OF TRANSPORTATION**

**EXPANSION JOINT CONSTRUCTION DETAILS  
 STRUCTURE NO. 050-0212 (SB) & STRUCTURE NO. 050-0213 (NB)**

SCALE: SHEET 6 OF 11 SHEETS STA. TO STA.


F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
39	(50-1VB & 50-1B)BRR	LASALLE	30	24
CONTRACT NO. 66L17				
ILLINOIS FED. AID PROJECT				






**PLAN DETAIL**

STRUCTURE NO. 050-0212 (SB)  
STRUCTURE NO. 050-0213 (NB)




**SECTION T-T**

- NOTES:
1. DETAILS SHOWN ARE FOR THE SOUTH ABUTMENT, NORTHBOUND STRUCTURE.
  2. SOUTHBOUND STRUCTURE, DETAILS SHALL BE SIMILAR FROM WHAT IS SHOW.
  3. EXISTING SHOULDER INLET BOXES AND GRATES (WHEN PRESENT) SHALL REMAIN IN PLACE AND BE INCORPORATED INTO THE NEW CONSTRUCTION.
  4. a<sub>11</sub>(E), a<sub>12</sub>(E), a<sub>14</sub>(E) AND a<sub>15</sub>(E) BARS SHALL BE CUT INFIELD TO FIT CURB.



**SECTION X-X**



**SECTION Y-Y**

- GENERAL NOTES:
- THE JOINT OPENING SHALL BE ADJUSTED FOR TEMPERATURE PER ARTICLE 520.04 OF THE STANDARD SPECIFICATIONS. HOWEVER, SINCE THIS DETAIL IS FOR JOINTLESS STRUCTURES, THE LENGTH OF BRIDGE USED TO CALCULATE THE ADJUSTMENT SHALL BE EQUAL TO HALF THE TOTAL BRIDGE LENGTH PLUS THE LENGTH OF THE BRIDGE APPROACH SLAB.
  - APPROACH SLAB SHALL BE PAID FOR AS CONCRETE SUPERSTRUCTURE (APPROACH SLAB).
  - APPROACH FOOTING CONCRETE SHALL BE PAID FOR AS CONCRETE STRUCTURES.
  - THE APPROACH FOOTING MAXIMUM APPLIED SERVICE BEARING PRESSURE (QMAX) = 2.0 KSF.
  - COST OF EXCAVATION FOR APPROACH SLAB/FOOTING SHALL BE INCLUDED WITH CONCRETE SUPERSTRUCTURE/STRUCTURES.

MODEL: Default  
FILE: \\nas01\pub\baronm.d\allink\spc\PROJECTS\DOT Documents\DOT Office\Drawings\3\Projects\033661\17\CADD\033661\_17-cover.dgn


USER NAME = woodshankr	DESIGNED - RW	REVISED -
DRAWN - RW	CHECKED - EM	REVISED -
PLOT SCALE = 100,0000' / in.	DATE - 8/5/2020	REVISED -
PLOT DATE = 12/17/2020		

**STATE OF ILLINOIS  
DEPARTMENT OF TRANSPORTATION**


**APPROACH SLAB CONSTRUCTION DETAILS - SOUTH APPROACH  
STRUCTURE NO. 050-0212 (SB) & STRUCTURE NO. 050-0213 (NB)**

SCALE: SHEET 8 OF 11 SHEETS STA. TO STA.


F.A.I. RTE. 39	SECTION (50-1VB & 50-1B)BRR	COUNTY LASALLE	TOTAL SHEETS 30	SHEET NO. 26
CONTRACT NO. 66L17				
ILLINOIS FED. AID PROJECT				




**a13(E) BAR**




**a17(E) BAR**






**d2(E) BAR**



**d3(E) BAR**



**v(E) BAR**



**BILL OF MATERIALS  
STRUCTURE NO. 050-0212 (SB)**

BAR	NO. BARS	SIZE	LENGTH	SHAPE
a9(E)	4	# 7	19' - 4"	—————
a10(E)	4	# 7	23' - 4"	—————
a11(E)	90	# 5	18' - 10"	—————
a12(E)	120	# 8	18' - 10"	—————
a13(E)	124	# 5	6' - 8"	—————┘
a14(E)	90	# 5	22' - 10"	—————
a15(E)	120	# 8	22' - 10"	—————
a16(E)	72	# 4	11' - 9"	—————
a17(E)	18	# 4	10' - 10"	—————┘
b5(E)	124	# 5	29' - 9"	—————
b6(E)	200	# 9	29' - 9"	—————
b7(E)	4	# 5	20' - 8"	—————
b8(E)	276	# 6	25' - 1"	—————
b9(E)	24	# 5	25' - 1"	—————
d2(E)	8	# 4	5' - 2"	—————
d3(E)	8	# 5	3' - 11"	—————
h2(E)	8	# 6	17' - 9"	—————
h3(E)	8	# 6	21' - 9"	—————
t1(E)	160	# 4	9' - 9"	—————
v1(E)	40	# 4	3' - 6"	—————
v2(E)	80	# 5	3' - 6"	—————┘
w2(E)	80	# 5	18' - 10"	—————
w3(E)	80	# 5	22' - 10"	—————
CONCRETE REMOVAL			CU. YD.	11.8
APPROACH SLAB REMOVAL			SQ. YD.	534
BRIDGE APPROACH SHOULDER REMOVAL			SQ. YD.	47
PAVED SHOULDER REMOVAL			SQ. YD.	272
CONCRETE SUPERSTRUCTURE			CU. YD.	11.5
CONCRETE SUPERSTRUCTURE (APPROACH SLAB)			CU. YD.	82.6
CONCRETE STRUCTURES			CU. YD.	26
REINFORCEMENT BARS EPOXY COATED			POUNDS	60000
PAVEMENT CONNECTOR (PCC) FOR BRIDGE APPROACH SLAB			SQ. YD.	648
BRIDGE DECK GROOVING			SQ. YD.	915
PROTECTICE COAT			SQ. YD.	390
TIE BARS 1 1/4"			EACH	78
SHOULDER INLET WITH CURB			EACH	2
WELDED WIRE REINFORCEMENT			SQ. YD.	187

**BILL OF MATERIALS  
STRUCTURE NO. 050-0213 (NB)**

BAR	NO. BARS	SIZE	LENGTH	SHAPE
a9(E)	4	# 7	19' - 4"	—————
a10(E)	4	# 7	23' - 4"	—————
a11(E)	90	# 5	18' - 10"	—————
a12(E)	120	# 8	18' - 10"	—————
a13(E)	124	# 5	6' - 8"	—————┘
a14(E)	90	# 5	22' - 10"	—————
a15(E)	120	# 8	22' - 10"	—————
a16(E)	72	# 4	11' - 9"	—————
a17(E)	18	# 4	10' - 10"	—————┘
b5(E)	124	# 5	29' - 9"	—————
b6(E)	200	# 9	29' - 9"	—————
b7(E)	4	# 5	20' - 8"	—————
b8(E)	276	# 6	25' - 1"	—————
b9(E)	24	# 5	25' - 1"	—————
d2(E)	8	# 4	5' - 2"	—————
d3(E)	8	# 5	3' - 11"	—————
h2(E)	8	# 6	17' - 9"	—————
h3(E)	8	# 6	21' - 9"	—————
t1(E)	160	# 4	9' - 9"	—————
v1(E)	40	# 4	3' - 6"	—————
v2(E)	80	# 5	3' - 6"	—————┘
w2(E)	80	# 5	18' - 10"	—————
w3(E)	80	# 5	22' - 10"	—————
CONCRETE REMOVAL			CU. YD.	11.8
APPROACH SLAB REMOVAL			SQ. YD.	534
BRIDGE APPROACH SHOULDER REMOVAL			SQ. YD.	47
PAVED SHOULDER REMOVAL			SQ. YD.	272
CONCRETE SUPERSTRUCTURE			CU. YD.	11.5
CONCRETE SUPERSTRUCTURE (APPROACH SLAB)			CU. YD.	82.6
CONCRETE STRUCTURES			CU. YD.	26
REINFORCEMENT BARS EPOXY COATED			POUNDS	60000
PAVEMENT CONNECTOR (PCC) FOR BRIDGE APPROACH SLAB			SQ. YD.	648
BRIDGE DECK GROOVING			SQ. YD.	915
PROTECTICE COAT			SQ. YD.	390
TIE BARS 1 1/4"			EACH	78
SHOULDER INLET WITH CURB			EACH	2
WELDED WIRE REINFORCEMENT			SQ. YD.	187

MODEL: Default  
 FILE: Model: 30448barroom.dwg  
 PLOT DATE = 12/17/2020  
 PROJECT: 30448barroom.dwg  
 OFFICE: 30448barroom.dwg  
 CADD: 30448barroom.dwg

USER NAME = woodshankr	DESIGNED - RW	REVISED -
DRAWN - RW	CHECKED - EM	REVISED -
PLOT SCALE = 100.0000' / in.	DATE - 8/5/2020	REVISED -


**STATE OF ILLINOIS  
DEPARTMENT OF TRANSPORTATION**

**GENERAL PLAN AND ELEVATION  
STRUCTURE NO. 050-0212 (SB) & STRUCTURE NO. 050-0213 (NB)**

SCALE: SHEET 9 OF 11 SHEETS STA. TO STA.

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
39	(50-1VB & 50-1B)BRR	LASALLE	30	27
CONTRACT NO. 66L17				
ILLINOIS FED. AID PROJECT				





**STANDARD BAR SPLICER ASSEMBLY PLAN**  
(ALL COMPONENTS SHALL BE PROVIDED FROM ONE SUPPLIER)

THREADED SPLICER BAR LENGTH = MIN. LAP LENGTH + 1 1/2" + THREAD LENGTH


\* EPOXY NOT REQUIRED ON BAR SPLICER ASSEMBLY COMPONENTS USED IN CONJUNCTION WITH BLACK BARS.

**STRUCTURE NO. 050-0212 (SB)**

LOCATION	BAR SIZE	NO. ASSEMBLIES REQUIRED	MINIMUM LAP LENGTH
N. ABUT. DECK	#7	2	4'-8"
N. ABUT END DAM	#6	4	4'-0"
N. APPROACH SLAB	#5	45	3'-0"
	#8	60	4'-9"
N APPROACH FOOTING	#5	40	3'-0"
N APPROACH PAVEMENT CONNECTOR	#4	18	2'-5"
S. ABUT. DECK	#7	2	4'-8"
S. ABUT END DAM	#6	4	3'-4"
S. APPROACH SLAB	#5	45	3'-0"
	#8	60	4'-9"
S. APPROACH FOOTING	#5	40	3'-0"
S. APPROACH PAVEMENT CONNECTOR	#4	18	2'-5"
<b>TOTAL</b>		<b>338</b>	


**STRUCTURE NO. 050-0213 (NB)**

LOCATION	BAR SIZE	NO. ASSEMBLIES REQUIRED	MINIMUM LAP LENGTH
N. ABUT. DECK	#7	2	4'-8"
N. ABUT END DAM	#6	4	4'-0"
N. APPROACH SLAB	#5	45	3'-0"
	#8	60	4'-9"
N APPROACH FOOTING	#5	40	3'-0"
N APPROACH PAVEMENT CONNECTOR	#4	18	2'-5"
S. ABUT. DECK	#7	2	4'-8"
S. ABUT END DAM	#6	4	3'-4"
S. APPROACH SLAB	#5	45	3'-0"
	#8	60	4'-9"
S. APPROACH FOOTING	#5	40	3'-0"
S. APPROACH PAVEMENT CONNECTOR	#4	18	2'-5"
<b>TOTAL</b>		<b>338</b>	



**INSTALLATION AND SETTING METHODS**

"A" : SET BAR SPLICER ASSEMBLY BY MEANS OF A TEMPLATE BOLT.  
 "B" : SET BAR SPLICER ASSEMBLY BY NAILING TO WOOD FORMS OR CEMENTING TO STEEL FORMS.  
 (E) : INDICATES EPOXY COATING.



**BAR SPLICER**

**STRUCTURE NO. 050-0212 (SB)**

LOCATION	BAR SIZE	NO. ASSEMBLIES REQUIRED
N. ABUT END DAM	#5	62

**STRUCTURE NO. 050-0213 (NB)**

LOCATION	BAR SIZE	NO. ASSEMBLIES REQUIRED
N. ABUT END DAM	#5	62

NOTES:  
 SPLICER BARS SHALL BE DEFORMED WITH THREADED ENDS AND HAVE A MINIMUM 60 KSI YIELD STRENGTH.  
 ALL REINFORCEMENT SHALL BE LAPPED AND TIED TO THE SPLICER BARS.  
 BAR SPLICER ASSEMBLIES SHALL BE EPOXY COATED ACCORDING TO THE REQUIREMENTS FOR REINFORCEMENT BARS. SEE SECTION 508 OF THE STANDARD SPECIFICATIONS.  
 SEE APPROVED LIST OF BAR SPLICER ASSEMBLIES AND MECHANICAL SPLICERS FOR ALTERNATIVES.

MODEL: Default  
 FILE NAME: \\p0101amr001\p0101\work\050-0212\050-0212.dwg  
 PROJECT: 050-0212  
 OFFICE: DISTRICT 3  
 DATE: 1/26/2021


USER NAME = woodshank1	DESIGNED - RW	REVISED -
	DRAWN - RW	REVISED -
PLOT SCALE = 100,0000' / in.	CHECKED - EM	REVISED -
PLOT DATE = 1/26/2021	DATE - 8/5/2020	REVISED -

**STATE OF ILLINOIS  
 DEPARTMENT OF TRANSPORTATION**

**BAR SPLICER ASSEMBLY AND MECHANICAL SPLICER DETAILS FOR  
 STRUCTURE NO. 050-0212 (SB) & STRUCTURE NO. 050-0213 (NB)**


SCALE: SHEET 11 OF 11 SHEETS STA. TO STA.

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
39	(50-1VB & 50-1B)BRR	LASALLE	30	29
CONTRACT NO. 66L17				
ILLINOIS FED. AID PROJECT				



**LINEATOR DELINEATOR APPLICATION TO STANDARD GALVANIZED GUARDRAIL**

LINEATOR DELINEATOR SHALL BE APPLIED ACCORDING TO THE MANUFACTURER'S RECOMMENDATIONS



**TYPICAL PAVEMENT MARKINGS**

MODEL: Default  
FILE: \\nas01c.pw.us.ibm.com\data\illinois.gov\PIW\DOT\Documents\DOT\_Offices\District 3\Projects\17\17-Cover.dgn

USER NAME = woodshankrl	DESIGNED - RW	REVISED -
	DRAWN - RW	REVISED -
PLOT SCALE = 100.0000' / in.	CHECKED - EM	REVISED -
PLOT DATE = 12/17/2020	DATE - 8/5/2020	REVISED -

**STATE OF ILLINOIS  
DEPARTMENT OF TRANSPORTATION**

<b>MISCELLANEOUS DETAILS</b>			
SCALE:	SHEET 1 OF 1 SHEETS	STA.	TO STA.

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
39	(50-1VB & 50-1B)BRR	LASALLE	30	30
CONTRACT NO. 66L17				
ILLINOIS		FED. AID PROJECT		