

IOTES:

LIMIT OF RESURFACING ON SIDE-STREETS THROUGH OUT THE IMPROVEMENT SHALL BE TO THE RADIUS OF RETURN OR AS DIRECTED BY THE ENGINEER

ALL FINAL PAVEMENT MARKINGS SHALL BE THERMOPLASTIC (OF THE EXTRUDED TYPE) AND SHOULD BE PLACED IN ACCORDANCE WITH "DISTRICT ONE TYPICAL PAVEMENT MARKINGS" DETAIL, (TC-13).

ALL RAISED REFLECTIVE PAVEMENT MARKINGS SHALL BE PLACED IN ACCORDANCE WITH THE DISTRICT ONE "TYPICAL APPLICATIONS RAISED REFLECTIVE PAVEMENT MARKER DETAIL." (TC-11).

FILE NAME =	USER NAME = banksl	DESIGNED -	REVISED -	Γ
c:\projects\d103408\design_aa.dgn		DRAWN -	REVISED -	
	PLOT SCALE = 50:0.0000 ':' / IN.	CHECKED -	REVISED -	
	PLOT DATE = 2/19/2008	DATE -	REVISED -	Ŀ

	STATE	OF	ILLINOIS	
DEPARTI	MENT	OF '	TRANSPORTATION	

IL. ROUTE	31@ CRYS	STAL	LAKE	AVEN	IUE
PROPOSED I	ROADWAY	AND	PAVE	MENT	MARKING PLANS
SCALE:	SHEET NO.	OF	SHEETS	STA.	TO STA.

F.A.P RTE.	SI	ECTION		COUNTY	TOTAL SHEETS	SHEET NO.
336	11	2 R-N-1		McHENRY	31	11
				CONTRACT	NO. 6	OD52
FED. RO	DAD DIST. NO.	ILLINOIS	FED. AID	PROJECT		