

1. ALL LANDSCAPED AREAS SHALL INCLUDE 6" OF NEW TOPSOIL UNLESS OTHERWISE NOTED. THIS WORK SHALL BE PAID FOR AS TOPSOIL FURNISH AND PLACE, 6"

2. FOR SLOPES STEEPER THAN 1:3, USE HEAVY DUTY EROSION CONTROL BLANKET.

SEEDING, CLASS 2A WITH HEAVY DUTY EROSION CONTROL BLANKET

SEEDING, CLASS 3 WITH HEAVY DUTY EROSION CONTROL BLANKET

SEEDING, CLASS 4A (MODIFIED) WITH EROSION CONTROL BLANKET

SEEDING, CLASS 4B (MODIFIED) WITH EROSION CONTROL BLANKET

STONE RIPRAP, CLASS A3

120003

WETLANDS

(+)

SURFACE WATERS

PROPOSED TREE PROPOSED SHRUB

### ABBREVIATIONS OF COMMON NAMES

SR (SMOOTH SUMAC)

HM (COMMON HACKBERRY)

SWO (SWAMP WHITE OAK)

CO (CHINKAPIN OAK)

CBC (COMMON BALD CYPRESS)

SHS (STAGHORN SUMAC)

GMSM (GREEN MOUNTAIN SUGAR MAPLE)

EKC (EXPRESSO KENTUCKY COFFEETREE)

DR (DAWN REDWOOD)

CSPL (CHINA SNOW PEKING LILAC)

WO (WHITE OAK) IW (IRONWOOD)





USER NAME = NoahA	DESIGNED -	SRB	REVISED -	
	DRAWN -	DJW	REVISED -	
PLOT SCALE = 100.0000 / in.	CHECKED -	MAG	REVISED -	
PLOT DATE = 12/12/2024	DATE -	12/13/24	REVISED -	


STATE OF ILLINOIS **DEPARTMENT OF TRANSPORTATION** 


IL ROUTE 53										
	PERMANENT EROSION CONTROL AND LANDSCAPING PLAN									
SCALE:	1" = 50'	SHEET	5	OF	19	SHEETS	STA.	1161+50.00	TO STA.	1171+00.00


A.P. TE.	SECTION			COUNTY	TOTAL SHEETS	SHEET NO.
42	2018-100-BR			соок	1351	501
				CONTRACT	NO. 62	2N91
	ILLIN	IOIS	FED. AI	D PROJECT		











1. ALL LANDSCAPED AREAS SHALL INCLUDE 6" OF NEW TOPSOIL UNLESS OTHERWISE NOTED. THIS WORK SHALL BE PAID FOR AS TOPSOIL FURNISH AND PLACE, 6"

2. FOR SLOPES STEEPER THAN 1:3, USE HEAVY DUTY EROSION CONTROL BLANKET.

### PERMANENT EROSION CONTROL LEGEND

SEEDING, CLASS 2A WITH EROSION CONTROL BLANKET

SEEDING, CLASS 2A WITH HEAVY DUTY EROSION CONTROL BLANKET

SEEDING, CLASS 3 WITH HEAVY DUTY EROSION CONTROL BLANKET

SEEDING, CLASS 4A (MODIFIED) WITH EROSION CONTROL BLANKET SEEDING, CLASS 4B (MODIFIED) WITH EROSION CONTROL BLANKET

2000 STONE RIPRAP, CLASS A3

\_\_\_\_ WETLANDS

(+)

SURFACE WATERS PROPOSED TREE PROPOSED SHRUB

### ABBREVIATIONS OF COMMON NAMES

SR (SMOOTH SUMAC)

HM (COMMON HACKBERRY)

SWO (SWAMP WHITE OAK)

CO (CHINKAPIN OAK)

CBC (COMMON BALD CYPRESS)

SHS (STAGHORN SUMAC)

GMSM (GREEN MOUNTAIN SUGAR MAPLE)

EKC (EXPRESSO KENTUCKY COFFEETREE)

DR (DAWN REDWOOD)

CSPL (CHINA SNOW PEKING LILAC)

WO (WHITE OAK)


IW (IRONWOOD)





USER NAME = NoahA	DESIGNED - SRB	REVISED -	
	DRAWN - DJW	REVISED -	
PLOT SCALE = 100.0000 / in.	CHECKED - MAG	REVISED -	
PLOT DATE = 1/20/2025	DATE - 12/13/24	REVISED -	


### STATE OF ILLINOIS **DEPARTMENT OF TRANSPORTATION**

F.A.P. RTE	SECTION			COUNTY	TOTAL SHEETS	SHE
342	2018-100-BR			COOK	1351	50
				CONTRACT	NO. 62	2N91
	ILLIN	IOIS	FED. A	D PROJECT		









1. ALL LANDSCAPED AREAS SHALL INCLUDE 6" OF NEW TOPSOIL UNLESS OTHERWISE NOTED. THIS WORK SHALL BE PAID FOR AS TOPSOIL FURNISH AND PLACE, 6"

2. FOR SLOPES STEEPER THAN 1:3, USE HEAVY DUTY EROSION CONTROL BLANKET.

### PERMANENT EROSION CONTROL LEGEND

SEEDING, CLASS 2A WITH EROSION CONTROL BLANKET

SEEDING, CLASS 2A WITH HEAVY DUTY EROSION CONTROL BLANKET

SEEDING, CLASS 3 WITH HEAVY DUTY EROSION CONTROL BLANKET

SEEDING, CLASS 4A (MODIFIED) WITH EROSION CONTROL BLANKET

SEEDING, CLASS 4B (MODIFIED) WITH EROSION CONTROL BLANKET

20003 STONE RIPRAP, CLASS A3 

(+)

WETLANDS

SURFACE WATERS

PROPOSED TREE PROPOSED SHRUB

### ABBREVIATIONS OF COMMON NAMES

SR (SMOOTH SUMAC)

HM (COMMON HACKBERRY)

SWO (SWAMP WHITE OAK)

CO (CHINKAPIN OAK)

CBC (COMMON BALD CYPRESS)

SHS (STAGHORN SUMAC)

GMSM (GREEN MOUNTAIN SUGAR MAPLE)

EKC (EXPRESSO KENTUCKY COFFEETREE)

DR (DAWN REDWOOD)

CSPL (CHINA SNOW PEKING LILAC)


WO (WHITE OAK)


IW (IRONWOOD)




USER NAME = NoahA	DESIGNED -	SRB	REVISED -	
	DRAWN -	DJW	REVISED -	
PLOT SCALE = 100.0000 / in	CHECKED -	MAG	REVISED -	
PLOT DATE = 12/12/2024	DATE -	12/13/24	REVISED -	

F.A.P. RTE	SECTION		COUNTY	TOTAL SHEETS	SHEE NO.
342	2018-100-BR	COOK	1351	506	
			CONTRACT	NO. 62	2N91
	ILLINOIS I	FED. AI	D PROJECT		







1. ALL LANDSCAPED AREAS SHALL INCLUDE 6" OF NEW TOPSOIL UNLESS OTHERWISE NOTED. THIS WORK SHALL BE PAID FOR AS TOPSOIL FURNISH AND PLACE, 6"

2. FOR SLOPES STEEPER THAN 1:3, USE HEAVY DUTY EROSION CONTROL BLANKET.

SEEDING, CLASS 2A WITH EROSION CONTROL BLANKET

SEEDING, CLASS 2A WITH HEAVY DUTY EROSION CONTROL BLANKET

SEEDING, CLASS 3 WITH HEAVY DUTY EROSION CONTROL BLANKET 

SEEDING, CLASS 4A (MODIFIED) WITH EROSION CONTROL BLANKET

SEEDING, CLASS 4B (MODIFIED) WITH EROSION CONTROL BLANKET

120003 STONE RIPRAP, CLASS A3

WETLANDS

(+)

SURFACE WATERS

PROPOSED TREE PROPOSED SHRUB

### ABBREVIATIONS OF COMMON NAMES

SR (SMOOTH SUMAC)

HM (COMMON HACKBERRY)

SWO (SWAMP WHITE OAK)

CO (CHINKAPIN OAK)

CBC (COMMON BALD CYPRESS)

SHS (STAGHORN SUMAC)

GMSM (GREEN MOUNTAIN SUGAR MAPLE)

EKC (EXPRESSO KENTUCKY COFFEETREE)

DR (DAWN REDWOOD)

CSPL (CHINA SNOW PEKING LILAC)


WO (WHITE OAK)


IW (IRONWOOD)


1170 SOUTH HOUBOLT I JOLIET, ILLINOIS 60431 1170 SOUTH HOUBOLT ROAD **STRAND** (815) 744-4200


USER NAME = NoahA	DESIGNED - SRB	REVISED -	
	DRAWN - DJW	REVISED -	
PLOT SCALE = 100.0000 / in.	CHECKED - MAG	REVISED -	
PLOT DATE = 12/12/2024	DATE - 12/13/24	REVISED -	

F.A.P. RTE	SECTION		COUNTY	TOTAL SHEETS	SHEE'
342	2018-100-BR	соок	1351	507	
		CONTRACT	NO. 62	2N91	
	ILLINOIS FE	D. AI	D PROJECT		









1. ALL LANDSCAPED AREAS SHALL INCLUDE 6" OF NEW TOPSOIL UNLESS OTHERWISE NOTED. THIS WORK SHALL BE PAID FOR AS TOPSOIL FURNISH AND PLACE, 6"

2. FOR SLOPES STEEPER THAN 1:3, USE HEAVY DUTY EROSION CONTROL BLANKET.

### PERMANENT EROSION CONTROL LEGEND

SEEDING, CLASS 2A WITH EROSION CONTROL BLANKET

SEEDING, CLASS 2A WITH HEAVY DUTY EROSION CONTROL BLANKET

SEEDING, CLASS 3 WITH HEAVY DUTY EROSION CONTROL BLANKET 

SEEDING, CLASS 4A (MODIFIED) WITH EROSION CONTROL BLANKET

SEEDING, CLASS 4B (MODIFIED) WITH EROSION CONTROL BLANKET

120003 STONE RIPRAP, CLASS A3

WETLANDS

(+)

SURFACE WATERS

PROPOSED TREE PROPOSED SHRUB

### ABBREVIATIONS OF COMMON NAMES

SR (SMOOTH SUMAC)

HM (COMMON HACKBERRY)

SWO (SWAMP WHITE OAK)

CO (CHINKAPIN OAK)

CBC (COMMON BALD CYPRESS)

SHS (STAGHORN SUMAC)

GMSM (GREEN MOUNTAIN SUGAR MAPLE)

EKC (EXPRESSO KENTUCKY COFFEETREE)

DR (DAWN REDWOOD)

CSPL (CHINA SNOW PEKING LILAC)


WO (WHITE OAK)


IW (IRONWOOD)




USER NAME = NoahA	DESIGNED - SRB	REVISED -	
	DRAWN - DJW	REVISED -	
PLOT SCALE = 100.0000 / in	CHECKED - MAG	REVISED -	
PLOT DATE = 12/12/2024	DATE - 12/13/24	REVISED -	

F.A.P. RTE	SECTION		COUNTY	TOTAL SHEETS	SHEE NO.
342	2018-100-BR	соок	1351	509	
			CONTRACT	NO. 62	2N91
	ILLINOIS F	ED. AI	D PROJECT		







1. ALL LANDSCAPED AREAS SHALL INCLUDE 6" OF NEW TOPSOIL UNLESS OTHERWISE NOTED. THIS WORK SHALL BE PAID FOR AS TOPSOIL FURNISH AND PLACE, 6"

2. FOR SLOPES STEEPER THAN 1:3, USE HEAVY DUTY EROSION CONTROL BLANKET.

### PERMANENT EROSION CONTROL LEGEND

SEEDING, CLASS 2A WITH EROSION CONTROL BLANKET

SEEDING, CLASS 2A WITH HEAVY DUTY EROSION CONTROL BLANKET

SEEDING, CLASS 3 WITH HEAVY DUTY EROSION CONTROL BLANKET

SEEDING, CLASS 4A (MODIFIED) WITH EROSION CONTROL BLANKET

SEEDING, CLASS 4B (MODIFIED) WITH EROSION CONTROL BLANKET

20003 STONE RIPRAP, CLASS A3

WETLANDS SURFACE WATERS

PROPOSED SHRUB

(+)PROPOSED TREE

## HM (COMMON HACKBERRY)

ABBREVIATIONS OF COMMON NAMES

SR (SMOOTH SUMAC)

SWO (SWAMP WHITE OAK)

CO (CHINKAPIN OAK)

SHS (STAGHORN SUMAC)

CBC (COMMON BALD CYPRESS)

GMSM (GREEN MOUNTAIN SUGAR MAPLE)

EKC (EXPRESSO KENTUCKY COFFEETREE)

DR (DAWN REDWOOD)

CSPL (CHINA SNOW PEKING LILAC)

WO (WHITE OAK)


IW (IRONWOOD)


2	1170 SOUTH HOUBOLT ROA
	JOLIET, ILLINOIS 60431


STRAND (815) 744-4200

USER NAME = NoahA	DESIGNED - SRB	REVISED -	
	DRAWN - DJW	REVISED -	
PLOT SCALE = 100.0000 / in	CHECKED - MAG	REVISED -	
PLOT DATE = 12/12/2024	DATE 12/13/24	REVISED -	ı

F.A.P. RTE	SECT	ION		COUNTY	TOTAL SHEETS	SHEET NO.
342	2018-100-BR		соок	1351	510	
·				CONTRACT	NO. 62	2N91
		ILLINOIS	FED. A	ID PROJECT		







1. ALL LANDSCAPED AREAS SHALL INCLUDE 6" OF NEW TOPSOIL UNLESS OTHERWISE NOTED. THIS WORK SHALL BE PAID FOR AS TOPSOIL FURNISH AND PLACE, 6"

2. FOR SLOPES STEEPER THAN 1:3, USE HEAVY DUTY EROSION CONTROL BLANKET.

### PERMANENT EROSION CONTROL LEGEND

SEEDING, CLASS 2A WITH EROSION CONTROL BLANKET

SEEDING, CLASS 2A WITH HEAVY DUTY EROSION CONTROL BLANKET

SEEDING, CLASS 3 WITH HEAVY DUTY EROSION CONTROL BLANKET

SEEDING, CLASS 4A (MODIFIED) WITH EROSION CONTROL BLANKET

SEEDING, CLASS 4B (MODIFIED) WITH EROSION CONTROL BLANKET

00000 STONE RIPRAP, CLASS A3

WETLANDS

(+)

SURFACE WATERS

PROPOSED TREE PROPOSED SHRUB

### ABBREVIATIONS OF COMMON NAMES

SR (SMOOTH SUMAC)

HM (COMMON HACKBERRY)

SWO (SWAMP WHITE OAK)

CO (CHINKAPIN OAK)

CBC (COMMON BALD CYPRESS)

SHS (STAGHORN SUMAC)

GMSM (GREEN MOUNTAIN SUGAR MAPLE)

EKC (EXPRESSO KENTUCKY COFFEETREE)

DR (DAWN REDWOOD)

CSPL (CHINA SNOW PEKING LILAC)

WO (WHITE OAK)


IW (IRONWOOD)


1170 SOUTH HOUSE.
JOLIET, ILLINOIS 60431
(815) 744-4200 1170 SOUTH HOUBOLT ROAD **STRAND** (815) 744-4200


USER NAME = NoahA	DESIGNED - SRB	REVISED -
	DRAWN - DJW	REVISED -
PLOT SCALE = 100.0000 / in.	CHECKED - MAG	REVISED -
PLOT DATE = 12/12/2024	DATE - 12/13/24	REVISED -

### STATE OF ILLINOIS **DEPARTMENT OF TRANSPORTATION**

A.P. RTE	SECTION		COUNTY	TOTAL SHEETS	SHEET NO.
342	2018-100-BR	соок	1351	511	
		CONTRACT	NO. 62	2N91	
	ILLINOIS FEI	D. A	ID PROJECT		







1170 SOUTH HOUBOLT ROAD
JOLIET, ILLINOIS 60431

STRAND
(815) 744-4200
ASSO CIATES\*


 USER NAME
 = NoshA
 DESIGNED
 SRB
 REVISED


 PLOT SCALE
 = 100,0000 ' / in.
 CHECKED
 MAG
 REVISED

 PLOT DATE
 = 12/12/2024
 DATE
 12/13/24
 REVISED


STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION


F.A.P. RTE	SECTION		COUNTY	TOTAL SHEETS	SHEET NO.
342	2018-100-BR	соок	1351	512	
		CONTRACT	NO. 62	2N91	
	ILLINOIS	FED. A	ID PROJECT		





12/13/24





### PROPOSED LANDSCAPING SCHEDULE

GREEN MOUN	ITAIN SUGAR	MAPLE (A200	1816)	SWAMP WHIT	E OAK (A2006	6516)	
FROM STATION	TO STATION	LT/RT	EACH	FROM STATION	TO STATION	LT/RT	EACH
1511+00.00	1512+50.00	LT	2	1411+00.00	1414+50.00	LT	3
WHITE OAK (	A2006420)			CHINKAPIN O	AK (A2006816	5)	
FROM STATION	TO STATION	LT/RT	EACH	FROM STATION	TO STATION	LT/RT	EACH
1134+00.00	1137+00.00	LT	1	1134+00.00	1137+00.00	LT	2
1133+00.00	1134+00.00	RT	1	1513+00.00	1515+00.00	LT	2
COMMON HA	CKBERRY (A20	002916)		COMMON BA	LD CYPRESS (	A2007616)	
FROM	TO STATION	LT/RT	EACH	FROM	TO STATION	LT/RT	EACH

STATION	TO STATION	LI/IXI	LACII			
1409+00.00	1411+00.00	RT	2			
1416+00.00	1417+00.00	LT	1			
1513+00.00	1515+00.00	LT	2			
DAWN REDW	OOD (B20053	85)				
FROM STATION	TO STATION	LT/RT	EACH			
1411+00.00	1414+50.00	LT	1			
1409+00.00 1411+00.00 RT 1						
IRONWOOD (A2C05660)						

DUNDEE ROAD

() ()

1449+14.00

710.29' RT

IRONWOOD (A2C05660)						
FROM STATION	TO STATION	LT/RT	EACH			
1134+00.00	1137+00.00	LT	3			
1133+00.00	1134+00.00	RT	2			
1513+00.00	1515+00.00	LT	3			

EXPRESSO KENTUCKY COFFEETREE (A2005040)					
FROM	TO STATION	LT/RT	EACH		
1134+00.00	1137+00.00	LT	3		

	COMMON BAI	_D CYPRESS (	A2007616)	
	FROM STATION	TO STATION	LT/RT	EACH
	1411+00.00	1414+50.00	LT	3

		CHINA SNOW	PEKING LILA	(B2006116)		
_		FROM STATION	TO STATION	LT/RT	EACH	
		1132+00.00	1133+00.00	LT	3	
	STAGHORN SUMAC (C3006024)					

J	STATION	TO STATION	LT/RT	EACH			
]	1415+50.00	1417+50.00	LT	50			
1							
	SMOOTH SUMAC (C3005924)						

SMOOTH SUM	<u>1AC (C300592</u>	4)	
FROM STATION	TO STATION	LT/RT	EACH
1130+50.00	1132+50.00	LT	25
1513+00.00	1515+00.00	LT	50

### PERMANENT EROSION CONTROL LEGEND

EX ROW

SEEDING, CLASS 2A WITH EROSION CONTROL BLANKET

SEEDING, CLASS 2A WITH HEAVY DUTY EROSION CONTROL BLANKET

SEEDING, CLASS 3 WITH HEAVY DUTY EROSION CONTROL BLANKET SEEDING, CLASS 4A (MODIFIED) WITH EROSION CONTROL BLANKET

SEEDING, CLASS 4B (MODIFIED) WITH EROSION CONTROL BLANKET

120003 STONE RIPRAP, CLASS A3

(+)

SCALE: 1" = 50' SHEET 19 OF 19 SHEETS STA. 0+00

EX ROW

1445+13.95 313.25' RT

WETLANDS SURFACE WATERS

PROPOSED TREE PROPOSED SHRUB

### ABBREVIATIONS OF COMMON NAMES

SR (SMOOTH SUMAC)

HM (COMMON HACKBERRY)

SWO (SWAMP WHITE OAK)

CO (CHINKAPIN OAK)

CBC (COMMON BALD CYPRESS)

SHS (STAGHORN SUMAC)

GMSM (GREEN MOUNTAIN SUGAR MAPLE)

EKC (EXPRESSO KENTUCKY COFFEETREE)

DR (DAWN REDWOOD)

CSPL (CHINA SNOW PEKING LILAC)

WO (WHITE OAK)

IW (IRONWOOD)

1454+99.69 300.05' RT

1. ALL LANDSCAPED AREAS SHALL INCLUDE 6" OF NEW TOPSOIL UNLESS OTHERWISE NOTED. THIS WORK SHALL BE PAID FOR AS TOPSOIL FURNISH AND PLACE, 6"

2. FOR SLOPES STEEPER THAN 1:3, USE HEAVY DUTY EROSION CONTROL BLANKET.

STATE OF ILLINOIS

DUNDEE ROAD NE RAMP PERMANENT EROSION CONTROL AND LANDSCAPING PLAN

SECTION 2018-100-BR COOK 1351 515 CONTRACT NO. 62N91

1170 SOUTH HOUBOLT F JOLIET, ILLINOIS 60431 1170 SOUTH HOUBOLT ROAD **STRAND** (815) 744-4200

SRB DESIGNED -REVISED DRAWN DJW REVISED LOT SCALE = 100.0000 / in. HECKED MAG REVISED 12/13/24

EX BE RAMP B

1448+98.20

719.46 RT

**DEPARTMENT OF TRANSPORTATION** 

# TRAFFIC SIGNAL LEGEND


(NOT TO SCALE)

				(NOT TO SCALE)				
<u>ITEM</u>	EXISTING	PROPOSED	ITEM	EXISTING	PROPOSED	<u>ітем</u>	EXISTING	PROPOSED
CONTROLLER CABINET		$\blacksquare$	HANDHOLE -SQUARE		<b>N 0</b>	SIGNAL HEAD -(P) PROGRAMMABLE SIGNAL HEAD		R R
COMMUNICATION CABINET	ECC	cc	-ROUND	_		TO THOUSANDADE STORAGE TEAD		Y C C
MASTER CONTROLLER	EMC	MC	HEAVY DUTY HANDHOLE -SQUARE -ROUND		⊞ ⊕		8	C C C C C C C C C C C C C C C C C C C
MASTER MASTER CONTROLLER	EMMC	ммс	DOUBLE HANDHOLE			Marin spheridaes - Discourt transferent Steels - P.C. spheridae and discourt Africa.		, 
UNINTERRUPTABLE POWER SUPPLY	<b>3</b>	<b>3</b>	JUNCTION BOX		•	SIGNAL HEAD WITH BACKPLATE  -(P) PROGRAMMABLE SIGNAL HEAD  -(RB) RETROREFLECTIVE BACKPLATE		R R Y
SERVICE INSTALLATION	P	P	RAILROAD CANTILEVER MAST ARM	X <del>0X</del> == <del>X</del> X	<del>161 1</del>			G G G G 4Y 4Y 4Y 4G
-(P) POLE MOUNTED  SERVICE INSTALLATION			RAILROAD FLASHING SIGNAL	<del>∑⊙</del> ∑	X+X		P RB	P RB
-(G) GROUND MOUNTED -(GM) GROUND MOUNTED METERED	$\boxtimes^{G}\boxtimes^{GM}$	<b>⊠</b> <sup>G</sup> <b>⊠</b> <sup>GM</sup>	RAILROAD CROSSING GATE	<del>XoX</del> =-	X->	PEDESTRIAN SIGNAL HEAD	<b>©</b>	•
TELEPHONE CONNECTION	ET	Т	RAILROAD CROSSBUCK	查		AT RAILROAD INTERSECTIONS	<b>®</b> <b>X</b>	×
STEEL MAST ARM ASSEMBLY AND POLE	0	•	RAILROAD CONTROLLER CABINET		⋗⋖	PEDESTRIAN SIGNAL HEAD	© C D	<b>₽</b> C <b>★</b> D
ALUMINUM MAST ARM ASSEMBLY AND POLE	a===		UNDERGROUND CONDUIT (UC), GALVANIZED STEEL		<del></del>	WITH COUNTDOWN TIMER	0	
STEEL COMBINATION MAST ARM ASSEMBLY AND POLE WITH LUMINAIRE	o¤—	•*	TEMPORARY SPAN WIRE, TETHER WIRE, AND CABLE	( <del></del>	98	ILLUMINATED SIGN "NO LEFT TURN"/"NO RIGHT TURN"		
SIGNAL POST -(BM) BARREL MOUNTED - TEMPORARY	0	• • BM	SYSTEM ITEM INTERSECTION ITEM	S	SP IP	NUMBER OF CONDUCTORS, ELECTRIC CABLE NO. 14, UNLESS NOTED OTHERWISE. ALL DETECTOR LOOP CABLE TO BE SHIELDED	_5	
WOOD POLE	8	0	REMOVE ITEM	•	R	GROUND CABLE IN CONDUIT,	— <u>(1#6)</u> —	
GUY WIRE	>-	>-	RELOCATE ITEM		RL	NO. 6 SOLID COPPER (GREEN)	2:0	100
SIGNAL HEAD	>	-	ABANDON ITEM		Α	ELECTRIC CABLE IN CONDUIT, TRACER NO. 14 1/C	<del>_</del> 1	
SIGNAL HEAD WITH BACKPLATE	+(>	+-	CONTROLLER CABINET AND		RCF	COAXIAL CABLE	<u> </u>	—©—
SIGNAL HEAD OPTICALLY PROGRAMMED	-> <sup>p</sup> +> <sup>p</sup>	→ P + → P	FOUNDATION TO BE REMOVED  MAST ARM POLE AND			VENDOR CABLE	_ <u>_</u>	<b>─</b> ♥─
FLASHER INSTALLATION -(FS) SOLAR POWERED	ot> <sup>F</sup> ot> <sup>FS</sup>	•► FS	FOUNDATION TO BE REMOVED		RMF	COPPER INTERCONNECT CABLE,		
	oh⇒ <sup>F</sup> oh⇒ <sup>FS</sup>	■→ FS	SIGNAL POST AND FOUNDATION TO BE REMOVED		RPF	NO. 18, 3 PAIR TWISTED, SHIELDED	<u></u>	<u></u>
PEDESTRIAN SIGNAL HEAD	-D	- <del>-  </del>	DETECTOR LOOP, TYPE I			FIBER OPTIC CABLE -NO. 62.5/125, MM12F -NO. 62.5/125, MM12F SM12F		—(12F)—
PEDESTRIAN PUSH BUTTON -(APS) ACCESSIBLE PEDESTRIAN PUSH BUTTON		⊚ ⊚ APS	PREFORMED DETECTOR LOOP	P (P)	PP	-NO. 62.5/125, MM12F SM24F		—(24F)—
RADAR DETECTION SENSOR	(R)1	R	SAMPLING (SYSTEM) DETECTOR	s (s)	5 (5)		—(36F)—	
VIDEO DETECTION CAMERA	L()	<b>⊙</b> •	INTERSECTION AND SAMPLING (SYSTEM) DETECTOR	15 (15)	IS (IS)	2221112 222		
RADAR/VIDEO DETECTION ZONE		<b>=</b>	QUEUE AND SAMPLING (SYSTEM) DETECTOR	qs qs	os os	GROUND ROD -(C) CONTROLLER -(M) MAST ARM	T T T T	T T T
PAN, TILT, ZOOM (PTZ) CAMERA	PTZ]]	PTZ <b>■</b>	WIRELESS DETECTOR SENSOR	<b>®</b>	<b>Ø</b>	-(P) POST -(S) SERVICE		
EMERGENCY VEHICLE LIGHT DETECTOR	$\Diamond$	=	WIRELESS ACCESS POINT		-			
CONFIMATION BEACON	D0							
WIRELESS INTERCONNECT	○ <del>+   </del>	<u>•+III</u>						
WIRELESS INTERCONNECT RADIO REPEATER	ERR	RR						
USER NAME - footemj  PLOT SCALE = 50.0000 ' / I  PLOT DATE - 3/4/2019	NO	IP REVISED .		TE OF ILLINOIS T OF TRANSPORTATION	Leader Comment	DISTRICT ONE  NDARD TRAFFIC SIGNAL DESIGN DETAILS  HEET 1 OF 7 SHEETS STA. TO STA.	F.A.P. SECTIO RTE. 342 2018-100 TS-05	en and alleria


### LOOP DETECTOR NOTES

- EACH PAIR OF LOOP WIRES SHALL BE PLACED IN A SEPARATE EMPTY COILABLE NONMETALLIC CONDUIT FROM THE EDGE OF PAVEMENT TO THE HANDHOLE. SPACING BETWEEN THE HOLES DRILLED IN THE PAVEMENT SHALL NOT BE LESS THAN 6" (150 mm). EMPTY COILABLE NONMETALLIC CONDUIT SHALL BE INCLUDED IN THE COST OF THE LOOP WIRE.
- THE NUMBER OF LOOP TURNS SHALL BE AS RECOMMENDED BY THE AMPLIFIER MANUFACTURER.
  ALL ADJACENT SIDES OF THE LOOPS SHALL BE INSTALLED IN SUCH A WAY THAT THE CURRENT
  FLOW IS IN THE SAME DIRECTION TO REINFORCE ITS MAGNETIC FIELDS FOR SMALL VEHICLE
  DETECTION.
- 3. EACH LOOP LEAD-IN SHALL BE IDENTIFIED AND PERMANENTLY TAGGED IN THE HANDHOLE. EACH LEAD-IN CABLE TAG SHALL INDICATE THE LOCATION OF THE LOOP, LOOP ROTATION (CLOCKWISE/COUNTERCLOCKWISE), LOOP LEAD-IN DIRECTION (IN OR OUT), LOOP CABLE NUMBER AND LOCATION IN CABINET, AND NUMBER OF TURNS IN THE DETECTOR LOOPS IN WATER PROOF INK AS INDICATED ON THE DISTRICT 1 STANDARD TRAFFIC SIGNAL DESIGN DETAIL. THE CONTRACTOR SHALL MARK LOOP LOCATIONS ON RECORD DRAWINGS AND PRESENT TO THE ENGINEER AFTER FINAL INSPECTION. LOOPS SHALL BE MARKED BY LANE AND LOOP NUMBER. SEE DETAIL BELOW.
- 4. ALL LOOP CABLE SHALL BE FASTENED WITH PLASTIC TIE WRAP TO THE HANDHOLE HOOKS.
- 5. IN ASPHALT PAVEMENT, LOOPS SHOULD BE PLACED IN THE BINDER AND DIVEHOLES MARKED AT THE CURB WITH A SAW-CUT. THE SAW-CUT SHALL BE CUT IN ACCORDANCE WITH LOCAL AND E,P,A, DUST CONTROL REQUIREMENTS. DETECTOR LOOP(S) SHALL NOT BE INSTALLED IN WET CONDITIONS AND THE SAW-CUTS MUST BE FREE OF DEBRIS AND RESIDUE SUCH AS DUST AND WATER WHICH IS TO BE ACHIEVED BY THE USE OF COMPRESSED AIR, WIRE BRUSHING AND HEAT DRYING ACCORDING TO SEALANT MANUFACTURER REQUIREMENTS. THE DETECTOR WIRE SHALL BE HELD IN PLACE BY THE USE OF FORM WEDGES. WEDGES SHALL BE SPACED NO MORE THAN 18" (450 mm) APART.
- LOOP SPLICES SHALL BE SOLDERED USING A SOLDERING IRON. BLOW TORCHES OR OTHER DEVICES WHICH OXIDIZE COPPER CABLE SHALL NOT BE ALLOWED FOR SOLDERING OPERATIONS. SEE DETAIL BELOW RIGHT.
- 7. PREFORMED DETECTOR LOOPS SHALL BE USED, AS SHOWN ON THE PLANS, WHERE NEW CONCRETE PAVEMENT IS PROPOSED. THE INSTALLATION OF PREFORMED LOOPS SHALL BE IN ACCORDANCE WITH THE DISTRICT 1 SPECIFICATIONS OR AS DIRECTED BY THE ENGINEER.

### LOOP LEAD-IN CABLE TAG





- A. LANE 1 IS THE LANE CLOSEST TO THE CENTERLINE OF THE ROADWAY
- B. LOOP #1 IS THE LOOP IN THE LANE CLOSEST TO THE INTERSECTION.
- C. LABEL LOOP CABLE "IN" OR LOOP CABLE "OUT".
- D. LABEL LOOP CABLE CLOCKWISE OR LOOP CABLE COUNTERCLOCKWISE.



### **DETECTOR LOOP WIRING SCHEMATIC**

- LOOPS SHALL BE SPLICED IN SERIES.
   SAW-CUTS SHALL BE A MINIMUM WIDTH OF 5/16" (8 mm).
- SAW-CUT DEPTHS SHALL BE 3" (75 mm). IF IN CONCRETE,
- THE SAW-CUT DEPTH SHALL BE TO THE TOP OF THE REINFORCEMENT.
- LOOP CORNERS SHALL BE DRILLED WITH A 2" (50 mm) DIAMETER CORE.





### LOOP DETECTOR SPLICE

- 1 WESTERN UNION SPLICE SOLDERED WITH ROSIN CORE FLUX. ALL EXPOSED SURFACES OF THE SOLDER SHALL BE SMOOTH. THE WESTERN UNION SPLICES SHALL BE STAGGERED.
- (2) WCSMW 30/100 HEAT SHRINK TUBE, MINIMUM LENGTH 3" (75 mm), UNDERWATER GRADE.
- (3) WCS 200/750 HEAT SHRINK TUBE, MINIMUM LENGHT 6" (150 mm), UNDERWATER GRADE.

SCALE: NONE

(4) NO. 14 2/C TWISTED, SHIELDED CABLE.

- 5 LOOP CONDUCTOR WITH FLEXIBLE PLASTIC TUBE. PRE-FORMED LOOP
- (6) XL POLYOLEFIN 2 CONDUCTOR
- (7) BREAKOUT SEALS. TYCO CBR-2 OR APPROVED EQUAL


STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

MODEL: Detault

### TRAFFIC SIGNAL MAST ARM AND SIGNAL POST


MAST ARM MOUNTED SIGNALS IN EXISTING, PROPOSED OR FUTURE SIDEWALK/BICYCLE PATH AREA. INTERSECTION SHOWN WITH PEDESTRIAN SIGNALS AND

PEDESTRIAN PUSHBUTTON DETECTORS.




- 2. REFER TO THE TRAFFIC SIGNAL EQUIPMENT OFFSET TABLE.
- PROVIDE A LEVEL ALL-WEATHER SURFACE (CONCRETE SIDEWALK, ASPHALT BICYCLE PATH SURFACE OR MATCHING MATERIAL TO THE ADJACENT SURFACE) UP TO THE MAST ARM SHAFT OR THE SIGNAL POST.
- THE FACE OF THE PEDESTRIAN PUSHBUTTON SHALL BE PARALLEL TO THE CROSSWALK TO BE USED.
- 5. THE LOCATIONS AND INSTALLATION OF PEDESTRIAN SIGNAL HEADS AND PEDESTRIAN PUSHBUTTONS SHALL MEET THE REQUIREMENTS OF THE MUTCD AND INFORMATION FOUND IN THE "AMERICANS WITH DISABILITIES ACT ACCESSIBILITY GUIDELINES FOR BUILDINGS AND FACILITIES."

# PEDESTRIAN SIGNAL POST AND PEDESTRIAN PUSH BUTTON POST



### NOTES:

- 1. REFER TO THE TRAFFIC SIGNAL EQUIPMENT OFFSET TABLE.
- PROVIDE A LEVEL ALL-WEATHER SURFACE (CONCRETE SIDEWALK, ASPHALT BICYCLE PATH SURFACE OR MATCHING MATERIAL TO THE ADJACENT SURFACE) UP TO THE PEDESTRIAN SIGNAL POST OR THE PEDESTRIAN PUSH BUTTON POST.
- THE FACE OF THE PEDESTRIAN PUSHBUTTON SHALL BE PARALLEL TO THE CROSSWALK TO BE USED.
- 4. THE LOCATIONS AND INSTALLATION OF PEDESTRIAN SIGNAL HEADS AND PEDESTRIAN PUSHBUTTONS SHALL MEET THE REQUIREMENTS OF THE MUTCD AND INFORMATION FOUND IN THE "AMERICANS WITH DISABILITIES ACT ACCESSIBILITY GUIDELINES FOR



- \* WHERE THERE ARE CONSTRAINTS THAT MAKE IT IMPRACTICAL TO PLACE THE PEDESTRIAN PUSHBUTTON BETWEEN 1.5 FT (0.45 m) AND 6 FT (1.8 m) FROM THE EDGE OF THE CURB, SHOULDER, OR PAVEMENT, IT SHOULD NOT BE FURTHER THAN 10 FT (3 m) FROM THE EDGE OF CURB, SHOULDER, OR PAVEMENT.
- \*\* WHERE THERE ARE CONSTRAINTS ON A PARTICULAR CORNER THAT MAKE IT IMPRACTICAL TO PROVIDE THE 10 FT (3 m) SEPERATION BETWEEN THE TWO PEDESTRIAN PUSHBUTTONS, THE PUSHBUTTONS MAY BE PLACED CLOSER TOGETHER OR ON THE SAME POLE.

### NOTES:

- PEDESTRIAN SIGNAL HEADS SHALL BE MOUNTED WITH THE BOTTOM OF THE SIGNAL HOUSING INCLUDING BRACKETS NOT LESS THAN 8 FT (2.4 m) OR MORE THAN 10 FT (3 m) ABOVE SIDEWALK LEVEL, AND SHALL BE POSITIONED AND ADJUSTED TO PROVIDE MAXIMUM VISIBILITY AT THE BEGINNING OF THE CONTROLLED CROSSWALK.
- THE BOTTOM OF THE SIGNAL HOUSING (INCLUDING BRACKETS) OF A VEHICULAR SIGNAL FACE THAT IS NOT LOCATED OVER A HIGHWAY SHALL BE AT LEAST 8 FT (2.4 m) BUT NOT MORE THAN 19 FT (5.8 m) ABOVE THE SIDEWALK OR, IF THERE IS NO SIDEWALK, ABOVE THE PAVEMENT GRADE AT THE CENTER OF THE ROADWAY.
- 3. THE BOTTOM OF THE SIGNAL HOUSING AND ANY RELATED ATTACHMENTS TO A SIGNAL FACE LOCATED OVER ANY PORTION OF A HIGHWAY SHALL BE ACCORDING TO CURRENT STATE STANDARDS 877001, 877002, 877006, 877011 AND 877012 WITH A MINIMUM OF 16 FT (5.0 m) AND A MAXIMUM OF 18 FT. (5.5 m) FROM THE HIGHEST POINT OF PAVEMENT.
- 4. THE BOTTOM OF THE TEMPORARY SPAN WIRE MOUNTED SIGNAL HOUSING AND ANY RELATED ATTACHMENTS TO A SIGNAL FACE LOCATED OVER ANY PORTION OF A HIGHWAY SHALL BE ACCORDING TO CURRENT STATE STANDARD 880001 WITH A MINIMUM OF 17 FT (5.18 m) FROM THE HIGHEST POINT OF PAVEMENT.
- THE TOP OF THE SIGNAL HOUSING OF A SIGNAL FACE LOCATED OVER ANY PORTION OF A HIGHWAY SHALL NOT BE MORE THAN 25.6 FT (7.8 m) ABOVE THE PAVEMENT.

#### TRAFFIC SIGNAL EQUIPMENT OFFSET

TRAFFIC SIGNAL EQUIPMENT	COMBINATION CONCRETE CURB AND GUTTER (MINIMUM DISTANCE FROM BACK OF CURB TO CENTERLINE OF FOUNDATION)	SHOULDER/NON-CURBED AREA (MINIMUM DISTANCE FROM EDGE OF PAVEMENT TO CENTERLINE OF FOUNDATION)
TRAFFIC SIGNAL MAST ARM POLE	6 FT (1.8m)	SHOULDER WIDTH + 2 FT (0.5m), MINIMUM 10 FT (3.0m)
TRAFFIC SIGNAL POST	4 FT (1,2m)	SHOULDER WIDTH + 2 FT (0.6m), MINIMUM 10 FT (3.0m)
PEDESTRIAN SIGNAL POST	4 FT (1.2m)	SHOULDER WIDTH + 2 FT (0.6m), MINIMUM 10 FT (3.0m)
PEDESTRIAN PUSHBUTTON POST	4 FT (1.2m)	SHOULDER WIDTH + 2 FT (0.5m), MINIMUM 10 FT (3.0m)
TEMPORARY WOOD POLE	6 FT (1.8m)	SHOULDER WIDTH + 2 FT (0.6m). MINIMUM 10 FT (3.0m)
CONTROLLER CABINET	6 FT (1.8m) MINIMUM DISTANCE SEE NOTE 2	SHOULDER WIDTH + 6 FT (1.3m), MINIMUM 16 FT (4.9m) SEE NOTE 3.
SERVICE INSTALLATION, GROUND MOUNT	6 FT (1.8m) MINIMUM DISTANCE SEE NOTE 2	SHOULDER WIDTH + 6 FT (1.8m), MINIMUM 16 FT (4.9m) SEE NOTE 3.

### NOTES:


- 1. CONTACT THE "AREA TRAFFIC SIGNAL MAINTENANCE AND OPERATIONS ENGINEER" FOR ASSISTANCE IN LOCATING THE TRAFFIC SIGNAL EQUIPMENT WHEN THERE ARE CONFLICTS WITH DITCHES OR THE MINIMUM OFFSET DISTANCES CANNOT BE MET.
- 2. MINIMUM DISTANCE FROM THE BACK OF CURB TO THE ROADWAY SIDE OF THE FOUNDATION.
- 3. MINIMUM DISTANCE FROM THE EDGE OF PAVEMENT TOTHE ROADWAY SIDE OF THE FOUNDATION.
- 4. ANY CHANGES TO THE OFFSETS OF THE FOUNDATIONS, FROM THE MINIMUM DISTANCES LISTED IN THE "TRAFFIC SIGNAL EQUIPMENT OFFSET" CHART AND THE TRAFFIC SIGNAL INSTALLATION PLAN, COULD EFFECT THE PLACEMENT OF THE SIGNAL HEADS, PEDESTRIAN SIGNAL HEADS AND THE PEDESTRIAN PUSHBUTTONS. THE SIGNAL HEAD PLACEMENT ON THE MAST ARMS SHALL REMAIN AS PER THE TRAFFIC SIGNAL INSTALLATION PLAN AND THE "TRAFFIC SIGNAL MAST ARM AND SIGNAL POST" DETAIL ABOVE. THE PROPOSED MAST ARM LENGTHS MAY NEED TO BE REVISED TO MEET THE ABOVE REQUIREMENTS. THE PEDESTRIAN SIGNAL HEADS AND PEDESTRIAN PUSHBUTTONS MUST MEET THE REQUIREMENTS UNDER THE DETAILS ON THIS SHEET.


SCALE: NONE


USER NAME - footemj	DESIGNED =	REVISED -
	DRAWN -	REVISED .
PLOT SCALE = 50.0000 ' / In.	CHECKED -	REVISED -
PLOT DATE = 3/4/2019	DATE -	REVISED -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

	F.A.P.	LATATE FOR CONTROL OF	4	TOTAL	SHEE
DISTRICT ONE	RTE.	SECTION	COUNTY	SHEETS	NO.
STANDARD TRAFFIC SIGNAL DESIGN DETAILS	SIGNAL DESIGN DETAILS	2018-100-BR	соок	1351	518
STANDARD TRAFFIC SIGNAL DESIGN DETAILS		TS-05	CONTRAC	F NO. 62	2N91
SHEET 3 OF 7 SHEETS STA, TO STA,		ILLINOIS FED	AID PROJECT		







TYPE C
FOR GROUND MOUNTED
SUPER P (TYPE IV) AND SUPER R (TYPE V)
CONTROLLER CABINETS

SEE NOTE 5	
2° x 6° (51mm x 152mm) WOOD FRAMING (TYP.)	72701 Dece
TRAFFIC SIGNAL —— CONTROLLER CABINET	
UPS   CABINET	
¾" (19mm) TREATED PHYWOOD DECK	
2" x 6" (51mm x 152mm) TREATED WOOD	
-6" x 6" (152mm x 152mm)	
NOTES: TREATED WOOD POSTS  1. BASED ON CONTROLLER CABINET TYPE IV WITH BASE DIMENSIONS OF 26" x 44" (660mm x 1118mm).	

- 1. BASED ON CONTROLLER CABINET TYPE IV WITH BASE DIMENSIONS OF 26" x 44" (660mm x 1118mm). ADJUST PLATFORM SIZE TO FIT CABINET BASE DIMENSIONS BEING SUPPLIED
- 2. BASED ON UNINTERRUPTIBLE POWER SUPPLY CABINET WITH BASE DIMENSIONS OF 16° x 25° (406mm x 635mm). ADJUST PLATFORM SIZE TO FIT CABINET BASE DIMENSIONS BEING SUPPLIED.
- 3. PLATFORM SIZE FOR CONTROLLER CABINET TYPE IV.
- 4. PLATFORM SIZE FOR CONTROLLER CABINET TYPE IV AND UNINTERRUPTIBLE POWER SUPPLY CABINET.
- 5. DRILLED HOLES THROUGH THE PLATFORM BASE TO MATCH THE CONTROLLER CABINET BOLT TEMPLATE. FASTEN THE CONTROLLER CABINET TO THE PLATFORM WITH CARRIAGE BOLTS, WASHERS AND NUTS.
- 6. FASTEN ALL SUPPORT WOOD FRAMING TO THE WOOD POSTS WITH 2 LAG SCREWS FOR EACH CONNECTION..

# TEMPORARY SIGNAL CONTROLLER WOOD SUPPORT PLATFORM

CABLE SLACK LENGTH	FEET	METER
HANDHOLE	6.5	2.0
DOUBLE HANDHOLE	13.0	4.0
SIGNAL POST	2.0	0.6
MAST ARM	2.0	0.6
CONTROLLER CABINET	1.5	0,5
FIBER OPTIC AT CABINET	13.0	4.0
ELECTRIC SERVICE AT (CABINET OR SERVICE LOCATION)	1.5	0.5
GROUND CABLE (SIGNAL POST, MAST ARM, CABINET)	1.5	0.5
GROUND CABLE (BETWEEN FRAME AND COVER)	5.0	1.6

VERTICAL CABLE LENGTH	FEET	METER
MAST ARM POLE ( MAST ARM MOUNTED SIGNAL HEAD) (L = MAST ARM LENGTH - DISTANCE TO SIGNAL HEAD FROM END OF ARM)	20.0+L	6.0+L
BRACKET MOUNTED (MAST ARM POLE OR SIGNAL POLE)	13.0	4.0
PEDESTRIAN PUSH BUTTON	6.0	2.0
SERVICE INSTALLATION POLE MOUNT TO SERVICE DROP	13,5	4.1
SERVICE INSTALLATION POLE MOUNT TO GROUND	13.5	4.1
SERVICE INSTALLATION GROUND MOUNT	6.0	2.0
FOUNDATION (SIGNAL POST, MAST ARM POLE, CONTROLLER CABINET, SERVICE-GROUND MOUNT)	3.0	1.0

### VERTICAL CABLE LENGTH

CABLE SLACK

FOUNDATION	DEPTH
TYPE A - Signal Post	4'-0" (1.2m)
TYPE C - CONTROLLER W/ UPS	4'-0" (1.2m)
TYPE D - CONTROLLER	4'-0" (1.2m)
SERVICE INSTALLATION, GROUND MOUNT, TYPE A - SQUARE	4'-0" (1.2m)

### DEPTH OF FOUNDATION


Mast Arm Length	① Foundation Depth	Diameter	Spiral Diameter	Rebars	Size of Rebars
Less than 30' (9.1 m)	10'-0" (3.0 m)	30" (750mm)	24" (600mm)	8	6(19)
Greater than or equal to	13'-6" (4.1 m)	30" (750mm)	24" (600mm)	8	6(19)
30' (9.1 m) and less than 40' (12.2 m)	11'-0" (3.4 m)	36" (900mm)	30" (750mm)	12	7(22)
Greater than or equal to 40' (12,2 m) and less than 50' (15,2 m)	13'-0" (4.0 m)	36" (900mm)	30" (750mm)	12	7(22)
Greater than or equal to 50' (15,2 m) and up to 55' (16,8 m)	15'-0" (4,6 m)	36" (900mm)	30" (750mm)	12	7(22)
Greater than or equal to 56' (16,8 m) and less than 65' (19,8 m)	21'-0" (6.4 m)	42" (1060mm)	36" (900mm)	16	8(25)
Greater than or equal to 65' (19,8 m) and up to 75' (22,9 m)	25'-0" (7.6 m)	42" (1060mm)	36" (900mm)	16	8(25)

#### NOTES:

- These foundation depths are for sites which have cohesive soils (clayey silt, sandy clay, etc.) along
  the length of the shoft, with an average Unconfined Compressive Strength (0u) > 1.0 tsf (100 kpa).
  This strength shall be verified by boring data prior to construction or with testing by the Engineer
  during foundation drilling. The Bureau of Bridges & structures should be contacted for a revised
  design if other conditions are encountered.
- 2. Combination mast arm assemblies under 55 feet (16.8 m) shall use 36" (900 mm) diameter foundations.
- 3. Combination mast arm assemblies under 56 feet (16.8 m) through 75 feet (22.9 m) shall use 42" (1060 mm) diameter foundations
- 4. For mast arm assemblies with dual arms refer to state standard 878001...


### DEPTH OF MAST ARM FOUNDATIONS, TYPE E

USER NAME - footemj	DESIGNED -	REVISED -		DISTRICT ONE	F.A.P RTE.	SECTION	COUNTY	TOTAL	SHEET NO.
3	DRAWN -	REVISED -	STATE OF ILLINOIS	STANDARD TRAFFIC SIGNAL DESIGN DETAILS	342	2018-100-BR	соок	1351	520
PLOT SCALE = 50,0000 ' / In.	CHECKED -	REVISED -	DEPARTMENT OF TRANSPORTATION	STANDARD TRAFFIC SIGNAL DESIGN DETAILS		TS-05	CONTRAC	T NO. 62	N91
PLOT DATE - 3/4/2019	DATE -	REVISED -		SCALE: NONE SHEET 5 OF 7 SHEETS STA. TO STA.		ILLINOIS F	ED, AID PROJECT		



- CONDUIT DEPTH SHALL BE A MINIMUM OF 30" (760mm) BELOW THE BOTTOM OF THE DRAINAGE DITCH OR ANY SLOPING GROUND
- THE MINIMUM CONDUIT DEPTH APPLIES TO ALL CONDUIT PLACED UNDER ROADWAY PAVEMENT, MULTI-USE PATHS, SIDEWALKS AND SOIL SURFACES.
- THE MINIMUM CONDUIT DEPTH APPLIES TO ALL HANDHOLES, HEAVY DUTY HANDHOLES AND DOUBLE HANDHOLES.

# HANDHOLE WITH MINIMUM CONDUIT DEPTH (NOT TO SCALE)



MAST ARM MOUNT

EMERGENCY VEHICLE DETECTOR WITH CONFIRMATION
BEACON MOUNTING DETAIL

(1675mm) (915mm) (1035mm) CONTROLLER CABINET BASE PROPOSED-TOP VIEW APRON -NO. 3 DOWEL 18" (450mm NO. 6 BARE COPPER WIRE LONG (8 REQ.) BUSHING-GROUND/ CLAMP EXISTING-ANCHOR BOLTS GRADE LINE BEVEL (300mm) (225mm) (225mm) EXISTING CONDUITS EXISTING GROUND ROD MODIFY EXISTING TYPE "D" FOUNDATION TO TYPE "C" FOUNDATION

(NOT TO SCALE)


ITEM	NO. IDENTIFICATION
1	OUTLET BOX- GALV. 21 CU.IN. (0.000344 CU-M)
2	LAMP HOLDER AND COVER
3	OUTLET BOX COVER
4	RUBBER COVER GASKET
5	REDUCING BUSHING
6	¾*(19 mm) CLOSE NIPPLE
7	¾ (19 mm) LOCKNUT
8	¾*(19 mm) HOLE PLUG
9	SADDLE BRACKET - GALV.
10	6 WATT PAR 38 LED FLOOD LAMP
11	DETECTOR UNIT
12	POST CAP [18 FT. (5.4 m) POST MIN.]

### NOTES:

- ALL ELECTRICAL ITEMS, EXCEPT ITEMS #2 AND #11 SHALL BE ALUMINUM OR GALVANIZED
- 2, ITEM #1- OZ/GEDNEY FSX-1-50 OR EQUIVALENT ITEM #2- MULBERRY CON-O-SHADE LAMP SHIELD OR EQUIVALENT ITEM #9- "BAND-IT" SADDLE BRACKET OR EQUIVALENT
- 3. WHEN POST MOUNTING IS SPECIFIED, ITEM #9 SHALL NOT BE REQUIRED. THE DETECTION UNIT SHALL BE MOUNTED DIRECTLY ON TOP OF THE CAP BY DRILLING AND TAPPING A 3/4 "(19 mm) HOLE WITH PIPE THREADS. THE POST CAP SHALL EITHER BE SCREWED TO THE TOP OF THE POST OR A MINIMUM OF 3 TIGHTENING SCREWS SHALL BE REQUIRED ON EACH CAP.

STATE OF ILLINOIS

**DEPARTMENT OF TRANSPORTATION** 




Α	В	С	HEIGHT	WEIGHT
VARIES	9.5"(241mm)	19*(483mm)	7" (178mm) - 12" (300mm)	53 lbs (24kg)
VARIES	10.75*(273mm)	21.5*(546mm)	7" (178mm) - 12" (300mm)	68 lbs (31 kg)
VARIES	13,0"(330mm)	26"(660mm)	7" (178mm) - 12" (300mm)	81 lbs (37 kg)
VARIES	18.5"(470mm)	37*(940mm)	7" (178mm) - 12" (300mm)	126 lbs (57 kg)


### SHROUD

#### NOTES:

- DIMENSION "A" IS EQUAL TO THE DIAMETER OF THE MAST ARM POLE AT THE TOP OF THE SHROUD.
  THE SHROUD SHALL BE TIGHT TO THE MAST ARM POLE.
- 2. THE SUPPLIER SHALL VERIFIED THE ABOVE DIMENSIONS BASED ON MAST ARM REQUIREMENTS.
- 3. THE HEIGHT OF THE SHROUD SHALL COVER THE ANCHOR BOLTS, NUTS AND MAST ARM POLE BASE




### MODIFY EXISTING TYPE "D" FOUNDATION



#### NOTES

- 1. HANDHOLE CONSTRUCTED PER STATE STANDARD 814001.
- REMOVAL OF THE EXISTING CONDUIT FROM THE HANDHOLE AND THE INSTALLATION OF THE CONDUIT BUSHINGS SHALL BE INCLUDED WITH THE COST OF THE HANDHOLE.

### HANDHOLE TO INTERCEPT EXISTING CONDUIT



**DEPARTMENT OF TRANSPORTATION** 

COOK 1351 522

CONTRACT NO. 62N91

TS-05

STANDARD TRAFFIC SIGNAL DESIGN DETAILS


SHEET 7 OF 7 SHEETS STA.


PLOT SCALE - 100,0000 ' / in.


CHECKED -

REVISED

### SIGN PANEL - TYPE 1 OR TYPE 2







DESIGN	AREA	SIGN PANEL	SHEETING	OTY.
SERIES	(SQ FT)	TYPE	TYPE	REQUIRED
D OR C	10	1 OR 2	ZZ	8

# COMMON STREET NAME ABBREVIATIONS AND WIDTHS

MANG	ADDDEVATION	WIDTH (INCH)			
NAME	ABBREVATION	SERIES "C"	SERIES "D"		
AVENUE	Ave	15.000	18.250		
BOULEVARD	Blvd	17.125	20,000		
CIRCLE	Cir	11.125	13.000		
COURT	Ct	8. 250	9.625		
DRIVE	Dr	8.625	10.125		
HIGHWAY	Hwy	18.375	22,000		
ILLINOIS	IL	7.000	8. 250		
LANE	Ln	9.125	10.750		
PARKWAY	Pkwy	23. 375	27.375		
PLACE	PΙ	7.125	7. 750		
ROAD	Rd	9.625	11.125		
ROUTE	Rte	12.625	14.500		
STREET	St	8.000	9.125		
TERRACE	Ter	12.625	14.625		
TRAIL	Tr	7. 750	9.125		
UNITED STATES	US	10.375	12.250		

### **GENERAL NOTES**

- 1. WHERE MAST ARM MOUNTED STREET NAME SIGNS ARE SPECIFIED, THE MAST ARM ASSEMBLY AND POLES SHALL BE DESIGNED TO SUPPORT THE LOADINGS CALLED FOR ON STANDARDS 877001, 877002, 877006, 877011 AND 877012, AS APPLICABLE, PLUS TWO (2) SIGN PANELS 2'-6" x 8'-0" MOUNTED AS SHOWN. THE DESIGN SHALL BE IN ACCORDANCE WITH THE REQUIREMENTS OF THE CURRENT "STANDARD SPECIFICATIONS FOR STRUCTURAL SUPPORTS FOR HIGHWAY SIGNS, LUMINAIRES, AND TRAFFIC SIGNALS" AS PUBLISHED BY THE AMERICAN ASSOCIATION OF STATE HIGHWAY AND TRANSPORTATION OFFICIALS FOR 80 M.P.H. WIND VELOCITY.
- ALL SIGNS SHALL CONSIST OF A WHITE LEGEND AND BORDER (TYPE ZZ SHEETING) ON A GREEN BACKGROUND (TYPE ZZ SHEETING)
- 3. THE SIGN LENGTH SHALL BE IN 6-INCH INCREMENTS, BUT THE OVERALL LENGTH SHALL NOT EXCEED 8'-0". ALL BORDERS IF POSSIBLE, BUT MAY BE REDUCED TO 5" WHEN SPACING IS CRITICAL. A MINIMUM OF 2-1/2" SHALL BE INCLUDED BETWEEN THE WORD AND THE RIGHT AND LEFT EDGES OF THE SIGN.
- 4. A PREFERRED METHOD FOR THE SIGN DESIGN IS TO USE SERIES "D" LETTER ON A ONE-LINE SIGN 18" IN HEIGHT AND A MAXIMUM OF 8"-0" IN WIDTH. IF SERIES "D" DOES NOT FIT ON A 8"-0" SIGN, THEN SERIES "C" SHOULD BE TRIED. IF SERIES "C" DOES NOT FIT ON A 8"-0" SIGN, A 30" HIGH TWO-LINE SIGN CAN BE USED. THE CROSSROAD DESIGNATION AS TO STREET, AVENUE, ETC. SHOULD BE SPELLED OUT ON THE SECOND LINE, IF THE ABBREVIATION CANNOT FIT ON THE FIRST LINE.
- LED ILLUMINATED STREET NAME SIGNS CAN BE USED IN PLACE OF REGULAR SIGN PANELS BUT ANY SPECIAL WORDING AND SYMBOLOGY MUST BE APPROVED BY THE DEPARTMENT. GENERAL DESIGN REQUIREMENT AS LISTED ABOVE (COLOR, FONT, SIZE, ETC.) MUST BE FOLLOWED.
- 6. SIGNFIX ALUMINUM CHANNEL FRAMING SYSTEM SHALL BE USED FOR ALL SIGNS ATTACHED TO SIGNAL POLES AND POSTS.

LOCAL SUPPLIERS: PARTS LISTING:

 J.O. HERBERT COMPANY, INC MIDLOTHIAN, VA

- WESTERN REMAC, INC.

WOODRIDGE, IL

SIGN CHANNEL SIGN SCREWS PART #HPN053 (MED. CHANNEL) 1/4" × 14 × 1" H.W.H. #3 SELF TAPPING WITH NEOPRENE WASHER

BRACKETS


PART #HPN034 (UNIVERSAL) CHANNEL CLAMPS WITH STAINLESS STEEL STRAPPING

SCALE:


OTHER BRANDS OF MOUNTING HARDWARE ARE ACCEPTABLE, BASED UPON THE DEPARTMENT'S APPROVAL AND COMPATIBILITY WITH THE CHANNEL/BRACKET OF THE ABOVE PRODUCT.

### MOUNTING LOCATION

ARM OR POLE MOUNTED



### SUPPORTING CHANNELS



### STANDARD ALPHABETS SPACING CHART

(8") UPPER CASE AND (6") LOWER CASE

381	FHWA SEF			- 1		RIES "D"	ř
C <b>h</b> aracter	LEFT SPACING (INCH)	WIDTH (INCH)	RIGHT SPACING (INCH)	CHARACTER	LEFT SPACING (INCH)	WIDTH (INCH)	RIGHT SPACINO (INCH)
А	0.240	5.122	0.240	Α	0, 240	6.804	0.240
В	0.880	4.482	0.480	В	0.960	5.446	0.400
С	0.720	4.482	0.720	С	0,800	5.446	0,800
D	0.880	4.482	0.720	D	0, 960	5.446	0,800
E	0.880	4.082	0.480	E	0.960	4.962	0.400
F G	0.880 0.720	4.082	0.240	F G	0,960	4. 962 5. 446	0, 240
Н	0. 120	4.482	0.880	H	0, 960	5.446	0, 960
ī	0.880	1.120	0.880	i	0, 960	1.280	0, 960
Ĵ	0.240	4.082	0.880	j	0, 240	5, 122	0, 960
К	0.880	4.482	0.480	K	0, 960	5.604	0.400
L	0.880	4.082	0.240	L	0.960	4.962	0, 240
М	0.880	5. 284	0.880	М	0.960	6. 244	0.960
N	0.880	4.482	0.880	N	0,960	5.446	0,960
0	0.720	4.722	0.720	0	0,800	5.684	0,800
P	0.880	4.482	0.720	P	0, 960	5.446	0, 240
Q	0.720	4.722	0.720	Q	0.800	5. 684 5. 446	0,800
R S	0.880 0.480	4.482	0.480	R S	0.960	5.446	0,400
T	0.480	4.482	0.480	T	0, 400	4, 962	0, 400
Ü	0.880	4. 482	0.880	Ü	0, 960	5. 446	0, 960
٧	0.240	4. 962	0.240	v	0. 240	6. 084	0. 240
W	0.240	6.084	0.240	w	0. 240	7. 124	0.240
Х	0.240	4.722	0.240	Х	0,400	5.446	0,400
Υ	0.240	5.122	0.240	Υ	0, 240	6.884	0, 240
Z	0.480	4.482	0.480	Z	0.400	5.446	0.400
а	0.320	3.842	0.640	a	0.400	4.562	0. 720
Ь	0.720	4.082	0.480	b	0.800	4.802	0.480
С	0.480	4.002	0.240	C	0,480	4.722	0, 240
d	0.480	4.082	0.720	d	0.480	4. 802 4. 722	0, 800
e f	0.480	2.480	0.320	e f	0. 480	2.882	0. 320
g	0.480	4.082	0. 720	g	0. 480	4. 802	0. 800
h	0.720	4.082	0.640	h	0, 800	4. 722	0, 720
ī	0.720	1.120	0.720	1	0.800	1.280	0.800
j	0.000	2.320	0.720	j.	0.000	2.642	0.800
k	0.720	4. 322	0.160	k	0.800	5.122	0.160
1	0.720	1.120	0.720		0.800	1.280	0.800
m	0.720	6.724	0.640	m	0,800	7.926	0,720
n	0.720	4.082	0.640	n	0.800	4.722	0. 720
0	0.480	4. OB2	0.480	0	0.480	4.882	0.480
P	0.720	4.082	0.480	р	0.800	4.802	0.480
q	0.480 0.720	4. 082 2. 642	0.720	q	0.480	4. 802 3. 042	0.800
r s	0. 720	3. 362	0. 240	Г 5	0. 320	3. 762	0. 160
+	0.080	2.882	0.080	t	0. 080	3. 202	0.080
ū	0.640	4.082	0.720	u	0. 720	4. 722	0.800
٧	0.160	4. 722	0.160	v	0. 160	5. 684	0. 160
w	0.160	7. 524	0.160	W	0.160	9.046	0.160
х	0.000	5.202	0.000	х	0.000	6. 244	0.000
У	0.160	4.962	0.160	у	0.160	6.004	0.160
z	0.240	3. 362	0.240	Z	0. 240	4.002	0.240
1	0.720	1.680	0.880	1	0.800	2.000	0. 960
2	0.480	4.482	0.480	2	0.800	5.446	0.800
3	0.480	4.482	0.480	3 4	1.440 0.160	5.446	0.800
5	0.240 0.480	4. 482	0.720	5	0. 800	6.004 5.446	0.960
6	0.480	4.482	0.720	6	0.800	5.446	0.800
7	0.120	4.482	0. 720	7	0.560	5.446	0.560
8	0.480	4. 482	0.480	8	0.800	5.446	0.800
9	0.480	4.482	0.480	9	0.800	5.446	0.800
0	0.720	4.722	0.720	0	0.800	5. 684	0.800
	0.240	2.802	0.240	- 2	0. 240	2.802	0.240

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

F.A.P. SECTION COUNTY TOTAL SHEET NO.

342 2018-100-BR COOK 1351 523

TS-02 CONTRACT NO. 62 № 1

ILLINOIS FED. AID PROJECT

ITEM	LINIT	TOTAL	IL RTE 62 AND IL RTE 53	IL RTE 62 AND IL RTE 53	US RTE 12 AND IL RTE 53				US 12	IL RTE 68
		QUANTITY	WEST RAMP	EAST RAMP	WEST RAMP	EAST RAMP	WEST RAMP	EAST RAMP	INTERCONNECT	INTERCONNECT
SIGN PANEL - TYPE 1 SIGN PANEL - TYPE 2	SQ FT	118.3 88.8	32.5 15.0	32.5 15.0	11.3	12.0 22.5	12.5	41.3 12.5		
UNDERGROUND CONDUIT, GALVANIZED STEEL, 2" DIA.	FOOT	5,260	475	465	387	970	516	1,667	780	
UNDERGROUND CONDUIT, GALVANIZED STEEL, 3" DIA.	FOOT	1,389	378	348	57	192	139	275	1	
UNDERGROUND CONDUIT, GALVANIZED STEEL, 4" DIA.	FOOT	2,372	381	338	332	376	232	458	255	
HANDHOLE	EACH	5		1		2		2		
HEAVY-DUTY HANDHOLE	EACH	22	2	2	2	3	2	8	3	
DOUBLE HANDHOLE	EACH	1						1		
MAINTENANCE OF EXISTING TRAFFIC SIGNAL INSTALLATION ELECTRIC CABLE IN CONDUIT, TRACER, NO. 14 1C	FOOT	5 9,229		1			1		6,923	2 206
ELECTRIC CABLE IN CONDUIT, INACER, NO. 14 1C	FOOT	612			448	164			6,923	2,306
ELECTRIC CABLE IN CONDUIT, SIGNAL NO. 14 3C	FOOT	4,602	722	535	1,049	1,258	490	549		
ELECTRIC CABLE IN CONDUIT, SIGNAL NO. 14 5C	FOOT	17,991	4,681	3,857	1,384	3,026	2,279	2,764		
ELECTRIC CABLE IN CONDUIT, SIGNAL NO. 14 7C	FOOT	3,657	409	289	1,348	1,364		247		
ELECTRIC CABLE IN CONDUIT, LEAD-IN, NO. 14 1 PAIR	FOOT	24,306	5,278	5,771	1,602	3,942	2,260	5,453		
ELECTRIC CABLE IN CONDUIT, SERVICE, NO. 4 2 C	FOOT	1,112			656			456		
ELECTRIC CABLE IN CONDUIT, SERVICE, NO. 6 2 C	FOOT	92	0.50	27	044	28	37	4.075		
ELECTRIC CABLE IN CONDUIT, EQUIPMENT GROUNDING CONDUCTOR, NO. 6 1C TRAFFIC SIGNAL POST, GALVANIZED STEEL 16 FT.	FOOT EACH	5,365 17	869	836	914	1,020 3	450 3	1,276		
TRAFFIC SIGNAL POST, GALVANIZED STEEL 18 FT.	EACH	1	3	3	1	<u>5</u> 1	3	4	1	
STEEL MAST ARM ASSEMBLY AND POLE, 24 FT.	EACH	4	2		1	1				
STEEL MAST ARM ASSEMBLY AND POLE, 26 FT.	EACH	2	_	2	_					
STEEL MAST ARM ASSEMBLY AND POLE, 30 FT.	EACH	6	1			1	3	1		
STEEL MAST ARM ASSEMBLY AND POLE, 32 FT.	EACH	2						2		
STEEL MAST ARM ASSEMBLY AND POLE, 34 FT.	EACH	1				1				
STEEL MAST ARM ASSEMBLY AND POLE, 36 FT.	EACH	1			_			1	-	
STEEL MAST ARM ASSEMBLY AND POLE, 48 FT.	EACH	2	1	1	1				-	
STEEL MAST ARM ASSEMBLY AND POLE, 52 FT. STEEL COMBINATION MAST ARM ASSEMBLY AND POLE 22 FT.	EACH EACH	1		1 1					+	-
STEEL COMBINATION MAST ARM ASSEMBLY AND POLE 30 FT.	EACH	1		1			1		1	
STEEL COMBINATION MAST ARM ASSEMBLY AND POLE 38 FT.	EACH	1		1			-			
STEEL COMBINATION MAST ARM ASSEMBLY AND POLE 50 FT.	EACH	1	1	_						
STEEL COMBINATION MAST ARM ASSEMBLY AND POLE 52 FT.	EACH	1				1				
STEEL COMBINATION MAST ARM ASSEMBLY AND POLE 54 FT.	EACH	1			1					
CONCRETE FOUNDATION, TYPE A	FOOT	92	12	16	8	20	16	20		
CONCRETE FOUNDATION, TYPE C	FOOT	4			40			4		
CONCRETE FOUNDATION, TYPE E 30-INCH DIAMETER	FOOT	70	20 39	30	10	10	44	44		
CONCRETE FOUNDATION, TYPE E 36-INCH DIAMETER CONCRETE FOUNDATION, TYPE E 42-INCH DIAMETER	FOOT	202	39	26	28	49	44	44		
DRILL EXISTING HANDHOLE	EACH	90	23	20	17	15	14	1		
SIGNAL HEAD, LED, 1-FACE, 3-SECTION, MAST-ARM MOUNTED	EACH	57	13	13	5	9	8	9		
SIGNAL HEAD, LED, 1-FACE, 3-SECTION, BRACKET MOUNTED	EACH	31	6	6	2	5	6	6		
SIGNAL HEAD, LED, 1-FACE, 4-SECTION, BRACKET MOUNTED	EACH	6	1	1	1	2		1		
SIGNAL HEAD, LED, 1-FACE, 4-SECTION, MAST ARM MOUNTED	EACH	3			1	2				
SIGNAL HEAD, LED, 1-FACE, 5-SECTION, BRACKET MOUNTED	EACH	6	1	1	3			1		
SIGNAL HEAD, LED, 1-FACE, 5-SECTION, MAST-ARM MOUNTED	EACH	5			3	2				
PEDESTRIAN SIGNAL HEAD, LED, 1-FACE, BRACKET MOUNTED WITH COUNTDOWN TIMER	EACH	6 65	12	13	9	2 13				
TRAFFIC SIGNAL BACKPLATE, LOUVERED, FORMED PLASTIC INDUCTIVE LOOP DETECTOR	EACH EACH	40	13	7	3	13 	8 2	9 14		
DETECTOR LOOP, TYPE I	FOOT	2,640	152	215	323	924	123	903		
LIGHT DETECTOR	EACH	15	202	220	4	5	3	3		
LIGHT DETECTOR AMPLIFIER	EACH	4			1	1	1	1		
TEMPORARY TRAFFIC SIGNAL INSTALLATION	EACH	4	1		1	1		1		
RELOCATE EXISTING EMERGENCY VEHICLE PRIORITY SYSTEM, DETECTOR UNIT	EACH	6	3	3						
REMOVE ELECTRIC CABLE FROM CONDUIT	FOOT	23,205	2,895	3,058	4,615	1,600	1,496		6,557	2,984
REMOVE EXISTING TRAFFIC SIGNAL EQUIPMENT	EACH	6	1	1	1	1	1	1	1	
REBUILD EXISTING HANDHOLE TO HEAVY-DUTY HANDHOLE REMOVE EXISTING HANDHOLE	EACH EACH	1 16		1	1	1		1 12	+	
REMOVE EXISTING HANDHOLE REMOVE EXISTING CONCRETE FOUNDATION	EACH	16 36	6	7	2 5	1 5	6	7	+	<del>                                     </del>
EMERGENCY VEHICLE PRIORITY SYSTEM LINE SENSOR CABLE, NO. 20 3/C	FOOT	5,387	722	535	1,476	1,615	490	549		
ROD AND CLEAN EXISTING CONDUIT	FOOT	5,183			=,	_, >==	1.50	3.0	3,986	1,197
CENTRACS LICENSE EXPANSION	EACH	4			1	1	1	1		
TERMINAL SERVER	EACH	2				1	1			
FULL-ACTUATED CONTROLLER AND TYPE SUPER P CABINET (SPECIAL)	EACH	1						1		
OUTDOOR RATED NETWORK CABLE	FOOT	978	115	337	218	227	81		1	-
SERVICE INSTALLATION, GROUND MOUNTED, METERED	EACH	5		1	1	1	1 1	1	1	
REMOTE CONTROLLED VIDEO SYSTEM	EACH	3			1	1		1		
LAYER II (DATALINK) SWITCH UPGRADE EXISTING CONTROLLER TO NTCIP SPECIAL	EACH EACH	3			1 1	1	1 1	1	+	<del>                                     </del>
PEDESTRIAN SIGNAL POST, 10 FT.	EACH	3			3		-			
RELOCATE EXISTING PTZ CAMERA	EACH	2	1	1	-					
PEDESTRIAN SIGNAL POST, 5 FT.	EACH	1				1				
ELECTRIC METER	EACH	1	1							
UNINTERRUPTABLE POWER SUPPLY (SPECIAL)	EACH	1						1		
FIBER OPTIC CABLE IN CONDUIT, NO. 62.5/125, MM12F SM24F	FOOT	9,273					_		6,923	2,350
FIBER OPTIC INTERCONNECT CENTER, 48 PORT	EACH	5			1	1	2	1	1	-
ACCESSIBLE PEDESTRIAN SIGNALS  CONCRETE FOLINDATION TYPE A 12 INCH DIAMETER	EACH	16			4	2			1	-
CONCRETE FOUNDATION, TYPE A 12-INCH DIAMETER  LED SIGNAL FACE, LENS COVER	FOOT EACH	16 108	21	21	12 15	20	14	17	-	
CONFIRMATION BEACON	EACH	6	3	3	13	۷0	14	1/	1	<del>                                     </del>
RE-OPTIMIZE TRAFFIC SIGNAL SYSTEM LEVEL 1	EACH	2			1	1				
TEMPORARY TRAFFIC SIGNAL TIMING	EACH	6	1	1	1	1	1	1		
STEEL COMBINATION MAST ARM ASSEMBLY AND POLE WITH DUAL MAST ARMS, 44 FT. AND 26 FT.	EACH	1				1				


1170 SOUTH HOUBOLT ROAD JOLIET, ILLINOIS 60431 STRAND ASSOCIATES"


USER NAME = AlexaM	DESIGNED	-	RRS	REVISED	-
	DRAWN	-	ACM	REVISED	-
PLOT SCALE = 40.0000 / in.	CHECKED	-	KRH	REVISED	-
PLOT DATE = 1/22/2025	DATE	-	12/13/24	REVISED	-

STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION

SCALE:

		_	D 4 F F I	^ ^	MONIAL	0011501111	-	F.A.P. RTE	SEC <sup>-</sup>	TION		COUNTY	TOTAL SHEETS	SHEET NO.
TRAFFIC SIGNAL SCHEDULE						342 2018-100-BR			соок	1351	524			
												CONTRACT	NO. 62	2N91
N.T.S.	SHEET	1	OF	1	SHEETS	STA.	TO STA.			ILLINOIS	FED. A	D PROJECT		







CHECKED -KRH REVISED

STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION

IL RTE 62 (ALGONQUIN ROAD) AT IL RTE 53 WEST RAMPS SCALE: 1" = 20' SHEET 2 OF 2 SHEETS STA.

CONTRACT NO. 62N91







DRAWN -LOT SCALE = 40.0000 / in. CHECKED -KRH REVISED

STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION

IL RTE 62 (ALGONQUIN ROAD) AT IL RTE 53 WEST RAMPS SCALE: 1" = 20' SHEET 2 OF 2 SHEETS STA.

COOK 1351 524D CONTRACT NO. 62N91 2018-100-BR






LOT SCALE = 40.0000 / in. REVISED

STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION

IL RTE 62 (ALGONQUIN ROAD) AT IL RTE 53 WEST RAMPS SCALE: 1" = 20' SHEET 2 OF 2 SHEETS STA.

COUNTY	SHEET	NO.
COOK	1351	524F
CONTRACT	NO.	62N91
AID PROJECT		

### **EXISTING AND TEMPORARY CONTROLLER SEQUENCE**



# **EXISTING AND TEMPORARY**

## **EMERGENCY VEHICLE PREEMPTION SEQUENCE**

<b>(5)</b>	IL RTE 53 WEST RAMPS
	IL RTE 62
	(ALGONQUIN ROAD)

ELECTRIC SERVICE R	EQUIREMEN <sup>*</sup>	TS	
### TYPE    SIGNAL HEAD	QUANTITY	UNIT WATTAGE	TOTAL WATTAGE
SIGNAL HEAD			
1 OR 3 - SECTION	12	11	132
4 - SECTION		14	
5 - SECTION	2	13	26
PROGRAMMABLE SIGNALS			
3 - SECTION		22	
4 - SECTION		32	
5 - SECTION		28	
PED. SIGNAL		15	
CONTROLLER	1	150	150
MASTER CONTROLLER		100	
UPS	1	25	25
DETECTION RADAR OR VIDEO	1	20	20
BLANK-OUT SIGN		25	
NETWORK SWITCH II OR III	1	35	35
CELLULAR MODEM		15	
PTZ CAMERA	1	75	75
TOTAL UPS SIZING			463
UPS CHARGING	1	225	225
BATTERY HEATER MAT	1	180	180
CABINET HEATER	1	200	200
FLASHER		15	
LED STREET NAME SIGN		120	
UPS DETECTION RADAR OR VIDEO BLANK-OUT SIGN NETWORK SWITCH II OR III CELLULAR MODEM PTZ CAMERA  TOTAL UPS SIZING UPS CHARGING BATTERY HEATER MAT CABINET HEATER FLASHER LED STREET NAME SIGN LUMINAIRE TOTAL SERVICE WIRE SI		240	
TOTAL SERVICE WIRE SI	ZING		1068

TRAFFIC SIGNAL

### **LEGEND**:

**◆ \* PROTECTED PHASE** 


← -(\*)- - PROTECTED/PERMITTED PHASE

√-(\*)- ► PEDESTRIAN PHASE

♦ OL OVERLAP

### **RIGHT TURN OVERLAP PHASE DESIGNATION:**

OVERLAP		PERMISSIVE		PROTECTE
LETTER		PHASE		PHASE
В	=	4	+	5
С	=	6	+	4



**NOTES:** 

1. PRIOR TO PRESTAGE D, THE CONTRACTOR SHALL DISCONNECT THE EXISTING EB LEFT TURN LOOP DETECTORS IN THE TRAFFIC SIGNAL CABINET. THE CONTRACTOR SHALL RECONNECT THE LOOPS AFTER THE COMPLETION OF PRESTAGE E AND PRIOR TO STAGE 1. THIS WORK SHALL BE INCLUDED IN THE CONTRACT UNIT PRICE FOR TEMPORARY TRAFFIC SIGNAL INSTALLATION.

> TS 2670 **IDOT CENTRACS FORMER ECON 96**

1170 SOUTH HOUDGE... JOLIET, ILLINOIS 60431 (815) 744-4200

1170 SOUTH HOUBOLT ROAD

DESIGNED - RRS REVISED DRAWN ACM REVISED HECKED KRH REVISED PLOT DATE = 1/22/2025 DATE 12/13/24 REVISED

METER NUMBER

CONTACT: JAMES CAMPBELL PHONE: (630) 940-6805

COMPANY: COMED ACCOUNT NUMBER: 6831011222

ENERGY COSTS TO:


**ENERGY SUPPLY** 


VILLAGE OF SCHAUMBURG 101 SCHAUMBURG COURT SCHAUMBURG, IL 60193-1878


> STATE OF ILLINOIS **DEPARTMENT OF TRANSPORTATION**

TEMPORARY CABLE PLAN, PHASE DESIGNATION DIAGRAM, AND EMERGENCY VEHICLE PREEMPTION SEQUENCE IL RTE 62 (ALGONQUIN ROAD) AND IL RTE 53 WEST RAMPS SHEET 1 OF 1 SHEETS STA.

SECTION 2018-100-BR 342 COOK 1351 524G CONTRACT NO. 62N91








PLOT SCALE = 40.0000 / in.


PLOT DATE = 12/12/2024





# EXISTING AND PROPOSED EMERGENCY VEHICLE PREEMPTION

**SEQUENCE** 



rô l				
3-11-5	TRAFFIC	SIGNAL		
n&SE	ELECTRIC SERVICE	REQUIRE	MENTS	
Plan-Algonquin&SB-1L53-	ТҮРЕ	QUANTITY	UNIT WATTAGE	TOTA WATTA
A-ne	SIGNAL HEAD			
P P	1 OR 3 - SECTION	19	11	209
Sheets\C2-D162N91-sht-ts-23-Cable	4 - SECTION	1	14	14
23-0	5 - SECTION	1	13	13
t-ts-	PROGRAMMABLE SIGNALS			
1-sh	3 - SECTION		22	
5N9	4 - SECTION		32	
016	5 - SECTION		28	
C2-I	PED. SIGNAL		15	
ets	CONTROLLER	1	150	150
	MASTER CONTROLLER		100	
SAD	UPS	1	25	25
\$4/	DETECTION RADAR OR VIDEO	)	20	
5-50	BLANK-OUT SIGN		25	
Micr	NETWORK SWITCH II OR III	1	35	35
AD	CELLULAR MODEM		15	
0/56	PTZ CAMERA	1	75	<b>7</b> 5
awin	TOTAL UPS SIZII	NG		521
3/Dr	UPS CHARGING	1	225	225
/113	BATTERY HEATER MAT	1	180	180
346	CABINET HEATER	1	200	200
6399\6346\113\Drawings\CAD\Micros-SS4\CAD	FLASHER		15	
-63	LED STREET NAME SIGN		120	

LUMINAIRE

### **LEGEND**:

**◆ \* PROTECTED PHASE** 

← -(\*)- - PROTECTED/PERMITTED PHASE

√
\*

PEDESTRIAN PHASE

Output

Description

Output

Description

Output


Description

Des

OVERLAP

# RIGHT TURN OVERLAP PHASE DESIGNATION:

OVERLAP		PERMISSIVE		PROTECTE
LETTER		PHASE		PHASE
В	=	4	+	5
С	=	6	+	4



-(1#6)-

QS

TS 2670 IDOT CENTRACS FORMER ECON 96

TOTAL SERVICE WIRE SIZING 1366 METER NUMBER: 1170 SOUTH HOUB..... JOLIET, ILLINOIS 60431 (815) 744-4200 DESIGNED - RRS REVISED 1170 SOUTH HOUBOLT ROAD DRAWN -ACM REVISED LOT SCALE = 20.0000 / in. HECKED KRH REVISED PLOT DATE = 12/12/2024 REVISED DATE 12/13/24

VILLAGE OF SCHAUMBURG

101 SCHAUMBURG COURT

SCHAUMBURG, IL 60193-1878

CONTACT: JAMES CAMPBELL

COMPANY: COMED

ACCOUNT NUMBER: 6831011222

PHONE: (630) 940-6805

ENERGY COSTS TO:

ENERGY SUPPLY

240

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

CABLE PLAN, PHASE DESIGNATION DIAGRAM, AND EMERGENCY VEHICLE PREEMPTION SEQUENCE IL RTE 62 (ALGONOUIN ROAD) AND IL RTE 53 WEST RAMPS

SHEET 1 OF 1 SHEETS STA. TO STA.

FA.P. SECTION COUNTY TOTAL SHEETS NO. 342 2018-100-BR COK 1351 528

CONTRACT NO. 62 N91

### SIGN PANEL – TYPE 2

ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED.



DESIGN	AREA	SIGN PANEL	SHEETING	OTY.
SERIES	(SQ FT)	TYPE	TYPE	REQUIRED
D	15	2	ZZ	1

NOTE: FOR ADDITIONAL DESIGN AND INSTALLATION INFORMATION SEE DISTRICT ONE MAST ARM MOUNTED STREET NAME SIGNS DETAIL.


## **SCHEDULE OF QUANTITIES**


ITEM	UNIT	QUANTITY
SIGN PANEL - TYPE 1	SQ FT	32.5
SIGN PANEL - TYPE 2	SQ FT	15.0
UNDERGROUND CONDUIT, GALVANIZED STEEL, 2" DIA.	FOOT	475
UNDERGROUND CONDUIT, GALVANIZED STEEL, 3" DIA.	FOOT	378
UNDERGROUND CONDUIT, GALVANIZED STEEL, 4" DIA.	FOOT	381
HEAVY-DUTY HANDHOLE	EACH	2
ELECTRIC CABLE IN CONDUIT, SIGNAL NO. 14 3C	FOOT	722
ELECTRIC CABLE IN CONDUIT, SIGNAL NO. 14 5C	FOOT	4,681
ELECTRIC CABLE IN CONDUIT, SIGNAL NO. 14 7C	FOOT	409
ELECTRIC CABLE IN CONDUIT, LEAD-IN, NO. 14 1 PAIR	FOOT	5,278
ELECTRIC CABLE IN CONDUIT, EQUIPMENT GROUNDING CONDUCTOR, NO. 6 1C	FOOT	869
TRAFFIC SIGNAL POST, GALVANIZED STEEL 16 FT.	EACH	3
STEEL MAST ARM ASSEMBLY AND POLE, 24 FT.	EACH	2
STEEL MAST ARM ASSEMBLY AND POLE, 30 FT.	EACH	1
STEEL MAST ARM ASSEMBLY AND POLE, 48 FT.	EACH	1
STEEL COMBINATION MAST ARM ASSEMBLY AND POLE 50 FT.	EACH	1
CONCRETE FOUNDATION, TYPE A	FOOT	12
CONCRETE FOUNDATION, TYPE E 30-INCH DIAMETER	FOOT	20
CONCRETE FOUNDATION, TYPE E 36-INCH DIAMETER	FOOT	39
DRILL EXISTING HANDHOLE	EACH	23
SIGNAL HEAD, LED, 1-FACE, 3-SECTION, MAST-ARM MOUNTED	EACH	13
SIGNAL HEAD, LED, 1-FACE, 3-SECTION, BRACKET MOUNTED	EACH	6
SIGNAL HEAD, LED, 1-FACE, 4-SECTION, BRACKET MOUNTED	EACH	1
SIGNAL HEAD, LED, 1-FACE, 5-SECTION, BRACKET MOUNTED	EACH	1
TRAFFIC SIGNAL BACKPLATE, LOUVERED, FORMED PLASTIC	EACH	13
INDUCTIVE LOOP DETECTOR	EACH	7
DETECTOR LOOP, TYPE I	FOOT	152
TEMPORARY TRAFFIC SIGNAL INSTALLATION	EACH	1
RELOCATE EXISTING EMERGENCY VEHICLE PRIORITY SYSTEM, DETECTOR UNIT	EACH	3
REMOVE ELECTRIC CABLE FROM CONDUIT	FOOT	2,895
REMOVE EXISTING TRAFFIC SIGNAL EQUIPMENT	EACH	1
REMOVE EXISTING CONCRETE FOUNDATION	EACH	6
EMERGENCY VEHICLE PRIORITY SYSTEM LINE SENSOR CABLE, NO. 20 3/C	FOOT	722
OUTDOOR RATED NETWORK CABLE	FOOT	115
RELOCATE EXISTING PTZ CAMERA	EACH	1
ELECTRIC METER	EACH	1
LED SIGNAL FACE, LENS COVER	EACH	21
CONFIRMATION BEACON	EACH	3
TEMPORARY TRAFFIC SIGNAL TIMING	EACH	1
*1000/ COST TO THE CITY OF BOLLING MEADOWS		

<sup>\*100%</sup> COST TO THE CITY OF ROLLING MEADOWS


**TS 2670 IDOT CENTRACS FORMER ECON 96** 

USER NAME = AlexaM	DESIGNED	-	RRS	REVISED -
	DRAWN	-	ACM	REVISED -
PLOT SCALE = 40.0000 / in	CHECKED	-	KRH	REVISED -
PLOT DATE = 1/22/2025	DATE	-	12/13/24	REVISED -







# **EXISTING CONTROLLER SEQUENCE**




#### TEMPORARY CONTROLLER **SEQUENCE**



# **EXISTING EMERGENCY VEHICLE** PREEMPTION SEQUENCE



### **TEMPORARY EMERGENCY VEHICLE** PREEMPTION SEQUENCE



TRAFFIC SIGNAL							
ELECTRIC SERVICE REQUIREMENTS							
TRAFFIC SIG ELECTRIC SERVICE RI TYPE	TYPE QUANTITY UNIT WATTAGE						
SIGNAL HEAD							
1 OR 3 - SECTION	12	11	132				
SIGNAL HEAD  1 OR 3 - SECTION  4 - SECTION  5 - SECTION  PROGRAMMABLE SIGNALS  3 - SECTION  4 - SECTION  5 - SECTION  PED. SIGNAL  CONTROLLER  MASTER CONTROLLER		14					
5 - SECTION	2	13	26				
PROGRAMMABLE SIGNALS							
3 - SECTION		22					
4 - SECTION		32					
5 - SECTION		28					
PED. SIGNAL		15					
CONTROLLER	1	150	150				
MASTER CONTROLLER		100					
	1	25	25				
DETECTION RADAR OR VIDEO	1	20	20				
BLANK-OUT SIGN		25					
NETWORK SWITCH II OR III	1	35	35				
CELLULAR MODEM		15					
PTZ CAMERA	1	75	75				
TOTAL UPS SIZING			463				
UPS CHARGING	1	225	225				
BATTERY HEATER MAT	1	180	180				
CABINET HEATER	1	200	200				
FLASHER		15					
DETECTION RADAR OR VIDEO BLANK-OUT SIGN NETWORK SWITCH II OR III CELLULAR MODEM PTZ CAMERA  TOTAL UPS SIZING UPS CHARGING BATTERY HEATER MAT CABINET HEATER FLASHER LED STREET NAME SIGN LUMINAIRE		120					
LUMINAIRE		240					

#### ENERGY COSTS TO: CITY OF ROLLING MEADOWS 3600 KIRCHOFF RD ROLLING MEADOWS, IL 60008 CONTACT: JAMES CAMPBELI ENERGY SUPPLY: PHONE: (630) 940-6805 COMPANY: COMED ACCOUNT NUMBER: 84692841222

### **LEGEND**:

**◆ \* PROTECTED PHASE** ← -(\*)- - PROTECTED/PERMITTED PHASE √- (\*)- PEDESTRIAN PHASE OL OVERLAP

SEE NOTE 2-

SEE NOTE 3

-SEE NOTE 1

SEE NOTE 2-

5

-(1#6)

-SEE NOTE 3

**CABLE PLAN** 

(NOT TO SCALE)

SEE NOTE 3

EXISTING TYPE IV CABINET-

TRAFFIC SIGNAL INSTALLATION.

2)-

#### NOTES:

EXISTING TRACER CABLE-

EXISTING INTERCONNECT TO

1. PRIOR TO PRESTAGE D, THE CONTRACTOR SHALL DISCONNECT THE EXISTING EB LEFT TURN LOOP DETECTORS IN THE TRAFFIC SIGNAL CABINET. THE CONTRACTOR SHALL RECONNECT THE LOOPS AFTER THE COMPLETION OF PRESTAGE E AND PRIOR TO STAGE 1. THIS WORK SHALL BE INCLUDED IN THE CONTRACT UNIT PRICE FOR MAINTENANCE OF EXISTING

- 2. IL RTE 53 NB EXIT RAMP AT ALGONQUIN ROAD WILL BE CLOSED DURING STAGE 1. PRIOR TO STAGE 1, THE CONTRACTOR SHALL DISCONNECT THE EXISTING NB EXIT RAMP UPTIGHT LOOP DETECTORS IN THE TRAFFIC SIGNAL CABINET. THE CONTRACTOR SHALL RECONNECT THE LOOPS AFTER THE COMPLETION OF STAGE 1 AND PRIOR TO STAGE 2. THIS WORK SHALL BE INCLUDED IN THE CONTRACT UNIT PRICE FOR MAINTENANCE OF EXISTING TRAFFIC SIGNAL INSTALLATION.
- 3. THE CONTRACTOR SHALL BAG AND DEENERGIZE SIGNAL HEADS DURING STAGE 1.

STRAND (815) 744-4200

1170 SOUTH HOUBOLT F JOLIET, ILLINOIS 60431

1170 SOUTH HOUBOLT ROAL

TOTAL SERVICE WIRE SIZING

DESIGNED - RRS REVISED DRAWN ACM REVISED OT SCALE = 20.0000 / in. HECKED KRH REVISED PLOT DATE = 1/22/2025 DATE 12/13/24 REVISED

METER NUMBER:

1068

STATE OF ILLINOIS **DEPARTMENT OF TRANSPORTATION** 

TEMPORARY CABLE PLAN, PHASE DESIGNATION DIAGRAM, AND EMERGENCY VEHICLE PREEMPTION SEQUENCE IL RTE 62 (ALGONQUIN ROAD) AND IL RTE 53 EAST RAMPS SCALE: N.T.S. SHEET 1 OF 1 SHEETS STA.

SECTION 342 2018-100-BR COOK 1351 529C CONTRACT NO. 62N91


1#6


IL RTE 62 (ALGONQUIN ROAD)


CABLE

EXISITNG INTERCONECT TO MAGNOLIA DRIVE


-EXISTING TRACER








### **EXISTING AND PROPOSED CONTROLLER SEQUENCE**



### **EXISTING AND PROPOSED EMERGENCY VEHICLE PREEMPTION SEQUENCE**



TRAFFIC	SIGNAL		
ELECTRIC SERVICE	REQUIRE	MENTS	
ТҮРЕ	QUANTITY	UNIT WATTAGE	TOTA WATTA
SIGNAL HEAD			
1 OR 3 - SECTION	19	11	209
4 - SECTION	1	14	14
5 - SECTION	1	13	13
PROGRAMMABLE SIGNALS			
3 - SECTION		22	
4 - SECTION		32	
5 - SECTION		28	
PED. SIGNAL		15	
CONTROLLER	1	150	150
MASTER CONTROLLER		100	
UPS	1	25	25
DETECTION RADAR OR VIDEO	)	20	
BLANK-OUT SIGN		25	
NETWORK SWITCH II OR III	1	35	35
CELLULAR MODEM		15	
PTZ CAMERA	1	75	75
TOTAL UPS SIZII	NG	,	521
UPS CHARGING	1	225	225
BATTERY HEATER MAT	1	180	180
CABINET HEATER	1	200	200
FLASHER		15	

#### LEGEND:

- **★** PROTECTED PHASE
- ← -(\*)- PROTECTED/PERMITTED PHASE
- √
  \*

  PEDESTRIAN PHASE

  Output

  Description

  PEDESTRIAN

  AND

  Description

  PEDESTRIAN

  PHASE

  PHASE

  PEDESTRIAN

  PHASE

  PEDESTRIAN

  PHASE


  PEDESTRIAN

  PHASE

  P
- ◆ OL OVERLAP

#### **RIGHT TURN OVERLAP PHASE DESIGNATION:**

VERLAP		<b>LEKWI22IAF</b>		PROTECTE
ETTER		PHASE		PHASE
В	=	4	+	5
С	=	6	+	4



QS

1#6

(5)

TS 2665 **IDOT CENTRACS** FORMER ECON 96

TOTAL SERVICE WIRE SIZING 1170 SOUTH HOUBOLT F JOLIET, ILLINOIS 60431 1170 SOUTH HOUBOLT ROAD **STRAND** (815) 744-4200

LED STREET NAME SIGN

240

480

REVISED DRAWN -ACM REVISED OT SCALE = 20.0000 / in. HECKED KRH REVISED PLOT DATE = 12/12/2024 12/13/24

CONTACT: JAMES CAMPBELL PHONE: (630) 940-6805

COMPANY: COMED

ACCOUNT NUMBER: 84692841222

3600 KIRCHOFF RD ROLLING MEADOWS, IL 60008

**ENERGY SUPPLY** 


STATE OF ILLINOIS **DEPARTMENT OF TRANSPORTATION** 

CABLE PLAN, PHASE DESIGNATION DIAGRAM, AND EMERGENCY VEHICLE PREEMPTION SEQUENCE
IL RTE 62 (ALGONQUIN ROAD) AND IL RTE 53 EAST RAMPS SCALE: N.T.S. SHEET 1 OF 1 SHEETS STA.

SECTION 2018-100-BR 342 COOK 1351 533 CONTRACT NO. 62N91

# SIGN PANEL – TYPE 2

ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED.



DESIGN	AREA	SIGN PANEL	SHEETING	QTY.
SERIES	(SQ FT)	TYPE	TYPE	REQUIRED
D	15	2	ZZ	1


NOTE: FOR ADDITIONAL DESIGN AND INSTALLATION INFORMATION SEE DISTRICT ONE MAST ARM MOUNTED STREET NAME SIGNS DETAIL.


# **SCHEDULE OF QUANTITIES**


ITEM	UNIT	QUANTITY
SIGN PANEL - TYPE 1	SQ FT	32.5
SIGN PANEL - TYPE 2	SQ FT	15.0
UNDERGROUND CONDUIT, GALVANIZED STEEL, 2" DIA.	FOOT	465
UNDERGROUND CONDUIT, GALVANIZED STEEL, 3" DIA.	FOOT	348
JNDERGROUND CONDUIT, GALVANIZED STEEL, 4" DIA.	FOOT	338
HANDHOLE	EACH	1
HEAVY-DUTY HANDHOLE	EACH	2
MAINTENANCE OF EXISTING TRAFFIC SIGNAL INSTALLATION	EACH	1
ELECTRIC CABLE IN CONDUIT, SIGNAL NO. 14 3C	FOOT	535
ELECTRIC CABLE IN CONDUIT, SIGNAL NO. 14 5C	FOOT	3,857
ELECTRIC CABLE IN CONDUIT, SIGNAL NO. 14 7C	FOOT	289
ELECTRIC CABLE IN CONDUIT, LEAD-IN, NO. 14 1 PAIR	FOOT	5,771
ELECTRIC CABLE IN CONDUIT, SERVICE, NO. 6 2 C	FOOT	27
ELECTRIC CABLE IN CONDUIT, EQUIPMENT GROUNDING CONDUCTOR, NO. 6 1C	FOOT	836
TRAFFIC SIGNAL POST, GALVANIZED STEEL 16 FT.	EACH	3
STEEL MAST ARM ASSEMBLY AND POLE, 26 FT.	EACH	2
STEEL MAST ARM ASSEMBLY AND POLE, 52 FT.	EACH	1
STEEL COMBINATION MAST ARM ASSEMBLY AND POLE 22 FT.	EACH	1
STEEL COMBINATION MAST ARM ASSEMBLY AND POLE 38 FT.	EACH	1
CONCRETE FOUNDATION, TYPE A	FOOT	16
CONCRETE FOUNDATION, TYPE E 30-INCH DIAMETER	FOOT	30
CONCRETE FOUNDATION, TYPE E 36-INCH DIAMETER	FOOT	26
DRILL EXISTING HANDHOLE	EACH	20
SIGNAL HEAD, LED, 1-FACE, 3-SECTION, MAST-ARM MOUNTED	EACH	13
SIGNAL HEAD, LED, 1-FACE, 3-SECTION, BRACKET MOUNTED	EACH	6
SIGNAL HEAD, LED, 1-FACE, 4-SECTION, BRACKET MOUNTED	EACH	1
SIGNAL HEAD, LED, 1-FACE, 5-SECTION, BRACKET MOUNTED	EACH	1
TRAFFIC SIGNAL BACKPLATE, LOUVERED, FORMED PLASTIC	EACH	13
INDUCTIVE LOOP DETECTOR	EACH	7
DETECTOR LOOP, TYPE I	FOOT	215
RELOCATE EXISTING EMERGENCY VEHICLE PRIORITY SYSTEM, DETECTOR UNIT	EACH	3
REMOVE ELECTRIC CABLE FROM CONDUIT	FOOT	3,058
REMOVE EXISTING TRAFFIC SIGNAL EQUIPMENT	EACH	1
REMOVE EXISTING HANDHOLE	EACH	1
REMOVE EXISTING CONCRETE FOUNDATION	EACH	7
MERGENCY VEHICLE PRIORITY SYSTEM LINE SENSOR CABLE, NO. 20 3/C	FOOT	535
DUTDOOR RATED NETWORK CABLE	FOOT	337
SERVICE INSTALLATION, GROUND MOUNTED, METERED	EACH	1
RELOCATE EXISTING PTZ CAMERA	EACH	1
LED SIGNAL FACE, LENS COVER	EACH	21
CONFIRMATION BEACON	EACH	3
FEMPORARY TRAFFIC SIGNAL TIMING	EACH	1

TS 2665 **IDOT CENTRACS** FORMER ECON 96

USER NAME = AlexaM	DESIGNED	-	RRS	REVISED -
	DRAWN	-	ACM	REVISED -
PLOT SCALE = 40.0000 / in.	CHECKED	-	KRH	REVISED -
PLOT DATE = 1/22/2025	DATE	-	12/13/24	REVISED -








#### **NOTES:**


- THE EXISTING TRAFFIC SIGNAL EQUIPMENT SHALL NOT BE REMOVED UNTIL THE PROPOSED TRAFFIC SIGNAL EQUIPMENT IS FULLY OPERATIONAL OR AS DIRECTED BY THE ENGINEER.
- 2. ALL EXISTING TRAFFIC SIGNAL CABLE NO LONGER REQUIRED SHALL BE REMOVED.
- 3. CONTRACTOR SHALL DISCONNECT EXISTING WESTBOUND FAR BACK LOOP DETECTOR ON US RTE 12 (RAND ROAD) IN EXISTING CABINET AND FAR BACK LOOP DETECTOR HANDHOLE AND INSTALL VIDEO DETECTION SYSTEM, PER THE MANUFACTURES RECOMMENDATIONS. THE MOUNTING LOCATION OF THE VIDEO DETECTION CAMERA SHALL BE DETERMINED PER THE MANUFACTURERS RECOMMENDATIONS. THE VIDEO DETECTION SYSTEM SHALL CONNECT AND BE OPERATED THROUGH THE EXISTING TRAFFIC SIGNAL CONTROLLER. THIS WORK AND ALL NECESSARY EQUIPMENT TO OPERATE THE VIDEO DETECTION SYSTEM THROUGH THE EXISTING TRAFFIC SIGNAL CONTROLLER SHALL BE INCLUDED IN THE UNIT COST OF TEMPORARY TRAFFIC SIGNAL INSTALLATION PAY ITEM.
- CONTRACTOR SHALL INSTALL 2" CONDUIT (30 FEET IN LENGTH) FROM 10 FEET UP THE TEMPORARY WOOD POLE INTO THE EXISTING HANDHOLE. THE COST OF THE TEMPORARY WOOD POLE, CONDUIT, AND DRILLING OF EXISTING HANDHOLE SHALL BE INCLUDED IN THE UNIT COST OF TEMPORARY TRAFFIC SIGNAL INSTALLATION PAY ITEM. CONTRACTOR SHALL INSTALL VIDEO CAMERA DETECTION VENDOR CABLE DOWN TEMPORARY WOOD POLE, THROUGH CONDUIT AND DOUBLE HANDHOLE AND INTO EXISTING CONTROLLER CABINET.
- 5. PROPOSED INTERCONNECT SHALL BE INSTALLED AND OPERATIONAL PRIOR TO REMOVAL OF EXISTING INTERCONNECT. SEE INTERCONNECT DRAWINGS FOR DETAILS.


TS 11290 **ECON 164** 



USER NAME = AlexaM	DESIGNED -	RRS	REVISED -
	DRAWN -	ACM	REVISED -
PLOT SCALE = 40.0000 / in.	CHECKED -	KRH	REVISED -
PLOT DATE = 12/12/2024	DATE -	12/13/24	REVISED -







DRAWN ACM REVISED OT SCALE = 20.0000 '/ in. HECKED KRH REVISED PLOT DATE = 12/12/2024 12/13/24 REVISED


JOLIET, ILLINOIS 60431

STRAND (815) 744-4200

STATE OF ILLINOIS **DEPARTMENT OF TRANSPORTATION** 


**EMERGENCY VEHICLE PREEMPTION SEQUENCE** US RTE 12 (RAND ROAD) AND IL RTE 53 WEST RAMP/N FRONTAGE ROAD OF 1 SHEETS STA.


2018-100-BR COOK 1351 539 CONTRACT NO. 62N91




#### **NOTES:**

- THE EXISTING TRAFFIC SIGNAL EQUIPMENT SHALL NOT BE REMOVED UNTIL THE PROPOSED TRAFFIC SIGNAL EQUIPMENT IS FULLY OPERTATIONAL OR AS DIRECTED BY THE ENGINEER.
- 2. ALL EXISTING TRAFFIC SIGNAL CABLE NO LONGER REQUIRED SHALL BE REMOVED.
- 3. ALL PROPOSED TRAFFIC SIGNAL CABLE SHALL BE ROUTED THROUGH THE PROPOSED CONDUIT.
- 4. A SEPARATE LEAD-IN CABLE SHALL BE INSTALLED FOR THE DETECTOR LOOP ON THE EB AND EB US RTE 12 OUTSIDE THROUGH LANE(S) AND ON THE WB US RTE 12 THROUGH LANES.
- 5. EACH DETECTOR LOOP SHALL HAVE ITS OWN 1" COILABLE NON-METALLIC CONDUIT BETWEEN THE EDGE OF PAVEMENT AND THE ADJACENT HANDHOLE AS SHOWN ON THE PLANS AND AS STATED IN THE TRAFFIC SIGNAL SPECIFICATIONS.
- SEE ITS INSTALLATION PLANS FOR IDOT MICRODUCT, FIBER OPTIC CABLE, AND COMMUNICATION VAULT DETAILS.
- 7. PROPOSED CONDUIT SHALL BE SPLICED TO THE EXISTING CONDUIT AND EXTENDED VERTICALLY THROUGH THE PROPOSED FOUNDATION AT THE GROUND MOUNTED SERVICE LOCATION. THE COST OF THE CONDUIT SHALL BE INCLUDED IN THE COST OF CONCRETE FOUNDATION, TYPE A.







TS 11290 ECON 164


COOK 1351 541

CONTRACT NO. 62N91

COUNTY



USER NAME = AlexaM	DESIGNED - RRS	REVISED -	
	DRAWN - ACM	REVISED -	l
PLOT SCALE = 40.0000 / in.	CHECKED - KRH	REVISED -	l
PLOT DATE = 12/12/2024	DATE - 12/13/24	REVISED -	



**DEPARTMENT OF TRANSPORTATION** 

US RTE 12 (RAND ROAD) AND IL RTE 53 WEST RAMP/N FRONTAGE ROAD

SHEET 1 OF 1 SHEETS STA.

SCALE: N.T.S.

CONTRACT NO. 62N91

**STRAND** (815) 744-4200

LOT SCALE = 20.0000 / in.

PLOT DATE = 12/12/2024

HECKED

DATE

KRH


12/13/24

REVISED

REVISED

# SIGN PANEL - TYPE 2

ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED.



DESIGN	AREA	SIGN PANEL	SHEETING	OTY.
SERIES	(SQ FT)	TYPE	TYPE	REQUIRED
D	11.25	2	ZZ	1

NOTE: FOR ADDITIONAL DESIGN AND INSTALLATION INFORMATION SEE DISTRICT ONE MAST ARM MOUNTED STREET NAME SIGNS DETAIL.


# **SCHEDULE OF QUANTITIES**


ITEM	UNIT	QUANTITY
SIGN PANEL - TYPE 2	SQ FT	11.3
JNDERGROUND CONDUIT, GALVANIZED STEEL, 2" DIA.	FOOT	387
UNDERGROUND CONDUIT, GALVANIZED STEEL, 3" DIA.	FOOT	57
INDERGROUND CONDUIT, GALVANIZED STEEL, 4" DIA.	FOOT	332
IEAVY-DUTY HANDHOLE	EACH	2
LECTRIC CABLE IN CONDUIT, SIGNAL NO. 14 2C	FOOT	448
LECTRIC CABLE IN CONDUIT, SIGNAL NO. 14 3C	FOOT	1,049
LECTRIC CABLE IN CONDUIT, SIGNAL NO. 14 5C	FOOT	1,384
LECTRIC CABLE IN CONDUIT, SIGNAL NO. 14 7C	FOOT	1,348
LECTRIC CABLE IN CONDUIT, LEAD-IN, NO. 14 1 PAIR	FOOT	1,602
LECTRIC CABLE IN CONDUIT, SERVICE, NO. 4 2 C	FOOT	656
LECTRIC CABLE IN CONDUIT, EQUIPMENT GROUNDING CONDUCTOR, NO. 6 1C	FOOT	914
RAFFIC SIGNAL POST, GALVANIZED STEEL 16 FT.	EACH	1
TEEL MAST ARM ASSEMBLY AND POLE, 24 FT.	EACH	1
TEEL MAST ARM ASSEMBLY AND POLE, 48 FT.	EACH	1
TEEL COMBINATION MAST ARM ASSEMBLY AND POLE 54 FT.	EACH	1
ONCRETE FOUNDATION, TYPE A	FOOT	8
ONCRETE FOUNDATION, TYPE E 30-INCH DIAMETER	FOOT	10
ONCRETE FOUNDATION, TYPE E 42-INCH DIAMETER	FOOT	28
RILL EXISTING HANDHOLE	EACH	17
IGNAL HEAD, LED, 1-FACE, 3-SECTION, MAST-ARM MOUNTED	EACH	5
GNAL HEAD, LED, 1-FACE, 3-SECTION, BRACKET MOUNTED	EACH	2
GNAL HEAD, LED, 1-FACE, 4-SECTION, BRACKET MOUNTED	EACH	1
IGNAL HEAD, LED, 1-FACE, 4-SECTION, MAST ARM MOUNTED	EACH	1
IGNAL HEAD, LED, 1-FACE, 5-SECTION, BRACKET MOUNTED	EACH	3
IGNAL HEAD, LED, 1-FACE, 5-SECTION, MAST-ARM MOUNTED	EACH	3
EDESTRIAN SIGNAL HEAD, LED, 1-FACE, BRACKET MOUNTED WITH COUNTDOWN TIMER	EACH	4
RAFFIC SIGNAL BACKPLATE, LOUVERED, FORMED PLASTIC	EACH	9
NDUCTIVE LOOP DETECTOR	EACH	3
ETECTOR LOOP, TYPE I	FOOT	323
IGHT DETECTOR	EACH	4
GHT DETECTOR AMPLIFIER	EACH	1
EMPORARY TRAFFIC SIGNAL INSTALLATION	EACH	1
EMOVE ELECTRIC CABLE FROM CONDUIT	FOOT	4,615
EMOVE EXISTING TRAFFIC SIGNAL EQUIPMENT	EACH	1
EMOVE EXISTING HANDHOLE	EACH	2
EMOVE EXISTING CONCRETE FOUNDATION	EACH	5
MERGENCY VEHICLE PRIORITY SYSTEM LINE SENSOR CABLE, NO. 20 3/C	FOOT	1,476
ENTRACS LICENSE EXPANSION	EACH	1
UTDOOR RATED NETWORK CABLE	FOOT	218
ERVICE INSTALLATION, GROUND MOUNTED, METERED	EACH	1
EMOTE CONTROLLED VIDEO SYSTEM	EACH	1
AYER II (DATALINK) SWITCH	EACH	1
PGRADE EXISTING CONTROLLER TO NTCIP SPECIAL	EACH	1
EDESTRIAN SIGNAL POST, 10 FT.	EACH	3
IBER OPTIC INTERCONNECT CENTER, 48 PORT	EACH	1
CCESSIBLE PEDESTRIAN SIGNALS	EACH	4
ONCRETE FOUNDATION, TYPE A 12-INCH DIAMETER	FOOT	12
ED SIGNAL FACE, LENS COVER	EACH	15
E-OPTIMIZE TRAFFIC SIGNAL SYSTEM LEVEL 1	EACH	1
EMPORARY TRAFFIC SIGNAL TIMING	EACH	1


<sup>\*100%</sup> COST TO THE VILLAGE OF PALATINE


TS 11290 ECON 164


USER NAME = AlexaM	DESIGNED - RRS	REVISED -
	DRAWN - ACM	REVISED -
PLOT SCALE = 40.0000 / in	CHECKED - KRH	REVISED -
PLOT DATE = 12/12/2024	DATE - 12/13/24	REVISED -






















### SIGN PANEL - TYPE 1 OR TYPE 2

ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED.



DESIGN	AREA	SIGN PANEL	SHEETING	OTY.
SERIES	(SQ FT)	TYPE	TYPE	REQUIRED
D	11.25	2	ZZ	



DESIGN	AREA	SIGN PANEL	SHEETING	OTY.
SERIES	(SQ FT)	TYPE	TYPE	REQUIRED
D	6	1	ZZ	

NOTE: FOR ADDITIONAL DESIGN AND INSTALLATION INFORMATION SEE DISTRICT ONE MAST ARM MOUNTED STREET NAME SIGNS DETAIL.

# **SCHEDULE OF QUANTITIES**

ITEM	UNIT	QUANTIT
SIGN PANEL - TYPE 1	SQ FT	12.0
SIGN PANEL - TYPE 2	SQ FT	22.5
UNDERGROUND CONDUIT, GALVANIZED STEEL, 2" DIA.	FOOT	970
UNDERGROUND CONDUIT, GALVANIZED STEEL, 3" DIA.	FOOT	192
UNDERGROUND CONDUIT, GALVANIZED STEEL, 4" DIA.	FOOT	376
HANDHOLE	EACH	2
HEAVY-DUTY HANDHOLE	EACH	3
ELECTRIC CABLE IN CONDUIT, SIGNAL NO. 14 2C	FOOT	164
ELECTRIC CABLE IN CONDUIT, SIGNAL NO. 14 3C	FOOT	1,258
ELECTRIC CABLE IN CONDUIT, SIGNAL NO. 14 5C	FOOT	3,026
ELECTRIC CABLE IN CONDUIT, SIGNAL NO. 14 7C	FOOT	1,364
ELECTRIC CABLE IN CONDUIT, LEAD-IN, NO. 14 1 PAIR	FOOT	3,942
ELECTRIC CABLE IN CONDUIT, SERVICE, NO. 6 2 C	FOOT	28
ELECTRIC CABLE IN CONDUIT, EQUIPMENT GROUNDING CONDUCTOR, NO. 6 1C	FOOT	1,020
TRAFFIC SIGNAL POST, GALVANIZED STEEL 16 FT.	EACH	3
TRAFFIC SIGNAL POST, GALVANIZED STEEL 18 FT.	EACH	1
STEEL MAST ARM ASSEMBLY AND POLE, 24 FT.	EACH	1
STEEL MAST ARM ASSEMBLY AND POLE, 30 FT.	EACH	1
STEEL MAST ARM ASSEMBLY AND POLE, 34 FT.	EACH	1
STEEL COMBINATION MAST ARM ASSEMBLY AND POLE 52 FT.	EACH	1
CONCRETE FOUNDATION, TYPE A	FOOT	20
CONCRETE FOUNDATION, TYPE E 30-INCH DIAMETER	FOOT	10
CONCRETE FOUNDATION, TYPE E 36-INCH DIAMETER	FOOT	49
DRILL EXISTING HANDHOLE	EACH	15
SIGNAL HEAD, LED, 1-FACE, 3-SECTION, MAST-ARM MOUNTED	EACH	9
SIGNAL HEAD, LED, 1-FACE, 3-SECTION, BRACKET MOUNTED	EACH	5
SIGNAL HEAD, LED, 1-FACE, 4-SECTION, BRACKET MOUNTED	EACH	2
SIGNAL HEAD, LED, 1-FACE, 4-SECTION, MAST ARM MOUNTED	EACH	2
SIGNAL HEAD, LED, 1-FACE, 5-SECTION, MAST-ARM MOUNTED	EACH	2
PEDESTRIAN SIGNAL HEAD, LED, 1-FACE, BRACKET MOUNTED WITH COUNTDOWN TIMER	EACH	2
TRAFFIC SIGNAL BACKPLATE, LOUVERED, FORMED PLASTIC	EACH	13
INDUCTIVE LOOP DETECTOR	EACH	7
DETECTOR LOOP, TYPE I	FOOT	924
LIGHT DETECTOR	EACH	5
LIGHT DETECTOR AMPLIFIER	EACH	1
TEMPORARY TRAFFIC SIGNAL INSTALLATION	EACH	1
REMOVE ELECTRIC CABLE FROM CONDUIT	FOOT	1,600
REMOVE EXISTING TRAFFIC SIGNAL EQUIPMENT	EACH	1
REMOVE EXISTING HANDHOLE	EACH	1
REMOVE EXISTING CONCRETE FOUNDATION	EACH	5
EMERGENCY VEHICLE PRIORITY SYSTEM LINE SENSOR CABLE, NO. 20 3/C	FOOT	1,615
CENTRACS LICENSE EXPANSION	EACH	1
TERMINAL SERVER	EACH	1
OUTDOOR RATED NETWORK CABLE	FOOT	227
SERVICE INSTALLATION, GROUND MOUNTED, METERED	EACH	1
REMOTE CONTROLLED VIDEO SYSTEM	EACH	1
LAYER II (DATALINK) SWITCH	EACH	1
UPGRADE EXISTING CONTROLLER TO NTCIP SPECIAL	EACH	1
PEDESTRIAN SIGNAL POST, 5 FT.	EACH	1
FIBER OPTIC INTERCONNECT CENTER, 48 PORT	EACH	1
ACCESSIBLE PEDESTRIAN SIGNALS	EACH	2
CONCRETE FOUNDATION, TYPE A 12-INCH DIAMETER	FOOT	4
LED SIGNAL FACE, LENS COVER	EACH	20
RE-OPTIMIZE TRAFFIC SIGNAL SYSTEM LEVEL 1	EACH	1
TEMPORARY TRAFFIC SIGNAL TIMING	EACH	1


TS 11295 **ECON** 164


COOK 1351 552


CONTRACT NO. 62N91


COUNTY


USER NAME = AlexaM	DESIGNED	-	RRS	REVISED -
	DRAWN	-	ACM	REVISED -
PLOT SCALE = 40.0000 / in	CHECKED	-	KRH	REVISED -
PLOT DATE = 12/12/2024	DATE	-	12/13/24	REVISED -












PLOT DATE = 12/12/2024 12/13/24 DATE


SCALE: 1" = 20' SHEET 2 OF 2 SHEETS STA.

CONTRACT NO. 62N91



# SIGN PANEL - TYPE 2

ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED.



DESIGN	AREA	SIGN PANEL	SHEETING	QTY.
SERIES	(SQ FT)	TYPE	TYPE	REQUIRED
D	12.5	2	ZZ	

NOTE: FOR ADDITIONAL DESIGN AND INSTALLATION INFORMATION SEE DISTRICT ONE MAST ARM MOUNTED STREET NAME SIGNS DETAIL.

# SCHEDULE OF QUANTITIES

ITEM	UNIT	QUANTIT
SIGN PANEL - TYPE 2	SQ FT	12.5
UNDERGROUND CONDUIT, GALVANIZED STEEL, 2" DIA.	FOOT	516
UNDERGROUND CONDUIT, GALVANIZED STEEL, 3" DIA.	FOOT	139
UNDERGROUND CONDUIT, GALVANIZED STEEL, 4" DIA.	FOOT	232
HEAVY-DUTY HANDHOLE	EACH	2
MAINTENANCE OF EXISTING TRAFFIC SIGNAL INSTALLATION	EACH	1
ELECTRIC CABLE IN CONDUIT, SIGNAL NO. 14 3C	FOOT	490
ELECTRIC CABLE IN CONDUIT, SIGNAL NO. 14 5C	FOOT	2,279
ELECTRIC CABLE IN CONDUIT, LEAD-IN, NO. 14 1 PAIR	FOOT	2,260
ELECTRIC CABLE IN CONDUIT, SERVICE, NO. 6 2 C	FOOT	37
ELECTRIC CABLE IN CONDUIT, EQUIPMENT GROUNDING CONDUCTOR, NO. 6 1C	FOOT	450
TRAFFIC SIGNAL POST, GALVANIZED STEEL 16 FT.	EACH	3
STEEL MAST ARM ASSEMBLY AND POLE, 30 FT.	EACH	3
STEEL COMBINATION MAST ARM ASSEMBLY AND POLE 30 FT.	EACH	1
CONCRETE FOUNDATION, TYPE A	FOOT	16
CONCRETE FOUNDATION, TYPE E 36-INCH DIAMETER	FOOT	44
DRILL EXISTING HANDHOLE	EACH	14
SIGNAL HEAD, LED, 1-FACE, 3-SECTION, MAST-ARM MOUNTED	EACH	8
SIGNAL HEAD, LED, 1-FACE, 3-SECTION, BRACKET MOUNTED	EACH	6
TRAFFIC SIGNAL BACKPLATE, LOUVERED, FORMED PLASTIC	EACH	8
INDUCTIVE LOOP DETECTOR	EACH	2
DETECTOR LOOP, TYPE I	FOOT	123
LIGHT DETECTOR	EACH	3
LIGHT DETECTOR AMPLIFIER	EACH	1
REMOVE ELECTRIC CABLE FROM CONDUIT	FOOT	1,496
REMOVE EXISTING TRAFFIC SIGNAL EQUIPMENT	EACH	1
REMOVE EXISTING CONCRETE FOUNDATION	EACH	6
EMERGENCY VEHICLE PRIORITY SYSTEM LINE SENSOR CABLE, NO. 20 3/C	FOOT	490
CENTRACS LICENSE EXPANSION	EACH	1
TERMINAL SERVER	EACH	1
OUTDOOR RATED NETWORK CABLE	FOOT	81
SERVICE INSTALLATION, GROUND MOUNTED, METERED	EACH	1
REMOTE CONTROLLED VIDEO SYSTEM	EACH	1
LAYER II (DATALINK) SWITCH	EACH	1
UPGRADE EXISTING CONTROLLER TO NTCIP SPECIAL	EACH	1
FIBER OPTIC INTERCONNECT CENTER, 48 PORT	EACH	2
LED SIGNAL FACE, LENS COVER	EACH	14
TEMPORARY TRAFFIC SIGNAL TIMING	EACH	1
TEMPORARY TRAFFIC SIGNAL TIMING *100% COST TO THE VILLAGE OF PALATINE	EACH	1


<sup>\*100%</sup> COST TO THE VILLAGE OF PALATINE

TS 12155 ECON 92

1170 SOUTH HOUBOLT RC
JOLIET, ILLINOIS 60431


STRAND
(815) 744-4200
ASSOCIATES\*


USER NAME = AlexaM	DESIGNED - RRS	REVISED -
	DRAWN - ACM	REVISED -
PLOT SCALE = 40.0000 / in	CHECKED - KRH	REVISED -
PLOT DATE = 12/12/2024	DATE - 12/13/24	REVISED -



PLOT DATE = 12/12/2024 DATE 12/13/24 SCALE: 1" = 20' SHEET 1 OF 1 SHEETS STA.

COOK 1351 558 CONTRACT NO. 62N91





#### **LEGEND:**

**◆** PROTECTED PHASE

← -(\*)- - PROTECTED/PERMITTED PHASE

√- \*- PEDESTRIAN PHASE

◆ OL OVERLAP

eo	TRAFFIC SIGNAL						
nude	ELECTRIC SERVICE REQUIREMENTS						
Plan-Dundee&II	ТҮРЕ	QUANTITY	UNIT WATTAGE	TOTAL WATTAGI			
Sheets\C2-D162N91-sht-ts-26a-TEMP-Cable	SIGNAL HEAD						
Ÿ	1 OR 3 - SECTION	12	11	132			
<u>=</u>	4 - SECTION	2	14	28			
-697	5 - SECTION		13				
-ts	PROGRAMMABLE SIGNALS						
Ę.	3 - SECTION		22				
2N9	4 - SECTION		32				
916	5 - SECTION		28				
3	PED. SIGNAL		15				
ets	CONTROLLER	1	150	150			
	MASTER CONTROLLER		100				
8	UPS	1	25	25			
54/(	DETECTION RADAR OR VIDE	3	20	60			
S	BLANK-OUT SIGN		25				
Σ	NETWORK SWITCH II OR III		35				
AD)	CELLULAR MODEM		15				
gs/C	PTZ CAMERA		75				
.113\Drawings\CAD\Micros SS4\CAD	TOTAL UPS SIZI	NG		395			
ğ	UPS CHARGING	1	225	225			
Ë	BATTERY HEATER MAT	1	180	180			

ENERGY COSTS TO: VILLAGE OF ARLINGTON HEIGHTS 33 S. ARLINGTON HEIGHTS RD ARLINGTON HEIGHTS, IL 60005

200

200

15 120

240

CONTACT JAMES CAMPBELL PHONE: (630) 940-6805 ACCOUNT NUMBER:

BARREL MOUNTED-(5) R Y A G (5) (5) R ◆Y ◆G R ◆Y ◆G IL RTE 68
DUNDEE ROAD \$ \$\frac{1}{27}\$ \$ \$\frac{1}{2}\$ -5 © ≺ ¬ 5 7 R Y 4G

TEMPORARY CABLE PLAN
(NOT TO SCALE)

TS 12160 ECON 92

1170 SOUTH HOUBOLT F
JOLIET, ILLINOIS 60431

STRAND
(815) 744-4200
ASSOCIATES\*

CABINET HEATER

LED STREET NAME SIGN

FLASHER

LUMINAIRE

1170 SOUTH HOUBOLT ROAD


TOTAL SERVICE WIRE SIZING

SER NAME = AlexaM DESIGNED - RRS REVISED DRAWN -ACM REVISED LOT SCALE = 20.0000 / in. CHECKED KRH REVISED PLOT DATE = 12/12/2024 REVISED DATE 12/13/24


STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

TEMPORARY CABLE PLAN AND TEMPORARY PHASE DESIGNATION DIAGRAM IL RTE 68 (DUNDEE ROAD) AT IL RTE 53 EAST RAMPS SHEET 1 OF 1 SHEETS STA.

SECTION COUNTY 2018-100-BR COOK 1351 559 342 CONTRACT NO. 62N91








## SIGN PANEL - TYPE 2

ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED.



DESIGN	AREA	SIGN PANEL	SHEETING	QTY.
SERIES	(SQ FT)	TYPE	TYPE	REQUIRED
D	12.5	2	ZZ	1

NOTE: FOR ADDITIONAL DESIGN AND INSTALLATION INFORMATION SEE DISTRICT ONE MAST ARM MOUNTED STREET NAME SIGNS DETAIL.


## **SCHEDULE OF QUANTITIES**


ITEM	UNIT	QUANTIT
SIGN PANEL - TYPE 1	SQ FT	41.3
SIGN PANEL - TYPE 2	SQ FT	12.5
UNDERGROUND CONDUIT, GALVANIZED STEEL, 2" DIA.	FOOT	1,667
UNDERGROUND CONDUIT, GALVANIZED STEEL, 3" DIA.	FOOT	275
UNDERGROUND CONDUIT, GALVANIZED STEEL, 4" DIA.	FOOT	458
HANDHOLE	EACH	2
HEAVY-DUTY HANDHOLE	EACH	8
DOUBLE HANDHOLE	EACH	1
ELECTRIC CABLE IN CONDUIT, SIGNAL NO. 14 3C	FOOT	549
ELECTRIC CABLE IN CONDUIT, SIGNAL NO. 14 5C	FOOT	2,764
ELECTRIC CABLE IN CONDUIT, SIGNAL NO. 14 7C	FOOT	247
ELECTRIC CABLE IN CONDUIT, LEAD-IN, NO. 14 1 PAIR	FOOT	5,453
ELECTRIC CABLE IN CONDUIT, SERVICE, NO. 4 2 C	FOOT	456
ELECTRIC CABLE IN CONDUIT, EQUIPMENT GROUNDING CONDUCTOR, NO. 6 1C	FOOT	1,276
TRAFFIC SIGNAL POST, GALVANIZED STEEL 16 FT.	EACH	4
STEEL MAST ARM ASSEMBLY AND POLE, 30 FT.	EACH	1
STEEL MAST ARM ASSEMBLY AND POLE, 32 FT.	EACH	2
STEEL MAST ARM ASSEMBLY AND POLE, 36 FT.	EACH	1
CONCRETE FOUNDATION, TYPE A	FOOT	20
CONCRETE FOUNDATION, TYPE C	FOOT	4
CONCRETE FOUNDATION, TYPE E 36-INCH DIAMETER	FOOT	44
DRILL EXISTING HANDHOLE	EACH	1
SIGNAL HEAD, LED, 1-FACE, 3-SECTION, MAST-ARM MOUNTED	EACH	9
SIGNAL HEAD, LED, 1-FACE, 3-SECTION, BRACKET MOUNTED	EACH	6
SIGNAL HEAD, LED, 1-FACE, 4-SECTION, BRACKET MOUNTED	EACH	1
SIGNAL HEAD, LED, 1-FACE, 5-SECTION, BRACKET MOUNTED	EACH	1
TRAFFIC SIGNAL BACKPLATE, LOUVERED, FORMED PLASTIC	EACH	9
INDUCTIVE LOOP DETECTOR	EACH	14
DETECTOR LOOP, TYPE I	FOOT	903
LIGHT DETECTOR	EACH	3
LIGHT DETECTOR AMPLIFIER	EACH	1
TEMPORARY TRAFFIC SIGNAL INSTALLATION	EACH	1
REMOVE EXISTING TRAFFIC SIGNAL EQUIPMENT	EACH	1
REBUILD EXISTING HANDHOLE TO HEAVY-DUTY HANDHOLE	EACH	1
REMOVE EXISTING HANDHOLE	EACH	12
REMOVE EXISTING CONCRETE FOUNDATION	EACH	7
EMERGENCY VEHICLE PRIORITY SYSTEM LINE SENSOR CABLE, NO. 20 3/C	FOOT	549
CENTRACS LICENSE EXPANSION	EACH	1
FULL-ACTUATED CONTROLLER AND TYPE SUPER P CABINET (SPECIAL)	EACH	1
SERVICE INSTALLATION, GROUND MOUNTED, METERED	EACH	1
LAYER II (DATALINK) SWITCH	EACH	1
UNINTERRUPTABLE POWER SUPPLY (SPECIAL)		1
FIBER OPTIC INTERCONNECT CENTER, 48 PORT	EACH EACH	1
·		
LED SIGNAL FACE, LENS COVER	EACH	17
TEMPORARY TRAFFIC SIGNAL TIMING *100% COST TO THE VILLAGE OF ARLINGTON HEIGHTS	EACH	1

<sup>\*100%</sup> COST TO THE VILLAGE OF ARLINGTON HEIGHTS

TS 12160 ECON 92

USER NAME = AlexaM	DESIGNED	-	RRS	REVISED -
	DRAWN	-	ACM	REVISED -
PLOT SCALE = 40.0000 / in.	CHECKED	-	KRH	REVISED -
PLOT DATE = 12/12/2024	DATE	-	12/13/24	REVISED -





1170 SOUTH HOUBOLT ROAD
JOLIET, ILLINOIS 60431

STRAND (815) 744-4200
ASSOCIATES\*

 USER NAME
 = AlexaM
 DESIGNED
 RRS
 REVISED

 DRAWN
 ACM
 REVISED

 PLOT SCALE
 = 100,0000 ' / in.
 CHECKED
 KRH
 REVISED


 PLOT DATE
 = 12/12/2024
 DATE
 12/13/24
 REVISED


STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

REMOVAL INTERCONNECT PLAN

US RTE 12 (RAND ROAD) FROM N WILLIAMS DRIVE TO KENNICOTT DRIVE

SCALE: 1": 50' SHEET 1 OF 2 SHEETS STA. TO STA.





1170 SOUTH HOUBOLT ROAD
JOLIET, ILLINOIS 60431

STRAND (815) 744-4200
ASSOCIATES\*

 USER NAME
 = AlexaM
 DESIGNED
 RRS
 REVISED

 DRAWN
 ACM
 REVISED


 PLOT SCALE
 = 100,0000 ' / in.
 CHECKED
 KRH
 REVISED

 PLOT DATE
 = 12/12/2024
 DATE
 12/13/24
 REVISED

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

US RTE 12 (RAND ROAD) FROM N WILLIAMS DRIVE TO KENNICOTT DRIVE

SCALE: 1": 50' SHEET 2 OF 2 SHEETS STA. TO STA.




1170 SOUTH HOUBOLT ROAD
JOLIET, ILLINOIS 60431
STRAND
(815) 744-4200
ASSOCIATES\*


STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

SCALE: N.T.S.

RTE. 3LC110V COOKT SHEETS NO. 342 2018-100-BR COOK 1351 566

CONTRACT NO. 62N91






1170 SOUTH HOUBOLT ROAD
JOLIET, ILLINOIS 60431
STRAND
ASSOCIATES\*
(815) 744-4200

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

TEMPORARY AND PROPOSED INTERCONNECT PLAN
US RTE 12 (RAND ROAD) FROM N WILLIAMS DRIVE TO KENNICOTT DRIVE

SCALE: 1": 50' SHEET 1 OF 3 SHEETS STA. TO STA.




1170 SOUTH HOUBOLT RY JOLIET, ILLINOIS 60431 STRAND ASSOCIATES\*

USER NAME = AlexaM	DESIGNED	-	RRS	REVISED -	
	DRAWN	-	ACM	REVISED -	
PLOT SCALE = 100.0000 / in.	CHECKED	-	KRH	REVISED -	
PLOT DATE = 1/22/2025	DATE	-	12/13/24	REVISED -	

STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION

TEN	<b>IPORAR</b>	Υ	AND F	PRO	POSED	INTE	ERCONNE	CT PLAN		F.A RT
US RTE 12 (RAI	ND ROA	۱D)	FROM	N	WILLIA	MS	DRIVE TO	KENNICOTT	DRIVE	34
SCALE: 1" : 50'	SHEET	2	OF	3	SHEETS	STA		TO STA.		

SECTION COOK 1351 568 CONTRACT NO. 62N91 2018-100-BR






**ECON 164** 

USER NAME = AlexaM	DESIGNED - RRS	REVISED -
	DRAWN - ACM	REVISED -
PLOT SCALE = 100.0000 / in.	CHECKED - KRH	REVISED -
PLOT DATE = 12/13/2024	DATE - 12/13/24	REVISED -

STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION

TEN	IPORARY A	AND PRO	POSED	INTERCONNEC	T PLAN		F.A.P. RTE
US RTE 12 (RAN	ND ROAD)	FROM N	WILLIA	MS DRIVE TO	KENNICOTT D	RIVE	342
SCALE: 1" : 50'	SHEET 3	OF 3	SHEETS	STA.	TO STA.		

	F.A.P. RTE	SECTION		COUNTY	TOTAL SHEETS	SHEE NO.
:	342	2018-100-BR		соок	1351	569
				CONTRACT	NO. 62	2N91
		ILLINOIS	FED. A	D PROJECT		




1170 SOUTH HO
JOLIET, ILLINOIS
STRAND
ASSOCIATES®
(815) 744-4200


LOT SCALE = 40.0000 / in. HECKED KRH REVISED PLOT DATE = 1/22/2025 DATE 12/13/24 REVISED


STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION


US RTE 12 (RAND ROAD)
SHEET 1 OF 1 SHEETS STA. SCALE: N.T.S. TO STA.


2018-100-BR COOK 1351 570 342 CONTRACT NO. 62N91












1170 SOUTH HOUBOLT ROAD
JOLIET, ILLINOIS 60431

STRAND (815) 744-4200
ASSOCIATES\*

DRAWN - ACM	USER NAME = AlexaM	DESIGNED - RRS	REVISED -
		DRAWN - ACM	REVISED -
PLOT DATE = 12/13/2024 DATE - 12/13/24 REVISED -	PLOT SCALE = 40.0000 / in.	CHECKED - KRH	REVISED -
	PLOT DATE = 12/13/2024	DATE - 12/13/24	REVISED -

TRAFFIC SIGNAL MODERNIZATION PLAN	F.A.P. RTE	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
LAKE COOK ROAD AT OLD HICKS ROAD	342	2018-100-BR	соок	1351	575
LAKE COOK HOAD AT OLD HICKS HOAD			CONTRACT	NO. 62	2N91
SCALE: 1" = 20'   SHEET 1 OF 1 SHEETS   STA. TO STA.		ILLINOIS FED. A	ID PROJECT		



вестим, 00-А5011-05-ОН

CABLE PLAN LEGEND

12' TRAFFIC SIGNAL SECTION

VEHICLE DETECTOR. INQUOTION LOOP


GROUNDING SYSTEM CONNECTION SHIELDED & TWISTED

SERVICE INSTALLATION

CONTROLLER CABINET

CONTROLLER SEQUENCE


REFFERING TO STANDARD 857001. THE VEHICULAR AND PEDESTRIAN PHASES USED ARE DESIGNATED BELOW



## PHASE DESIGNATION DIAGRAM

DUAL ENTRY-ALL LEGS PROTECTED PERMITTED LEFT TURN PHASING

# FOR REFERENCE ONLY



CABLE PLAN NOT TO SCALE

COUNTY DE COOK DEPARTMENT OF HIGHWAYS TRAFFIC SIGNAL INSTALLATION AKE-COOK ROAD AT DLD HICKS ROAD

1170 SOUTH HOUBOLT ROAD **STRAND** (815) 744-4200

USER NAME = AlexaM	DESIGNED -	RRS	REVISED -
	DRAWN -	ACM	REVISED -
PLOT SCALE = 40.0000 / in	CHECKED -	KRH	REVISED -
PLOT DATE = 12/13/2024	DATE -	12/13/24	REVISED -


CABLE PLAN								
LAKE	COO	K R	OAD	AT 0	LD HICK	S ROAD	342	
SHEET	1	OF	1	SHEETS	STA.	TO STA.		

SCALE: 1" = 20'

LIG	HTING AND ELECTRICAL LEGEND			
SYMBOL	DESCRIPTION			
○—(E)	EXISTING LIGHT POLE W/ MAST ARM TO REMAIN			
EE	EXISTING MEDIAN MOUNTED LIGHT POLE W/ DUAL MAST ARM TO REMAIN			
o—(R)	EXISTING LIGHTING UNIT TO BE REMOVED. EXISTING LUMINAIRE TO BE SALVAGED.			
EXISTING MEDIAN MOUNTED LIGHTING UNIT TO BE REMOVED.  EXISTING LUMINAIRE & LIGHTING ARM TO BE SALVAGED.				
TEMPORARY HIGH MAST LIGHTING UNIT, 90-FT WOOD POLE, 70 FT MOUNTING HEIGHT 15-FT MAST ARM, LUMINAIRE, LED, ROADWAY OUTPUT DESIGNATION K (240VAC)				
	TEMPORARY WOOD POLE, CLASS 4, 50 FT			
REMOVE EXISTING LUMINAIRE, SALVAGE. INSTALL LUMINAIRE SAFETY CABLE AND LED LUMINAIRE (HORIZONTAL MOUNT, OUTPUT DESIGNATION H) ON EXISTING GROUND MOUNTED LIGHT POLE AND MAST ARM.				
<b>®</b> → <b>®</b>	REMOVE EXISTING MEDIAN LUMINAIRES AND INSTALL SAFETY CABLES, AND 2 LED LUMINAIRES (HORIZONTAL MOUNT, OUTPUT DESIGNATION H) ON EXISTING MEDIAN MOUNTED LIGHT POLE.			
<b>QQ</b>	REMOVE EXISTING MEDIAN LUMINAIRES AND DUAL MAST ARMS, SALVAGE. INSTALL 6-FT DUAL MAST ARMS, LUMINAIRE SAFETY CABLES, AND 2 LED LUMINAIRES (HORIZONTAL MOUNT, OUTPUT DESIGNATION H) ON EXISTING MEDIAN MOUNTED LIGHT POLE.			
PROPOSED LIGHTING UNIT MOUNTED ON BREAKAWAY DEVICE, NEW METAL FOUNDATION (UNLESS OTHERWISE NOTED), 47.5 FT MOUNTING HEIGHT, 15 FT MAST ARM, LUMINAIRE TO BE LED, HORIZONTAL MOUNT OUTPUT DESIGNATION H (240VAC).				
<b>P</b> - <b>P</b>	PROPOSED LIGHTING UNIT MOUNTED ON MEDIAN, NEW CONCRETE BARRIER FOUNDATION, 47.5 FT MOUNTING HEIGHT, 2-6 FT MAST ARMS, 2 LUMINAIRES TO BE LED, HORIZONTAL MOUNT OUTPUT DESIGNATION H (240VAC).			
<u>-</u> ₩	PROPOSED IDOT LIGHTING UNIT MOUNTED ON PROPOSED TRAFFIC SIGNAL POLE, 45 FT M.H. U.N.O., 15 FT MAST ARM, LUMINAIRE TO BE LED, HORIZONTAL MOUNT, OUTPUT DESIGNATION H (120 VAC) U.N.O.			
Ŭ E R	EXISTING UNDERPASS LUMINAIRE TO BE REMOVED			
J <sub>F</sub>	EXISTING JUNCTION BOX TO REMAIN			
J	EXISTING JUNCTION BOX TO BE REMOVED			
H <sub>E</sub>	EXISTING HANDHOLE TO BE REMOVED			
□ □	PROPOSED UNDERPASS LED LUMINAIRE, SUSPENDED MOUNT, OUTPUT DESIGNATION E			
	PROPOSED UNDERPASS LED LUMINAIRE, SUSPENDED MOUNT, OUTPUT DESIGNATION D			
J	PROPOSED JUNCTION BOX, TYPE AND SIZE AS NOTED			
H	PROPOSED HANDHOLE			
	EXISTING IDOT LIGHTING CONTROLLER TO REMAIN			
	EXISTING ELECTRICAL UTILITY SERVICE TO REMAIN			
Œ.	EXISTING HIGH MAST LIGHT TOWER TO REMAIN			

ABBREVIATIONS					
ADDDE MATION					
ABBREVIATION	DESCRIPTION				
AC A/C	ALTERNATING CURRENT AERIAL CABLE				
ATS	ATTACHED TO STRUCTURE				
B.O.C.	BACK OF CURB				
СВ	CIRCUIT BREAKER				
CKT	CIRCUIT				
CM	CENTIMETER COMMONWEALTH EDISON COMPANY				
CP	CONTROL PANEL				
CT	CURRENT TRANSFORMER				
DA	DAVIT ARM				
DC	DIRECT CURRENT				
DIA DP	DIAMETER DISTRIBUTION PANEL				
E	EXISTING UNIT TO REMAIN				
EX.	EXISTING				
ECA	ELECTRIC CABLE ASSEMBLY				
ElS	EMBEDDED IN STRUCTURE				
E.O.P. F.O.C.	EDGE OF PAVEMENT FACE OF CURB				
FT FT	FEET OR FOOT				
FU	FUSE				
GND	GROUND				
HID JB	HIGH INTENSITY DISCHARGE JUNCTION BOX				
KVA	KILOVOLT-AMPERE				
KW	KILOWATTS				
LED	LIGHT EMITTING DIODE				
LP	LIGHT POLE				
M MA	METER MAST ARM				
MC	MULTI-CONDUCTOR				
MM	MILLIMETER				
M.H.	MOUNTING HEIGHT				
MW NESC	MESSENGER WIRE NATIONAL ELECRIC SAFETY CODE				
NO.#	NUMBER				
N.T.S.	NOT TO SCALE				
P	PROPOSED				
PB PNL	PUSH BUTTON PANEL				
PVC	POLYVINYL CHLORIDE				
PVCC RGC	PVC COATED RIGID GALVANIZED CONDUIT				
PT	POTENTIAL TRANSFORMER				
R	EXISTING UNIT TO BE REMOVED				
RR	(OWNER SALVAGED U.N.O.) EXISTING UNIT TO BE REMOVED AND				
	REINSTALLED				
RECP	RECEPTACLE				
RGC	RIGID GALVANIZED CONDUIT				
ROW SEL SW	RIGHT OF WAY SELECTOR SWITCH				
SPARE	SPARE				
SPACE	SPACE				
ss	STAINLESS STEEL				
STA	STATION				
T/F UD	TOP OF FOUNDATION UNIT DUCT				
U.N.O.	UNLESS NOTED OTHERWISE				
UGC, GS	UNDERGROUND CONDUCT, GALVANIZED STEEL				
VAC	VOLTS, ALTERNATING CURRENT				
W	WATTS				
WP XFMR	WOOD POLE TRANSFORMER				
HPS	HIGH PRESSURE SODIUM				
LPS	LOW PRESSURE SODIUM				
LTFM	LIQUID TIGHT FLEXIBLE METALLIC				

## CALL-OUT SAMPLE **DEFINITION AND EXAMPLE** CONDUIT QUANTITY, SIZE, TYPE, LENGTH 3" DIA. UGC, GS 40' CKT: CONDUCTORS A&B: 3#2 & 1#4 GND /RACEWAY 1 ½" DIA. UD CONTROLLER DESIGNATION LOCATION DESCRIPTION - CONTROLLER DESIGNATION CIRCUIT DESIGNATION CIRCUIT NUMBER LED LUMINAIRE OUTPUT DESIGNATION LETTER À 1, LED-H STA. 205+10 SET BACK 18' FROM F.O.C. OR E.O.P. STATION -PROPOSED LIGHTING UNIT SET BACK SET BACK E.O.P. POLE SET BACK DETAIL



SCALE:

#### **GENERAL NOTES**

- THE ELECTRICAL WORK SHALL BE PERFORMED IN ACCORDANCE WITH THE LATEST CODES, STANDARDS. AND THE IDOT STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION ADOPTED JANUARY 1, 2022, AND SUPPLEMENTAL SPECIFICATIONS AND RECURRING SPECIAL PROVISIONS.
- THE CONTRACTOR SHALL CONTACT MEADE ELECTRIC CO. DISTRICT ONE ELECTRICAL
  MAINTENANCE CONTRACTOR TO LOCATE IDOT ELECTRICAL EQUIPMENT AND UNDERGROUND
  CABLES 773-287-7672.
- 3. THE CONTRACTOR SHALL TAKE PROPER MEASURE NOT TO DAMAGE THE EXISTING CABLES COMING OUT THE EXISTING MEDIAN BARRIER WALL FOUNDATIONS.

NOTIFY THE IDOT DISTRICT ONE ELECTRICAL MAINTENANCE OFFICE LONG TRAN, LONG. TRAN@ILLINOIS.GOV, 847-705-4232 TWO WEEKS PRIOR TO THE ANTICIPATED LIGHTING MAINTENANCE TRANSFER.

#### **IDOT-D1 STANDARDS**:

STANDARD NO	. <u>TITLE</u>
BE-240	COMBINATION LIGHTING, TRAFFIC SIGNAL SCHEMATIC
BE-322	24" DIA. LIGHT POLE FOUNDATION INTEGRAL WITH DOUBLE FACE BARRIER WALL
BE-400	ALUMINUM LIGHT POLE 47'-6" (14.478 m) MOUNTING HEIGHT
BE-701	LUMINAIRE SAFETY CABLE ASSEMBLY
BE-702	MISC. ELECTRICAL DETAILS SHEET A
BE-703	MISCELLANEOUS ELECTRICAL DETAILS, SHEET B
BE-800	TEMPORARY LIGHT POLE DETAILS
BE-801	TEMPORARY AERIAL CABLE INSTALLATION
BE-901	SUSPENDED MOUNT LED UNDERPASS LUMINAIRE INSTALLATION DETAILS

SINGH SINGH+ASSOCIATES, INC.

JSER NAME = vnunez	DESIGNED - VG	REVISED -
	DRAWN - AP/MAG	REVISED -
PLOT SCALE = 2 0000 / in	CHECKED - RP/MG	REVISED -
PLOT DATE = 1/23/2025	DATE - 1/24/2025	REVISED -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

LIGHTING	LEGEND	AND	GENERAL	NOTES		
SHEET	OF	SHEETS	STA.		TO S	TA.

				L.	Γ-01
SECTIO	N		COUNTY	TOTAL SHEETS	SHEET NO.
2018-100	-BR		COOK	1351	577
			CONTRACT	NO. 62	2N91
ILL	INOIS	FED. A	D PROJECT		

342

		LUMINAIRE, LED, ROAD\	WAY, OUTPUT DESIGNATION H			EACH	104
		LUMINAIRE, LED, UNDER	RPASS, SUSPENDED, OUTPUT DESIGNAT	TION D		EACH	10
		LUMINAIRE, LED, UNDER	RPASS, SUSPENDED, OUTPUT DESIGNAT	TION E		EACH	46
		LIGHT POLE, ALUMINUM	1, 47.5 FT. M.H., 2-6 FT. MAST ARMS			EACH	11
		LIGHT POLE FOUNDATION	DN, 24" DIAMETER			FOOT	15
		REMOVAL OF TEMPORA	RY LIGHTING UNIT			EACH	11
		REMOVAL OF LIGHTING				EACH	17
		REMOVAL OF POLE FOL	·			EACH	17
		REMOVE TEMPORARY V					13
						EACH	803
		ROD AND CLEAN EXISTI				FOOT	
		REMOVAL OF CABLE IN				FOOT	3,511
		REMOVAL OF LUMINAIR	E, SALVAGE			EACH	443
		6 FT DUAL MAST ARMS,	ALUMINUM, 180 DEGREES APART			EACH	38
		JUNCTION BOX, NON-ME	ETALLIC, EMBEDDED IN STRUCTURE, 20"	" X 13" X 12"		EACH	7
		COMBINATION LIGHTING	G CONTROLLER			EACH	4
		TEMPORARY WOOD PO	LE,90 FT.,CLASS 2, 15 FT. MAST ARM			EACH	11
		TEMPORARY WOOD PO	LE, 50 FT., CLASS 4			EACH	13
		LIGHT POLE FOUNDATION	ON, INTEGRAL WITH BARRIER WALL			EACH	10
		LIGHT POLE FOUNDATION	ON, INTEGRAL WITH BARRIER WALL, 24"	DIAMETER		FOOT	90
		REMOVAL OF LUMINAIR	E, SALVAGE, UNDERPASS			EACH	20
		REMOVAL OF LUMINAIR	E, NO SALVAGE, UNDERPASS			EACH	52
		LUMINAIRE SAFETY CAE	BLE ASSEMBLY			EACH	443
		MAINTENANCE OF LIGH	TING SYSTEM			CAL MO	9
		REMOVAL OF LIGHTING	ARM. SALVAGE			EACH	76
			WAY, REPLACEMENT, OUTPUT DESIGNA	TION H		EACH	339
	USER NAME = vnunez	DESIGNED - VG	REVISED -		T		
1	PLOT SCALE = 2 ' / in.	DRAWN - AP/MAG	REVISED - REVISED -	STATE OF ILLINOIS		LIGHT	TING BILL OF N
INC. ERS	PLOT SCALE = 2 / In.  PLOT DATE = 1/23/2025	CHECKED - RP/MG  DATE - 1/24/2025	REVISED -	DEPARTMENT OF TRANSPORTATION	SCALE:	SHEET	OF SHEETS

UNDERGROUND CONDUIT, GALVANIZED STEEL, 4" DIA.

CONDUIT EMBEDDED IN STRUCTURE, 2" DIA., PVC

CONDUIT EMBEDDED IN STRUCTURE, 4" DIA., PVC

CONDUIT ATTACHED TO STRUCTURE, 1" DIA., PVC COATED GALVANIZED STEEL

JUNCTION BOX, STAINLESS STEEL, ATTACHED TO STRUCTURE, 6" X 6" X 4"

JUNCTION BOX, STAINLESS STEEL, ATTACHED TO STRUCTURE, 12" X 10" X 6"

JUNCTION BOX, STAINLESS STEEL, ATTACHED TO STRUCTURE, 18" X 12" X 6"

JUNCTION BOX, STAINLESS STEEL, ATTACHED TO STRUCTURE, 18" X 18" X 8"

UNIT DUCT, 600V, 3-1C NO.2, 1/C NO.4 GROUND, 1 1/2" DIA. POLYETHYLENE

UNIT DUCT, 600V, 4-1C NO.2, 1/C NO.4 GROUND, 1 1/2" DIA. POLYETHYLENE

ELECTRIC CABLE IN CONDUIT, 600V (XLP-TYPE USE) 1/C NO. 10

ELECTRIC CABLE IN CONDUIT, 600V (XLP-TYPE USE) 1/C NO. 4

ELECTRIC CABLE IN CONDUIT, 600V (XLP-TYPE USE) 1/C NO. 2

AERIAL CABLE, 3-1/C NO. 2 WITH MESSENGER WIRE

AERIAL CABLE, 4-1/C NO. 2 WITH MESSENGER WIRE

TOTAL SHEET NO.



LIGHTING BILL OF MATERIALS						3
SHEET	OF	SHEETS	STA.	TO STA.		_

TOTAL

QUANTITY

1887

1914

2,321

283

54

24

3,307

5,512

9,101

2,700

10,292

2,119

4,547

UNIT

FOOT

FOOT

FOOT

FOOT

EACH

EACH

EACH

EACH

FOOT

FOOT

FOOT


FOOT


FOOT


FOOT


EACH

TE	SECTION			COUNTY	SHEETS	N
42 2018-100-BR			соок	1351	57	
				CONTRACT	NO. 62	2N9
		ILLINOIS	FED. A	D PROJECT		









LT-06

SINGH - ASSOCIATES, INC.

USER NAME = vnunez	DESIGNED - VG	REVISED -
	DRAWN - AP/MAG	REVISED -
PLOT SCALE = 100.0000 / in.	CHECKED - RP/MG	REVISED -
PLOT DATE = 1/23/2025	DATE - 1/24/2025	REVISED -

STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION

IL ROUTE 53					
TEMPORARY AND REMOVAL LIGHTING PLAN					
SHEET	OF	SHEETS	STA.	TO STA.	


SCALE: 1" - 50'

 
 F.A.P. RTE.
 SECTION
 COUNTY
 TOTAL SHEETS
 SHEET NO.

 342
 2018-100-BR
 COOK
 1351
 582

 CONTRACT NO. 62N91

 ILLINOIS
 FED. AID PROJECT



LT-07


TAL SHEET NO. 351 583
0. 62N91


	USER NAME = vnunez	DESIGNED - VG	REVISED -
Γ		DRAWN - AP/MAG	REVISED -
Γ	PLOT SCALE = 100.0000 / in.	CHECKED - RP/MG	REVISED -
	PLOT DATE = 1/23/2025	DATE - 1/24/2025	REVISED -


SCALE: 1" = 50'

SHEET

IL ROUTE 53 TEMPORARY AND REMOVAL LIGHTING PLAN					F.A.P. RTE	RTE. SECTION			COUNTY	SHEETS	S	
					342	2018-	00-BR		СООК	1351		
	TEMPORARI AND REMOVAL EIGHTING FLAN									CONTRAC	T NO. 6	2١
	SHEET	OF	SHEETS	STA.	TO STA.			ILLINOIS	FED. A	ID PROJECT		







### **REMOVAL LEGEND:**

EXISTING LIGHT POLE, MAST ARM, LUMINAIRE, AND FOUNDATION TO BE REMOVED. REMOVAL AND REPLACEMENT OF MEDIAN MOUNTED LIGHTING UNITS SHALL BE DONE IN ACCORDANCE WITH THE MAINTENANCE OF TRAFFIC PLANS. LIGHTING UNIT SHALL REMAIN OPERATIONAL UNTIL TEMPORARY LIGHTING SYSTEM IS INSTALLED AND OPERATIONAL

SCALE:1" = 50"

#### **TEMPORARY LEGEND:**

A AERIAL CABLE, 4-1/C NO. 2 WITH MESSENGER WIRE

#### **NOTES:**

- EXISTING CIRCUITS SHALL REMAIN UNTIL THE TEMPORARY LIGHTING SYSTEM IS INSTALLED AND OPERATIONAL.
- 2. AERIAL CABLES SHALL BE INSTALLED TO PROVIDE A MINIMUM OF 18-FEET CLEARANCE BETWEEN THE SURFACE OF THE ROADWAY AND THE CABLE
- 3. ROD & CLEAN CONDUIT AFTER REMOVAL OF CABLE IN CONDUIT.

SINGH - ASSOCIATES, INC. CONSULTING PAGINFERS

USER NAME = vnunez	DESIGNED - VG	REVISED -	
	DRAWN - AP/MAG	REVISED -	
PLOT SCALE = 100.0000 / in.	CHECKED - RP/MG	REVISED -	
PLOT DATE = 1/23/2025	DATE - 1/24/2025	REVISED -	

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION


	IL	F.A.P. SECTION							
EMPORARY AND REMOVAL LIGHTING PLAN					342		2018-1	00-BR	
LIVII OIL	INIT ORAINT AND INLINIOVAL LIGITITING FLAN								
HEET	OF	SHEETS	STA	TO STA.				TUTMOIS	EED AI


LT-08


COOK 1351 584

CONTRACT NO. 62N91

D PROJECT







### **TEMPORARY LEGEND:**

- A AERIAL CABLE, 4-1/C NO. 2 WITH MESSENGER WIRE
- K UNIT DUCT, 600V, 4-1/C NO. 2, 1/C NO. 4 GROUND IN 1 1/2" DIA.

SCALE: 1'=50"

#### NOTES:

- EXISTING CIRCUITS SHALL REMAIN UNTIL THE TEMPORARY LIGHTING SYSTEM IS INSTALLED AND OPERATIONAL.
- 2. ROD & CLEAN CONDUIT AFTER REMOVAL OF CABLE IN CONDUIT.

SINGH ASSOCIATES, INC.

USER NAME = vnunez	DESIGNED - VG	REVISED -	
	DRAWN - AP/MAG	REVISED -	
PLOT SCALE = 100.0000 / in.	CHECKED - RP/MG	REVISED -	
PLOT DATE = 1/23/2025	DATE - 1/24/2025	REVISED -	

STATE OF ILLINOIS	
DEPARTMENT OF TRANSPORTATION	


IL ROUTE 53						F.A. P. RTE	SEC.	LION		
TEMP∩R	TEMPORARY AND REMOVAL LIGHTING PLAN					342	2018-	00-BR		
ILIVII OIL	AITI AITD	ILLIVIOVA	LLIGITIIN	IG I LAN						_
SHEET	OF	SHEETS	STA	T	O STA.			TELIMOIS	EED AL	D D


 LT—09


 COUNTY
 TOTAL SHEETS NO.

 COOK
 1351
 585

 CONTRACT NO.
 62N91








S	N	G	H
		SSOCIA	

USER NAME = vnunez	DESIGNED - VG	REVISED -
	DRAWN - AP/MAG	REVISED -
PLOT SCALE = 100.0000 / in.	CHECKED - RP/MG	REVISED -
PLOT DATE = 1/23/2025	DATE - 1/24/2025	REVISED -

STATE OF ILLINOIS	
DEPARTMENT OF TRANSPORTATION	

**SCALE:** 1' = 50" SHEET

				LT-1	10
IL ROUTE 53	F.A.P. RTE	SECTION	COUNTY	TOTAL SHE	EET O.
TEMPORARY AND REMOVAL LIGHTING PLAN	342	2018-100-BR	соок	1351 58	86
TEIMI ONANT AND NEMOVAL EIGITING I EAN			CONTRAC	TNO. 62N9	1
SHEET OF SHEETS STA. TO STA.		ILLINOIS FED.	AID PROJECT		



DESIGNED - VG REVISED DRAWN - AP/MAG REVISED PLOT SCALE = 100.0000 / in CHECKED - RP/MG REVISED PLOT DATE = 1/23/2025


STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION


IL ROUTE 53 TEMPORARY AND REMOVAL LIGHTING PLAN SCALE: 1" = 50' SHEET OF SHEETS STA. 1364+00.00 TO STA. 1378+50.00


LT-11 COUNTY TOTAL SHEET NO.

COOK 1351 587

CONTRACT NO. 62N91 SECTION 2018-100-BR







STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION

IL ROUTE 53 TEMPORARY AND REMOVAL LIGHTING PLAN SCALE: 1" = 50' SHEET OF SHEETS STA. 1378+50.00 TO STA. 1391+50.00

COUNTY TOTAL SHEET NO.

COOK 1351 588

CONTRACT NO. 62N91 SECTION 2018-100-BR

LT-12

PLOT SCALE = 100.0000 / in

PLOT DATE = 1/23/2025

DESIGNED - VG


DRAWN - AP/MAG


CHECKED - RP/MG


REVISED

REVISED

REVISED







## NOTES:

1. ROD & CLEAN CONDUIT AFTER REMOVAL OF CABLE IN CONDUIT.

S	N	G	H
		SSOCIA'	

USER NAME = vnunez	DESIGNED - VG	REVISED -
	DRAWN - AP/MAG	REVISED -
PLOT SCALE = 100.0000 / in.	CHECKED - RP/MG	REVISED -
PLOT DATE = 1/23/2025	DATE - 1/24/2025	REVISED -


STATE OF ILLINOIS	
DEPARTMENT OF TRANSPORTATION	


							F.A.P. SECTION				COUN	
TEMPORARY AND REMOVAL LIGHTING PLAN						342	2018-	100-BR		COOK		
TEMPORATI AND REMOVAL EIGHTING PLAN											CONTR	
	SHEET	OF	SHEETS	STA.	1391+50.00	TO STA.	1406+50.00			ILLINOIS	FED. A	D PROJECT


LT-13


SCALE: 1" = 50'

OK 1351 **589** TRACT NO. 62N91









0 50 100 150

SCALE IN FEET

LT-17


i	(	:	N	11		L
NAME OF	3	i	IN	I	J	
4		-	JGH+	•	CIAT	ES.IN


USER NAME = vnunez	DESIGNED - VG	REVISED -
	DRAWN - AP/MAG	REVISED -
PLOT SCALE = 100.0000 / in.	CHECKED - RP/MG	REVISED -
PLOT DATE = 1/23/2025	DATE - 1/24/2025	REVISED -


STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

SCALE:

				LI-I	
IL ROUTE 53	F.A.P. RTE	SECTION	COUNTY	TOTAL SHEE SHEETS NO	
TEMPORARY AND REMOVAL LIGHTING PLAN	342	2018-100-BR	соок	1351 593	
TENNI CHANT AND HEMOVAL EIGHTING TEAN			CONTRAC	TNO. 62N91	П
SHEET OF SHEETS STA. TO STA.		ILLINOIS FEE	. AID PROJECT		$\exists$










- 1/24/2025

OF SHEETS STA.








S	N	G	H
		SSOCIA	


USER NAME = vnunez	DESIGNED - VG	REVISED -
	DRAWN - AP/MAG	REVISED -
PLOT SCALE = 100.0000 / in.	CHECKED - RP/MG	REVISED -
PLOT DATE = 1/23/2025	DATE - 1/24/2025	REVISED -


STATE OF ILLINOIS	
DEPARTMENT OF TRANSPORTATION	

											LT	Γ–21
I			IL	ROUTE 5	3		F.A.P. RTE	SECTION	ı	COUNTY	TOTAL SHEETS	SHEET NO.
l	T	EMPORAR	/ AND	REMOVA	L LIGHTING	PLAN	342	2018-100-E	BR	COOK	1351	597
Ì	SCALE: 1" - 50'	SHEET	OF	SHEETS	STA.	TO STA.		ILLIN	NOIS FED. AI	CONTRACT D PROJECT	I NO. 62	21191

TILE INSIDE








SCALE:1" - 50'


SING


USER NAME = vnunez	DESIGNED - VG	REVISED -
	DRAWN - AP/MAG	REVISED -
PLOT SCALE = 100.0000 / in.	CHECKED - RP/MG	REVISED -
PLOT DATE = 1/23/2025	DATE - 1/24/2025	REVISED -

STATE OF ILLINOIS	
DEPARTMENT OF TRANSPORTATION	

										Lī	-22
	IL ROUTE 53				F.A.P. RTE	SECTION		COUNTY	TOTAL SHEETS	SHEET NO.	
TEMPORARY AND REMOVAL LIGHTING PLAN				342	2018-100-BR	соок	1351	598			
	TEINI OIDAN AND HEMOVAE EN								CONTRACT	FNO. 63	2N91
	SHEET	OF	SHEETS	STA.	TO STA.		ILLINOIS FED. AID P				
							-				







S		N	G	H
	SI	NGH+A	SSOCIAT	
	$\alpha$	XNSULTI	NG ENG	INEERS

USER NAME = vnunez	DESIGNED - VG	REVISED -
	DRAWN - AP/MAG	REVISED -
PLOT SCALE = 100.0000 / in.	CHECKED - RP/MG	REVISED -
PLOT DATE = 1/23/2025	DATE - 1/24/2025	REVISED -

STATE OF ILLINOIS	
DEPARTMENT OF TRANSPORTATION	

IL ROUTE 53						F.A.P. RTE				COUNTY		
	TEMPORARY AND REMOVAL LIGHTING PLAN						342	342 2018-100-BR			соок	П
TENTONANT AND REMOVAL EIGHTING FEAR										CONTRACT	N	
	SCALE: 1" - 50'	SHEET	OF	SHEETS	STA.	TO STA.			ILLINOIS	FED. A	ID PROJECT	

LT-23

| TOTAL | SHEET | NO. | 1351 | 599 | T NO. | 62N91 |

