

PROTECTIVE SHIELD, SPECIAL DETAIL

APPLIES TO RIDGELAND AVENUE ONLY

- L 3X3X1/2" BOLTED TO EXISTING STEEL FRAMING WITH 3/4" DIA. H.S. BOLTS AT 12" O.C. BOLTED TO FASCIA FRAME. *PAINTED STEEL FRAME WITH LASER-CUT PATTERN AND TRANSLUCENT POLYCARBONATE SHEET FASTENED WITH SLEEVED FASTENERS. -3/4" DIA. H.S. BOLTS AT EACH END OF FASCIA FRAME. LOCATE BOLTS AT A MINIMUM SPACING TO ENSURE THAT HEX-NUT IS FLUSH WITH FASCIA FRAME ---*L3x2x1/4" ANGLE (LLH) WITH 7/8" Ø PRE-DRILLED HOLES AT 3" CTS. *LED LIGHTING - ILLUMILINE— 36 IP OPTIC 30 RGB MOTTOR GNA POTTOM 3/16 *1 1/2" CONDUIT W/ ELCBL C COMM 16 1 PR T/STL.-**FASCIA FRAME *1/4"X6" PERFORATED 中一 * DENOTES ALL WORK SHALL BE INCLUDED IN THE UNIT PRICE FOR GATEWAY MONUMENT SIGN COMPLETE AND WILL NOT BE MEASURED SEPARATELY FOR PAYMENT. ** EXISTING FASCIA FRAME WAS OBSERVED TO BE DAMAGED.
CONTRACTOR MAY LOCATE BOLTS ALONG LENGTH OF THE ANGLE TO ENSURE THAT HEX-NUTS ARE FLUSH WITH THE FASCIA FRAME. MINIMUM SPACING OF BOLTS IS 3".

GATEWAY MONUMENT SIGN COMPLETE DETAIL

APPLIES TO RIDGELAND AVENUE ONLY

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION