Station 7	lype	No. Panels				Interio	r lloit				I		1				-		
- and the second	Туре			Danal I	Interior Unit			Upper & Lower Chord		Verticals; Horizontals; Vertical, Horizontal, and Interior Diagonals		Camber at	-phong hange						
372+50			Lgth.(Le)			No. Panels per Unit		Panel Lath.(P)	1	Wall	0.D.	Wall	Midspan	Bolt. No./Splice		Weld W	Sizes W1	А	В
	II-A	5	the second s	5'- 3.5"		6		5'-3.5"		5/16"	3"	5/16"	2.4"	6	1"	3/8"		9 1/4"	12 1
388+90	II-A	7	39'-11.25	'5'-5.25'	1	6	33'-10.5"	5'-5.25	7"	. 5/16"	3"	5/16"	3.75"	6		3/8"	1/4"	11.5"	15'
·····											•	· · · · ·							
									· · ·		· · · ·								l
·····				· ·									<u> </u>		··· · · ···		·		
										· · ·	1		l			·			
													l .	, ,		· · ·			
		· · ·							}								ļ]		
							Image: sector	Image: sector	Image: series of the series	Image: state	Image: Section of the section of t	Image: Section of the section of t	Image: Section of the section of t	Image: Section of the section of t	Image: Section of the section of t	Image: Series of the series	Image: Series of the series	Image: Series of the series	Image: Serie Seri



(1) Splicing Flanges shall be attached to each truss unit with the truss shop assembled to camber shown. Truss units shall be in proper alignment and flange surfaces shall be shop bolted into full contact before welding. Sufficient external welds or tacks shall be made to secure flanges until remaining welds are made after disassembly. Adjacent flanges shall be "match marked" to insure proper field assembly.

AC4 4 0



Upper Chord

.c to c of support frame Camber required See table.

CAMBER DIAGRAM Camber curve shown is theoretical. Actual camber attained by slope changes at splices between units.





Camber shown is for fabrication only, measured with truss fully supported. (No-load condition)

US4-A-2	1-20-11					,			
FILE NAME =	USER NAME =	DESIGNED -	REVISED		OVERHEAD SIGN STRUCTURES - ALUMINUM TRUSS DETAILS	RTE- SECTION COUNTY TOTAL SHEET NO.			
	,	CHECKED	REVISED -	STATE OF ILLINOIS		Verious D-9 OVD SIN STR REPL 12-12 Various 17 7			
	PLOT SCALE =	ORAWN	REVISED	DEPARTMENT OF TRANSPORTATION	FOR TRUSS TYPES I-A, II-A AND III-A	CONTRACT NO. 46185			
	PLOT DATE .	CHECKED -	REVISED	·····		ILLINOIS FED. AID PROJECT			



Splicing Flange-



TRUSS TYPES I-A, II-A, & III-A



TRUSS TYPES II-A & III-A SPLICING FLANGES

ASTM B221, Alloy 6061-T6 or ASTM B209, Alloy 6061-T651 *To fit O.D. of Chord with maximum gap of 16".