

NOTES

Detail I - With Bar Splicer or Couplers: Connect one (1) 1" x 7" 'x "W" steel f_c to the top layer of couplers with 2- $\frac{5}{8}$ " ϕ bolts screwed to coupler at approximate € of each barrier panel.


Detail II - With Extended Reinforcement Bars: Connect one (1) 1" \times 7" \times "W" steel $\mathbb P$ to the concrete slab or concrete wearing surface with $2^{-5}8$ " ϕ Expansion Anchors or cast in place inserts spaced between the top layer of reinforcement at approximate & of each barrier panel.


Cost of anchorage is included with Temporary Concrete Barrier. The 1" x 7" x "W" plate shall not be removed until stage II construction forms and all reinforcement bars are in place and the concrete is ready to be placed.


SECTIONS THRU SLAB OR DECK BEAM

*** Dimension shown is minimum required embedment into concrete. If hot-mix asphalt wearing surface is present, minimum embedment shall be in addition to wearing surface depth.

**** If existing deck beam is to remain in place after stage construction, embedment shall only be into wearing surface and not into existing deck beam concrete.







STEEL RETAINER P 1" x 7" x "W"

* Required only with Detail II

** Wood blocks may be omitted when required to provide minimum stage traffic lane width. When the wood blocks are omitted, the concrete barrier shall be in direct contact with the steel retainer plate.

"W" = Top bars spacing + 4"

R-27

7-1-10 DESIGNED - JSG USER NAME = REVISED -#Primera PLOT SCALE : CHECKED - LRG REVISED -DRAWN - MPS REVISED -

CHECKED - JXH

REVISED

STATE OF ILLINOIS

TEMPORARY CONCRETE BARRIER STRUCTURE No. 049-0197 STA. 45 + 00.00 SHEET NO. SB7 OF SB10 SHEETS

DATE:	DATE: 09-14-2011			ILLINOIS FED. AID PROJECT				
					CONTRACT	NO. (62187	
335		145	X-T		LAKE	80	41	
F.A.P. RTE.		SEC	TION		COUNTY	TOTAL SHEETS	SHEET NO.	

DEPARTMENT OF TRANSPORTATION