

GENERAL NOTES

14 (356) min. for

7 (178) opening

Frame and grate (See General Notes)

12(300)

bars

(150)

8 (200)

min. 🖷

- 1. Inlet construction shall be in accordance with Section 602 of the Standard Specifications.
- Combination Concrete Curb & Gutter shall be constructed in accordance with Section 606 of the Standard Specifications.

Set frame level and at elevation

Grate type- 12 (300)

Pavement

- #4 (#15) bars

sand cushion

-6 (150)

thickness

see plans

3/4 (20) Mortar

30 (750)

ELEVATION SIDE

of edge of pavement at the intersection of ¢ of inlet frame.

3. See District CADD Standard 604001-D4 for frame and grates.

All dimensions are in inches (millimeters) unless otherwise noted.

0	1-01-97 RENUM, B-4.01, NEW REVISION BOX	T.P.		STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	INLETS, TYPE G-1			F.A.P RTE.	SECTION	COUNTY	TOTAL SHEET SHEETS NO.
	10-99 REVISION TO GENERAL NOTES	J.A.						399	36 R-7	TAZEWELL	390 294
	02-00 REVISION TO DESIGNER NOTES	J.A.								CONTRACT	NO. 68370
10	0-16-06 REVISED TO 2007 SPEC.	M.A.	_1		NOT TO SCALE		CADD STD. 602001-D4	FED. ROAD DIST.	NO. ILLINOIS FE	D. AID PROJECT	

5.4.4.5.