



				IEUULE.	LIGHTING FIXTURE SC		
	REMARKS	DUNTING	olts	LAMPS/ WATTS	MANUFACTURER & CATALOG NO.	DESCRIPTION	fixt. Type
WET LOCATION NSTALLED IN TOF RE.		irface to hard Illing		2-32W T8 HOOK 19 TOTAL NPUT WATTS	DMW-2-32-AR-120- CW-GEB10RS-WLF	4 FT. WET LOCATION LISTED ENCLOSED AND GASKETED INDUSTRIAL, FLUORESCENT LIGHT FIXTURE, IMPACT RESISTANT, UV RESISTANT REINFORCED POLYESTER FIBERGLASS HOUSING, HIGH IMPACT ACRYLIC DIFFUSER, RAPID START COLD WEATHER O DEG. F. ELECTRONIC BALLAST WITH LESS THAN OR EQUAL TO 10% THD.	
NET LOCATION NSTALLED IN TOF IE.		irface to hard Ilung		:-32W T8 :100K :9 Total :Put Watts	DMW-2-32-AR-120- CW-GEB10RS-WLF	SAME AS F1 EXCEPT PROVIDE AN EMERGENCY BALLAST CAPABLE OF OPERATING 2 LAMPS FOR 90 MINUTES AT 1100-1400 TOTAL LUMENS, BODINE #550ST. NOTE BALLAST WILL HAVE TO BE REMOTE MOUNTED NEAR FIXTURE AS INDICATED ON THE PLANS.	F1A
TO WALL SWITCH ON THE INSIDE C ING.		OVE EXTERIOR	/ C /	-42W TRT 1 100K 7 Total PUT Watts	TWA-42TRT-120-SF- CR-DMB-LPI	COMPACT FLUORESCENT WALL-PAK, ONE PIECE INJECTION MOLDED UV STABILIZED POLYCARBONATE HOUSING, HICH PERFORMANCE SPECULAR ANODIZED SEGMENTED REFLECTOR, ONE PIECE HICH TEMPURATURE SILICONE GASKET, MEDIUM BRONZE FINISH, HIGH POWERFACTOR ELECTRONIC BALLAST WITH LESS THAN OR EQUAL TO 10% THD, UL LISTED FOR WET LOCATIONS, FUSED.	- 2
		OUUK FRAME.				WITH LESS THAN OR EQUAL TO 10% THD, UL	

NOTE 15 AMP & 20 AMP BRANCH CIRCUITS FOR LIGHTING & RECEPTACLES SHALL USE #12 AWG THWN (MIN.).

METROPOLIS MUNICIPAL AIRPORT
METROPOLIS, ILLINOIS

-	Slename	EL-101.DWG	,
Z	Scole	$1/2^*=1^*-0$	
	Date	12/02/05	
	LAYOUT	KNE	11/17/05
	DRAWN	۸M	11/21/05
•	REVIEWED	CAH	12/16/05

Harson Professional Services Inc. 1525 South Streat Springfield, Illinois 6270-2696 Offices Nationwice

CONSTRUCT
NEW VAULT
PROPOSED VAULT LIGHTING
AND RECEPTACLE PLAN

10