


NOTES


- TRENCHES WITH MORE THAN 2 CABLES SHALL BE INCREASED 3" IN WIDTH FOR EACH ADDITIONAL CABLE. IF SPECIFIED ON PLANS, TWO PARALLEL
- DEPTH OF TRENCHES SHALL BE AS SHOWN ABOVE UNLESS OTHERWISE SPECIFIED ON THE PLANS.
- 3. SAND BACKFILL SHALL BE USED IF THE EXISTING SOIL DOES NOT MEET THE BACKFILL REQUIREMENTS.
- 4. ALL DISTURBED SURFACES SHALL BE RESTORED TO THEIR ORIGINAL CONDITION, COST IS INCIDENTAL TO

NOTE: AT CONTRACTOR'S OPTION, CABLE PLOWING MAY BE USED IN LIEU OF TRENCHING



CABLE IN UNIT-DUCT - PLOWED

N.T.S.



HEAT SHRINKABLE TUBING WITH HEAT SHRINKABLE TUBING WITH HEAT SHRINKABLE TUBING WITH INTERNAL ADHESIVE, PER SPECS. INTERNAL ADHESIVE, PER SPECS. INTERNAL ADHESIVE, PER SPECS. FACTORY MOLDED L-823 ADDITIONAL ADHESIVE TRANSFORMER LEADS SHRINKING (TYP.) COMPOUND FILLER ADDITIONAL ADHESIVE ADDITIONAL ADHESIVE RECEPTACLE END - PLUG END COMPOUND FILLER COMPOUND FILLER ∠UNDERGROUND CABLE SPEC. L-824, TYP. PLUG END FIELD INSTALLED L-823 RECEPTACLE END FOR SPLICES AT TAXIWAY LIGHTS AND SIGNS.

NOT TO BE USED IN THIS PROJECT UNLESS OTHERWISE DIRECTED BY ENGINEER


TYPE B

CABLE SPLICES N.T.S.

TYPE D

NOTES


- INSIDE DIAMETER OF CONNECTOR SHALL PROPERLY MATCH THE OUTSIDE DIAMETER OF CABLE.
- 2. THE COST OF FURNISHING AND INSTALLING ALL SPLICE MATERIALS SHALL BE INCIDENTAL TO THE ASSOCIATED CABLE
- 3. THE CONTRACTOR SHALL HAVE A MINIMUM OF TWO (2) TYPE A SPLICE KITS ON THE JOB SITE AT ALL TIMES FOR EMERGENCY REPAIRS.



TURF CABLE / SPLICE MARKER

NOTES

- CABLE MARKERS SHALL BE INSTALLED AT ALL BENDS AND EVERY 200' ALONG THE HOMERUN.
- 2. ITEM 610 CONCRETE SHALL BE USED.
- 3. ALL EXPOSED EDGES SHALL BE EDGED WITH A 14" RADIUS
- 4. THE COST OF FURNISHING AND INSTALLING NEW MARKERS SHALL BE INCIDENTAL TO THE ASSOCIATED ITEMS.
- 5. 0.049 CU. YD. CONCRETE PER MARKER.
- A MARKER CONFORMING TO THIS DETAIL MARKED "SPLICE" SHALL BE INSTALLED AT ALL SPLICE LOCATIONS NOT IN LIGHT CANS OR MANHOLES.



:\DanvilleAp\0504203\Drow\Sheets\

FILE: 19_ELECDETL4.dwg

LAYOUT: ELECDETL4

VE044