03-10-2023 LETTING ITEM 053

INDEX OF SHEETS

COVER SHEET

GENERAL NOTES
SUMMARY OF QUANTITIES
SCHEDULE OF QUANTITIES
EXISTING TYPICAL SECTION

STAGING TYPICAL SECTIONS LINE DIAGRAM

STAGE II PLAN

PRESTAGE PLAN STAGEIPLAN

0

0

0

HIGHWAY STANDARDS

BRIDGE REPAIR PLANS

000001-08 STANDARD SYMBOLS, ABBREVIATIONS AND PATTERNS

001001-02 AREAS OF REINFORCEMENT BARS 001006 DECIMAL OF AN INCH AND OF A FOOT

701321-18 LANE CLOSURE, 2L, 2W, BRIDGE REPAIR WITH BARRIER
701326-04 LANE CLOSURE, 2L, 2W, PAVEMENT WIDENING FOR SPEEDS GREATER THAN OR
EQUAL TO 45 MPH
701901-08 TRAFFIC CONTROL DEVICES


704001-08 TEMPORARY CONCRETE BARRIER 780001-05 TYPICAL PAVEMENT MARKINGS

782006-01 GUARDRAIL AND BARRIER WALL REFLECTOR MOUNTING DETAILS

DISTRICT STANDARDS

780001-D4 TYPICAL PAVEMENT MARKINGS

FUNCTIONAL CLASSIFICATION MINOR ARTERIAL 2019 ADT: 3250 PV: 88.5% SU + MU: 11.5%



FULL SIZE PLANS HAVE BEEN PREPARED USING STANDARD ENGINEERING SCALES. REDUCED SIZED PLANS WILL NOT CONFORM TO STANDARD SCALES. IN MAKING MEASUREMENTS ON REDUCED PLANS, THE ABOVE SCALES MAY BE USED.

JOINT UTILITY LOCATION INFORMATION FOR EXCAVATION 1-800-892-0123

OR 811

PROJECT ENGINEER: BEN TELLEFSON (309) 671-4477 PROJECT MANAGER: MARK ECKHOFF (309) 671-4463

SN 090-0063 IL 9 OVER

STA. 709+40.81

CONTRACT NO. 68H16 CATALOG NO. 036331-00D




STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION

PROPOSED HIGHWAY PLANS

FAP ROUTE 693 (IL ROUTE 9) SECTION 119B(BR)BJR,P PROJECT STATE 0-02177-40147 BRIDGE JOINT REPLACEMENT/REPAIR **TAZEWELL COUNTY**

C-94-054-22



GROSS LENGTH = 501 FT. = 0.094 MILE NET LENGTH = 737.5 FT. = 0.134 MILE

SECTION (1198)BR TAZEWELL 17 1

D-94-037-22



DESCRIPTION OF PROJECT:

THIS PROJECT CONSISTS OF AGGREGATE SHOULDER REPLACEMENT WITH HOT-MIX ASPHALT SHOULDERS, BRIDGE JOINT, DECK DRAIN CLEANING AND SEALING, AND DECK PATCHING AT SN 090-0063 CARRYING IL ROUTE 9 OVER THE MACKINAW RIVER.



PRINTED BY THE AUTHORITY OF THE STATE OF ILLINOIS

REV. 1/9/23

GENERAL NOTES

- THE CONSTRUCTION SHALL BE GOVERNED BY THE "STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION"
 2022 EDITION AND "SUPPLEMENTAL SPECIFICATIONS AND RECURRING SPECIAL PROVISIONS", CURRENT EDITION.
- 2. ALL ELEVATIONS, STATIONS AND OFFSETS SHOWN ON THE PLANS SHALL BE FIELD VERIFIED BY THE CONTRACTOR PRIOR TO CONSTRUCTION.
- 3. ALL ELEVATIONS SHOWN ON THE PLANS ARE ESTABLISHED FROM U.S.G.S. MEAN SEA LEVEL DATUM.
- 4. TEN FEET (10 FT.) TRANSITIONS SHALL BE USED TO MATCH PROPOSED ITEMS OF WORK TO EXISTING ITEMS IN THE FIELD UNLESS OTHERWISE SHOWN. THE TRANSITION SHALL BE PAID FOR AT THE CONTRACT UNIT PRICE FOR THE PROPOSED ITEM OF WORK SPECIFIED.
- 5. POLYMERIZED BITUMINOUS MATERIALS (TACK COAT) RATES

SURFACE TYPE	RESIDUAL RATE
MILLED (HMA OR PCC)	0.08 LB/SF
EXISTING PAVEMENT	0.08 LB/SF
FOG COAT (BETWEEN LIFTS)	0.08 LB/SF

6. HOT-MIX ASPHALT MIXTURE REQUIREMENTS

LOCATIONS:	SHOULDERS
MIXTURE USES:	HMA BINDER COURSE 8"
PG:	PG 64-22 OR PG 70-22
DESIGN AIR VOIDS:	4% @ N50
MIXTURE COMPOSITION:	IL-9.5
FRICTION AGGREGATE:	N.A.
QUALITY MANAGEMENT:	QC/QA

NOTES:

- 1) INDIVIDIAL LIFT THICKNESSES OF EACH MIX WILL BE NO LESS THAN (3) TIMES NOMINAL MAXIMUM AGGREGATE SIZE AND NO MORE THAN FIVE (§) TIMES NOMINAL AGGREGATE MAXIMUM SIZE, UNLESS OTHERWISE APPROVED BY THE ENGINEER.
- FOR DESIGN PURPOSES, MIXTURE WEIGHT FOR ALL MIXES IS DETERMINED TO BE 112.0 lb./s.y./in., UNLESS OTHERWISE NOTED.
- 3) SUBLOT SIZES FOR PFP AND QCP MIXES WILL BE 1,000 TONS, UNLET OTHERWISE AGREED TO BY THE ENGINEER AND THE PAVING CONTRACTOR

7. ENVIRONMENTAL REVIEWS

PRIOR TO THE USE OF ANY PROPOSED BORROW AREAS, USE AREAS (TEMPORARY ACCESS ROADS, DETOURS, RUN-AROUNDS, ETC.) AND/OR WASTE AREAS, THE CONTRACTOR SHALL FILE THE REQUIRED ENVIRONMENTAL RESOURCE REQUEST SURVEYS ACCORDING TO SECTION 107.22 OF THE STANDARD SPECIFICATIONS. THESE SURVEYS ARE REQUIRED IN ORDER FOR THE DEPARTMENT TO CONDUCT CULTURAL AND BIOLOGICAL RESOURCE SURVEYS FOR THE PROPOSED SITE.

THE REQUIRED ENVIRONMENTAL RESOURCE DOCUMENTATION SHALL INCLUDE THE FOLLOWING:

BDE FORM 2289 (BORROW SITE REVIEW)
BDE FORM 2290 (WASTE/USE AREA REVIEW)
A LOCATION MAP SHOWING THE SIZE LIMITS AND LOCATION OF THE USE AREA
COLOR PHOTOGRAPHS DEPICTING THE USE AREA
BORROW AREA ENTRY AGREEMENT FORM D4 P10101

PRIOR TO ANY WASTE MATERIALS BEING REMOVED FROM THE CONSTRUCTION SITE THE REQUIRED ENVIRONMENTAL RESOURCE SURVEYS SHALL BE OBTAINED AND FILED BY THE CONTRACTOR. EXCESS WASTE PRODUCTS REMOVED FROM THE CONSTRUCTION SITE SHALL BE DISPOSED OF AS REQUIRED IN SECTION 202.03 OF THE STANDARD SPECIFICATIONS.

ANY PROTRUDING METAL BARS SHALL BE REMOVED PRIOR TO THE DISPOSAL OF BROKEN CONCRETE AT APPROVED DISPOSAL SITES.

PLEASE NOTE THAT A MINIMUM OF FOUR WEEKS SHALL BE ALLOWED FOR THE DISTRICT TO OBTAIN THE REQUIRED WASTE SITE ENVIRONMENTAL CLEARANCES AND SIX WEEKS FOR THE REQUIRED BORROW SITE ENVIRONMENTAL CLEARANCES.

8. PROPERTY OWNER ACCESS REQUIREMENT

ACCESS MUST BE MAINTAINED TO ALL EXISTING PROPERTIES DURING THE CONSTRUCTION PER ARTICLE 107.09 UNLESS ARRANGEMENTS ARE MADE IN WRITING BY THE CONTRACTOR WITH THE PROPERTY OWNERS WITH A COPY TO THE ENGINEER FOR SHORT-TERM CLOSURES.

COMMITMENTS

COMMITMENTS ARE NOT TO BE ALTERED WITHOUT THE WRITTEN APPROVAL OF ALL PARTIES TO WHICH THE COMMITMENT WAS MADE.

NO COMMITMENTS HAVE BEEN MADE FOR THIS PROJECT.

TERRA ENGINEERING LTD.

_			
	USER NAME = brennar	DESIGNED .	REVISED _
		DRAWN - CM	REVISED -
	PLOT SCALE = 2.000 ' / in.	CHECKED - BKR	REVISED -
•	PLOT DATE = 10/21/2022	DATE -	REVISED .

SCALE:

		GE	NEP	RAL NO	TES		F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
							693	(119B)BR	TAZEWELL	17	2
									CONTRACT	NO. E	8H16
SHEET	1	OF	1	SHEETS	STA.	TO STA.		ILUNOIS FED ALL) PROJECT		

				CONSTR. CODE
				100% STATE
			TOTAL	BRIDGE
ITEM NO.	DESCRIPTION	UNIT	QUANTITY	47
				090-0063
20200500	EARTH EXCAVATION (WIDENING)	CU YD	111	111
40600290	BITUMINOUS MATERIALS (TACK COAT)	POUND	999	999
440000400	DAVENATALT DENAOVAL	SOVE	207	207
44000100	PAVEMENT REMOVAL	SQ YD	207	207
48203029	HOT MIX ASPHALT SHOULDERS, 8"	SQ YD	722	722
50102400	CONCRETE REMOVAL	CU YD	8.6	8.6
50300255	CONCRETE SUPERSTRUCTURE	CU YD	8.6	8.6
50300300	PROTECTIVE COAT	SQ YD	26	26
50800205	REINFORCEMENT BARS, EPOXY COATED	POUND	1200	1200
50800515	BAR SPLICERS	EACH	12	12
52000110	PREFORMED JOINT STRIP SEAL	FOOT	90	90
67100100	MOBILIZATION	L SUM	1	1
70100405	TRAFFIC CONTROL AND PROTECTION, STANDARD 701321	EACH	1	1
70100500	TRAFFIC CONTROL AND PROTECTION, STANDARD 701326	L SUM	1	1
70400500	TENANCORA DV. DDID CE. TDA EEIO CICAVA C			
70106500	TEMPORARY BRIDGE TRAFFIC SIGNALS	EACH	1	1



USER NAME = brennar	DESIGNED .	REVISED _
	DRAWN - CM/KF	REVISED -
PLOT SCALE = 2.000 ' / in.	CHECKED - BKR	REVISED -
PLOT DATE = 10/21/2022	DATE _	REVISED _

STATE (DF ILLINOIS
DEPARTMENT O	F TRANSPORTATION

SCALE.

SUMMARY OF QUANTITIES						F.A.P.	SEC	TION		COUNTY	TOTAL	SHEET			
	COMMAN OF COARTITIES						693	(119	B)BR		TAZEWELL	17	3		
													CONTRACT	NO 6	8H16
	SHEET	1	OF	2	SHEETS	STA	TO STA				ILLINOIS	FED. Al	D PROJECT		

				100% STATE
			TOTAL	BRIDGE
ITEM NO.	DESCRIPTION	UNIT QUANTITY EACH 6 CAL DA 28 FOOT 762.5 FOOT 762.5 EACH 2 EACH 2 FOOT 6096 SQ FT 2032 SQ YD 53	47	
				090-0063
70106700	TEMPORARY RUMBLE STRIPS	EACH	6	6
70107025	CHANGEABLE MESSAGE SIGN	CAL DA	28	28
70400100	TEMPORARY CONCRETE BARRIER	FOOT	762.5	762.5
70400200	RELOCATE TEMPORARY CONCRETE BARRIER	FOOT	762.5	762.5
70600250	IMPACT ATTENUATORS, TEMPORARY (NON-REDIRECTIVE), TEST LEVEL 3	EACH	2	2
70600350	IMPACT ATTENUATORS, RELOCATE (NON-REDIRECTIVE), TEST LEVEL 3	EACH	2	2
78001110	PAINT PAVEMENT MARKING - LINE 4"	FOOT	6096	6096
78300202	PAVEMENT MARKING REMOVAL - WATER BLASTING	SQ FT	2032	2032
Z0016200	DECK SLAB REPAIR (PARTIAL)	SQ YD	53	53
X0326394	FLOOR DRAINS TO BE CLEANED	EACH	134	134
*= SPECIALTY ITEM		1		



CONSTR. CODE

	PAVEMENT SCHEDULE								
	20200500	40600290	440000100	48203029	78001110	78300202			
	EARTH EXCAVATION (WIDENING)	BITUMINOUS MATERIALS (TACK COAT)	PAVEMENT REMOVAL	HOT-MIX ASPHALT SHOULDERS, 8"	PAINT PAVEMENT MARKING -LINE 4"	PAVEMENT MARKING REMOVAL -WATER BLASTING			
STATION TO STATION	CU YD	POUND	SQ YD	SQ YD	FOOT	SQ FT			
698+90 TO 702+84	38.7	351.3	72.2	252.8	1576.0	525.3			
702+84 TO 707+97					2052.0	684.0			
707+97 TO 714+14	71.5	646.8	133.9	468.6	2468.0	822.7			
SUBTOTAL	110.2	998.1	206.1	721.4	6096.0	2032			
TOTAL	111	999	207	722	6096	2032			

	TRAFFIC CONTROL SCHEDULE									
	67100100	70100405	70100500	70106500	70106700	70107025	70400100	70400200	70600250	70600350
		TRAFFIC CONTROL	TRAFFIC CONTROL	TEMPORARY	TEMPODARY	TEMPORARY CHANGEABLE RUMBLE STRIPS MESSAGE SIGN	TEMPORARY	RELOCATE	IMPACT ATTENUATORS,	IMPACT ATTENTUATORS,
	MOBILIZATION	AND PROTECTION,	AND PROTECTION	BRIDGE TRAFFIC	100-11-10-10-10-1		CONCRETE	TEMPORARY	TEMPORARY (NON-	RELOCATE (NON-
		STANDARD 701321	STANDARD 701326	SIGNALS	RUIVIBLE STRIPS		BARRIER	CONCRETE BARRIER	REDIRECTIVE), TEST LEVEL 3	REDIRECTIVE), TEST LEVEL 3
STATION TO STATION	L SUM	EACH	L SUM	EACH	EACH	CAL DA	FOOT	FOOT	EACH	EACH
702+90.22 TO 702+94.22				0.5	3		137.5	137.5	1	1
702+94.22 TO 707+86.85							487.5	487.5		
707+86.85 TO 707+90.85				0.5	3		137.5	137.5	1	1,
700+00.00 TO 709+00.00	1	1	1			28				
SUBTOTAL	1	1	1	1	6	28	762.5	762.5	2	2
TOTAL	1	1	1	1	6	28	762.5	762.5	2	2


: Border (ME: pw	TERRA	
MODEL FILE N	ENGINEERING LTD.	

USER NAME = brennar	DESIGNED .	REVISED _
	DRAWN . CM	REVISED -
PLOT SCALE = 2.000 / in.	CHECKED - BKR	REVISED -
PLOT DATE = 10/21/2022	DATE _	REVISED .

STATE OF ILLINOIS	
DEPARTMENT OF TRANSPORTATION	

SCALE.

SCHEDULE OF QUANTITIES								F.A.P.	SECTION	COUN	TY SHEE		SHEET NO.
								693	(119B)BR	TAZEW	ELL 17	-	5
										CONT	RACT NO	68	н16
	SHEET	1	OF	1	SHEETS	STA	TO STA		ILLINOIS	FED. AID PROJECT			



EXISTING TYPICAL SECTION STA. 699+34 TO 702+84 STA. 707+97 TO 714+14

€ IL-9 –EX. GUARDRAIL EX. GUARDRAIL 3/16 "/FT 3/16 "/FT PR. EARTH EXCAVATION (WIDENING) (20200500)
PR. PAVEMENT REMOVAL (44000100)
PR. BITUMINOUS MATERIALS (TACK COAT) (40600290)
PR. HOT-MIX ASPHALT SHOULDER, 8" (48203029) EX. AGG. SHLDR. └─ EX. SUBGRADE EX. HMA BINDER CSE - EX. HMA SURFACE EX. AGG. SHLDR. PR. EARTH EXCAVATION (WIDENING) (20200500)

— PR. PAVEMENT REMOVAL (44000100)

PR. BITUMINOUS MATERIALS (TACK COAT) (40600290)

PR. HOT-MIX ASPHALT SHOULDER, 8" (48203029)

PROPOSED TYPICAL SECTION STA. 699+34 TO 702+84 STA. 707+97 TO 714+14

NOTE: TRAFFIC CONTROL FOR HMA SHOULDER WIDENING SHALL BE IN ACCORDANCE WITH TRAFFIC CONTROL AND PROTECTION, STANDARD 701326.


FILE NAME: pw	TERRA
	ENGINEERING LTD.

USER NAME = brennar	DESIGNED .	REVISED _
	DRAWN . CM	REVISED -
PLOT SCALE = 2.000 ' / in.	CHECKED - BKR	REVISED -
PLOT DATE = 10/21/2022	DATE _	REVISED .


STATE OF ILLINOIS	
DEPARTMENT OF TRANSPORTATION	J

SCALE:

TYPICAL SECTION								F.A.P. RTE	SECTION	COU
								693	(119B)BR	TAZEV
										CON
	SHEET	1	OF	1	SHEETS	STA.	TO STA.		ILLINOIS FED. A	D PROJECT



STAGE ONE



 $\frac{\textit{CROSS SECTION}}{\textit{(Looking East)}}$


STAGE TWO

wd :	TEDDA	L
NAME	I ERRA	_
FILE	ENGINEERING LTD.	P


USER NAME = brennar	DESIGNED .	REVISED _
	DRAWN . CM	REVISED -
PLOT SCALE = 2.000 / in.	CHECKED - BKR	REVISED -
PLOT DATE = 10/21/2022	DATE _	REVISED _

STATE OF ILLINOIS	
DEPARTMENT OF TRANSPORTATI	ΟN

STAGING TYPICAL SECTIONS							F.A.P. RTE	SECTION		COUNTY	SHEE	
							693	(119B)BR		TAZEWELL	17	
											CONTRACT	NO
	SHEET	1	OF	1	SHEETS	STA.	TO STA.		ILLINOIS	FED. AIL	PROJECT	







NOT TO SCALE



USER NAME = brennar	DESIGNED .	REVISED _
	DRAWN . CM	REVISED -
PLOT SCALE = 2.000 / in.	CHECKED - BKR	REVISED -
PLOT DATE = 10/21/2022	DATE _	REVISED _

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION


				RTF	SECTION			Ш.,			
PRESTAGE							693	(119	B)BR		T
											C
SHEET	1	OF	1	SHEETS	STA	TO STA			ILLINOIS	FED. All	D PR

WORK AREA

TRAFFIC SIGNAL

STOP BAR





NOT TO SCALE



USER NAME = brennar	DESIGNED .	REVISED _
	DRAWN . CM	REVISED -
PLOT SCALE = 2.000 / in.	CHECKED - BKR	REVISED -
PLOT DATE = 10/21/2022	DATE _	REVISED _

STATE OF ILLINOIS	
DEPARTMENT OF TRANSPORTATION	


							RTF	SECTION		COUNTY
	STAGEI							(119B)BR		TAZEWELL
										CONTRACT
EET	1	OF	1	SHEETS	STA	TO STA		ILLINOIS	FED. AI	D PROJECT

WORK AREA

N

STOP BAR

TRAFFIC SIGNAL



NOT TO SCALE



USER NAME = brennar	DESIGNED .	REVISED .
	DRAWN . CM	REVISED -
PLOT SCALE = 2.000 / in.	CHECKED - BKR	REVISED -
PLOT DATE = 10/21/2022	DATE _	REVISED _

STATE OF ILLING	DIS
DEPARTMENT OF TRANS	PORTATION

STAGEII							F.A.P.	SEC	TION		COUNTY	TOTAL	SHEET
STAGE II						693	(119	B)BR		TAZEWELL	17	11	
											CONTRACT	NO 0	58H16
SHEET	1	OF	1	SHEETS	STA	TO STA			ILLINOIS	FED. Al	D PROIECT	3,000	

Existing Structure: S.N. 090-0063 was originally constructed in 1929 as SBI Rte. 164 as Section 119 B&C and repaired as Section 119CB-I, and was reconstructed as Route FA-693, Section 119B-BR at Station 705+40.38 in 1982. The existing

83'-5 3/8 "

structure consists of 6 spans. The beams are 42" PPC I-beams with a $7\frac{1}{2}$ " R.C. deck, with different skews in each span. The back to back abutment measures $490'-7\frac{1}{2}"$ and 35'-2" out to out of deck. The structure is to have the expansion joints removed and replaced, approach pavement and deck repaired, and deck drains cleaned and sealed. Traffic is to remain open with stage construction.

100000000

INDEX OF SHEETS

- 1. General Plan and Elevation
- 2. Joint Details West Abutment
- 3. Joint Details East Abutment 4. Preformed Joint Strip Seal
- 5. Bar Splicer Assembly & Mechanical Splicer Details
- 6. Floor Drains To Be Cleaned

SCOPE OF WORK


- 1. Setup Traffic Control.
- 2. Remove and replace expansion joints at abutments.
- Clean and seal deck drains.
- 4. Bridge deck repair.
- Switch stages and repeat.

TOTAL BILL OF MATERIAL

	ITEM	UNIT	QUANTITY
	Concrete Removal	Cu. Yd.	8.6
	Concrete Superstructure	Cu. Yd.	8.6
*	Protective Coat	Sq. Yd.	26
	Reinforcement Bars, Epoxy Coated	Pounds	1,200
	Bar Splicers	Each	12
	Preformed Joint Strip Seal	Foot	90
	Deck Slab Repair (Partial)	Sq. Yd.	53
	Floor Drains to be Cleaned	Each	134

*Apply to new concrete only.

83'-5 1/8 "



PLAN

490'-7 1/2 "

ELEVATION

81'-4 1/2 '

80'-8"

81'-4 1/2 "

80'-4"

Elev. 587.33

11'-0" Stage II Traffic


4'-0"

1/4" per ft.

12'-0'

© of Structure & IL-9

& Stage Construction Line



DATE SIGNED : 02/03/2023 LIC. EXP. DATE: 11/30/2024

GENERAL NOTES

All structural steel shall be AASHTO M 270 Grade 36 unless otherwise noted.

Reinforcement bars designated (E) shall be epoxy coated.

Prior to pouring the new concrete deck, all heavy or loose rust, loose mill scale, and other loose or potentially detrimental foreign material shall be removed from the surfaces in contact with concrete. Tightly adhered paint may remain unless otherwise noted. Removal shall be accomplished by methods that will not damage the steel and the cost will be included in the pay item covering removal of the existing concrete.

Plan dimensions and details relative to existing plans are subject to nominal construction variations. The Contractor shall field verify existing dimensions and details affecting new construction and make necessary approved adjustments prior to construction or ordering of materials. Such variations shall not be cause for additional compensation for a change in scope of the work, however, the Contractor will be paid for the quantity actually furnished at the unit price bid for the work.


Existing reinforcement bars extending into the removal area shall be cleaned, straightened and incorporated inoto the new construction. Any reinforcement bars that are damaged during Concrete Removal shall be replaced with an approved bar splicer or anchorage system. Cost included with Concrete Removal.

Joint openings shall be adjusted according to article 520.04 of the standard specifications when the deck is poured at an ambient temperature other than 50° Fahrenheit.

Deck slab and approach slab total repair area is an estimated quantity made at the time of plan preparation. Actual areas to be repaired shall be determined by the Engineer in the field at the time of construction and shown on the As-Built plans.

The deck surface shall have its final finish tined according to Article 420.09(e)(1) of the Standard Specifications. Cost included with Concrete Superstructure.

The Contractor shall use extreme care during Concrete Removal so as not to damage the PPC I-Beams on the Deck side and the Precast Concrete Approach Beams at the Abutment corners.



GENERAL PLAN & ELEVATION ILL 9 OVER MACKINAW RIVER IL 9 (FAP-693) - SECTION 119B-BR TAZEWELL COUNTY STATION 705+40.38 STRUCTURE NO. 090-0063

:	
	USE
IERRA	<u> </u>
ENGINEERING LT	D PLC
- ENGINEERING EN	PLO

4'-0"

11'-0" Stage I Traffic

Stage Removal Line

See Standard 704001

Temp. Conc.

Barrier, typ.

	USER NAME	=	AlexF	DESIGNED	BKR	REVISED	-
				CHECKED	KF	REVISED	-
	PLOT SCALE	=	54.167 ' / in.	DRAWN	BKR	REVISED	-
· .	PLOT DATE	=	2/3/2023	CHECKED	KF	REVISED	-

CROSS SECTION

(Looking East)

35'-2" out to out Deck

__16'-7" Stage II Removal 18'-7" Stage I Removal

1'-101/2"

5 Spaces at 5'-10" = 29'-2

_17'-7" Stage II Construction 17'-7" Stage I Construction


12'-0"


STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION

GE	NERAL PLA	N AND	ELEVATION	
	STRUCTU	RE NO.09	0-0063	
	CHEET 1	OF 6	CHEETE	

F.A.P. RTE	SEC	ПОИ		COUNTY	TOTAL SHEETS	SHEET NO.
693	(1198	B)BR		TAZEWELL	17	12
				CONTRA	CT NO.	68H16
		ILLINOIS	FED. Al	D PROJECT		

Salvage: None






DESIGNED TOTAL SHEET NO. 17 13 REVISED SECTION JOINT DETAILS - WEST ABUTMENT TERRA **STATE OF ILLINOIS** CHECKED KF REVISED -(119B)BR 693 TAZEWELL STRUCTURE NO. 090-0063 DRAWN REVISED **DEPARTMENT OF TRANSPORTATION** ENGINEERING LTD. CONTRACT NO. 68H16 PLOT DATE = 2/3/2023 OF 6 SHEETS CHECKED REVISED -

600

4.3




BILL OF MATERIAL (EAST JOINT)

Bar	No.	Size	Length	Shape
		#7	6'-6"	
a1(E)	4			
a2(E)	4	#7	22'-6"	
d(E)	12	#4	5'-1"	L
d1(E)	12	#5	3'-11"	l
h1(E)	8	#6	22'-10"	
Reinforcement Bars, Epoxy Coated		Lbs.	600	
Concrete Superstructure		Cu. Yd.	4.3	
Concr	Concrete Removal		Cu. Yd.	4.3

Removal of existing expansion joint shall be included in the cost of Concrete Removal.

In parapet/joint removal areas, existing reinforcement bars shown are to be cleaned and incorporated into new construction.



SECTION

(119B)BR


JOINT DETAILS - EAST ABUTMENT

STRUCTURE NO. 090-0063

OF 6 SHEETS

BAR d(E)

BAR d1(E)



STATE OF ILLINOIS

DEPARTMENT OF TRANSPORTATION

TERRA

ENGINEERING LTD.

LOT SCALE = 8.3334 ' / in.

DESIGNED

CHECKED

DRAWN

CHECKED

REVISED

REVISED

REVISED .


REVISED -

TOTAL SHEET NO.

CONTRACT NO. 68H16

COUNTY

TAZEWELL



Notes:

The strip seal shall be made continuous and shall have a minimum thickness of $\frac{1}{4}$ ". The configuration of the strip seal shall match the configuration of the locking edge rails. Open or "webbed" strip seal gland configurations are not permitted. The gland shall be sized for a maximum rated movement of 4 inches.

The locking edge rails depicted are configured for typical applications and are conceptual only. The actual configuration of the locking edge rails and matching strip seal may vary from manufacturer to manufacturer provided they fit the application and meet the minimum anchorage shown. Flanged edge rails, however, will not be allowed. Locking edge rails may exceed the $4\frac{1}{2}$ " maximum depth provided the anchorage system is revised according to the manufacturer's recommendation.


The manufacturer's recommended installation methods shall be followed.

All steel components shall be galvanized after fabrication according to Article 520.03 of the Standard Specifications.

The Maximum space between locking edge rail segments shall be $\frac{3}{16}$ " and sealed with a suitable sealant; however, any rail joint within 10' measured perpendicular to the face of the curb or parapet shall be welded as shown in the locking edge rail splice detail.


Cost of parapet sliding plates, embedded plates, and anchorage studs included with Preformed Joint Strip Seal.

34" F-shape barrier shown, 42" F-shape similar as noted. The concrete opening below the strip seal will vary based on the locking edge rail chosen by the Contractor. Deck and parapet lengths shown elsewhere in the plans are dimensioned to the concrete opening, not the joint opening, and are based on the rolled locking edge rail. If the Contractor elects to use a different locking edge rail, dimensional adjustments may be required. One exception to this would be the strip seal joint at the end of the precast bridge approach slab. For these cases the pavement connector length shall be adjusted, not the length of the bridge approach slab.



LOCKING EDGE RAILS

** Back gouge not required if complete joint penetration is verified by mock-up.



LOCKING EDGE RAIL SPLICE

The inside of the locking edge rail groove shall be free of weld residue. Rolled rail shown, welded rail similar.

BILL OF MATERIAL

Item	Unit	Total
Preformed Joint Strip Seal	Foot	90

SECTION A-A

* Granular or solid flux filled headed studs conforming to Article 1006.32 of the Std. Specs., automatically end welded.

off flush with the plates after concrete is set.

TERRA ENGINEERING LTD.

USER NAME = AlexF	DESIGNED AF	REVISED -
	CHECKED KF	REVISED -
PLOT SCALE = 0.167 ' / in.	DRAWN AF	REVISED -
PLOT DATE = 2/3/2023	CHECKED KF	REVISED -

SHOWING ROLLED RAIL JOINT

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

SHOWING WELDED RAIL JOINT

PREFORMED STRUCTUR		-		
SHEET 4	OF	6	SHEETS	

F.A.P. RTE	SECTION		COUNTY	TOTAL SHEETS	SHEE NO.
693	(119B)BR		TAZEWELL	17	15
			CONTRA	CT NO.	68H16
	ILLINOIS.	EED A	D PPO IECT		


STANDARD BAR SPLICER ASSEMBLY PLAN

(All components shall be provided from one supplier)

Threaded splicer bar length = min. lap length + $1\frac{1}{2}$ " + thread length

* Epoxy not required on Bar Splicer Assembly components used in conjunction with black bars.

Location	Bar size	No. assemblies required	Minimum lap length
West Abutment	#6	4	5'-11"
West Abutment	#7	2	6'-10"
East Abutment	#6	4	5'-11"
East Abutment	#7	2	6'-10"



INSTALLATION AND SETTING METHODS

- "A" : Set bar splicer assembly by means of a template bolt.
- "B" : Set bar splicer assembly by nailing to wood forms or cementing to steel forms.

(E) : Indicates epoxy coating.

_Stage line if applicable Stage II construction Stage I construction Mechanical splicer (E) **?**{{{{}}}} Reinforcement bar └─Reinforcement bar

STANDARD MECHANICAL SPLICER

Location	Bar size	No. assemblies required

Notes:

Splicer bars shall be deformed with threaded ends and have a minimum 60 ksi yield strength.

All reinforcement shall be lapped and tied to the splicer bars. Bar splicer assemblies shall be epoxy coated according to the requirements

for reinforcement bars. See Section 508 of the Standard Specifications.
See approved list of bar splicer assemblies and mechanical splicers for

alternatives.

BSD-1


1-1-2020



	USER NAME =	brennar	DESIGNED	AF	REVISED	-
_			CHECKED	KF	REVISED	-
,	PLOT SCALE =	0.167 ' / in.	DRAWN	AF	REVISED	-
	PLOT DATE =	10/21/2022	CHECKED	KF	REVISED	-

STATE OF ILLINOIS **DEPARTMENT OF TRANSPORTATION** BAR SPLICER ASSEMBLY & MECHANICAL SPLICER DETAILS STRUCTURE NO. 090-0063 SHEET 5 OF 6 SHEETS

SECTION COUNTY (119B)BR TAZEWELL 17 16 CONTRACT NO. 68H16



TYPICAL "HOUR-GLASSED" FLOOR DRAIN

Note:

See Special Provision "Floor Drains to be Cleaned"

BILL OF MATERIAL

Item	Unit	Total
Floor Drains to be Cleaned	Each	134

TERRA ENGINEERING LTD.

USER NAME =	brennar	DESIGNED	AF	REVISED _
		CHECKED	KF	REVISED -
PLOT SCALE =	0.167 ' / in.	DRAWN	AF	REVISED -
PLOT DATE =	10/21/2022	CHECKED	KF	REVISED _

STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION FLOOR DRAINS TO BE CLEANED
STRUCTURE NO. 090–0063
SHEET 6 OF 6 SHEETS