

ROUTE NO.	SECTION	. COUNTY		TOTAL SHEETS	SHERY NO.	SHEET	ND. S15
FAU 2783	1314B	соок		160	93	<i>S40</i> sн	EETS
PED. ROAD DIST. NO. 7		ILLINGIS FED. ALC PRO		OJECT-	·		
CONTRACT	60293						

GENERAL NOTES

The strip seal shall be made continuous and shall have a minimum thickness of 6 mm. The configuration of the strip seal shall match the configuration of the Locking Edge Rails. The height and thickness of the Locking Edge Rails shown

The height and thickness of the Locking Edge Rails shown are minimum dimensions. The actual configuration of the Locking Edge Rails and matching strip seal may vary from manufacturer to manufacturer. Flanged edge rails will not be allowed.

Locking Edge Rails may be spliced at slope discontinuities and stage construction joints.

The manufacturer's recommended installation methods shall be followed.

The joint opening and deck dimensions detailed on the superstructure are based on a preformed joint seal. If the contractor elects to use the alternate strip seal joint, the opening and deck dimensions shall be modified according to the dimensions detailed on this sheet. Required modifications shall be made at no additional cost to the State. All dimensions are in millimeters (mm) except as noted.

REVISION	S ···	ILLINOIS DEPARTMENT OF TRANSPORTATION		
NAME	DATE	F.A.I. 90 (I-90)		
 		AT NAGLE AVENUE		
		F.A.U. RTE. 2783 SEC 1314B		
 1. A. 1. A.		COOK COUNTY STATION 0+998.813		
		STRUCTURE NO. 016-0708		
		SUPERSTRUCTURE DETAILS-VII		
 		SUPERSTRUCTURE DETAILS-VII		
		DRAWN BY KAC		
		CHECKED BY LDB/DGS DATE: DEC. 2004		
		· · · · · · · · · · · · · · · · · · ·		

27240142