

EROSION CONTROL DETAILS FOR SILT FENCE






REVISED 10-22-01

29.2

SLOTTED DRAIN PIPE



-FILLET WELD

STEEL MESH (HEEL GUARD)

-FILLET WELD

SECTION A-A

STANDARD DETAIL

SECTION A-A

DETAIL WITH MESH

(TRAPEZOIDAL GALVANIZED GRATE SHOWN)

NOTES

THE SLOTTED DRAIN SHALL BE CORRUGATED PIPE CULVERT WITH INTEGRAL SLOTTED DRAINS, BEFORE PLACING THE CONCRETE ADJACENT TO THE PIPE, THE SLOT SHALL BE COVERED BY EITHER THIN, FLAT METAL SHEETING OR

THE SLOT SHALL BE COVERED BY EITHER THIN, FLAT METAL SHEETING OR BY A BOARD NOTCHED TO FIT OVER THE GRATE BARS, THIS COVERING MUST FIT CLOSELY IN THE SLOT TO PREVENT ENTRY OF CONCRETE INTO THE PIPE. PAVING OVER THE SLOTTED DRAIN WILL THEN BE ONE CONTINUOUS OPERATION OVER THE PROTECTED DRAIN, THE PROTECTION FOR THE DRAIN SLOT SHALL THEN BE REMOVED. THE PIPE SHALL DRAIN INTO THE SIDE OF THE INLET. THE OPENING WHERE THE SLOT IS REMOVED SHALL BE COVERED TO PREVENT CONCRETE FROM ENTERING THE PIPE.

THE CORRUGATED STEEL PIPE USED IN THE SLOTTED DRAIN SHALL MEET THE REQUIREMENTS OF AASHTO M-36/ASTM A 760. THE CMP SHALL BE GALVANIZED

USE APPROVED END CAP TO PREVENT CONCRETE ENTRY INTO THE PIPE DURING GUTTER CONSTRUCTION ON THE UPSTREAM END OF PIPE.

HOLES IN GRATING, SUPPLYING AND PLACING AT BARS AND CONCRETE.

CLASS SI CONCRETE SHALL BE USED THROUGHOUT.


HEL-COR PIPE-

5 (3/16") BEARING BAR

WEB SPACER


HEL-COR PIPE

SECTION B-B



1. GRATING IS AVAILABLE IN DEPTHS OF 63 (2-1/2AND 150 (64)

- 2. VERTICAL GRATING (STRAIGHT SIDES) WITH VERTICAL SPACERS IS ALSO AVAILABLE.
- 3. FOR 150 (6") VERTICAL & TRAPIZOIDAL REQUIREMENTS, THE SLOTTED DRAIN BAND MAY BE FURNISHED WITH THE 100 (4") TECHCO BAND ANGLE.
- 5. REFERENCE CONTECH BAND MANUAL DWG. NO. 1008466 FOR BAND DETAILS.



-900 (36⁽¹⁾

OF SLOTTED DRAIN. OR ALUMINIZED STEEL TYPE 2. STEEL GRATING SHALL MEET THE GALVANIZING REQUIREMENTS OF AASHTO M-111. THIS WORK WILL BE PAID FOR AT THE CONTRACT UNIT PRICE PER FOOT FOR SLOTTED DRAIN PIPE, AND SHALL INCLUDE ELBOWS, DRILLING

CORRUGATED STEEL PIPE 375 (15")-

ALL DIMENSIONS ARE IN MILLIMETERS (INCHES) UNLESS

61.2

CONTRACT NO. 64596

COUNTY TOTAL SHEET NO.

WINNEBAGO 317 110

TO STA.

MANUFACTURING TOLERANCES

1. VERTICAL BOW +_10 (3/8")

3. TWIST +_13 (1/2")

2. HORIZONTAL BOW +_16 (5/8")

RTE. SECTION