F.A.P. SECTION COUNTY TOTAL SHEET SHEETS NO. 71 (11,12)RS-2 DEWITT 53 3

CONTRACT NO. 90867

GENERAL NOTES

G.N.-100 ENGLISH UNITS OF MEASUREMENT SHALL GOVERN OVER AND SUPERSEDE ANY METRIC UNITS SHOWN IN THIS CONTRACT. WHERE INCLUDED, METRIC UNITS ARE FOR INFORMATION ONLY.

G.N.-107.12 SPECIAL ATTENTION IS CALLED TO ARTICLE 107.12 REGARDING RAILROAD FLAGGERS. THE NAME, ADDRESS AND TELEPHONE NUMBER OF THE RAILROAD CONTACT PERSON FOR FLAGGERS IS:

> MR. HARDY TAYLOR 1907 MARION AVE MATTOON, IL 61938 (217) 238-2443

G.N.-406
THE QUANTITIES INCLUDED IN THE PLANS FOR BITUMINOUS CONCRETE
RESURFACING ARE INTENDED TO GIVE THE COVERAGE SHOWN ON THE TYPICAL
CROSS SECTIONS. IT IS NOT INTENDED TO INCREASE THE THICKNESS OF THE
BITUMINOUS MIXTURE IN ORDER TO USE ALL OF THE QUANTITIES INCLUDED IN
THE CONTRACT. DESIGN THICKNESS CAN BE BACK CALCULATED USING THE
CONVERSION FACTOR OF 1 IN. THICKNESS = 112 POUNDS/SQUARE YARD.

G. N. -406H MIXTURE REQUIREMENTS

The following mixture requirements are applicable for this project:

Location(s):	IL 54	IL 54
Mixture Use(s):	SURFACE COURSE	PARTIAL DEPTH PATCHES
	+ INCIDENTAL	
AC/PG:	PG 64-22	PG 64-22
RAP %: (Max)	15%	25%
Design Air Voids:	4.0% @ Ndes=50	4.0% @ Ndes=50
Mixture Composition:	IL 9.5	IL 9.5
(Gradation Mixture)		
Friction Aggregate:	MIX C	MIX C