## TRAFFIC SIGNAL LEGEND

ITEM	REMOVAL	EXISTING	PROPOSED	ITEM	REMOVAL	EXISTING	PROPOSED	<u>ITEM</u>	REMOVAL	EXISTING	PROPOSED
CONTROLLER CABINET	R			EMERGENCY VEHICLE LIGHT DETECTOR	R <sub></sub>	$\circ \triangleleft$	•	ELECTRICAL CABLE IN CONDUIT, TRACER,			
RAILROAD CONTROL CABINET		<b>R</b>	₽⋖	CONFIRMATION BEACON	$R_{O-(]}$	0-()	•-(	NO. 14 1/C, UNLESS NOTED OTHERWISE		~	
COMMUNICATIONS CABINET	R CC	EGC	СС	HANDHOLE	R	Ŋ		COAXIAL CABLE		<del>-</del> Ø-	C
MASTER CONTROLLER		EMC	MC	HEAVY DUTY HANDHOLD	R	H H	Н	VENDOR CABLE FOR CAMERA		<del>-</del> Ø-	(V)
MASTER MASTER CONTROLLER		ENAMO	MMC	DOUBLE HANDHOLE	R	20		COPPER INTERCONNECT CABLE,		· .	
UNINTERRUPTIBLE POWER SUPPLY	IUPS	EUPS	UPS	JUNCTION BOX	R	<b>(</b>	0	NO. 18 3 PAIR TWISTED, SHIELDED		<del>-</del> (E)-	(6)
SERVICE INSTALLATION, (P) POLE OR (G) GROUND MOUNT	P	P	- <b>■</b> -P	GALVANIZED STEEL CONDUIT IN TRENCH (T) OR PUSHED (P)		The production of the producti		FIBER OPTIC CABLE NO. 62.5/125, MM12F			
TELEPHONE CONNECTION (P) POLE OF (G) GOUND MOUNT	R	P	P	TEMPORARY SPAN WIRE, TETHER WIRE, AND CABLE	<u>R</u>	***************************************		FIBER OPTIC CABLE NO. 62.5/125, MM12F SM12F		<del>-</del> 245-	<del>-</del> 24F-
STEEL MAST ARM ASSEMBLY AND POLE	R	O		COMMON TRENCH			CT	FIBER OPTIC CABLE NO. 62.5/125, (NUMBER OF FIBERS & TYPE TO BE		_	
ALUMINUM MAST ARM ASSEMBLY AND POLE	R	C.		COILABLE NONMETALLIC CONDUIT (EMPTY)		0	CNC	NOTED ON PLANS			
STEEL COMBINATION MAST ARM ASSEMBLY AND POLE WITH LUMINAIRE	R <sub>O</sub>	o- <del>-</del> ¤	•*	SYSTEM ITEM		5	S IP	GROUND ROD AT (C) cONTROLLER, (H) HANDHOLE, (P) POST, (M) MAST ARM, OR (S) SERVICE		Cultura	C 11
STEEL COMBINATION MAST ARM	R	0	<b></b>	INTERSECTION ITEM	R			CONTROLLER CABINET AND	RCF		
ASSEMBLY AND POLE WITH PTZ CAMERA	PIZ)	PZ	PIZ	REMOVE ITEM	RL A			FOUNDATION TO BE REMOVE		•	
SIGNAL POST	R <sub>O</sub>	0	•	ABANDON ITEM	А	77		STEEL MAST ARM POLE AND FOUNDATION TO BE REMOVE	RMF O		
TEMPORARY WOOD POLE (CLASS 5 OR BETTER) 45 FOOT (13.7m) MINIMUM	R⊗	$\otimes$	•	12" (300mm) TRAFFIC SIGNAL SECTION		R	R	ALUMINUM MAST ARM POLE AND FOUNDATION TO BE REMOVE	RMF		
GUY WIRE	<u> </u>	>	>—	12" (300mm) RED WITH 8" (200mm) YELLOW AND GREEN TRAFFIC SIGNAL FACE				STEEL COMBINATION MAST ARM ASSEMBLY			
SIGNAL HEAD	<b>R</b> →	>	-			(R)	R	AND POLE WITH LUMINAIRE AND FOUNDATION TO BE REMOVE	RMF O-XX		
SIGNAL HEAD CONSTRUCTION STAGES (NUMBERS INDICATE THE CONSTRUCTION STAGE)			<b>-</b>	CIONAL FACE			Y	SIGNAL POST AND FOUNDATION	DIME		
SIGNAL HEAD WITH BACKPLATE	+L>R	$+\triangleright$	+	SIGNAL FACE		• • • • • • • • • • • • • • • • • • •	<b>←</b> Y <b>←</b> G	TO BE REMOVE	RMF	FEE3	
SIGNAL HEAD OPTICALLY PROGRAMMED	-R "P"	-⊳ "P"	<b>-▶</b> "P"					INTERSECTION & SAMPLING (SYSTEM) DETECTOR		IS	IS
FLASHER INSTALLATION (S DENOTES SOLAR POWER)	○P "F"	○ Ç	••"F"	SIGNAL FACE WITH BACKPLATE. "P" INDICATES PROGRAMMED HEAD			R	SAMPLING SYSTEM DETECTOR		s .	S
PEDESTRIAN SIGNAL HEAD	-0					G T	G <b>◆</b> Y	EXISTING INTERSECTION LOOP DETECTOR PROPOSED INTERSECTION AND SAMPLING (SYSTEM) DETECTOR	OR .	P	
PEDESTRIAN PUSHBUTTON DETECTOR	<b>R</b> ⊚	6	•			<u>#8"</u>	<b>4</b> G	EXISTING PREFORMED INTERSECTION LOOP DETECTOR	<b>.</b>	[PP]	
ACCESSIBLE PEDESTRIAN PUSHBUTTON DETECTOR	R	∘ ⊚ APS	⊚ APS	10" (000 ) DEDECTEMAN CLONIAL HEAD			-P-	PROPOSED INTERSECTION AND SAMPLING (SYSTEM) DETECTO	)R		
ILLUMINATED SIGN	R (P)			12" (300mm) PEDESTRIAN SIGNAL HEAD WALK/DON'T WALK SYMBOL				PREFORMED INTERSECTION AND SAMPLING (SYSTEM) DETECTOR		PIS	PIS
"NO LEFT TURN"  ILLUMINATED SIGN	R Ø			12" (300mm) PEDESTRIAN SIGNAL HEAD INTERNATIONAL SYMBOL, OUTLINED			-	PREFORMED SAMPLING (SYSTEM) DETECTOR		PS	PS
"NO RIGHT TURN"  DETECTOR LOOP, TYPE I				12" (300mm) PEDESTRIAN SIGNAL HEAD INTERNATIONAL SYMBOL, SOLID			<b>₽</b>	RAILROAD SYMBOLS			
PREFORMED DETECTOR LOOP		IP]	P	PEDESTRIAN SIGNAL HEAD, INTERNATIONAL			<b>₩</b> C				
MICROWAVE VEHICLE SENSOR	R	M	M	SYMBOL, WITH COUNTDOWN TIMER	B						
VIDEO DETECTION CAMERA	R Vì		<b>V</b> ■	RADIO INTERCONNECT	##*O	##0	++++•	RAILROAD CONTROL CABINET			R
VIDEO DETECTION ZONE	200			RADIO REPEATER	R ERR	ERR	RR	RAILROAD CANTILEVER MAST ARM	2	XXXX	XeX X
PAN, TILT, ZOOM CAMERA	R PIZ)	PTZ[:]	PIZ	DENOTES NUMBER OF CONDUCTORS, ELECTRIC CABLE NO. 14, UNLESS NOTED OTHERWISE,	National and American Community	hacamana-accordend		FLASHING SIGNAL		XOX	<b>X</b> ⊖ <b>X</b>
WIRELESS DETECTOR SENSOR	. R	<b>(W)</b>	W	ALL DETECTOR LOOP CABLE TO BE SHIELDED		_(5)	-5-	CROSSING GATE			<b>X</b> - <b>X</b> -
WIRELESS ACCESS POINT	R			GROUND CABLE IN CONDUIT NO. 6 SOLID COPPER (GREEN)		(1)	(1)	CROSSBUCK		*	*
LE NAME = USER NAME = \$USER\$		IGNED - ĐẠO	REVISED -	· .				DISTRICT ONE	F.A.P. RTE.	SECTION	COUNTY TOTAL SHEE
PLOT SCALE = \$SCALE\$	DRA CHE	WN - BAGA, EA CKED - BAO, EA	REVISED -	STATE DEPARTMENT	OF ILLINOIS			STANDARD TRAFFIC SIGNAL DESIGN DETAILS	2578	532B	DuPage 781 430 CONTRACT NO. 60477