



WIRING DIAGRAM

NOTES:

- 1. ALL DIMENSIONS ARE IN INCHES (MILLIMETERS) UNLESS OTHERWISE SHOWN
- 2. ALL CONDUIT ATTACHED TO STRUCTURE SHALL BE GALVANIZED RIGID METALIC CONDUIT, PVC COATED (GRMC, PVC)
- 3. THE USE OF LIQUID TIGHT METAL CONDUIT (TYPE LFMC)
 SHALL BE LIMITED TO LOCATIONS WHERE MOVEMENT IS
 ANTICIPATED AND SHALL NOT EXCEED 5' (1.5 m) IN LENGTH
- 4. ALL WORK INDICATED SHALL BE INCLUDED IN THE PAY ITEM FOR ELECTRIC CONNECTION TO SIGN STRUCTURE
- 5. THE SAFETY SWITCH SHALL BE LOCATED ON THE SIDE OF THE SIGN STRUCTURE WHICH IS CLOSEST TO THE SHOULDER, OR EDGE OF PAVEMENT.

FILE NAME =	USER NAME = gaglianobt	DESIGNED -	REVISED - 09-19-04			ELECTRIC CONNECTION TO SIGN STRUCTURE		F.A.	SECTION	COUNTY	TOTAL SHEET
Wi\diststd\22×34\be600.dgn		DRAWN ~	REVISED -	STATE OF ILLINOIS	SPAN TYPE SCALE: NONE SHEET NO. 1 OF 2 SHEETS STA. TO STA.			80	99(4&4-1)RS-3	WILL	203 190
	PLOT SCALE = 50.0000 ' / IN.	CHECKED -	REVISED -	DEPARTMENT OF TRANSPORTATION					BE-600	CONTRACT	NO. 60M66
	PLOT DATE = 1/4/2008	DATE -	REVISED -					FED. RO	DAD DIST. NO. 1 ILLINOIS FED. A	ID PROJECT	n