





- BASED ON CONTROLLER CABINET TYPE IV WITH BASE DIMENSIONS OF 26" x 44" (660mm x 1118mm).
 ADJUST PLATFORM SIZE TO FIT CABINET BASE DIMENSIONS BEING SUPPLIED.
- BASED ON UNINTERRUPTIBLE POWER SUPPLY CABINET WITH BASE DIMENSIONS OF 16" x 25" (406mm x 635mm).
 ADJUST PLATFORM SIZE TO FIT CABINET BASE DIMENSIONS BEING SUPPLIED.
- 3. PLATFORM SIZE FOR CONTROLLER CABINET TYPE IV.
- 4. PLATFORM SIZE FOR CONTROLLER CABINET TYPE IV AND UNINTERRUPTIBLE POWER SUPPLY CABINET.
- 5. DRILLED HOLES THROUGH THE PLATFORM BASE TO MATCH THE CONTROLLER CABINET BOLT TEMPLATE. FASTEN THE CONTROLLER CABINET TO THE PLATFORM WITH CARRIAGE BOLTS, WASHERS AND NUTS.
- 6. FASTEN ALL SUPPORT WOOD FRAMING TO THE WOOD POSTS WITH 2 LAG SCREWS FOR EACH CONNECTION.

TEMPORARY SIGNAL CONTROLLER WOOD SUPPORT PLATFORM

CABLE SLACK LENGTH	FEET	METER
HANDHOLE	6.5	2.0
DOUBLE HANDHOLE	13.0	4.0
SIGNAL POST	2.0	0.6
MAST ARM	2.0	0.6
CONTROLLER CABINET	1.5	0.5
FIBER OPTIC AT CABINET	13.0	4.0
ELECTRIC SERVICE AT (CABINET OR SERVICE LOCATION)	1.5	0.5
GROUND CABLE (SIGNAL POST, MAST ARM, CABINET)	1.5	0.5
GROUND CABLE (BETWEEN FRAME AND COVER)	5.0	1.6

CABLE SLACK

FEET	METER
20.0+L	6.0+L
13.0	4.0
6.0	2.0
13.5	4.1
13.5	4.1
6.0	2.0
3.0	1.0
	20.0+L 13.0 6.0 13.5 13.5

VERTICAL CABLE LENGTH

FOUNDATION	DEPTH
TYPE A - Signal Post	4'-0" (1.2m)
TYPE C - CONTROLLER W/ UPS	4'-0" (1.2m)
TYPE D - CONTROLLER	4'-0" (1.2m)
SERVICE INSTALLATION, GROUND MOUNT, TYPE A - SQUARE	4'-0" (1.2m)

DEPTH OF FOUNDATION

Mast Arm Length	① Foundation Depth	Foundation Diameter	Spiral Diameter	Quantity of Rebars	Size of Rebars
Less than 30' (9.1 m)	10'-0" (3.0 m)	30" (750mm)	24" (600mm)	8	6(19)
Greater than or equal to	13'-6" (4.1 m)°	30" (750mm)	24" (600mm)	8	6(19)
30' (9.1 m) and less than 40' (12.2 m)	11'-0" (3 ₄ m)	36" (900mm)	30" (750mm)	12	7(22)
Greater than or equal to 40' (12.2 m) and less than 50' (15.2 m)	13'-0'' (4.0 m)	36" (900mm)	30" (750mm)	12	7(22)
Greater than or equal to 50' (15.2 m) and up to 55' (16.8 m)	15'-0'' (4.6 m)	36" (900mm)	30" (750mm)	12	7(22)
Greater than or equal to 56' (16.8 m) and less than 65' (19.8 m)	21'-0" (6.4 m)	42" (1060mm)	36" (900mm)	16	8(25)
Greater than or equal to 65' (19.8 m) and up to 75' (22.9 m)	25'-0" (7.6 m)	42" (1060mm)	36" (900mm)	16	8(25)

NOTES:

- These foundation depths are for sites which have cohesive soils (clayey slit, sandy clay, etc.) along
 the length of the shaft, with an average Unconfined Compressive Strength (0u) > 1.0 tsf (100 kpa).
 This strength shall be verified by boring data prior to construction or with testing by the Engineer
 during foundation drilling. The Bureau of Bridges & structures should be contacted for a revised
 design if other conditions are encountered.
- 2. Combination mast arm assemblies under 55 feet (16.8 m) shall use 36" (900 mm) diameter foundations.
- Combination most arm assemblies under 56 feet (16.8 m) through 75 feet (22.9 m) shall use 42" (1060 mm) diameter foundations.
- 4. For most arm assemblies with dual arms refer to state standard 878001.

DEPTH OF MAST ARM FOUNDATIONS, TYPE E

FILE NAME =	USER NAME = #USER#	DESIGNED - DAG	REVISED -		DISTRICT ONF	F.A. SECTION	COUNTY TOTAL SHEET
\$FILEL\$		DRAWN - BCK	REVISED -	STATE OF ILLINOIS	STANDARD TRAFFIC SIGNAL DESIGN DETAILS		
	PLOT SCALE = \$SCALE\$	CHECKED - DAD	REVISED -	DEPARTMENT OF TRANSPORTATION	COME NOW CHEET NO F OF C. CHEET C. C.T.A. TO C.T.A.	TS05	CONTRACT NO
	PLOT DATE = *DATE*	DATE - 10:28:09	REVISED		SCALE: NONE SHEET NO. 5_ OF 6 SHEETS STA TO STA	FED. ROAD DIST. NO. 1 ILLINOI	IS FED. AID PROJECT

KANE COUNTY
DIVISION OF TRANSPORTATION

	USER NAME = JM	DESIGNED	-	DG	REVISED	-	
		DRAWN	-	JM/SM	REVISED	-	
	PLOT SCALE = 1° = 50°	CHECKED	-	DG	REVISED	-	
	PLOT DATE = 12-21-2010	DATE	-	12-21-2010	REVISED	-	
-							

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

DISTRICT ONE Standard traffic design details		F.A.P	F.A.P SECTION		TOTAL	TAL SHEET	
		336	336 09-00272-01-TL		68	67	
					CONTRAC	T NO. 6	3540
SCALE: NONE	SHEET NO. 5 OF 6 SHEETS STA.	TO STA.	I ISTD-4	ILLINOIS FED. A	ID PROJECT		