

## STANDARD BAR SPLICER ASSEMBLY

Minimum Lap Lengths							
Bar size to be spliced Table 1		Table 2	Table 3	Table 4	Table 5		
3, 4	1'-5''	1'-11''	2'-1''	2'-4''	2'-3''		
5	1'-9''	2'-5''	2'-7''	2'-11''	2'-10''		
6	2'-1''	2'-11''	3'-1''	3'-6''	3'-4''		
7	2'-9''	3′-10′′	4'-2''	4'-8''	4'-6''		
8	3'-8''	5'-1''	5'-5''	6'-2''	5′-10′′		
9	4'-7''	6'-5''	6'-10''	7'-9''	7'-5''		

Table 1: Black bar, 0.8 Class C

Table 2: Black bar, Top bar lap, 0.8 Class C

Table 3: Epoxy bar, 0.8 Class C

Table 4: Epoxy bar, Top bar lap, 0.8 Class C

Table 5: Epoxy bar, Top bar lap, Class B

Threaded splicer bar length = min. Iap length +  $1_2^{\prime}$  + thread length

\* Epoxy not required on Bar Splicer Assembly components used in conjunction with black bars.

Bar Size	No. Assemblies Required	Location		
#4	25	West Approach		
#4	25	East Approach		
#5	137	Deck		
#5	46	West Approach		
#5	46	East Approach		
#5	24	Pier 1 Wall		
#5	24	Pier 2 Wall		
#5	40	West Approach Footing		
#5	40	East Approach Footing		
#7	8	West Abutment		
#7	8	East Abutment		
#7	9	Pier 1 Cap		
#7	9	Pier 2 Cap		

## Alfred Benesch & Company benesch a Company 205 benesch engineers - scientists - planners book of Morth Michigan Avenue, Suite 2400 Chicago, Illinois 66061 312-565-0450 Job No. 3938 Job No. 3938

FILE NAME =	USER NAME = joreisher	DESIGNED - JDC	REVISED -		
\038-0220-66960-018-brsp.dgn		CHECKED - JMS	REVISED -	STATE OF ILLINOIS	BAR SPLICER ASSEMBLY AND MECHA
	PLCT SCALE = \$SCALE\$	DRAWN - MRW	REVISED -	DEPARTMENT OF TRANSPORTATION	STRUCTURE NO. 038-
	PLOT DATE = 12\09\2010	CHECKED - JDC	REVISED -		SHEET NO. 18 OF 22 SHEETS



## INSTALLATION AND SETTING METHODS

"A" : Set bar splicer assembly by means of a template bolt. "B" : Set bar splicer assembly by nailing to wood forms or cementing to steel forms. (E) : Indicates epoxy coating.



10

## NOTES

Splicer bars shall be deformed with threaded ends and have a minimum 60 ksi yield strength.

All reinforcement shall be lapped and tied to the splicer bars. Bar splicer assemblies shall be epoxy coated according to the requirements for reinforcement bars. See Section 508 of the Standard Specifications. See approved list of bar splicer assemblies for alternatives.

CHANICAL SPLICER DETAILS	F.A.P. RTÉ.	SECTION		COUNTY	TOTAL SHEETS	SHEET NO.	120
	681	(117)	BR-1	IROQUOIS	41	2.9	60
038–0220				CONTRACT	NO. 6	6960	$\sim$
HEETS	FED. RO	AD DIST. NO.	ILLINOIS FED. A	ID PROJECT			1