## MIXTURE REQUIREMENTS

Location(s):	Hot-Mix Asphalt Surface Course Polymerized Hot-Mix Asphalt Surface Course, Mix D,
Mixture Use(s):	Polymerized Hot-Mix Asphalt Surface Course, Mix D, N90
AC/PG:	SBS PG76-22
RAP % (Max):	0
Design Air Voids:	4.0%, 90 Gyration Design
Mixture	II-9.5 mm or II12.5 mm
Composition:	
(Gradation Mixture)	
Friction Aggregate:	D Surface
TITIOTTOTT Aggrogato-	
Location(s):	Hot-Mix Asphalt Binder Course (Top Lift, 2 1/4") Polymerized Hot-Mix Asphalt Binder Course, N90,
Mixture Use(s):	Polymerized Hot-Mix Asphalt Binder Course, N90,
	IL-19.0
AC/PG:	SBS PG76-22
RAP % (Max):	0
Design Air Voids:	4.0%, 90 Gyration Design
Mixture	IL-19.0 mm
Composition:	
(Gradation Mixture)	
Friction Agaregate:	None
Location(s):	Hot-Mix Asphalt Binder Course (Lower lifts)
Mixture Use(s):	Hot-Mix Asphalt Binder Course, N90, IL-19.0
AC/PG:	PG64-22
RAP % (Max):	10
Design Air Voids:	4.0%, 90 Gyration Design
Mixture.	IL-19.0
Composition:	
(Gradation Mixture)	
Friction Aggregate:	None
Location(s):	Hot-Mix Asphalt Shoulders, 8"
Mixture Use(s):	Hot-Mix Asphalt Shoulders
AC/PG:	PG58-22
RAP % (Max):	50
Design Air Voids:	2.0%, 30 Gyration Design
Mixture	HMA Shoulder
Composition:	
(Gradation Mixture)	
Friction Aggregate:	None

## STANDARDS

000001-0 <b>6</b> 001001-02 001006	STANDARD SYMBOLS, ABBREVIATIONS, AND PATTERNS AREAS OF REINFORCEMENT BARS DECIMAL OF AN INCH AND OF A FOOT
280001-05 482001-02 482011-03	TEMPORARY EROSION CONTROL SYSTEMS HMA SHOULDER ADJACENT TO FELXIBLE PAVEMENT HMA SHLD. STRIPS/SHLDS. WITH RESURFACING OR WIDENING AND RESURFACING PROJECT
542301-03	PRECAST REINFORCED CONCRETE END SECTION
606101-04	TYPE A GUTTER - INLET, OUTLET, AND ENTRANCE
701001-02	OFF-ROAD OPERATIONS 2-L, 2-W, MORE THAN 15' AWAY
701006-03	OFF-ROAD OPERATIONS 2-L, 2-W, 15' TO 24" FROM PAVEMENT EDGE
701011-0 <b>2</b>	OFF-ROAD MOVING OPERATIONS, 2L, 2W, DAY ONLY
701201-04	LANE CLOSURE, 2L, 2W, DAY ONLY, FOR SPEEDS >45 MPH
701306-0 <b>3</b>	LANE CLOSURE, 2L, 2W, SLOW MOVING OPERATIONS DAY ONLY, FOR SPEEDS > 45 MPH
701311-0 <b>3</b>	LANE CLOSURE 2-L. 2-W MOVING OPERATIONS - DAY ONLY
701326-0 <b>4</b>	LANE CLOSURE, 2L, 2W, PAVEMENT WIDENING, FOR SPEEDS > 45 MPH
701336-0 <b>6</b>	LANE CLOSURE, 2L, 2W, WORK IN A SEIRES,
	FOR SPEEDS > 45 MPH
701901-01	TRAFFIC CONTROL DEVICES
780001-02	TYPICAL PAVEMENT MARKINGS
805001-01	ELECTRIC SERVICE INSTALLATION DETAILS
825001-01	
836001	LIGHTPOLE FOUNDATION
B. L. R. 22-6	TYPICAL APPLICATIONS OF TRAFFIC CONTROL DEVICES FOR
	CONSTUCTION ON RURAL LOCAL HIGHWAYS
	(TWO-LANE TWO WAY RURAL TRAFFIC), (ROAD CLOSED TO THRU TRAFFIC)
	( KUAD CLUSED TO THRU TRAFFIC)

FILE NAME =	USER NAME = naasdp	DESIGNED -	REVISED -
c:\pw_work\pwidot\naasdp\d0125145\d97811	5.sht_musc.dgn	DRAWN	REVISED -
	PLOT SCALE = 50.0000 '/ IN,	CHECKED -	REVISED -
	PLOT DATE = 12/21/2010	DATE -	REVISED -

STATE	OF	ILLINOIS
DEPARTMENT	0F	TRANSPORTATION

SCALE:

						F.A.P. RTE.	SECTION	COUNTY	TOTAL	SHE
MIXTURE REQUIREMENTS, STANDARDS			132	102 (N <sub>+</sub> L)	MASSAC	79	3			
				_				CONTRACT	NO.	78116
	SHEET NO.	0F	SHEETS	STA.	TO STA.		ILLINOIS FED.	AID PROJECT		