

STANDARD BAR SPLICER ASSEMBLY

	Minim	um Lap Leng	ths		
Bar size to be spliced	Table 1	Table 2	Table 3	Table 4	Table 5
3, 4	1'-5''	1'-11''	2'-1''	2'-4"	2'-3''
5	1'-9''	2'-5"	2'-7''	2'-11''	2'-10''
6	2'-1"	2'-11''	3'-1''	3'-6''	3'-4''
7	2'-9"	3'-10''	4'-2"	4'-8''	4'-6''
8	3'-8''	5′-1′′	5′-5′′	6'-2"	5′-10′′
9	4'-7"	6'-5''	6′-10′′	7'-9''	7'-5''

Table 1: Black bar, 0.8 Class C

Table 2: Black bar, Top bar lap, 0.8 Class C

Table 3: Epoxy bar, 0.8 Class C


Table 4: Epoxy bar, Top bar lap, 0.8 Class C

Table 5: Epoxy bar, Top bar lap, Class B

Threaded splicer bar length = min. lap length + I_2^{\prime} '' + thread length


* Epoxy not required on Bar Splicer Assembly components used in conjunction with black bars.

Location	Bar size	No. assemblies reauired	Table for minimum	
East Approach	#4	12	Table 4	
East Approach	#5	42	Table 3	
E. Appr. Footing	#5	80	Table 3	




INSTALLATION AND SETTING METHODS

"A": Set bar splicer assembly by means of a template bolt.
"B": Set bar splicer assembly by nailing to wood forms or cementing to steel forms.
(E): Indicates epoxy coating.




STANDARD MECHANICAL SPLICER

Location	Bar size	No. assemblies required



BAR SPLICER ASSEMBLY FOR #5 BAR ON INTEGRAL OR SEMI-INTEGRAL ABUTMENTS

No. required =



NOTES

Splicer bars shall be deformed with threaded ends and have a minimum 60 ksi yield strength.

All reinforcement shall be lapped and tied to the splicor bars. Bar splicer assemblies shall be epoxy coated according to the requirements

for reinforcement bars. See Section 508 of the Standard Specifications. See special provision for Mechanical Splicers.

See approved list of bar splicer assemblies and mechanical splicers for alternatives.

BSD-1

7-1-10

€ ENTRAN	USER NAME = 2sayerb	DESIGNED	-	BHS	REVISED -
		CHECKED	-	GSP	REVISED -
	PLOT SCALE = N/A	DRAWN	-	MJB	REVISED -
	PLOT DATE = 3/1/2011	CHECKED	-	GSP	REVISED ~
,					

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

BAR SPLICER ASSEMBLY AND MECHANICAL SPLICER DETAILS
S.N. 016-0367

SHEET NO. S5 OF 6 SHEETS