



WORK ZONE	W2-1115(O)-3618
SPEED LIMIT	R2-1-3648
BEGINS	W2-1114(O)-3612
SOX FINE MINIMUM	R2-1106-3618

- LEGEND AND NOTES:
- WORK ZONE
 - ARROW BOARD
 - DIRECTION INDICATOR BARRICADE WITH STEADY BURNING MONODIRECTIONAL LIGHT AT 50' C-C SPACING
 - DRUM WITH STEADY BURNING MONODIRECTIONAL LIGHT AT 25' C-C SPACING AT RAMP, 50' C-C SPACING IN LANE TAPERS AND 100' C-C SPACING AT ALL OTHER LOCATIONS.
 - VERTICAL PANEL AT 200' C-C SPACING ON TANGENT AND 100' C-C SPACING ON CURVE. NOT REQUIRED WITH GUARDRAIL.
 - IMPACT ATTENUATORS, TEMPORARY (FULLY REDIRECTIVE, NARROW), TEST LEVEL 3

1. ALL PAVEMENT MARKINGS SHALL BE WET REFLECTIVE TEMPORARY TAPE, TYPE III.
2. SEE STANDARDS 701401-05 AND 701411-05 AND DISTRICT DETAIL TC-9 IN ADDITION TO TRAFFIC CONTROL ITEMS SHOWN ON THIS SHEET.

FILE NAME = D168021-B41-STAGE.PLAN.STG1.dgn	USER NAME = dwozn1@rsk1	DESIGNED -	REVISED -	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	BISHOP FORD EXPRESSWAY (I-94) SUGGESTED MAINTENANCE OF TRAFFIC - STAGE I PLAN		F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
	PLOT SCALE = 100.00' / IN.	DRAWN -	REVISED -				94	(0405,ETC,42-7&0707)RS-11	COOK	133	41
	PLOT DATE = 2/5/2009	CHECKED -	REVISED -				CONTRACT NO. 60D21				
		DATE -	REVISED -				SCALE: 1" = 50' SHEET NO. 13 OF 24 SHEETS STA. 620+00 TO STA. 635+00 FED. ROAD DIST. NO. ILLINOIS FED. AID PROJECT				