

MAN HOLES TO BE ADJUSTED	
STATION	EASTBOUND
1015+08	1
1025+09	1
1027+60	1
1027+70	1
1030+30	1
1034+50	1
1044+70	1
1086+00	1
1114+93	1
1156+00	1
TOTAL EB	10
STATION	WESTBOUND
1014+49	1
1022+42	1
1022+40	1
1024+50	1
1029+80	1
1037+32	1
1044+13	1
1044+75	1
1114+09	1
TOTAL WB	9
TOTAL	19

VALVE VAULTS TO BE ADJUSTED	
STATION	EASTBOUND
1015+08	1
1027+46	1
1031+57	1
1035+40	1
1035+96	1
1038+21	1
1038+43	1
1039+73	1
1040+23	1
1040+65	1
1041+66	2
1060+50	1
TOTAL	13

PAVEMENT PATCHING SCHEDULE	
PARTIAL DEPTH PATCHING	
198	TON
PARTIAL DEPTH REMOVAL 2"	
1768	SQ YD
CLASS D PAVEMENT PATCHING	
TYPE I	21 SQ YD
TYPE II	1709 SQ YD
TYPE III	16 SQ YD

PORTLAND CEMENT CONCRETE SURFACE REMOVAL (COLD MILLING) VARIABLE DEPTH					
STATION	TO	STATION	LENGTH	WIDTH	AREA
1008+09.8	TO	1009+20.0	106.6		SQ YD
1028+94.8	TO	1030+86.0	85.2		SQ YD
1032+05.0	TO	1034+36.0	104.1		SQ YD
1035+98.8	TO	1037+66.3	74.9		SQ YD
1038+59.7	TO	1039+47.1	39.2		SQ YD
1040+38.7	TO	1041+20.6	36.0		SQ YD
1042+13.2	TO	1046+00.0	171.8		SQ YD
1046+00.0	TO	1048+93.0	130.3		SQ YD
1048+93.0	TO	1052+00.0	233.8		SQ YD
1052+59.4	TO	1055+62.7	211.7		SQ YD
1055+62.7	TO	1056+63.3	6.6		SQ YD
1056+63.3	TO	1060+82.0	315.8		SQ YD
1060+82.0	TO	1064+00.0	141.1		SQ YD
1064+00.0	TO	1066+72.0	111.8		SQ YD
1067+48.0	TO	1070+00.0	120.7		SQ YD
1070+00.0	TO	1071+40.0	62.0		SQ YD
1072+16.0	TO	1074+73.0	137.9		SQ YD
1157+46.5	TO	1160+13.0	171.1		SQ YD
TOTAL					2260.4 SQ YD

CORRUGATED MEDIAN (DOWELLED)					
LOCATION	LENGTH	WIDTH	AREA		
	FEET	FEET	SQ YD		
1008+08.8	TO	1009+64.0	155.2	VAR.	959.0
1072+16.0	TO	1074+73.0	257.0	VAR.	1241.0
1157+46.5	TO	1160+13.4	266.9	VAR.	1540.0
TOTAL					3740.0