

STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION



SHEET NO. 12 13 SHEETS



NEW SLAB

EXISTING SLAB

NOTES

Detail I - With Bar Splicer or Couplers:


Connect one (I) 1"x7"x10" steel P to the top layer of couplers with $2^{-5}8''\bar{\phi}$ bolts screwed to coupler at approximate & of each barrier panel.

Detail II - With Extended Reinforcement Bars: Connect one (1) 1"x7"x10" steel P to the concrete slab with 2-58'' Expansion Anchors or cast in place inserts spaced between the top layer of reinforcement at approximate € of each barrier panel.

Cost of anchorage is included with Temporary Concrete Barrier.

SECTIONS THRU SLAB

placed.





DETAIL I

when "A" is greater than 3'-6".

The I''x7''x10'' Plate shall not be removed until Stage II Construction forms and reinforcement bars are in place.

r			
DESIGNED		JSB	MARCH 8, 2004
CHECKED		ATH	EXAMINED John a. Morris
DRAWN		baliva	PASSED ENGINEER OF STRUCTURAL SERVICES
CHECKED	JSB	ATH	ENGINEER OF BRIDGES AND STRUCTURES
R-27	9-01-03		





P 1"x7"x10"

* Required only with Detail II

TEMPORARY CONCRETE BARRIER I-57 OVER CACHE RIVER F.A.I. RTE. 57 - SEC. (02-1B)I ALEXANDER COUNTY STATION 943+72.00 SN 002-0003 (NB) & 002-0004 (SB)