TRAFFIC SIGNAL LEGEND

PLOT SCALE = 50.0000 '/ IN. PLOT DATE = 11/4/2009		ECKED - DAD TE - 10-28-09	REVISED REVISED	DEPARTMENT	NT OF TRANSPORTATION		SCALE: NO		TS-05 CONTRACT N FED. ROAD DIST. NO. 1 ILLINOIS FED. AID PROJECT		CONTRACT NO. 6
.pw_work\PWIDOT\BAUERDL\dØ1Ø8315\ts05.dgn	DRA	AWN - BCK	K REVISED	······································	E OF ILLINOIS			DISTRICT ONE F.A. P. RTE. SECTION COUNTY SHEETS			
LE NAME = USER NAME = bouerdl		SIGNED - DAG/BCK	REVICEN	NO. 6 SOLID COPPER (GREEN)		~		Rev. Sheet 4-6-		25/345 (US 20)	** MCHENRY & KANE
WIRELESS ACCESS POINT	R		_	GROUND CABLE IN CONDUIT		(1)	(1)	CROSSBUCK		>15	*
WIRELESS DETECTOR SENSOR	RW	W	W	CABLE NO. 14, UNLESS NOTED OTHERWISE, ALL DETECTOR LOOP CABLE TO BE SHIELDED		_(5)_		CROSSING GATE		20 2 >	X-X-
AN, TILT, ZOOM CAMERA	R [P17]1	PIZI	PIZ	DENOTES NUMBER OF CONDUCTORS, ELECTRIC		K	<u></u>	FLASHING SIGNAL		$X \ominus X$	X O X
IDEO DETECTION ZONE				RADIO REPEATER	RERR	ERR	RR	RAILROAD CANTILEVER MAST ARM	2	X0X X	X QX X X
IDEO DETECTION CAMERA	ď∑j′	(V)a	: ♥ 1	RADIO INTERCONNECT	##*O			RAILROAD CONTROL CABINET		R ≥SR	
	R	M)	M	SYMBOL, WITH COUNTDOWN TIMER			C AD			EXISTING	PROPOSED
ICROWAVE VEHICLE SENSOR	R [M]J		•	PEDESTRIAN SIGNAL HEAD, INTERNATIONAL					·	- 	
REFORMED DETECTOR LOOP			Р	12" (300mm) PEDESTRIAN SIGNAL HEAD INTERNATIONAL SYMBOL, SOLID		(*	RAILROAD	SYMBO	OLS	
ETECTOR LOOP, TYPE I				INTERNATIONAL SYMBOL, OUTLINED						1. =1	1.71
LUMINATED SIGN NO RIGHT TURN"	R			12" (300mm) PEDESTRIAN SIGNAL HEAD				(SYSTEM) DETECTOR PREFORMED SAMPLING (SYSTEM) DETECTOR		i PS j	PS
NO LEFT TURN"		©	9	12" (300mm) PEDESTRIAN SIGNAL HEAD WALK/DON'T WALK SYMBOL		(DW) W		PREFORMED INTERSECTION AND SAMPLING		PIS	PIS
LLUMINATED SIGN	R	-	-			"P"	"P"	EXISTING PREFORMED INTERSECTION LOOP DETECTOR PROPOSED INTERSECTION AND SAMPLING (SYSTEM) DETEC	TOR	PP!	
ACCESSIBLE PEDESTRIAN PUSHBUTTON DETECTOR	R APS	@APS					4 Y 4 G	PROPOSED INTERSECTION AND SAMPLING (SYSTEM) DETEC	TOR	[P]	
EDESTRIAN PUSHBUTTON DETECTOR	R	©	©	SIGNAL FACE WITH BACKPLATE. "P" INDICATES PROGRAMMED HEAD			Y	EXISTING INTERSECTION LOOP DETECTOR			
PEDESTRIAN SIGNAL HEAD	R -	-0	-1			R	R	SAMPLING (SYSTEM) DETECTOR		[s]	S
LASHER INSTALLATION 5 DENOTES SOLAR POWER)	R ○>"F"	O-D'F"	◆► "F"			€	◆ G	INTERSECTION & SAMPLING (SYSTEM) DETECTOR			IS
GNAL HEAD OPTICALLY PROGRAMMED	R >''P''	~-\>''p''	-▶ "P"	SIGNAL FACE		G ∢ Y	G ◆Y	TO BE REMOVED	RMF O		
IGNAL HEAD WITH BACKPLATE	+R	+	+-			R	R	FOUNDATION TO BE REMOVED SIGNAL POST AND FOUNDATION	D. 15		
IGNAL HEAD CONSTRUCTION STAGES HUMBERS INDICATE THE CONSTRUCTION STAGE)			→ ²	YELLOW AND GREEN TRAFFIC SIGNAL FACE				STEEL COMBINATION MAST ARM ASSEMBLY AND POLE WITH LUMINAIRE AND	RMF		
IGNAL HEAD	R →	>	-	12" (300mm) RED WITH 8" (200mm)		R		FOUNDATION TO BE REMOVED	O		
UY WIRE	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	>	>	12" (300mm) TRAFFIC SIGNAL SECTION		R	R	FOUNDATION TO BE REMOVED ALUMINUM MAST ARM POLE AND	RMF		
EMPORARY WOOD POLE (CLASS 5 OR ETTER) 45 FOOT (13.7m) MINIMUM	^R ⊗	\otimes	③	ABANDON ITEM	Α			STEEL MAST ARM POLE AND	RMF		
SIGNAL POST	R _O	0	•	REMOVE ITEM RELOCATE ITEM	R RL			FOUNDATION TO BE REMOVED			
SSEMBLY AND POLE WITH PTZ CAMERA	PIZI	PZh	PTZ	INTERSECTION ITEM	D	I	IP	OR (S) SERVICE CONTROLLER CABINET AND	RCF		
SSEMBLY AND POLE WITH LUMINAIRE STEEL COMBINATION MAST ARM	R _C	0		SYSTEM ITEM		S	S	GROUND ROD AT (C) CONTROLLER, (H) HANDHOLE, (P) POST, (M) MAST ARM,		C	c _l l - →
STEEL COMBINATION MAST ARM	R _{O-X}	O-X	• ×	COILABLE NONMETALLIC CONDUIT (EMPTY)			CNC	NOTED ON PLANS)		\rightarrow	
STEEL MAST ARM ASSEMBLY AND POLE ALUMINUM MAST ARM ASSEMBLY AND POLE	R	0		COMMON TRENCH			СТ	FIBER OPTIC CABLE NO. 62.5/125, (NUMBER OF FIBERS & TYPE TO BE		<u> </u>	
P) POLE OR (G) GROUND MOUNT	R R	PI	<u> </u>	TEMPORARY SPAN WIRE, TETHER WIRE, AND CABLE	R	Associated transfer consideration and a state of the Associated As		FIBER OPTIC CABLE NO. 62.5/125, MM12F SM12F		-(24F)-	(24F)
FELEPHONE CONNECTION				GALVANIZED STEEL CONDUIT IN TRENCH (T) OR PUSHED (P)		TOTAL TOTAL TOTAL PROPERTY.		NO. 62.5/125, MM12F		—(12F)—	
ERVICE INSTALLATION, P) POLE OR (G) GROUND MOUNT	-□ ^R	P	- B P	JUNCTION BOX	R	(0	NO. 18 3 PAIR TWISTED, SHIELDED FIBER OPTIC CABLE			
NINTERRUPTIBLE POWER SUPPLY	UPS R	EUPS	MMC UPS	DOUBLE HANDHOLE	R			COPPER INTERCONNECT CABLE,		<u></u>	6
IASTER CONTROLLER IASTER MASTER CONTROLLER		EMC EMMC	MC	HEAVY DUTY HANDHOLE	R	H	H	VENDOR CABLE FOR CAMERA			(v)
OMMUNICATIONS CABINET	[CC]"	E C C	CC	HANDHOLE	R			CONTAC CABLE			©
AILROAD CONTROL CABINET		Ř R	B ◆B	CONFIRMATION BEACON	R _O -()	○ —()	•-4	COAXIAL CABLE		—(c)—	—c—
ONTROLLER CABINET	\bowtie R	\boxtimes	\blacksquare	EMERGENCY VEHICLE LIGHT DETECTOR	R≪	\bowtie	-	ELECTRIC CABLE IN CONDUIT, TRACER, NO. 14 1/C, UNLESS NOTED OTHERWISE			
								<u> </u>			