| TABULATION OF REMOVAL QUANTITIES | | | |
|---|---|---|---|
| LOCATION | PAVEMENT REMOVAL | CONCRETE HEADWALL REMOVAL | PIPE CULVERT REMOVAL |
| | SQYD | EACH | FOOT |
| JOBSITE | 133.0 | 3 | 32.0 |
| | | | |
| TOTAL | 133 | 3 | 32 |

| TABULATION OF EARTHWORK QUANTITIES | | | | | | |
|---|---|---|---|---|---|---|
| LOCATION | EARTH EXCAVATION | EARTH EXCAVATION ADJUSTED FOR SHRINKAGE *(FOR INFO ONLY) | EMBANKMENT *(FOR INFO ONLY) | EARTHWORK BALANCE WASTE (+) & SHORTAGE (–) *(FOR INFO ONLY) | FURNISHED EXCAVATION | GRADING & SHAPING DITCHES |
| | CUYD | CUYD | CUYD | CUYD | CUYD | FOOT |
| JOBSITE | 22.3 | 16.8 | 60.0 | –43.2 | 43.2 | 256.0 |
| | | | | | | |
| TOTAL | 23 | – | – | – | 44 | 256 |

| TABULATION OF DRAINAGE QUANTITIES | | | | | | |
|---|---|---|---|---|---|---|
| LOCATION | TRENCH BACKFILL | MH, TY A, 4'–DIAMETER, TY 8 GRATE | STORM SEWER, CL B, TY 1, 18" | PRECAST REINF. CONC. FLARED END SECTIONS 18" | GRATING FOR CONCRETE FLARED END SECTION 18" | CONRETE COLLAR |
| | CUYD | EACH | FOOT | EACH | EACH | EACH |
| JOBSITE | 19.0 | 2 | 91.0 | 2 | 2 | 1 |
| | | | | | | |
| TOTAL | 19 | 2 | 91 | 2 | 2 | 1 |