GENERAL NOTES

THIS SECTION SHALL BE CONSTRUCTED IN ACCORDANCE WITH THE PLANS, THE "STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION", ADOPTED JANUARY 1, 2007; THE "SUPPLEMENTAL SPECIFICATIONS AND RECURRING SPECIAL PROVISIONS" INDICATED ON THE CHECK SHEET, AND "THE SPECIAL PROVISIONS" INCLUDED IN THE PROPOSAL.

THE WORK INCLUDED IN THIS SECTION CONSISTS OF HMA SURFACE REMOVAL, DECK PATCHING, JOINT AND BEARING REPLACEMENT, MICROSILICA CONCRETE OVERLAY, AND OTHER WORK NECESSARY TO COMPLETE THE PROJECT.

PROVIDE TRAFFIC SIGNAL INDICATIONS FOR THE PRIVATE DRIVE WEST OF THE STRUCTURE IN ADDITION TO THE INDICATIONS SHOWN ON STANDARD 701321. COST SHALL BE INCLUDED IN THE BID PRICE FOR TEMPORARY BRIDGE TRAFFIC SIGNALS.

WIDENING THROUGH PRIVATE DRIVE WEST OF STRUCTURE MUST BE CONSTRUCTED IN STAGES UNLESS AN ALTERNATIVE CAN BE AGREED UPON WITH THE AFFECTED PARTIES.

BASE COURSE WIDENING SHALL BE CONSTRUCTED OF EITHER 8" THICK PCC OR 10" THICK HMA AT THE CONTRACTOR'S DISCRETION. WIDENING MAY REMAIN IN PLACE AT THE COMPLETION OF THE PROJECT.

THE MATERIAL USED FOR BITUMINOUS MATERIALS (PRIME COAT) SHALL BE RC-70, SS-1H, OR SS-1HP APPLIED AT THE RATE DIRECTED BY THE ENGINEER.

THE FOLLOWING REQUIREMENTS SHALL APPLY DURING STAGE 1: ERECT VERTICAL PANELS NEXT TO WIDENING AS SHOWN ON STANDARD 701321. PLACE NARROW (12" WIDE OR LESS) TRAFFIC CONTROL BARRELS OR BARRICADES WITH REFLECTIVE SHEETING NEXT TO PARAPET AT 50' INTERVALS TO PREVENT TRAFFIC ON EXISTING BRIDGE DECK DRAINS. COST OF THIS WORK SHALL BE INCLUDED IN THE BID PRICE FOR TRAFFIC CONTROL AND PROTECTION STANDARD 701321.

QUANTITIES OF HOT MIX ASPHALT SURFACE REMOVAL AND HOT MIX ASPHALT SURFACE COURSE HAVE BEEN PROVIDED TO ALLOW FOR RESURFACING OF THE APPROACHES. THIS WORK WILL ALLOW TRANSITION BETWEEN THE EXISTING PAVEMENT AND PROPOSED BRIDGE JOINTS. EXISTING RESURFACING ON THE APPROACHES IS ESTIMATED TO BE 2 INCHES THICK.

THE LOCATIONS AND/OR DEPTHS OF UNDERGROUND UTILITIES SHOWN HAVE BEEN TAKEN FROM INFORMATION FURNISHED BY THE UTILITY OWNERS AND MUST BE CONSIDERED APPROXIMATE. FIELD MARKINGS OF FACILITIES IN CRITICAL AREAS MAY BE OBTAINED BY PROVIDING A MINIMUM OF 96 HOURS ADVANCE NOTICE THROUGH THE J.U.L.I.E. SYSTEM BY CALLING 800-892-0123.

THE FOLLOWING MIXTURE REQUIREMENTS ARE APPLICABLE TO THIS PROJECT:

APPLICATION	AC/PG	DESIGN AIR VOIDS	MIXTURE COMPOSITION	FRICTION AGGREGATE
SURFACE COURSE	PG 64-22	4.0% @ N=70	IL - 9.5	MIXTURE C

INDEX OF SHEETS

SHEET NO TITLE

COVER SHEET

GENERAL NOTES, INDEX OF SHEETS

SUMMARY OF QUANTITIES

TYPICAL SECTIONS.

STAGE CONSTRUCTION DETAILS

6-16 STRUCTURAL SHEETS

THE FOLLOWING STANDARDS ARE A PART OF THESE PLANS AND ARE INCLUDED FOLLOWING THE LAST NUMBERED SHEET OF THE PLANS.

000001-05 STANDARD SYMBOLS, ABBREVIATIONS, AND PATTERNS

001001-02 AREAS OF REINFORCEMENT BARS

001006 DECIMAL OF AN INCH AND OF A FOOT

701006-03 CFF-ROAD OPERATIONS, 2L, 2W, 15' TO 24" FROM PAVEMENT EDGE

701201-03 LANE CLOSURE, 2L, 2W, DAY ONLY, FOR SPEEDS >= 45 MPH 701301-03 LANE CLOSURE, 2L, 2W, SHORT TIME OPERATIONS

701311-03 LANE CLOSURE, 2L, 2W, MOVING OPERATIONS - DAY ONLY 701321-10 LANE CLOSURE, 2L, 2W, BRIDGE REPAIR WITH BARRIER

701901-01 TRAFFIC CONTROL DEVICES

704001-06 TEMPORARY CONCRETE BARRIER

780001-02 TYPICAL PAVEMENT MARKINGS

781001-03 TYFICAL APPLICATIONS RAISED REFLECTIVE PAVEMENT MARKERS

COUNTY TOTAL SHEET NO. DESIGNED REVISED FILE NAME = JSER NAME = teasleyck SECTION **GENERAL NOTES &** STATE OF ILLINOIS Now_work\PWIDOT\TEASLEYCK\d0144212\ DRAWN REVISED 325 Shelby INDEX OF SHEETS PLOT SCALE = 50.0000 '/ IN. CHECKED REVISED **DEPARTMENT OF TRANSPORTATION** CONTRACT NO. 74403 SCALE: SHEET NO. OF SHEETS STA. TO STA. REVISED D7 BRIDGE REPAIRS 2010-2