



- 1. EROSION CONTROL TO BE IN PLACE BEFORE START OF WORK AND TO REMAIN IN PLACE UNTIL ENGINEER DIRECTS TO REMOVE. CONTRACTOR SHALL BE RESPONSIBLE FOR IMMEDIATE REPAIR/MAINTENANCE OF EROSION CONTROL ITEMS AS DIRECTED BY THE ENGINEER.
- 2. DITCH CHECKS SPACED AT APPROXIMATELY 100' INTERVALS, DITCH CHECKS SHALL ALSO BE USED AT FLARED END INLET STRUCTURES.

FILE NAME =	USER NAME = \$USER\$	DESIGNED - MAP	REVISED -			F.A.P. SECTION	COUNTY TOTAL SHEET SHEETS NO.
\$FILEL\$		DRAWN ~ JRH	REVISED -	STATE OF ILLINOIS	EROSION CONTROL PLAN - STAGE 1	344 (46-1S&47)WRS-3	LAKE 176 95
	PLOT SCALE = #SCALE#	CHECKED - JW	REVISED -	DEPARTMENT OF TRANSPORTATION		U.S. ROUTE 45 RECONSTRUCTION	ON CONTRACT NO. 60957
	PLOT DATE = \$DATE\$	DATE - 12-12-08	REVISED -		SCALE: 1" = 50' SHEET NO. 1 OF 4 SHEETS STA. 249+00 TO STA. 263+00	FED. ROAD DIST. NO. ILLINOIS FED	. AID PROJECT