



\* SEE DRAINAGE STRUCTURE TABLE FOR TYPE AND SIZE

## PIPE JACKING DETAIL

## NOTES:

- 1. WHEN EXCAVATING THE JACKING AND RECEIVING PITS, BRACED EXCAVATION SHALL BE UTILIZED.
- 2. PRIOR TO INSTALLATION OF THE BRACED EXCAVATION SYSTEM, THE CONTRACTOR WILL LOCATE THE EDGE OF THE FOOTING OF THE EXISTING RETAINING WALL. IT SHOULD BE NOTED THAT THE EXISTING FOOTING IS FOUNDED ON BATTERED PILES.
- 3. THE BRACED EXCAVATION SYSTEM SHALL BE INSTALLED WITH A MINIMUM 1'-0" CLEARANCE FROM THE EDGE OF THE FOOTING OF THE EXISTING RETAINING WALL.

FILE NAME =	USER NAME = 369Ø	DESIGNED - KF	REVISED -			F.A. RTE.	SECTION	COUNTY	TOTAL SHEE
S:\11-CADD\01-sht\25_D160D93-SHT-DETAIL.d	gn	DRAWN - ED	REVISED -	STATE OF ILLINOIS	PIPE JACKING DETAIL	290	2007-057 T	COOK	60 25
	PLOT SCALE = 1:1	CHECKED - AAC	REVISED -	DEPARTMENT OF TRANSPORTATION				CONTRACT	NO. 60D93
	PLOT DATE = Thursday, December 11, 2008	DATE - 12/12/20	REVISED -		SCALE: NO SCALE   SHEET NO.1 OF 1 SHEETS   STA. 10+00.00 TO STA. 25+67.92	FED. RO	COAD DIST. NO. ILLINOIS FED. AI	D PROJECT	