INDEX OF SHEETS

LIST OF STATE STANDARDS

HEET	NO.	DESCRIPTION	NDARD NO.	DESCRIPTION		
HEET A CONTROL OF THE CONTROL OF TH	1 2 3 4 5-8 9-13 14 15	COVER SHEET INDEX OF SHEETS, STANDARDS, AND GENERAL NOTES SUMMARY OF QUANTITIES TYPICAL SECTIONS PLAN ROADWAY & PAVEMENT MARKINGS PLANS DETECTOR LOOP REPLACEMENT PLANS DETAILS FOR FRAMES AND LIDS ADJUSTMENT WITH MILLING PAVEMENT PATCHING FOR HMA SURFACED PAVEMENT CURB OR CURB AND GUTTER REMOVAL AND REPLACEMENT	000001-05 STANDARD SYMBOLS, ABBREVIATIONS AND PATTERNS 442201-03 CLASS C AND D PATCHES 604001-03 FRAME AND LIDS, TYPE 1 604086-02 FRAME AND GRATES, TYPE 23 606001-04 COMBINATION CONCRETE CURB AND GUTTER 701301-03 LANE CLOSURE, 2L, 2W, SHORT TIME OPERATIONS 701602-04 URBAN LANE CLOSURE, MULTILANE, 2W WITH BIDIRECTIONAL LEFT TURN			
	16 17 18	CURB OR CURB AND GUTTER REMOVAL AND REPLACEMENT BUTT JOINT AND HMA TAPER DETAILS TRAFFIC CONTROL AND PROTECTION FOR SIDE ROADS, INTERSECTIONS, AND DRIVEWAYS	701606- <i>06</i> 701701- <i>06</i> 701901- <i>01</i> 886001- <i>01</i>	URBAN LANE CLOSURE, 2L, 2W, UNDIVIDED URBAN LANE CLOSURE, MULTILANE INTERSECTION TRAFFIC CONTROL DEVICES DETECTOR LOOP INSTALLATION		
	19 20 21 22 23	TYPICAL APPLICATIONS RAISED REFLECTIVE PAVEMENT MARKERS (SNOW-PLOW RESISTANT) DISTRICT ONE TYPICAL PAVEMENT MARKINGS. TRAFFIC CONTROL AND PROTECTION AT TURN BAYS (TO REMAIN OPEN TO TRAFFIC) PAVEMENT MARKING LETTERS AND SYMBOLS FOR TRAFFIC STAGING ARTERIAL ROAD INFORMATION SIGN	886006- <i>01</i>	TYPICAL LAYOUT FOR DETECTOR LOOPS		

GENERAL NOTES

BEFORE STARTING ANY EXCAVATION, THE CONTRACTOR SHALL CALL "JULIE" AT 800-892-0123 OR 811 FOR FIELD LOCATIONS OF BURIED ELECTRIC, TELEPHONE AND GAS FACILITIES.

(48 HOUR NOTIFICATION IS REQUIRED).

THE CONTRACTOR SHALL COORDINATE CONSTRUCTION ACTIVITIES WITH UTILITY COMPANIES AND THE VILLAGES OF BELLWOOD, HILLSIDE, MELROSE PARK AND STONE PARK.

THE CONTRACTOR WILL NOT BE ALLOWED TO SET UP A YARD OR FIELD OFFICE ON STATE PROPERTY WITHOUT WRITTEN PERMISSION FROM THE DEPARTMENT

WHEN MILLED PAVEMENT IS OPEN TO TRAFFIC THE MAXIMUM GRADE DIFFERENTIAL BETWEEN PASSES OF THE MILLING MACHINE SHALL NOT EXCEED 1 1/2 INCHES (40 MM) WHERE THE SPEED LIMIT IS 45 MPH (45 KM/H) OR LESS AND 1 INCH WHERE THE SPEED LIMIT IS GREATER THAN 45 MPH (45 KM/H). WITH WRITTEN APPROVAL FROM THE ENGINEER. A MAXIMUM GRADE DIFFERENTIAL OF 3 INCHES MAY BE ALLOWED IF THE EDGE OF THE MILLING IS SLOPED A MINIMUM 1:3 (V:H).

BUTT JOINTS WILL BE INSTALLED AT THE ENDS OF ALL RESURFACING (WHERE RESURFACING MEETS EXISTING PAVEMENT), IN ACCORDANCE WITH THE "BUTT JOINT AND HOT-MIX ASPHALT TAPER DETAILS" SHEET INCLUDED IN THE PLANS, UNLESS OTHERWISE SPECIFIED.

THE RESIDENT ENGINEER SHALL CONTACT MS PATRICE HARRIS
AREA TRAFFIC FIELD ENGINEER AT (708) 597-9800 A MINIMUM OF
2 WEEKS PRIOR TO PLACEMENT OF PERMANENT PAVEMENT MARKING.

THE RESIDENT ENGINEER SHALL VERIFY ALL EXISTING PAVEMENT MARKINGS BEFORE MILLING

DO NOT SCALE PLANS FOR CONSTRUCTION DIMENSIONS

DOUBLE LANE MARKERS ARE TO BE USED AS SHOWN ON THE DISTRICT ONE DETAIL "TYPICAL APPLICATIONS - RAISED REFLECTIVE PAVEMENT MARKERS (SNOW-PLOW RESISTANT)" SHOWN IN THE PLANS.

PAVEMENT MARKING TAPE, TYPE III SHALL BE USED FOR SHORT TERM PAVEMENT MARKING ON ALL FINAL SURFACES. THE COST OF THE PAVEMENT MARKING TAPE, TYPE III AND ITS REMOVAL SHALL BE INCLUDED IN THE COST OF SHORT TERM PAVEMENT MARKING.

ALL PAVEMENT PATCHING LOCATIONS WILL BE DETERMINED IN THE FIELD BY THE ENGINEER.

IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO VERIFY ALL DIMENSIONS AND CONDITIONS EXISTING IN THE FIELD PRIOR TO CONSTRUCTION AND ORDERING OF MATERIALS

THE CONTRACTOR SHALL CONTACT THE DISTRICT ONE TRAFFIC CONTROL SUPERVISOR AT (847)705-4470 A MINIMUM OF 72 HOURS IN ADVANCE OF BEGINNING WORK.

THE CONTRACTOR SHALL BE REQUIRED TO PROVIDE ACCESS TO ABUTTING PROPERTY AT ALL TIMES DURING THE CONSTRUCTION OF THIS PROJECT.

-	FILE NAME =	USER NAME = guilloumefp	DESIGNED -	REVISED -
	c:\pw_work\PWIDOT\GUILLAUMEFP\dms88737	sh_rdwy.dgn	DRAWN -	REVISED -
		PLOT SCALE = 50.0000 '/ IN.	CHECKED -	REVISED -
		PLOT DATE = 2/4/2009	DATE -	REVISED -

DISTRICT ONE DETECTOR LOOP INSTALLATION DETAILS FOR ROADWAY RESURFACING

	STATE	OF	ILLINOIS	*
DEPAR	TMENT	OF	TRANSPOR	RTATION

INDEX OF S	HEETS, LIST OF ST	ATE STANDARDS &	GENERAL NOTES
*	U.S. 12/20/45	(I-290 - LAKE ST.)	
SCALE: 1"=50'	SHEET NO. 1 OF 1	SHEETS STA.	TO STA.

	DIST. NO. HELIMOIS FE	CONTRACT	NO. E	OF 07
330	464Y-RS-2	СООК	24	2
 F.A.P RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.