

NOTES:

- 1. THE WIDTH OF THE FULL DEPTH PATCH OVER A TRENCH SHALL BE 12 (300) WIDER ON EACH SIDE OF THE TRENCH.
- 2. FOR METHOD OF MEASUREMENT AND BASIS OF PAYMENT, SEE RECURRING SPECIAL PROVISION "PATCHING WITH HOT-MIX ASPHALT OVERLAY REMOVAL".

SEQUENCE OF CONSTRUCTION (PATCHING FIRST)

- 1. REMOVE THE EXISTING HMA MATERIAL OVER THE AREA TO BE PATCHED.
- 2. REMOVE AND REPLACE WITH CLASS C OR D PATCH.
- 3. REPLACE HMA MATERIAL OVER THE AREA TO BE PATCHED.

SEQUENCE OF CONSTRUCTION (MILLING FIRST)

- 1. MILL HMA FIRST IF THERE IS AT LEAST $4\frac{1}{2}$ INCHES OR MORE OF HMA MATERIAL ON TOP OF THE EXISTING PAVEMENT OR IF THE PAVEMENT IS FULL DEPTH HMA. A MINIMUM OF 2 INCHES OF HMA MATERIAL SHALL BE IN PLACE AFTER MILLING.
- 2. REMOVE AND REPLACE WITH FULL DEPTH CLASS D PATCHES TO TOP OF MILLED SURFACE.

ALL DIMENSIONS ARE IN INCHES (MILLIMETERS) UNLESS OTHERWISE SHOWN.

FILE NAME =	USER NAME = paraynoal	DESIGNED ~ R. SHAH	REVISED -	A. ABBAS 04-27-98			PAVEMENT PATCHING FOR	F.A.	P. SECTION	COUNTY TOTAL SHEET
c:\pw_work\PWIDOT\PARAYNOAL\dms90669\D.stStd.dgn PLOT SCALE = 50.0000 '/ IN.		DRAWN -	REVISED - R. BORO 01-01-07 STATE OF ILLINOIS				5 118RS-4	LAKE 35 26		
		CHECKED	REVISED - R. BORO 09-04-07		DEPARTMENT OF TRANSPORTATION	HMA SURFACED PAVEMENT			BD400-04 (BD-22)	CONTRACT NO. 62779
	PLOT DATE = 2/2/2009	DATE - 10-25-94	REVISED -	K. ENG 10-27-08	SCAL	SCALE: NONE SHE	EET NO. 1 OF 1 SHEETS STA. TO STA.	FED.	. ROAD DIST. NO. 1 ILLINOIS FEE	D. AID PROJECT