



CONSTRUCTION NOTES

- B. 2-#4 Bars Continuous, Optional.
- C. 2 Dowel Bars at Expansion Joints.
- E. Min. 6-Bag Mix Concrete.
- F. Depressed Curb Configuration.

GENERAL NOTES

- Standard Curb and Gutter Shall be Used For All New Construction. Roll-Type Curb and Gutter is Not. Acceptable.
- 2. Preformed Expansion Joints of 3/4" Thickness Shall be Spaced a Maximum of 40' Apart, and at All Radius Points and 4' Either Side of Inlets.
- Formed or Saw-Cut Contraction Joints Shall be Spaced a Maximum of 10' Apart and Filled with a Silicone Sealant.
- 4. Concrete Barrier-Type Curb and Gutter Shall be Provided for All Parking Lots Accompdating Five (5) or More Parking Spaces.

VILLAGE OF WESTMONT

CURB AND GUTTER DETAIL

ISSUED: March 1988 REVISED: August 2003

- 08-00098-00-SW DU PAGE 12 10
FEDERAL RD. DIST, NO. ILLINOIS FEDERAL AID PROJECT

SECTION

file 48924_DETAILS_2

no. date by ckd

SHEETS

OCTOBER 29, 2008

designed M. BERENA

checked A. BRYANT

D. CHAVEZ

63132



VILLAGE OF WESTMONT PROPOSED 2008 CMAQ SIDEWALK PROJECT MISCELLANEOUS DETAILS (2 OF 3)

48924

D102 of 18 sheet 10 sheets