DETECTOR LOOP INDUCTANCE CHART							
DETECTOR LOOP SYSTEM	ø	LOCATION	TURNS PER LOOP	INDUCTANCE READING (MICROHENRIES)	FREQUENCY (HERTZ)	J PIN STATUS	
A	4	SBRT	5	261	37,779	ON	
В	4	SB	4	714	22,841	ON	
С	6	WB FAR	6	642	24,088	ON	
D	6	WB STBR	4	570	25,564	OFF	
E	1	WBLT	4	834	21,134	ON	
F	OL1	NBRT BK	5	384	31,146	OFF	
G	OL1	NBRT FR	5	560	25,792	ON	
Н	3	NBLT RL	4	657	23,812	ON	
I	3	NBLT LL	4	659	23,775	ON	
J	2	EB FAR	6	650	23,940	ON	
К	2	EB STBR	4	592	25,085	0FF	
L	5	EBLT	4	858	20,837	ON	

J PIN STATUS: "ON" MEANS STANDARD DETECTOR SETUP. "OFF" MEANS J WIRE HAS BEEN DISCONNECTED. BUT INTACT, AT THE HARNESS PANEL WITH THE NECESSARY SPADE CONNECTION ATTACHED, MARKED, AND INSULATED.

STREET NAME	COMPONENT	NUMBER	WATTAGE EACH	BURNT.
ARMOUR ROAD	RED	- 8	10	35
	YELLOW	8	19	5
	GREEN	8	14	60
	RED ARROW LT.	4	8	60
	YELLOW ARROW LT.	4	9	5
	GREEN ARROW LT.	4	3.4	35
WASHINGTON AVENUE	RED	2	10	60
	YELLOW	2	19	5
	GREEN	2	14	35
EDNECT	RED	4	10	50
ERNEST MOONEY DRIVE	YELLOW ARROW LT.	2	9	5
	GREEN ARROW LT.	2	3.4	45
	YELLOW ARROW RT.	2	9	5
	GREEN ARROW RT.	2	3.4	45
TRAFFIC SIGNAL	CONTROLLER	1	6	100
CABINET			4	
	VEHICLE DETECTORS	11		100
	l UPS I	1	50	100

AGENCY RESPONSIBLE FOR TRAFFIC SIGNAL ENERGY CHARGES: VILLAGE OF BOURBONNAIS

NOTE: DAMPENING DEVICE SHALL CONSIST OF A 24" X 30" TYPE 1, UNPAINTED ALUMINUM SIGN STOCK MOUNTED HORIZONTALLY ON TOP OF MAST ARM WITH THE 30" LENGTH PERPENDICULAR TO THE ARM. COST OF THE **ERNEST** MOONEY DR. DAMPENING DEVICE IS INCLUDED IN THE MAST ARM PAY ITEM.

TYPE ZZ SHEETING REQUIRED 8" D SERIES LETTERS 2 SIGNS REQUIRED = 15 SQ. FT. EACH = 30 SQ. FT. TOTAL

THIS STREET NAME SIGN SHALL BE PLACED ON THE SOUTHWEST CORNER AND NORTHEAST CORNER MAST ARMS PARALLEL WITH ERNEST MOONEY DRIVE

CONTRACT NO. 66560 COUNTY TOTAL SHEET NO. SECTION KANKAKEE 109 45 STA. TO STA. FED. ROAD DIST. NO. _ ILLINOIS FED. AID PROJECT

FAU ROUTE 6176 (ARMOUR ROAD) SECTION (79)W&RS & 140RS

LEFT ON GREEN ARROW ONLY

R10 - 5 24" X 30"


TYPE ZZ SHEETING REQUIRED 4 SIGNS REQUIRED = 5 SQ.FT. EACH = 20 SQ.FT. TOTAL

THIS SIGN SHALL BE LOCATED 6" TO 12" TO THE RIGHT OF EACH 5 SECTION MAST ARM MOUNTED LEFT TURN SIGNAL AND DIRECTLY BELOW AND PARALLEL TO THE BACKPLATE OF POST BRACKETED 5 SECTION LEFT TURN SIGNAL FOR THE EASTBOUND AND WESTBOUND APPROACHES.



TYPE 77 SHEETING REQUIRED 8" D SERIES LETTERS
2 SIGNS REQUIRED = 11.25 SQ. FT. EACH
= 22.5 SQ. FT. TOTAL

THIS STREET NAME SIGN SHALL BE PLACED ON THE MAST ARMS PARALLEL WITH ARMOUR ROAD



ARMOUR ROAD / WASHINGTON AVENUE / ERNEST MOONEY DRIVE

END OF -MAST A

2-5/8" STAINLESS STEEL BOLTS ______ THROUGH STAINLESS STEEL BANDING

MOUNT DAMPENING PLATE TO END OF EACH TRAFFIC SIGNAL MAST ARM.

WASHINGTON

AVENUE

DAMPENING PLATE DETAIL - TOP VIEW

ILLINOIS DEPARTMENT OF TRANSPORTATION TRAFFIC SIGNAL DETAILS FAU ROUTE 6176 (ARMOUR ROAD) SECTION (79)W&RS & 140RS KANKAKEE COUNTY SCALE: VERT. HORIZ. DATE 01/09 DRAWN BY ARR CHECKED BY JLS

DATE NAME SCALE NAME