COUNTY TOTAL SHEETS NO.

COOK 37 20 RTE. SECTION 94/90 TO STA.

FED. ROAD DIST. NO. ILLINOIS FED. AID PROJECT

GUARDRAIL OR PROP. EMBANKMENT CONCRETE BARRIER-WIDENING (VARIES) -2'-0" (600) MAXIMUM (2.4 m MIN.) - PROPOSED FORESLOPE 2:1 MAXIMUM MERGER POINT (3.6 m MAX.)

TYPICAL BENCHING DETAIL FOR EMBANKMENT

NOTES:

- CONSTRUCT SUCCEEDING BENCH CUTS AND EMBANKMENT PLACEMENT CONSTRUCT SUCCEEDING BENCH CUTS AND LABORATION AND COMPACTION FROM BOTTOM TO TOP IN STAIRSTEP FASHION.
- 2 EXISTING FORESLOPE PREPARED IN ACCORDANCE WITH ARTICLE 205.03 OF THE STANDARD SPECIFICATIONS.
- 3 BENCH CUT EXISTING SLOPE TYPICAL FOR EACH STEP.
- 4 TRIM TO FINAL SLOPE.
- EQUAL 8-INCH (200) LIFTS OF EMBANKMENT COMPACTED IN ACCORDANCE WITH ARTICLE 205.05 OF THE STANDARD SPECIFICATIONS.
- 6 EXCAVATION OF BENCH CUTS WITHIN EXISTING EMBANKMENT WILL BE PAID FOR AT THE CONTRACT UNIT PRICE PER CUBIC METER OR CUBIC YARD FOR "EARTH EXCAVATION". THIS PRICE WILL INCLUDE ALL LABOR AND MATERIAL, NO ADDITIONAL COMPENSATION WILL BE ALLOWED.
- The slopes shall be benched according to this detail when the SLOPE IS STEEPER THAN 4:1 AND THE HEIGHT IS GREATER THAN 5' (1.5 m).

ALL DIMENSIONS ARE IN INCHES (MILLIMETERS) UNLESS OTHERWISE SHOWN.

ILLINOIS DEPARTMENT OF TRANSPORTATION WIDENING

BENCHING DETAIL FOR EMBANKMENT

SCALE: VERT. NONE

DRAWN BY: CADD CHECKED BY: S.E.B.