

\*DEPRESSED CURB THROUGH SIDWALK EX CATCH BASIN



# CURB OUTLET (SPECIAL) N.T.S

\*WORK INCLUDES DEPRESSED CURB THROUGH SIDWALK




\* CROSS SLOPE 2% MAX OR AS SHOWN ON CROSS SECTIONS

### NOTES:

- 1 ALL REQUIRED EARTH EXCAVATION TO CONSTRUCT P.C.C. SIDEWALK SHALL BE INCIDENTAL TO THE P.C.C. SIDEWALK 5 INCH, SPECIAL.
- 2. WHEN FORMS ARE REMOVED FROM THE SIDEWALK EITHER THE SIDEWALK SHALL BE BARRICADED OR BACKFILLED WITHIN 24 HOURS.

## P.C.C. SIDEWALK, 5 INCH SPECIAL DETAIL



# DRIVEWAY PAVEMENT REPLACEMENT **DETAIL**

SECTION --- 06-00028-00-SW COOK 13 9 TO STA. FED. ROAD DIST. NO. ILLINOIS FED. AID PROJECT

CONTRACT NO. 63016

\* CROSS SLOPE 2% MAX OR AS SHOWN ON CROSS SECTIONS

SUBBASE GRANULAR MATERIAL, TYPE B

### NOTES:

- 1. ALL REQUIRED EARTH EXCAVATION TO CONSTRUCT P.C.C. SIDEWALK SHALL BE INCIDENTAL TO THE P.C.C. SIDEWALK 6 INCH, SPECIAL.
- 2. WHEN FORMS ARE REMOVED FROM THE SIDEWALK EITHER THE SIDEWALK SHALL BE BARRICADED OR BACKFILLED WITHIN 24 HOURS.

### P.C.C. SIDEWALK, 6 INCH SPECIAL **DETAIL**

BITUMINOUS MIXTURE REQUI	REMENTS		
ITEM	AC-TYPE	VOIDS	RAP %
HOT-MIX ASPHALT SURFACE COURSE, MIX "C", N50 (NON QC/QA)	PG 64-22	4% @ 50 GYR	15
HOT-MIX ASPHALT BINDER COURSE, IL-19.0 N50 (NON QC/QA)	PG 64-22/ 58-22	4% <b>c</b> 50 GYR	25
ASPHALT DRIVEWAY REPLACEMENT	PG 64-22	4% @ 50 GYR	15

THE UNIT WEIGHT USED TO CALCULATE ALL BITUMINOUS SURFACE MIXTURE QUANTITIES IS 112 LBS/SY/IN.

REVISIONS						DODT 1 TIO
NAME	DATE	ILLIN	OIS DEPARTM	ENI OF	TRANSPO	OKIAIIC
		CONSTRUCTION DETAILS				
			VILLAGE	OF PALO	OS PARK	
		SCALE		1	DRAWN BY M	HLN
		DATE	2 /14 /2009		PUECKED BY I	cc