## **GENERAL NOTES** :

#### **INDEX OF SHEETS**

# Sheet NO.Title1Cover Sheet2Smmary of Quantities3Sheet index, General Notes, Commitments4Typical Sections5Line Diagram /SWPPP6Standards7Details

#### COMMITMENTS

Commitments are not to be altered without the written approval of all parties to which the commitment was made.

### PROPERTY OWNER ACCESS REQUIREMENT

Access must be maintained to all existing properties during construction per Article 107.09 unless arrengements are made in writing by the Contractor with the property owners with a copy to the Engineer for short-term clousures.

# AGGREGATE SHOULDERS, TYPE B

Aggregate Shoulders, Type B shall be required for all granular construction of side roads, entrances, and mailbox turnouts, whether or not portions of the surfaces thus constructed are to be covered with a bituminous surface, except where noted differently in the plans.

# HOT-MIX ASPHALT MIXTURE REQUIREMENTS

Mixture Use(s):	Shoulders (Bottom Lifts)	Shoulders (Surface Lift)		
RAP % (MAX)**:	30%	30%		
AC/PG:	64-22	64-22		
Design Air Voids:	4.0 % @ N = 30	3.0 % @ N = 30		
Mixture Coposition:	IL 19.0 L	IL 9.5 L		
Friction Aggregate:	N.A.	Mix C		

\*\* If the RAP option is selected, the asphalt cement grade may need to be adjusted; this will be determined by the Engineer.

•			CONTRA	OT NO	6077
	TEAT		T		SHEET
	RTE.	SECTION	COUNTY	SHEETS	NO.
	698	1271	WOODFORD	7	3
	STA.		TO STA.		******
	FED. ROA	D DIST. NO. ILL	INOIS FED. ALD	PROJECT	

# COMMITMENTS:

# There are no commitments for this project.

REVISIONS		MENT OF TRANSPORTATION	
NAME D	ATE RELINCIS SELAT		
	GENE	RAL NOTES /	
	Сомм	COMMITMENTS	
	SCALE: VERT.	DRAWN BY	
	DATE	CHECKED BY	